

# Technical Note FL24

## Don't Look at ioPosOffset for Devices

### CONTENTS

[ioPosOffset](#)[Downloadables](#)

[Jun 01 1998]

---

## ioPosOffset

The Device Manager chapter of [Inside Macintosh: Devices](#) (and, for that matter, *Inside Macintosh Volume II* page 185) says that `ioPosOffset` is passed to and returned by `_Read` and `_Write` calls for devices. It also says that "After the transfer is completed, the `ioPosOffset` field indicates the current position of the block device." Actually, `ioPosOffset` is not changed by `_Read` and `_Write` calls to device drivers.

On the other hand, if the `_Read` or `_Write` call is made to a file (`ioRefNum` is a file reference number), `ioPosOffset` is updated to reflect the mark for that file reference number after the call. This is correctly documented in [Inside Macintosh: Files](#) (and *Inside Macintosh Volume II* page 110, and *Inside Macintosh Volume IV* page 140).

Note also that device drivers should **only** look at the `dCtlPosition` field of the DCE, and should not look directly at the `ioPosOffset` field of the parameter block. The Device Manager sets up `dCtlPosition` for the driver, taking into account both the `ioPosMode` and the `ioPosOffset`.

[Back to top](#)

## Downloadables



Acrobat version of this Note (K)

[Download](#)[Back to top](#)

---

Technical Notes by [Date](#) | [Number](#) | [Technology](#) | [Title](#)  
[Developer Documentation](#) | [Technical Q&As](#) | [Development Kits](#) | [Sample Code](#)