

NOTE: This Technical Note has been [retired](#). Please see the [Technical Notes](#) page for current documentation.

Technical Note TB15

"New" cdev Messages

CONTENTS

- [Introduction](#)
- [References](#)
- [Downloadables](#)

This Technical Note describes some previously undocumented messages that the Control Panel can send to a Control Panel device (cdev).

[Oct 01 1988]

Introduction

The Control Panel will send messages to a Control Panel device (cdev) in response to the user selecting the Undo, Cut, Copy, Paste, and Clear items of the Edit menu. It will also send a message if the cdev contains a 'CURS' = -4064 resource. The following is a list of the previously undocumented messages, descriptions, and values:

Message	Description	Value
undoDev	Undo selected	9
cutDev	Cut selected	10
copyDev	Copy selected	11
pasteDev	Paste selected	12
clearDev	Clear selected	13
cursorDev	Cursor resource	14

The Control panel only sends the undoDev, cutDev, copyDev, pasteDev, and clearDev messages to a cdev as a result of the Desk Manager sending an edit message to it when an application calls SystemEdit (_SysEdit). Since the call to SystemEdit (_SysEdit) is triggered by a mouse-down event in the menu bar, the messages to the cdev will be sent only as a result of the user selecting the Edit menu item with the mouse and not by pressing the Command-key equivalent.

Typically, you will call _DlgCut, _DlgCopy, _DlgPaste or _DlgDelete upon receipt of the cutDev, copyDev, pasteDev, or clearDev message, passing the DialogPtr that has been passed to the cdev to the call.

To respond to Command-key equivalents of the Edit menu commands, you must check for the specific characters and modifier keys themselves, even though this is never localized. Once you determine the character to be a Command-key equivalent, you must alter the what field of the event record that has been passed to the cdev to be a nullEvent to prevent the Dialog Manager from inserting the character into the editText item of the cdev. To alter the event record, you should treat the event record parameter which is passed to the cdev as a reference. In Pascal, this means declaring the interface to the cdev as follows:

```
FUNCTION MyCdev(message, item, numItems, CPanelID: INTEGER
VAR theEvent: EventRecord; (* the 'NEW' way *)
cdevStorage: Handle;
```

In C, you would do the following:

```
Handle MyCdev(message, item, numItems, CPanelID
theEvent, cdevStorage, CPDialog)
short message, item, numItems, CPanelID;
EventRecord *theEvent; /* the 'NEW' way */
Handle cdevStorage;
```

In assembly language, it means you do not make your own copy of the event record, so you are probably already set up to change the value of the what field of the event record.

If the cdev contains a 'CURS' = -4064 resource, the Control Panel will send it a cursorDev message whenever the cursor is over the cdev part of the Control Panel's window instead of setting the cursor to the light cross. The cdev can then set and use its own cursor. The Control Panel will handle the cursor elsewhere on the screen. The Control Panel does not examine the contents of the 'CURS' = -4064 resource.

[Back to top](#)

References

Inside Macintosh, Volume V, The Control Panel

[Back to top](#)

Downloadables



Acrobat version of this Note (K).

[Download](#)

Technical Notes by [Date](#) | [Number](#) | [Technology](#) | [Title](#)
[Developer Documentation](#) | [Technical Q&As](#) | [Development Kits](#) | [Sample Code](#)