

NOTE: This Technical Note has been [retired](#). Please see the [Technical Notes](#) page for current documentation.

# Technical Note NW09

## RegisterName

### CONTENTS

[Introduction](#)[References](#)[Downloadables](#)

[Feb 01 1989]

---

## Introduction

The verify flag indicator byte (`verifyFlag`) of the AppleTalk `RegisterName` function should always be set `TRUE` in published code.

The AppleTalk chapter of *Inside Macintosh*, Volume II-322, in describing the `RegisterName` function, states:

*"If `verifyFlag` is `TRUE`, `RegisterName` checks on the network to see if the name is already in use, and returns a result code of `nbpDuplicate` if so."*

Note that `verifyFlag` should **always** be `TRUE` in published code. The design of the Name Binding Protocol (NBP) requires that an entity name be unique. The way `RegisterName` ensures this uniqueness is by broadcasting a lookup request for the registered name. If any entity responds, then `RegisterName` knows that the name would not be unique and returns an error. Some developers, in anticipating the time delay involved in broadcasting a lookup request and waiting for a response, have opted to set `verifyFlag` to `FALSE`, not realizing the potential danger in doing so.

Apple provides `verifyFlag` for experimental or developmental purposes, such as narrowing down a problem in registering a name on a network. Always make sure that code which ships has `verifyFlag` set to `TRUE`.

[Back to top](#)

## References

*Inside Macintosh*, Volume II-261, The AppleTalk Manager

[Back to top](#)

## Downloadables



Acrobat version of this Note (K)

[Download](#)

[Back to top](#)

---

Technical Notes by [Date](#) | [Number](#) | [Technology](#) | [Title](#)  
[Developer Documentation](#) | [Technical Q&As](#) | [Development Kits](#) | [Sample Code](#)