

# New Technical Notes

Macintosh



®

---

Developer Support

## Changes in International Utilities and Resources

Text

M.TE.IUChanges

Revised by:

March 1988

Written by: Priscilla Oppenheimer

July 1987

The International Utilities package and the international resources have been changed with System file 4.1 to take advantage of the Script Manager.

---

### INTL vs. itl

In the past, there were two INTL resources in the System file, INTL 0 and INTL 1, which contained international formatting options. Starting with System 4.1, itl0 and itl1 replace INTL 0 and INTL 1. (INTL 0 and INTL 1 are still included with the System file so that applications that do a GetResource for them will still find them. Only these erroneous applications that use GetResource will access these resources now; the System will no longer look at them.) There can now be a set of international resources (itls) for each script that is installed. That is, where once there was one resource type (INTL) with IDs 0 and 1 there are now many different resource types (itl0, itl1, itl2, itlb, itlc, KCHR) with distinct resource IDs for the various countries. The U.S. System file uses resource ID 0 for all itl resources.

If your existing application calls IUGetIntl to get the appropriate international resource, you will have no problems under System 4.1. If, however, you call GetResource on INTL 0 or INTL 1 and then modify them, and expect that the System will use the modified resource, you will no longer work correctly. If your application has been released in the past with a modified System file to include your own INTL 0 and/or INTL 1, you may want to release your application with a modified itl0 and/or itl1.

### The International Sorting Routine

The international sorting routine is used to handle cases where letters are equal in primary ordering but different in secondary ordering (e.g., “ä” and “a”). The routine can also handle cases where one character sorts as if it were two, or two characters would sort as if they were one, or even character reversals.

Prior to System 4.1, the international sorting routine was stored starting with the localRtn field of INTL 1. As of System 4.1, this routine is now stored in itl2. An INTL 2 resource is also included with the international resources, just for consistency (the System never uses it). It is exactly the same as itl2.

Writing your own sorting routine can be dangerous if it is not done correctly. Before attempting to do this, we would highly recommend you check with Apple to determine if we are already doing one for the language of interest. We plan to do many international versions of

System file 4.1, and most developers' needs will be met by these. A new policy at Apple will now make it possible to license foreign versions of the System file from Software Licensing. Contact Software Licensing at (408) 973-4667 for more information about this.

## **Error in APDA draft of Inside Macintosh Volume V**

There is an error in the APDA draft of the International Utilities Package chapter of *Inside Macintosh Volume V*. It says that there is a flag in the Script Manager globals that overrides the current font and always uses the INTL 0 and INTL 1 resources. This is not true. INTL 0 and 1 have been replaced by itl0 and itl1, and are not used except by applications that explicitly get them by doing a GetResource. There is a relevant Script Manager flag called IntlForce that is correctly but incompletely explained in the Script Manager chapter. When IntlForce is false, the resources used by the International Utilities are determined by the current script. The script that is in use is determined by which font is in use for the port in use. For example, if you switch to the Kyoto font, then you will be using the Japanese Script Interface System (KanjiTalk). If you do this with IntlForce set to false, then you will use the resources that are associated with the Japanese Script Interface System.

When IntlForce is true, the International Utilities always use the resources that are associated with the system script; this is usually Roman. IntlForce is true by default. Actually, the Script Manager initialization routine reads the itlc resource to determine what the default is, and Apple plans to release the various international System files with this field set to true in the itlc resource. Applications that want to change the value of IntlForce can use the Script Manager call SetEnvirons with the smIntlForce verb. There is a Script Manager call, IntlScript, to find out the current value.

### **Bug in System 4.1 version of itl1**

There is a bug in the itl1 resource in System 4.1. The itl1 resource contains arrays of day and month names, as did the INTL 1 resource. Their formats are:

```
days ARRAY [1..7] of STRING[15]
months ARRAY[1..12] OF STRING[15]
```

Every day and month is supposed to be coded as a Pascal string with a maximum of 15 characters, and the actual length in the first byte of the string. In System 4.0 and System 4.1, the contents of each string is always a Pascal string of length 15, with the unused characters set to nulls. In other words, the length byte is set to hex 0F. This will be fixed in a future release of the System file. If it is currently causing your application problems, you can change the lengths with ResEdit, or change them at run time, or use your own itl1 resource and release your application with an installer script. The recommended approach is to wait for a fixed version of the System file from Apple.

### **Further Reference:**

- The International Utilities
- The Script Manager