

in

COLLABORATORS

	TITLE : in		
ACTION	NAME	DATE	SIGNATURE
WRITTEN BY		July 31, 2024	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	in	1
1.1	filereqclass.guide	1
1.2	filereqclass/--background--	1
1.3	filereqclass/FILEREQ_Drawer	1
1.4	filereqclass/FILEREQ_File	2
1.5	filereqclass/FILEREQ_MultiHook	2
1.6	filereqclass/FILEREQ_Path	2
1.7	filereqclass/FILEREQ_Pattern	3

Chapter 1

in

1.1 filereqclass.guide

Search
TABLE OF CONTENTS

filereqclass/--background--
filereqclass/FILEREQ_Drawer
filereqclass/FILEREQ_File
filereqclass/FILEREQ_MultiHook
filereqclass/FILEREQ_Path
filereqclass/FILEREQ_Pattern

1.2 filereqclass/--background--

NAME
Class: filereqclass
Superclass: aslreqclass
Include File: <libraries/bgui.h>

FUNCTION
To provide a BOOPSI interface class to the ASL FileRequester. The advantage of this class is that the objects remember their complete settings like requester size, path, directory, file and pattern strings as long as the object remains valid.

NOTE
All the ASL filerequester attributes as defined in <libraries/asl.h> are usable with this class. Applicability for these ASL attributes is (ISGU).

SEE ALSO
<libraries/asl.h>, aslreqclass.doc

1.3 filereqclass/FILEREQ_Drawer

NAME

FILEREQ_Drawer -- (STRPTR)

FUNCTION

To obtain a pointer to the directory name of the filerequester. When set, this tag is equivalent to ASLFR_InitialDrawer.

APPLICABILITY

(ISG).

SEE ALSO

FILEREQ_File, FILEREQ_Pattern, FILEREQ_Path

1.4 filereqclass/FILEREQ_File

NAME

FILEREQ_File -- (STRPTR)

FUNCTION

To obtain a pointer to the file name of the filerequester. When set, this tag is equivalent to ASLFR_InitialFile.

APPLICABILITY

(ISG).

SEE ALSO

FILEREQ_Drawer, FILEREQ_Pattern, FILEREQ_Path

1.5 filereqclass/FILEREQ_MultiHook

NAME

FILEREQ_MultiHook -- (struct Hook *) ** V40 **

FUNCTION

To install a callback hook for multi-select filerequesters. The hook is called with a pointer to the ASL FileRequester structure as the message packet in register A1.

You may not cache this pointer. Copy the data you need.

There is no return code specified for the callback hook.

DEFAULT

NULL.

APPLICABILITY

(ISG).

1.6 filereqclass/FILEREQ_Path

NAME

FILEREQ_Path -- (STRPTR)

FUNCTION

To obtain a pointer to the full path of the filerequester. This is simply the directory with the file name AddPart()'d to it.

APPLICABILITY

(G)

SEE ALSO

FILEREQ_Drawer, FILEREQ_File, FILEREQ_Pattern, dos.library/AddPart()

1.7 filereqclass/FILEREQ_Pattern

NAME

FILEREQ_Pattern -- (STRPTR)

FUNCTION

To obtain a pointer to the pattern string of the filerequester. When set, this tag is equivalent to ASLFR_InitialPattern.

APPLICABILITY

(ISG).

SEE ALSO

FILEREQ_Drawer, FILEREQ_File, FILEREQ_Path