

**in**

<b>COLLABORATORS</b>
----------------------

	TITLE :  in		
ACTION	NAME	DATE	SIGNATURE
WRITTEN BY		July 31, 2024	

<b>REVISION HISTORY</b>
-------------------------

NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1</b>	<b>in</b>	<b>1</b>
1.1	sliderclass.guide . . . . .	1
1.2	sliderclass/--background-- . . . . .	1
1.3	sliderclass/SLIDER_Level . . . . .	2
1.4	sliderclass/SLIDER_Max . . . . .	2
1.5	sliderclass/SLIDER_Min . . . . .	2
1.6	sliderclass/SLIDER_NoFrame . . . . .	3
1.7	sliderclass/SLIDER_ThinFrame . . . . .	3
1.8	sliderclass/SLIDER_XenFrame . . . . .	4

# Chapter 1

## in

### 1.1 sliderclass.guide

Search

TABLE OF CONTENTS

sliderclass/--background--  
sliderclass/SLIDER\_Level  
sliderclass/SLIDER\_Max  
sliderclass/SLIDER\_Min  
sliderclass/SLIDER\_NoFrame  
sliderclass/SLIDER\_ThinFrame  
sliderclass/SLIDER\_XenFrame

### 1.2 sliderclass/--background--

NAME

Class: sliderclass  
Superclass: propclass  
Include File: <libraries/bgui.h>

FUNCTION

To provide a gadget similar to the gadtools.library slider kind.  
Objects of this class send out the following attribute pairs in their  
notification events:

GA\_ID - Gadget object ID.  
SLIDER\_Level - Slider level.

NOTE

This class also supports the PGA\_NewLook and PGA\_Freedom attributes.  
Please refer to the system "propgclass" documentation for more  
information on these attributes.

Also all frameclass attributes are valid at create time and with

---

OM\_SET or OM\_UPDATE (ISU) .

### 1.3 sliderclass/SLIDER\_Level

NAME

SLIDER\_Level -- ( LONG )

FUNCTION

Set or get the current slider level.

DEFAULT

0.

APPLICABILITY

(ISGNU) .

SEE ALSO

SLIDER\_Min, SLIDER\_Max

### 1.4 sliderclass/SLIDER\_Max

NAME

SLIDER\_Max -- ( LONG )

FUNCTION

Set the maximum slider level. Please note that this attribute has been made settable since V39 of the library.

DEFAULT

15.

APPLICABILITY

(ISU) .

SEE ALSO

SLIDER\_Min, SLIDER\_Level

### 1.5 sliderclass/SLIDER\_Min

NAME

SLIDER\_Min -- ( LONG )

NCTION

Set the minimum slider level. Please note that this attribute has been made settable since V39 of the library.

DEFAULT

0.

APPLICABILITY

(ISU) .

SEE ALSO

SLIDER\_Max, SLIDER\_Level

## 1.6 sliderclass/SLIDER\_NoFrame

NAME

SLIDER\_NoFrame -- ( BOOL ) \*\* V40 \*\*

FUNCTION

To create a slider object without a frame around it.

DEFAULT

FALSE.

APPLICABILITY

(ISU) .

## 1.7 sliderclass/SLIDER\_ThinFrame

NAME

SLIDER\_ThinFrame -- ( BOOL )

FUNCTION

To make all slider object framing appear as thin frames. This will help you to make an aspect-ratio dependant GUI.

DEFAULT

---

FALSE.

APPLICABILITY

(I) .

## 1.8 sliderclass/SLIDER\_XenFrame

NAME

SLIDER\_XenFrame -- ( BOOL )

FUNCTION

To make all slider object framing appear as Xen style framing. This tag is only useful when you use the default frame type.

DEFAULT

FALSE.

APPLICABILITY

(I) .

---