

## Named Anchor

A named anchor provides a way of tagging a section of text as the target (AKA “the head”) of a link. For example, each heading within the large document might be tagged with Named Anchors, then HyperText links (AKA the “tail” of a link) jump to the document and automatically scroll to the specified Named Anchor. Obviously, for this scheme to work, each named anchor within a document must be unique.

To create a named anchor, select the text that is to become the jump-to point, then choose Named Anchor... from the Anchor menu and enter the name of the Named Anchor, as in:

```
<A NAME="edmonton">Edmonton</A> is Alberta's capital and...
```

Now to create a link to the named anchor, you include not only the filename, but also the named anchor, separated by a hash mark "#":

```
In <A HREF="cities.html#edmonton">Edmonton</a> we visited...
```

Now clicking on the word "Edmonton" in the above text would send the reader directly to the word "Edmonton" in the linked document.

### Within the Same Document

To create an anchors to a specific sections within the current document, the technique is exactly the same except that the file name is omitted, as in

```
In <A HREF="#edmonton">Edmonton</a> we visited...
```

Note: The NCSA Mosaic Back button does not work for an anchor within a document because the Back button is designed to move to a previous document. Move back manually within the document using the scroll bar.

Back to Anchor menu, on to Table of Contents, or return to Contents.