

## TKdoList

XFCN DLOG DITL

No. 4404

Version: 5.0 (public domain)

Copyright © 1990 - 1994 by Stan Gilbert

---

TKdoList allows you to create a standard Macintosh list dialog and return single or multiple selections. The dialog has one list field and two buttons, "Cancel" and "Select". You can use your own prompt. A unique feature of this XFCN is that you can use lists of items separated by commas, spaces, or returns. For much more versatility see TKdialog.

ð

### Examples

```
ÓÊget TKdoList("This,That,Them,Those,Things","", "m")
ÊÊ>get TKdoList(myList,"Select one...", "CR,left40,top12")
ÊÊ>get TKdoList(cd fld "Names","Leave memo to...", "cr,m")
```

### Parameters

Parm1: container

Container name of list items. You can use TKdoTEXT to retrieve a TEXT resource of list items.

Parm2: prompt

Puts a prompt at top of dialog box, Default is "Make a selection..."

Parm3: cmd string

separated by commas and NOT case or order sensitive

M: Allow multiple selections - Default single selection

SP: Use spaces as list item delimiters

CR: Use returns as delimiters - Default commas (,)

LEFTn: Set left location of dialog to n - Default centered

TOPn: Set top location of dialog to n - Default centered

### Requirements

```
ÓÊDLOG<resource # 4404 "TKdoList"
```

```
ÊÊ>DITLfiresource # 4404 "TKdoList"
```

### Return Values

ÓÊItem(s) selected, separated by commas.

### Related Topics

ÓÊSee TKdialog for creating lists in your own dialog box that  
ÊÊ>can be any size, font, and other controls (buttons,  
ÊÊ>checkboxes,etc.).

ÓÊSee TKdoTEXT for creating TEXT resources in your stacks to  
ÊÊsave lists.

ÓÊSee TKsort for sorting lists.

## Special Features

ÓRead from lists of items separated by commas (default), spaces, or returns.

.....