


New Technical Notes

Macintosh



Developer Support

Problem with WaitNextEvent in MultiFinder 1.0

Toolbox

Revised by:
Written by: Jim Friedlander

March 1988
November 1987

This Technical Note discusses a bug in `WaitNextEvent` in MultiFinder 1.0. This bug only occurs when `WaitNextEvent` is called from the background. This bug will be fixed in the next release of MultiFinder.

Change since 11/87: the bug will be fixed in Systems with versions greater than \$04FF.

In MultiFinder 1.0, applications that use `WaitNextEvent`:

```
FUNCTION WaitNextEvent(mask: INTEGER; VAR event: EventRecord;  
                      sleep: LONGINT; mouseRgn: RgnHandle): BOOLEAN;
```

```
pascal Boolean WaitNextEvent(mask, event, sleep, mouseRgn)  
  unsigned short mask;  
  EventRecord *event;  
  unsigned long sleep;  
  RgnHandle mouseRgn;
```

should **not** call `WaitNextEvent` from the background with a value of `sleep` that is greater than 50. This value has been determined empirically for a Macintosh II; larger values can be used on the Macintosh Plus and the Macintosh SE. If an application uses a large value of `sleep` when running in the background, MultiFinder 1.0 will hang under the following circumstances:

- The application that is calling `WaitNextEvent` with a large `sleep` value has been put in the background.
- That application becomes the foreground application when another application (including the desk accessory handler) quits.

If you use a value of `sleep` that is small enough, this problem will not occur. If you use an algorithm to calculate `sleep`, make sure that the maximum is clipped to 50.

This problem will be fixed in the next release of MultiFinder. You can call `SysEnviron`s to test for the system version number. This bug will not happen when the System version is greater than \$04FF.

Further Reference:

- M.TB.Multifinder
- M.TB.MultifinderMisc.