

Tables

```
<TABLE [BORDER=n] [CELLSPACING=n] [CELLPADDING=n]  
[WIDTH=n|n%]>
```

Start tag of a table. Must end with the `</TABLE>` tag.
The following parameters are allowed:

BORDER=n

Gives the table a 3D-look. n is the width of the border in dots.

CELLSPACING=n

Sets the space between cells in dots.

CELLPADDING=n

Sets the space between the contains of the cells to the cells border.

WIDTH=n|n%

Sets the width of the table in dots or in percent of the page.

BGCOLOR=rrggb|color

Defines the background color of the table. Read the 'Text styles'chapter for more. Internet Explorer tag.

BORDERCOLOR=rrggb|color

Defines the border color of the table. Read the 'Text styles'chapter for more. Internet Explorer tag.

BORDERCOLORLIGHT=rrggb|color

Defines the light shadow color of the table. Read the 'Text styles'chapter for more. Internet Explorer tag.

BORDERCOLORDARK=rrggb|color

Defines the dark shadow color of the table. Read the 'Text styles'chapter for more. Internet Explorer tag.

Table tags

```
<CAPTION [ALIGN=TOP|BOTTOM]>text</CAPTION>
```

"text" will be the tables header. Use this tag inside the `<TABLE>` tag, but not within lines. You can show the header over or under the TABLE by setting ALIGN to TOP

resp. BOTTOM.

```
<TR [ALIGN=LEFT|CENTER|RIGHT] [VALIGN=TOP|MIDDLE|BOTTOM|
BASELINE]>
```

Start a new line in the table. ALIGN sets the horizontal adjustments for the lines text and VALIGN the vertical adjustment. Must end with </TR>

```
<TD|TH [ALIGN=LEFT|CENTER|RIGHT] [VALIGN=TOP|MIDDLE|BOTTOM
|BASELINE] [NOWRAP] [COLSPAN=N] [ROWSPAN=N] [WIDTH=N]>
```

TD and TH insert a new cell. TH stands for 'table header' and shows up the contents of the cell in bold. ALIGN sets the adjustments of the text. NOWRAP prevents the browser from wrapping the cell contents. COLSPAN can be used to let the cell go over more than one column. Normal is 1. ROWSPAN is the same thing, but let the cell go over more than one line. Normal settings is 1. WIDTH sets the width of the cell. Must end with </TD>