

exec

COLLABORATORS

	<i>TITLE :</i> exec		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY		March 28, 2025	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	exec	1
1.1	exec.doc	1
1.2	exec.library/AbortIO	2
1.3	exec.library/AddDevice	2
1.4	exec.library/AddHead	3
1.5	exec.library/AddIntServer	3
1.6	exec.library/AddLibrary	4
1.7	exec.library/AddMemList	5
1.8	exec.library/AddPort	5
1.9	exec.library/AddResource	6
1.10	exec.library/AddSemaphore	7
1.11	exec.library/AddTail	8
1.12	exec.library/AddTask	8
1.13	exec.library/Alert	9
1.14	exec.library/AllocAbs	10
1.15	exec.library/Allocate	11
1.16	exec.library/AllocEntry	13
1.17	exec.library/AllocMem	14
1.18	exec.library/AllocSignal	16
1.19	exec.library/AllocTrap	17
1.20	exec.library/AllocVec	18
1.21	exec.library/AttemptSemaphore	18
1.22	exec.library/AvailMem	19
1.23	exec.library/CacheClearE	20
1.24	exec.library/CacheClearU	21
1.25	exec.library/CacheControl	22
1.26	exec.library/CachePostDMA	22
1.27	exec.library/CachePreDMA	23
1.28	exec.library/Cause	24
1.29	exec.library/CheckIO	25

1.30	exec.library/CloseDevice	26
1.31	exec.library/CloseLibrary	26
1.32	exec.library/ColdReboot	27
1.33	exec.library/CopyMem	27
1.34	exec.library/CopyMemQuick	28
1.35	exec.library/CreateIORequest	29
1.36	exec.library/CreateMsgPort	29
1.37	exec.library/Deallocate	30
1.38	exec.library/Debug	30
1.39	exec.library/DeleteIORequest	31
1.40	exec.library/DeleteMsgPort	31
1.41	exec.library/Disable	32
1.42	exec.library/DoIO	33
1.43	exec.library/Enable	33
1.44	exec.library/Enqueue	34
1.45	exec.library/FindName	34
1.46	exec.library/FindPort	35
1.47	exec.library/FindResident	36
1.48	exec.library/FindSemaphore	36
1.49	exec.library/FindTask	37
1.50	exec.library/Forbid	37
1.51	exec.library/FreeEntry	38
1.52	exec.library/FreeMem	39
1.53	exec.library/FreeSignal	39
1.54	exec.library/FreeTrap	40
1.55	exec.library/FreeVec	40
1.56	exec.library/GetCC	41
1.57	exec.library/GetMsg	41
1.58	exec.library/InitCode	42
1.59	exec.library/InitResident	43
1.60	exec.library/InitSemaphore	44
1.61	exec.library/InitStruct	45
1.62	exec.library/Insert	46
1.63	exec.library/MakeFunctions	46
1.64	exec.library/MakeLibrary	47
1.65	exec.library/ObtainSemaphore	48
1.66	exec.library/ObtainSemaphoreList	49
1.67	exec.library/ObtainSemaphoreShared	50
1.68	exec.library/OldOpenLibrary	51

1.69	exec.library/OpenDevice	51
1.70	exec.library/OpenLibrary	53
1.71	exec.library/OpenResource	54
1.72	exec.library/Permit	54
1.73	exec.library/Procure	55
1.74	exec.library/PutMsg	55
1.75	exec.library/RawDoFmt	56
1.76	exec.library/ReleaseSemaphore	58
1.77	exec.library/ReleaseSemaphoreList	59
1.78	exec.library/RemDevice	59
1.79	exec.library/RemHead	60
1.80	exec.library/RemIntServer	61
1.81	exec.library/RemLibrary	61
1.82	exec.library/Remove	62
1.83	exec.library/RemPort	62
1.84	exec.library/RemResource	63
1.85	exec.library/RemSemaphore	63
1.86	exec.library/RemTail	64
1.87	exec.library/RemTask	64
1.88	exec.library/ReplyMsg	65
1.89	exec.library/SendIO	66
1.90	exec.library/SetExcept	66
1.91	exec.library/SetFunction	67
1.92	exec.library/SetIntVector	68
1.93	exec.library/SetSignal	69
1.94	exec.library/SetSR	69
1.95	exec.library/SetTaskPri	70
1.96	exec.library/Signal	71
1.97	exec.library/StackSwap	71
1.98	exec.library/SumKickData	72
1.99	exec.library/SumLibrary	73
1.100	exec.library/SuperState	74
1.101	exec.library/Supervisor	74
1.102	exec.library/TypeOfMem	75
1.103	exec.library/UserState	76
1.104	exec.library/Vacate	76
1.105	exec.library/Wait	77
1.106	exec.library/WaitIO	77
1.107	exec.library/WaitPort	78

Chapter 1

exec

1.1 exec.doc

AbortIO ()	Debug ()	PutMsg ()
AddDevice ()	DeleteIORequest ()	RawDoFmt ()
AddHead ()	DeleteMsgPort ()	ReleaseSemaphore ()
AddIntServer ()	Disable ()	ReleaseSemaphoreList ()
AddLibrary ()	DoIO ()	RemDevice ()
AddMemList ()	Enable ()	RemHead ()
AddPort ()	Enqueue ()	RemIntServer ()
AddResource ()	FindName ()	RemLibrary ()
AddSemaphore ()	FindPort ()	Remove ()
AddTail ()	FindResident ()	RemPort ()
AddTask ()	FindSemaphore ()	RemResource ()
Alert ()	FindTask ()	RemSemaphore ()
AllocAbs ()	Forbid ()	RemTail ()
Allocate ()	FreeEntry ()	RemTask ()
AllocEntry ()	FreeMem ()	ReplyMsg ()
AllocMem ()	FreeSignal ()	SendIO ()
AllocSignal ()	FreeTrap ()	SetExcept ()
AllocTrap ()	FreeVec ()	SetFunction ()
AllocVec ()	GetCC ()	SetIntVector ()
AttemptSemaphore ()	GetMsg ()	SetSignal ()
AvailMem ()	InitCode ()	SetSR ()
CacheClearE ()	InitResident ()	SetTaskPri ()
CacheClearU ()	InitSemaphore ()	Signal ()
CacheControl ()	InitStruct ()	StackSwap ()
CachePostDMA ()	Insert ()	SumKickData ()
CachePreDMA ()	MakeFunctions ()	SumLibrary ()
Cause ()	MakeLibrary ()	SuperState ()
CheckIO ()	ObtainSemaphore ()	Supervisor ()
CloseDevice ()	ObtainSemaphoreList ()	TypeOfMem ()
CloseLibrary ()	ObtainSemaphoreShared ()	UserState ()
ColdReboot ()	OldOpenLibrary ()	Vacate ()
CopyMem ()	OpenDevice ()	Wait ()
CopyMemQuick ()	OpenLibrary ()	WaitIO ()
CreateIORequest ()	OpenResource ()	WaitPort ()
CreateMsgPort ()	Permit ()	
Deallocate ()	Procure ()	

1.2 exec.library/AbortIO

NAME

AbortIO - attempt to abort an in-progress I/O request

SYNOPSIS

```
AbortIO(iORequest)
    A1
```

```
VOID AbortIO(struct IORequest *);
```

FUNCTION

Ask a device to abort a previously started IORequest. This is done by calling the device's ABORTIO vector, with your given IORequest.

AbortIO is a command the device that may or may not grant. If successful, the device will stop processing the IORequest, and reply to it earlier than it would otherwise have done.

NOTE

AbortIO() does NOT Remove() the IORequest from your ReplyPort, OR wait for it to complete. After an AbortIO() you must wait normally for the reply message before actually reusing the request.

If a request has already completed when AbortIO() is called, no action is taken.

EXAMPLE

```
AbortIO(timer_request);
WaitIO(timer_request);
/* Message is free to be reused */
```

INPUTS

iORequest - pointer to an I/O request block (must have been used at least once. May be active or finished).

SEE ALSO

WaitIO, DoIO, SendIO, CheckIO

1.3 exec.library/AddDevice

NAME

AddDevice -- add a device to the system

SYNOPSIS

```
AddDevice(device)
    A1
```

```
void AddDevice(struct Device *);
```

FUNCTION

This function adds a new device to the system device list, making it available to other programs. The device must be ready to be

opened at this time.

INPUTS

device - pointer to a properly initialized device node

SEE ALSO

RemDevice, OpenDevice, CloseDevice, MakeLibrary

1.4 exec.library/AddHead

NAME

AddHead -- insert node at the head of a list

SYNOPSIS

```
AddHead(list, node)
          A0    A1
```

```
void AddHead(struct List *, struct Node *)
```

FUNCTION

Add a node to the head of a doubly linked list. Assembly programmers may prefer to use the ADDHEAD macro from "exec/lists.i".

WARNING

This function does not arbitrate for access to the list. The calling task must be the owner of the involved list.

INPUTS

list - a pointer to the target list header
node - the node to insert at head

SEE ALSO

AddTail, Enqueue, Insert, Remove, RemHead, RemTail

1.5 exec.library/AddIntServer

NAME

AddIntServer -- add an interrupt server to a system server chain

SYNOPSIS

```
AddIntServer(intNum, interrupt)
              D0-0:4  A1
```

```
void AddIntServer(ULONG, struct Interrupt *);
```

FUNCTION

This function adds a new interrupt server to a given server chain. The node is located on the chain in a priority dependent position. If this is the first server on a particular chain, interrupts will be enabled for that chain.

Each link in the chain will be called in priority order until the chain ends or one of the servers returns with the 68000's Z condition code clear (indicating non-zero). Servers on the chain should return with the Z flag clear if the interrupt was specifically for that server, and no one else. VERTB servers should always return Z set. (Take care with High Level Language servers, the language may not have a mechanism for reliably setting the Z flag on exit).

Servers are called with the following register conventions:

```
D0 - scratch
D1 - scratch

A0 - scratch
A1 - server is_Data pointer (scratch)

A5 - jump vector register (scratch)
A6 - scratch

all other registers must be preserved
```

INPUTS

```
intNum - the Paula interrupt bit number (0 through 14). Processor
        level seven interrupts (NMI) are encoded as intNum 15.
        The PORTS, COPER, VERTB, EXTER and NMI interrupts are
        set up as server chains.

interrupt - pointer to an Interrupt structure.
        By convention, the LN_NAME of the interrupt structure must
        point a descriptive string so that other users may
        identify who currently has control of the interrupt.
```

WARNING

Some compilers or assemblers may optimize code in unexpected ways, affecting the conditions codes returned from the function. Watch out for a "MOVEM" instruction (which does not affect the condition codes) turning into "MOVE" (which does).

BUGS

The graphics library's VBLANK server, and some user code, currently assume that address register A0 will contain a pointer to the custom chips. If you add a server at a priority of 10 or greater, you must compensate for this by providing the expected value (\$DFF000).

SEE ALSO

RemIntServer, SetIntVector, hardware/intbits.i, exec/interrupts.i

1.6 exec.library/AddLibrary

NAME

AddLibrary -- add a library to the system

SYNOPSIS

```
AddLibrary(library)
        A1
```

```
void AddLibrary(struct Library *);
```

FUNCTION

This function adds a new library to the system, making it available to other programs. The library should be ready to be opened at this time. It will be added to the system library name list, and the checksum on the library entries will be calculated.

INPUTS

library - pointer to a properly initialized library structure

SEE ALSO

RemLibrary, CloseLibrary, OpenLibrary, MakeLibrary

1.7 exec.library/AddMemList

NAME

AddMemList - add memory to the system free pool

SYNOPSIS

```
AddMemList( size, attributes, pri, base, name )
             D0          D1          D2   A0   A1
```

```
void AddMemList(ULONG, ULONG, LONG, APTR, STRPTR);
```

FUNCTION

Add a new region of memory to the system free pool. The first few bytes will be used to hold the MemHeader structure. The remainder will be made available to the rest of the world.

INPUTS

size - the size (in bytes) of the memory area
 attributes - the attributes word that the memory pool will have
 pri - the priority for this memory. CHIP memory has a pri of -10, 16 bit expansion memory has a priority of 0. The higher the priority, the closer to the head of the memory list it will be placed.
 base - the base of the new memory area
 name - the name that will be used in the memory header, or NULL if no name is to be provided. This name is not copied, so it must remain valid for as long as the memory header is in the system.

SEE ALSO

AllocMem, exec/memory.h

1.8 exec.library/AddPort

NAME

AddPort -- add a public message port to the system

SYNOPSIS

```
AddPort(port)
    A1
```

```
void AddPort(struct MsgPort *);
```

FUNCTION

This function attaches a message port structure to the system's public message port list, where it can be found by the FindPort() function. The name and priority fields of the port structure must be initialized prior to calling this function. If the user does not require the priority field, it should be initialized to zero.

Only ports that will be searched for with FindPort() need to be added to the system list. In addition, adding ports is often useful during debugging. If the port will be searched for, the priority field should be at least 1 (to avoid the large number of inactive ports at priority zero). If the port will be searched for often, set the priority in the 50-100 range (so it will be before other less used ports).

Once a port has been added to the naming list, you must be careful to remove the port from the list (via RemPort) before deallocating its memory.

NOTE

A point of confusion is that clearing a MsgPort structure to all zeros is not enough to prepare it for use. As mentioned in the Exec chapter of the ROM Kernel Manual, the List for the MsgPort must be initialized. This is automatically handled by AddPort(), and amiga.lib/CreatePort. This initialization can be done manually with amiga.lib/NewList or the assembly NEWLIST macro.

Do not AddPort an active port.

INPUTS

port - pointer to a message port

SEE ALSO

RemPort, FindPort, amiga.lib/CreatePort, amiga.lib/NewList

1.9 exec.library/AddResource

NAME

AddResource -- add a resource to the system

SYNOPSIS

```
AddResource(resource)
    A1
```

```
void AddResource(APTR);
```

FUNCTION

This function adds a new resource to the system and makes it available to other users. The resource must be ready to be called at this time.

Resources currently have no system-imposed structure, however they must start with a standard named node (LN_SIZE), and should with a standard Library node (LIB_SIZE).

INPUTS

resource - pointer an initialized resource node

SEE ALSO

RemResource, OpenResource, MakeLibrary

1.10 exec.library/AddSemaphore

NAME

AddSemaphore -- initialize then add a signal semaphore to the system

SYNOPSIS

```
AddSemaphore(signalSemaphore)
    A1
```

```
void AddSemaphore(struct SignalSemaphore *);
```

FUNCTION

This function attaches a signal semaphore structure to the system's public signal semaphore list. The name and priority fields of the semaphore structure must be initialized prior to calling this function. If you do not want to let others rendezvous with this semaphore, use InitSemaphore() instead.

If a semaphore has been added to the naming list, you must be careful to remove the semaphore from the list (via RemSemaphore) before deallocating its memory.

Semaphores that are linked together in an allocation list (which ObtainSemaphoreList() would use) may not be added to the system naming list, because the facilities use the link field of the signal semaphore in incompatible ways

INPUTS

signalSemaphore -- an signal semaphore structure

BUGS

Does not work in Exec <V36. Instead use this code:

```
#include <exec/execbase.h>
#include <exec/nodes.h>
extern struct ExecBase *SysBase;
...
void LocalAddSemaphore(s)
struct SignalSemaphore *s;
{
    s->ss_Link.ln_Type=NT_SIGNALSEM;
    InitSemaphore(s);
    Forbid();
    Enqueue(&SysBase->SemaphoreList,s);
}
```

```
    Permit();  
}
```

SEE ALSO

RemSemaphore, FindSemaphore, InitSemaphore

1.11 exec.library/AddTail

NAME

AddTail -- append node to tail of a list

SYNOPSIS

```
AddTail(list, node)  
        A0      A1
```

```
void AddTail(struct List *, struct Node *);
```

FUNCTION

Add a node to the tail of a doubly linked list. Assembly programmers may prefer to use the ADDTAIL macro from "exec/lists.i".

WARNING

This function does not arbitrate for access to the list. The calling task must be the owner of the involved list.

INPUTS

list - a pointer to the target list header
node - a pointer to the node to insert at tail of the list

SEE ALSO

AddHead, Enqueue, Insert, Remove, RemHead, RemTail

1.12 exec.library/AddTask

NAME

AddTask -- add a task to the system

SYNOPSIS

```
AddTask(task, initialPC, finalPC)  
        A1      A2      A3
```

```
APTR AddTask(struct Task *, APTR, APTR);
```

FUNCTION

Add a task to the system. A reschedule will be run; the task with the highest priority in the system will start to execute (this may or may not be the new task).

Certain fields of the task control block must be initialized and a stack allocated prior to calling this function. The absolute smallest stack that is allowable is something in the range of 100

bytes, but in general the stack size is dependent on what subsystems are called. In general 256 bytes is sufficient if only Exec is called, and 4K will do if anything in the system is called. DO NOT UNDERESTIMATE. If you use a stack sniffing utility, leave a healthy pad above the minimum value. The system guarantees that its stack operations will leave the stack longword aligned.

This function will temporarily use space from the new task's stack for the task's initial set of registers. This space is allocated starting at the SPREG location specified in the task control block (not from SPUPPER). This means that a task's stack may contain static data put there prior to its execution. This is useful for providing initialized global variables or some tasks may want to use this space for passing the task its initial arguments.

A task's initial registers are set to zero (except the PC).

The TC_MEMENTRY field of the task structure may be extended by the user to hold additional MemLists (as returned by AllocEntry()). These will be automatically be deallocated at RemTask() time. If the code you have used to start the task has already added something to the MEMENTRY list, simply use AddHead to add your new MemLists in. If no initialization has been done, a NewList will need to be performed.

INPUTS

task - pointer to the task control block (TCB). All unset fields must be zero.
 initialPC - the initial entry point's address
 finalPC - the finalization code entry point's address. If zero, the system will use a general finalizer. This pointer is placed on the stack as if it were the outermost return address.

RESULTS

For V36, AddTask returns either a NULL or the address of the new task. Old code need not check this.

WARNING

Tasks are a low-level building block, and are unable to call dos.library, or any system function that might call dos.library. See the AmigaDOS CreateProc() for information on Processes.

SEE ALSO

RemTask, FindTask, amiga.lib/CreateTask, dos/CreateProc, amiga.lib/NewList

1.13 exec.library/Alert

NAME

Alert -- alert the user of an error

SYNOPSIS

```
Alert(alertNum)
    D7
```

```
void Alert(ULONG);
```

FUNCTION

Alerts the user of a serious system problem. This function will bring the system to a grinding halt, and do whatever is necessary to present the user with a message stating what happened. Interrupts are disabled, and an attempt to post the alert is made. If that fails, the system is reset. When the system comes up again, Exec notices the cause of the failure and tries again to post the alert.

If the Alert is a recoverable type, this call MAY return.

This call may be made at any time, including interrupts.

POST-MORTEM DIAGNOSIS

There are several options for determining the cause of a crash. Descriptions of each alert number can be found in the "alerts.h" include file. Low numbers not mentioned in the include file represent 68000 exceptions, see a 68000 manual for details. The most common numbers are:

```
$00000003 - Address Error
$00000004 - Illegal Instruction
```

A remote terminal can be attached to the Amiga's first built-in serial port. Set the communication parameters to 9600 baud, 8 bits, no parity. Before resetting the machine, the Alert function will blink the power LED 10 times. While the power indicator is flashing, pressing DELETE on the remote terminal will invoke the ROMWack debugger.

For Alerts caused by a 68000 exception, all registers are copied to a magic low memory location (currently 16 longwords at \$180).

INPUT

```
alertNum    - a number indicating the particular alert.  -1 is
               not a valid input.
```

NOTE

Much more needs to be said about this function and its implications.

SEE ALSO

```
exec/alerts.h
```

1.14 exec.library/AllocAbs

NAME

```
AllocAbs -- allocate at a given location
```

SYNOPSIS

```
memoryBlock = AllocAbs(byteSize, location)
D0           D0           A1
```

```
void *AllocAbs(ULONG, APTR);
```

FUNCTION

This function attempts to allocate memory at a given absolute memory location. Often this is used by boot-surviving entities such as recoverable ram-disks. If the memory is already being used, or if there is not enough memory to satisfy the request, AllocAbs will return NULL.

This block may not be exactly the same as the requested block because of rounding, but if the return value is non-zero, the block is guaranteed to contain the requested range.

INPUTS

byteSize - the size of the desired block in bytes
 This number is rounded up to the next larger
 block size for the actual allocation.
 location - the address where the memory MUST be.

RESULT

memoryBlock - a pointer to the newly allocated memory block, or
 NULL if failed.

NOTE

If the free list is corrupt, the system will panic with alert
 AN_MemCorrupt, \$01000005.

The 8 bytes past the end of an AllocAbs will be changed by Exec
 relinking the next block of memory. Generally you can't trust
 the first 8 bytes of anything you AllocAbs.

SEE ALSO

AllocMem, FreeMem

1.15 exec.library/Allocate

NAME

Allocate - allocate a block of memory

SYNOPSIS

```
memoryBlock=Allocate(memHeader, byteSize)
D0                      A0                      D0
```

```
void *Allocate(struct MemHeader *, ULONG);
```

FUNCTION

This function is used to allocate blocks of memory from a given private free memory pool (as specified by a MemHeader and its memory chunk list). Allocate will return the first free block that is greater than or equal to the requested size.

All blocks, whether free or allocated, will be block aligned; hence, all allocation sizes are rounded up to the next block even value (e.g. the minimum allocation resolution is currently 8 bytes. A request for 8 bytes will use up exactly 8 bytes. A request for 7 bytes will also use up exactly 8 bytes.).

This function can be used to manage an application's internal data memory. Note that no arbitration of the MemHeader and associated free chunk list is done. You must be the owner before calling Allocate.

INPUTS

memHeader - points to the local memory list header.
 byteSize - the size of the desired block in bytes.

RESULT

memoryBlock - a pointer to the just allocated free block.
 If there are no free regions large enough to satisfy the request, return zero.

EXAMPLE

```
#include <exec/types.h>
#include <exec/memory.h>
void *AllocMem();
#define BLOCKSIZE 4096L /* Or whatever you want */

void main()
{
    struct MemHeader *mh;
    struct MemChunk *mc;
    APTR    block1;
    APTR    block2;

    /* Get the MemHeader needed to keep track of our new block */
    mh = (struct MemHeader *)
        AllocMem((long)sizeof(struct MemHeader), MEMF_CLEAR );
    if( !mh )
        exit(10);

    /* Get the actual block the above MemHeader will manage */
    mc = (struct MemChunk *)AllocMem( BLOCKSIZE, 0L );
    if( !mc )
    {
        FreeMem( mh, (long)sizeof(struct MemHeader) ); exit(10);
    }

    mh->mh_Node.ln_Type = NT_MEMORY;
    mh->mh_Node.ln_Name = "myname";
    mh->mh_First = mc;
    mh->mh_Lower = (APTR) mc;
    mh->mh_Upper = (APTR) ( BLOCKSIZE + (ULONG) mc );
    mh->mh_Free = BLOCKSIZE;

    /* Set up first chunk in the freelist */
    mc->mc_Next = NULL;
    mc->mc_Bytes = BLOCKSIZE;

    block1 = (APTR) Allocate( mh, 20L );
    block2 = (APTR) Allocate( mh, 314L );
    printf("mh=%lx mc=%lx\n",mh,mc);
    printf("Block1=%lx, Block2=%lx\n",block1,block2);
```

```

    FreeMem( mh, (long)sizeof(struct MemHeader) );
    FreeMem( mc, BLOCKSIZE );
}

```

NOTE

If the free list is corrupt, the system will panic with alert AN_MemCorrupt, \$01000005.

SEE ALSO

Deallocate, exec/memory.h

1.16 exec.library/AllocEntry

NAME

AllocEntry -- allocate many regions of memory

SYNOPSIS

```

memList = AllocEntry(memList)
D0                      A0

```

```

struct MemList *AllocEntry(struct MemList *);

```

FUNCTION

This function takes a memList structure and allocates enough memory to hold the required memory as well as a MemList structure to keep track of it.

These MemList structures may be linked together in a task control block to keep track of the total memory usage of this task. (See the description of TC_MEMENTRY under RemTask).

INPUTS

memList -- A MemList structure filled in with MemEntry structures.

RESULTS

memList -- A different MemList filled in with the actual memory allocated in the me_Addr field, and their sizes in me_Length. If enough memory cannot be obtained, then the requirements of the allocation that failed is returned and bit 31 is set.

WARNING: The result is unusual! Bit 31 indicates failure.

EXAMPLES

The user wants five regions of 2, 4, 8, 16, and 32 bytes in size with requirements of MEMF_CLEAR, MEMF_PUBLIC, MEMF_CHIP!MEMF_CLEAR, MEMF_CLEAR, and MEMF_PUBLIC!MEMF_CLEAR respectively. The following code fragment would do that:

```

MemListDecl:
    DS.B    LN_SIZE          * reserve space for list node
    DC.W    5                * number of entries
    DC.L    MEMF_CLEAR        * entry #0
    DC.L    2
    DC.L    MEMF_PUBLIC        * entry #1
    DC.L    4

```

```

DC.L    MEMF_CHIP!MEMF_CLEAR      * entry #2
DC.L    8
DC.L    MEMF_CLEAR                * entry #3
DC.L    16
DC.L    MEMF_PUBLIC!MEMF_CLEAR    * entry #4
DC.L    32

```

start:

```

LEA.L    MemListDecl(PC),A0
JSR      _LVOAllocEntry(a6)
BCLR.L   #31,D0
BEQ.S    success

```

----- Type of memory that we failed on is in D0

BUGS

If any one of the allocations fails, this function fails to back out fully. This is fixed by the "SetPatch" program on V1.3 Workbench disks.

SEE ALSO

exec/memory.h

1.17 exec.library/AllocMem

NAME

AllocMem -- allocate memory given certain requirements

SYNOPSIS

```

memoryBlock = AllocMem(byteSize, attributes)
D0                      D0          D1

```

```
void *AllocMem(ULONG, ULONG);
```

FUNCTION

This is the memory allocator to be used by system code and applications. It provides a means of specifying that the allocation should be made in a memory area accessible to the chips, or accessible to shared system code.

Memory is allocated based on requirements and options. Any "requirement" must be met by a memory allocation, any "option" will be applied to the block regardless. AllocMem will try all memory spaces until one is found with the proper requirements and room for the memory request.

INPUTS

byteSize - the size of the desired block in bytes. (The operating system will automatically round this number to a multiple of the system memory chunk size)

attributes -
requirements

If no flags are set, the system will return the best

available memory block. For expanded systems, the fast memory pool is searched first.

MEMF_CHIP: If the requested memory will be used by the Amiga custom chips, this flag **must** be set.

Only certain parts of memory are reachable by the special chip sets' DMA circuitry. Chip DMA includes screen memory, images that are blitted, audio data, copper lists, sprites and Pre-V36 trackdisk.device buffers.

MEMF_FAST: This is non-chip memory. If no flag is set MEMF_FAST is taken as the default.

DO NOT SPECIFY MEMF_FAST unless you know exactly what you are doing! If MEMF_FAST is set, AllocMem() will fail on machines that only have chip memory! This flag may not be set when MEMF_CHIP is set.

MEMF_PUBLIC: Memory that must not be mapped, swapped, or otherwise made non-addressable. ALL MEMORY THAT IS REFERENCED VIA INTERRUPTS AND/OR BY OTHER TASKS MUST BE EITHER PUBLIC OR LOCKED INTO MEMORY! This includes both code and data.

MEMF_LOCAL: This is memory that will not go away after the CPU RESET instruction. Normally, autoconfig memory boards become unavailable after RESET while motherboard memory may still be available. This memory type is now automatically set in V36. Pre-V36 systems may not have this memory type and AllocMem() will then fail.

MEMF_24BITDMA: This is memory that is within the address range of 24-bit DMA devices. (Zorro-II) This is required if you run a Zorro-II DMA device on a machine that has memory beyond the 24-bit addressing limit of Zorro-II. This memory type is now automatically set in V36. Pre-V36 systems may not have this memory type and AllocMem() will then fail.

options

MEMF_CLEAR: The memory will be initialized to all zeros.

MEMF_REVERSE: This allocates memory from the top of the memory pool. It searches the pools in the same order, such that FAST memory will be found first. However, the memory will be allocated from the highest address available in the pool. This option is new as of V36.

RESULT

memoryBlock - a pointer to the newly allocated memory block.
If there are no free memory regions large enough to satisfy the request, zero will be returned. The pointer must be checked for zero before the memory block may be used!

WARNING

The result of any memory allocation MUST be checked, and a viable error handling path taken. ANY allocation may fail if memory has been filled.

EXAMPLES

```
AllocMem(64,0L)           - Allocate the best available memory
AllocMem(25,MEMF_CLEAR)   - Allocate the best available memory, and
                           clear it before returning.
AllocMem(128,MEMF_CHIP)   - Allocate chip memory
AllocMem(128,MEMF_CHIP|MEMF_CLEAR) - Allocate cleared chip memory
AllocMem(821,MEMF_CHIP|MEMF_PUBLIC|MEMF_CLEAR) - Allocate cleared,
public, chip memory.
```

NOTE

If the free list is corrupt, the system will panic with alert AN_MemCorrupt, \$01000005.

This function may not be called from interrupts.

A DOS process will have its pr_Result2 field set to ERROR_NO_FREE_STORE if the memory allocation fails.

SEE ALSO

FreeMem

1.18 exec.library/AllocSignal

NAME

AllocSignal -- allocate a signal bit

SYNOPSIS

```
signalNum = AllocSignal(signalNum)
D0                                D0

BYTE AllocSignal(BYTE);
```

FUNCTION

Allocate a signal bit from the current tasks' pool. Either a

particular bit, or the next free bit may be allocated. The signal associated with the bit will be properly initialized (cleared). At least 16 user signals are available per task. Signals should be deallocated before the task exits.

If the signal is already in use (or no free signals are available) a -1 is returned.

Allocated signals are only valid for use with the task that allocated them.

WARNING

Signals may not be allocated or freed from exception handling code.

INPUTS

signalNum - the desired signal number {of 0..31} or -1 for no preference.

RESULTS

signalNum - the signal bit number allocated {0..31}. If no signals are available, this function returns -1.

SEE ALSO

FreeSignal

1.19 exec.library/AllocTrap

NAME

AllocTrap -- allocate a processor trap vector

SYNOPSIS

```
trapNum = AllocTrap(trapNum)
D0                                D0
```

```
LONG AllocTrap(LONG);
```

FUNCTION

Allocate a trap number from the current task's pool. These trap numbers are those associated with the 68000 TRAP type instructions. Either a particular number, or the next free number may be allocated.

If the trap is already in use (or no free traps are available) a -1 is returned.

This function only affects the currently running task.

Traps are sent to the trap handler pointed at by tc_TrapCode. Unless changed by user code, this points to a standard trap handler. The stack frame of the exception handler will be:

```
0(SP) = Exception vector number. This will be in the
      range of 32 to 47 (corresponding to the
      Trap #1...Trap #15 instructions).
4(SP) = 68000/68010/68020/68030, etc. exception frame
```

tc_TrapData is not used.

WARNING

Traps may not be allocated or freed from exception handling code. You are not allowed to write to the exception table yourself. In fact, on some machines you will have trouble finding it - the VBR register may be used to remap its location.

INPUTS

trapNum - the desired trap number {of 0..15} or -1 for no preference.

RESULTS

trapNum - the trap number allocated {of 0..15}. If no traps are available, this function returns -1. Instructions of the form "Trap #trapNum" will be sent to the task's trap handler.

SEE ALSO

FreeTrap

1.20 exec.library/AllocVec

NAME

AllocVec -- allocate memory and keep track of the size (V36)

SYNOPSIS

```
memoryBlock = AllocVec(byteSize, attributes)
D0                                D0          D1
```

```
void *AllocVec(ULONG, ULONG);
```

FUNCTION

This function works identically to AllocMem(), but tracks the size of the allocation.

See the AllocMem() documentation for details.

WARNING

The result of any memory allocation MUST be checked, and a viable error handling path taken. ANY allocation may fail if memory has been filled.

SEE ALSO

FreeVec, AllocMem

1.21 exec.library/AttemptSemaphore

NAME

AttemptSemaphore -- try to obtain without blocking

SYNOPSIS

```
success = AttemptSemaphore(signalSemaphore)
D0                      A0
```

```
LONG AttemptSemaphore(struct SignalSemaphore *);
```

FUNCTION

This call is similar to ObtainSemaphore(), except that it will not block if the semaphore could not be locked.

INPUT

signalSemaphore -- an initialized signal semaphore structure

RESULT

success -- TRUE if the semaphore was locked, false if some other task already possessed the semaphore.

NOTE

This call does NOT preserve registers.

SEE ALSO

ObtainSemaphore() ObtainSemaphoreShared(), ReleaseSemaphore(),
exec/semaphores.h

1.22 exec.library/AvailMem

NAME

AvailMem -- memory available given certain requirements

SYNOPSIS

```
size = AvailMem(attributes)
D0                      D1
```

```
ULONG AvailMem(ULONG);
```

FUNCTION

This function returns the amount of free memory given certain attributes.

To find out what the largest block of a particular type is, add MEMF_LARGEST into the requirements argument. Returning the largest block is a slow operation.

WARNING

Due to the effect of multitasking, the value returned may not actually be the amount of free memory available at that instant.

INPUTS

requirements - a requirements mask as specified in AllocMem. Any of the AllocMem bits are valid, as is MEMF_LARGEST which returns the size of the largest block matching the requirements.

RESULT

size - total free space remaining (or the largest free block).

NOTE

For V36 Exec, AvailMem(MEMF_LARGEST) does a consistency check on the memory list. Alert AN_MemoryInsane will be pulled if any mismatch is noted.

EXAMPLE

```
AvailMem(MEMF_CHIP|MEMF_LARGEST);  
/* return size of largest available chip memory chunk */
```

SEE ALSO

exec/memory.h

1.23 exec.library/CacheClearE

NAME

CacheClearE - Cache clearing with extended control (V37)

SYNOPSIS

```
CacheClearE(address,length,caches)  
            a0      d0      d1
```

```
void CacheClearE(APTR,ULONG,ULONG);
```

FUNCTION

Flush out the contents of the CPU instruction and/or data caches. If dirty data cache lines are present, push them to memory first.

Motorola CPUs have separate instruction and data caches. A data write does not update the instruction cache. If an instruction is written to memory or modified, the old instruction may still exist in the cache. Before attempting to execute the code, a flush of the instruction cache is required.

For most systems, the data cache is not updated by Direct Memory Access (DMA), or if some external factor changes shared memory.

Caches must be cleared after *any* operation that could cause invalid or stale data. The most common cases are DMA and modifying instructions using the processor.

Some examples:

- Self modifying code
- Building Jump tables
- Run-time code patches
- Relocating code for use at different addresses.
- Loading code from disk

INPUTS

address - Address to start the operation. This may be rounded due to hardware granularity.

length - Length of area to be cleared, or \$FFFFFFFF to indicate all addresses should be cleared.

caches - Bit flags to indicate what caches to affect. The current supported flags are:

```

        CACRF_ClearI    ;Clear instruction cache
        CACRF_ClearD    ;Clear data cache
    All other bits are reserved for future definition.

```

NOTES

On systems with a copyback mode cache, any dirty data is pushed to memory as a part of this operation.

Regardless of the length given, the function will determine the most efficient way to implement the operation. For some cache systems, including the 68030, the overhead partially clearing a cache is often too great. The entire cache may be cleared.

For all current Amiga models, Chip memory is set with Instruction caching enabled, data caching disabled. This prevents coherency conflicts with the blitter or other custom chip DMA. Custom chip registers are marked as non-cacheable by the hardware.

The system takes care of appropriately flushing the caches for normal operations. The instruction cache is cleared by all calls that modify instructions, including LoadSeg(), MakeLibrary() and SetFunction().

SEE ALSO

exec/execbase.i, CacheControl, CacheClearU

1.24 exec.library/CacheClearU

NAME

CacheClearU - User callable simple cache clearing (V37)

SYNOPSIS

```
CacheClearU()
```

```
void CacheClearU(void);
```

FUNCTION

Flush out the contents of any CPU instruction and data caches. If dirty data cache lines are present, push them to memory first.

Caches must be cleared after *any* operation that could cause invalid or stale data. The most common cases are DMA and modifying instructions using the processor. See the CacheClearE() autodoc for a more complete description.

Some examples of when the cache needs clearing:

```

    Self modifying code
    Building Jump tables
    Run-time code patches
    Relocating code for use at different addresses.
    Loading code from disk

```

SEE ALSO

exec/execbase.i, CacheControl, CacheClearE

1.25 exec.library/CacheControl

NAME

CacheControl - Instruction & data cache control

SYNOPSIS

```
oldBits = CacheControl(cacheBits,cacheMask)
D0                      D0          D1
```

```
ULONG CacheControl(ULONG,ULONG);
```

FUNCTION

This function provides global control of any instruction or data caches that may be connected to the system. All settings are global -- per task control is not provided.

The action taken by this function will depend on the type of CPU installed. This function may be patched to support external caches, or different cache architectures. In all cases the function will attempt to best emulate the provided settings. Use of this function may save state specific to the caches involved.

The list of supported settings is provided in the exec/execbase.i include file. The bits currently defined map directly to the Motorola 68030 CPU CACR register. Alternate cache solutions may patch into the Exec cache functions. Where possible, bits will be interpreted to have the same meaning on the installed cache.

INPUTS

cacheBits - new values for the bits specified in cacheMask.

cacheMask - a mask with ones for all bits to be changed.

RESULT

oldBits - the complete prior values for all settings.

NOTE

As a side effect, this function clears all caches.

SEE ALSO

exec/execbase.i, CacheClearU, CacheClearE

1.26 exec.library/CachePostDMA

NAME

CachePostDMA - Take actions after to hardware DMA (V37)

SYNOPSIS

```
CachePostDMA(vaddress,&length,flags)
a0          a1          d0
```

```
CachePostDMA(APTR, LONG *,ULONG);
```

FUNCTION

Take all appropriate steps after Direct Memory Access (DMA). This function is primarily intended for writers of DMA device drivers. The action will depend on the CPU type installed, caching modes, and the state of any Memory Management Unit (MMU) activity.

As implemented

```

68000 - Do nothing
68010 - Do nothing
68020 - Do nothing
68030 - Flush the data cache
68040 - Flush matching areas of the data cache
????? - External cache boards, Virtual Memory Systems, or
        future hardware may patch this vector to best emulate
        the intended behavior.
        With a Bus-Snooping CPU, this function may end up
        doing nothing.

```

INPUTS

```

address - Same as initially passed to CachePreDMA
length  - Same as initially passed to CachePreDMA
flags    - Values:
            DMA_NoModify - If the area was not modified (and
            thus there is no reason to flush the cache) set
            this bit.

```

SEE ALSO

exec/execbase.i, CachePreDMA, CacheClearU, CacheClearE

1.27 exec.library/CachePreDMA

NAME

CachePreDMA - Take actions prior to hardware DMA (V37)

SYNOPSIS

```

paddress = CachePreDMA(vaddress,&length,flags)
d0              a0      a1      d0

```

```

APTR CachePreDMA(APTR, LONG *, ULONG);

```

FUNCTION

Take all appropriate steps before Direct Memory Access (DMA). This function is primarily intended for writers of DMA device drivers. The action will depend on the CPU type installed, caching modes, and the state of any Memory Management Unit (MMU) activity.

This function supports advanced cache architectures that have "copyback" modes. With copyback, write data may be cached, but not actually flushed out to memory. If the CPU has unflushed data at the time of DMA, data may be lost.

As implemented

```

68000 - Do nothing
68010 - Do nothing
68020 - Do nothing
68030 - Do nothing

```

- 68040 - Write any matching dirty cache lines back to memory. As a side effect of the 68040's design, matching data cache lines are also invalidated -- future CPUs may be different.
- ????? - External cache boards, Virtual Memory Systems, or future hardware may patch this vector to best emulate the intended behavior. With a Bus-Snooping CPU, this function may end up doing nothing.

INPUTS

- address - Base address to start the action.
- length - Pointer to a longword with a length.
- flags - Values:
 - DMA_Continue - Indicates this call is to complete a prior request that was broken up.

RESULTS

- paddress- Physical address that corresponds to the input virtual address.
- &length - This length value will be updated to reflect the contiguous length of physical memory present at paddress. This may be smaller than the requested length. To get the mapping for the next chunk of memory, call the function again with a new address, length, and the DMA_Continue flag.

NOTE

Due to processor granularity, areas outside of the address range may be affected by the cache flushing actions. Care has been taken to ensure that no harm is done outside the range, and that activities on overlapping cache lines won't harm data.

SEE ALSO

exec/execbase.i, CachePostDMA, CacheClearU, CacheClearE

1.28 exec.library/Cause

NAME

Cause -- cause a software interrupt

SYNOPSIS

```
Cause(interrupt)
    A1
```

```
void Cause(struct Interrupt *);
```

FUNCTION

This function causes a software interrupt to occur. If it is called from user mode (and processor level 0), the software interrupt will preempt the current task. This call is often used by high-level hardware interrupts to defer medium-length processing down to a lower interrupt level. Note that a software interrupt is still a real interrupt, and must obey the same restrictions on what system function it may call.

Currently only 5 software interrupt priorities are implemented: -32, -16, 0, +16, and +32. Priorities in between are truncated, values outside the -32/+32 range are not allowed.

NOTE

When setting up the Interrupt structure, set the node type to NT_INTERRUPT, or NT_UNKOWN.

IMPLEMENTATION

- 1> Checks if the node type is NT_SOFTINT. If so does nothing since the softint is already pending. No nest count is maintained.
- 2> Sets the node type to NT_SOFTINT.
- 3> Links into one of the 5 priority queues.
- 4> Pokes the hardware interrupt bit used for softints.

The node type returns to NT_INTERRUPT after removal from the list.

INPUTS

interrupt - pointer to a properly initialized interrupt node

BUGS

Unlike other Interrupts, SoftInts must preserve the value of A6.

1.29 exec.library/CheckIO

NAME

CheckIO -- get the status of an IORequest

SYNOPSIS

```
result = CheckIO(ioRequest)
D0                      A1
```

```
BOOL CheckIO(struct IORequest *);
```

FUNCTION

This function determines the current state of an I/O request and returns FALSE if the I/O has not yet completed. This function effectively hides the internals of the I/O completion mechanism.

CheckIO() will NOT remove the returned IORequest from the reply port. This is best performed with WaitIO(). If the request has already completed, WaitIO() will return quickly. Use of the Remove() function is dangerous, since other tasks may still be adding things to your message port; a Disable() would be required.

This function should NOT be used to busy loop (looping until IO is complete). WaitIO() is provided for that purpose.

INPUTS

ioRequest - pointer to an I/O request block

RESULTS

result - NULL if I/O is still in progress. Otherwise D0 points to the IORequest block.

NOTE

CheckIO can hang if called on an IORequest that has never been used. This occurs if LN_TYPE of the IORequest is set to "NT_MESSAGE". Instead simply set LN_TYPE to 0.

SEE ALSO

DoIO, SendIO, WaitIO, AbortIO

1.30 exec.library/CloseDevice

NAME

CloseDevice -- conclude access to a device

SYNOPSIS

CloseDevice(iORequest)
A1

```
void CloseDevice(struct IORequest *);
```

FUNCTION

This function informs the device that access to a device/unit previously opened has been concluded. The device may perform certain house-cleaning operations.

The user must ensure that all outstanding IORequests have been returned before closing the device. The AbortIO function can kill any stragglers.

After a close, the I/O request structure is free to be reused. Starting with V36 exec it is safe to CloseDevice() with an IORequest that is either cleared to zeros, or failed to open.

INPUTS

iORequest - pointer to an I/O request structure

SEE ALSO

OpenDevice

1.31 exec.library/CloseLibrary

NAME

CloseLibrary -- conclude access to a library

SYNOPSIS

CloseLibrary(library)
A1

```
void CloseLibrary(struct Library *);
```

FUNCTION

This function informs the system that access to the given library

has been concluded. The user must not reference the library or any function in the library after this close.

Starting with V36, it is safe to pass a NULL instead of a library pointer.

INPUTS

library - pointer to a library node

NOTE

Library writers must pass a SegList pointer or NULL back from their open point. This value is used by the system, and not visible as a return code from CloseLibrary.

SEE ALSO

OpenLibrary

1.32 exec.library/ColdReboot

NAME

ColdReboot - reboot the Amiga (V36)

SYNOPSIS

ColdReboot()

void ColdReboot(void);

FUNCTION

Reboot the machine. All external memory and peripherals will be RESET, and the machine will start its power up diagnostics.

This function never returns.

INPUT

A chaotic pile of disoriented bits.

RESULTS

An altogether totally integrated living system.

1.33 exec.library/CopyMem

NAME

CopyMem - general purpose memory copy function

SYNOPSIS

CopyMem(source, dest, size)
 A0 A1 D0

void CopyMem(APTR, APTR, ULONG);

FUNCTION

CopyMem is a general purpose, fast memory copy function. It can

deal with arbitrary lengths, with its pointers on arbitrary alignments. It attempts to optimize larger copies with more efficient copies, it uses byte copies for small moves, parts of larger copies, or the entire copy if the source and destination are misaligned with respect to each other.

Arbitrary overlapping copies are not supported.

The internal implementation of this function will change from system to system, and may be implemented via hardware DMA.

INPUTS

source - a pointer to the source data region
dest - a pointer to the destination data region
size - the size (in bytes) of the memory area. Zero copies
zero bytes

SEE ALSO

CopyMemQuick

1.34 exec.library/CopyMemQuick

NAME

CopyMemQuick - optimized memory copy function

SYNOPSIS

```
CopyMemQuick( source, dest, size )
               A0      A1      D0
```

```
void CopyMemQuick(ULONG *,ULONG *,ULONG);
```

FUNCTION

CopyMemQuick is a highly optimized memory copy function, with restrictions on the size and alignment of its arguments. Both the source and destination pointers must be longword aligned. In addition, the size must be an integral number of longwords (e.g. the size must be evenly divisible by four).

Arbitrary overlapping copies are not supported.

The internal implementation of this function will change from system to system, and may be implemented via hardware DMA.

INPUTS

source - a pointer to the source data region, long aligned
dest - a pointer to the destination data region, long aligned
size - the size (in bytes) of the memory area. Zero copies
zero bytes.

SEE ALSO

CopyMem

1.35 exec.library/CreateIORequest

NAME

CreateIORequest() -- create an IORequest structure (V36)

SYNOPSIS

```
ioReq = CreateIORequest( ioReplyPort, size );
                        A0          D0

struct IORequest *CreateIORequest(struct MsgPort *, ULONG);
```

FUNCTION

Allocates memory for and initializes a new IO request block of a user-specified number of bytes. The number of bytes must be at least as large as a "struct Message".

INPUTS

ioReplyPort - Pointer to a port for replies (an initialized message port, as created by CreateMsgPort()). If NULL, this function fails.
size - the size of the IO request to be created.

RESULT

ioReq - A pointer to the new IORequest block, or NULL.

SEE ALSO

DeleteIORequest, CreateMsgPort(), amiga.lib/CreateExtIO()

1.36 exec.library/CreateMsgPort

NAME

CreateMsgPort - Allocate and initialize a new message port (V36)

SYNOPSIS

```
CreateMsgPort()

struct MsgPort * CreateMsgPort(void);
```

FUNCTION

Allocates and initializes a new message port. The message list of the new port will be prepared for use (via NewList). A signal bit will be allocated, and the port will be set to signal your task when a message arrives (PA_SIGNAL).

You *must* use DeleteMsgPort() to delete ports created with CreateMsgPort() !

RESULT

MsgPort - A new MsgPort structure ready for use, or NULL if out of memory or signals. If you wish to add this port to the public port list, fill in the ln_Name and ln_Pri fields, then call AddPort(). Don't forget RemPort() !

SEE ALSO

```
DeleteMsgPort(), exec/AddPort(), exec/ports.h, amiga.lib/CreatePort()
```

1.37 exec.library/Deallocate

NAME

Deallocate -- deallocate a block of memory

SYNOPSIS

```
Deallocate(memHeader, memoryBlock, byteSize)
           A0          A1          D0
```

```
void Deallocate(struct MemHeader *,APTR,ULONG);
```

FUNCTION

This function deallocates memory by returning it to the appropriate private free memory pool. This function can be used to free an entire block allocated with the above function, or it can be used to free a sub-block of a previously allocated block. Sub-blocks must be an even multiple of the memory chunk size (currently 8 bytes).

This function can even be used to add a new free region to an existing MemHeader, however the extent pointers in the MemHeader will no longer be valid.

If memoryBlock is not on a block boundary (MEM_BLOCKSIZE) then it will be rounded down in a manner compatible with Allocate(). Note that this will work correctly with all the memory allocation functions, but may cause surprises if one is freeing only part of a region. The size of the block will be rounded up, so the freed block will fill to an even memory block boundary.

INPUTS

memHeader - points to the memory header this block is part of.
memoryBlock - address of memory block to free.
byteSize - the size of the block in bytes. If NULL, nothing happens.

SEE ALSO

Allocate, exec/memory.h

1.38 exec.library/Debug

NAME

Debug -- run the system debugger

SYNOPSIS

```
Debug(flags)
      D0
```

```
void Debug(ULONG);
```

FUNCTION

This function calls the system debugger. By default this debugger is "ROM-WACK". Other debuggers are encouraged to take over this entry point (via SetFunction()) so that when an application calls Debug(), the alternative debugger will get control. Currently a zero is passed to allow future expansion.

NOTE

The Debug() call may be made when the system is in a questionable state; if you have a SetFunction() patch, make few assumptions, be prepared for Supervisor mode, and be aware of differences in the Motorola stack frames on the 68000, '10, '20, and '30.

SEE ALSO

SetFunction
your favorite debugger's manual
the ROM-WACK chapter of the ROM Kernel Manual

1.39 exec.library/DeleteIORequest

NAME

DeleteIORequest() - Free a request made by CreateIORequest() (V36)

SYNOPSIS

```
DeleteIORequest( ioReq );  
                a0  
  
void DeleteIORequest(struct IORequest *);
```

FUNCTION

Frees up an IO request as allocated by CreateIORequest().

INPUTS

ioReq - A pointer to the IORequest block to be freed, or NULL.
This function uses the mn_Length field to determine how much memory to free.

SEE ALSO

CreateIORequest(), amiga.lib/DeleteExtIO()

1.40 exec.library/DeleteMsgPort

NAME

DeleteMsgPort - Free a message port created by CreateMsgPort (V36)

SYNOPSIS

```
DeleteMsgPort(msgPort)  
                a0  
  
void DeleteMsgPort(struct MsgPort *);
```

FUNCTION

Frees a message port created by `CreateMsgPort()`. All messages that may have been attached to this port must have already been replied to.

INPUTS

`msgPort` - A message port. NULL for no action.

SEE ALSO

`CreateMsgPort()`, `amiga.lib/DeletePort()`

1.41 `exec.library/Disable`

NAME

`Disable` -- disable interrupt processing.

SYNOPSIS

```
Disable();
```

```
void Disable(void);
```

FUNCTION

Prevents interrupts from being handled by the system, until a matching `Enable()` is executed. `Disable()` implies `Forbid()`.

DO NOT USE THIS CALL WITHOUT GOOD JUSTIFICATION. THIS CALL IS VERY DANGEROUS!

RESULTS

All interrupt processing is deferred until the task executing makes a call to `Enable()` or is placed in a wait state. Normal task rescheduling does not occur while interrupts are disabled. In order to restore normal interrupt processing, the programmer must execute exactly one call to `Enable()` for every call to `Disable()`.

IMPORTANT REMINDER:

It is important to remember that there is a danger in using disabled sections. Disabling interrupts for more than ~250 microseconds will prevent vital system functions (especially serial I/O) from operating in a normal fashion.

Think twice before using `Disable()`, then think once more. After all that, think again. With enough thought, the need for a `Disable()` can often be eliminated. For the user of many device drivers, a write to disable *only* the particular interrupt of interest can replace a `Disable()`. For example:

```
MOVE.W #INTF_PORTS,_intena
```

Do not use a macro for `Disable()`, insist on the real thing.

This call may be made from interrupts, it will have the effect of locking out all higher-level interrupts (lower-level interrupts are automatically disabled by the CPU).

Note: In the event of a task entering a `Wait()` after disabling interrupts, the system "breaks" the disabled state and runs

normally until the task which called Disable() is rescheduled.

NOTE

This call is guaranteed to preserve all registers.

SEE ALSO

Forbid, Permit, Enable

1.42 exec.library/DoIO

NAME

DoIO -- perform an I/O command and wait for completion

SYNOPSIS

```
error = DoIO(iORequest)
D0          A1
```

```
BYTE DoIO(struct IORequest *);
```

FUNCTION

This function requests a device driver to perform the I/O command specified in the I/O request. This function will always wait until the I/O request is fully complete.

DoIO() handles all the details, including Quick I/O, waiting for the request, and removing the reply message, etc..

IMPLEMENTATION

This function first tries to complete the IO via the "Quick I/O" mechanism. The io_Flags field is always set to IOF_QUICK (0x01) before the internal device call.

The LN_TYPE field is used internally to flag completion. Active requests have type NT_MESSAGE. Requests that have been replied have type NT_REPLYMSG. It is illegal to start IO using a still active IORequest, or a request with type NT_REPLYMSG.

INPUTS

iORequest - pointer to an IORequest initialized by OpenDevice()

RESULTS

error - a sign-extended copy of the io_Error field of the IORequest. Most device commands require that the error return be checked.

SEE ALSO

SendIO, CheckIO, WaitIO, AbortIO, amiga.lib/BeginIO

1.43 exec.library/Enable

NAME

Enable -- permit system interrupts to resume.

SYNOPSIS

```
Enable();  
  
void Enable(void);
```

FUNCTION

Allow system interrupts to again occur normally, after a matching Disable() has been executed.

RESULTS

Interrupt processing is restored to normal operation. The programmer must execute exactly one call to Enable() for every call to Disable().

NOTE

This call is guaranteed to preserve all registers.

SEE ALSO

Forbid, Permit, Disable

1.44 exec.library/Enqueue

NAME

Enqueue -- insert or append node to a system queue

SYNOPSIS

```
Enqueue(list, node)  
      A0      A1  
  
void Enqueue(struct List *, struct Node *);
```

FUNCTION

Insert or append a node into a system queue. The insert is performed based on the node priority -- it will keep the list properly sorted. New nodes will be inserted in front of the first node with a lower priority. Hence a FIFO queue for nodes of equal priority

WARNING

This function does not arbitrate for access to the list. The calling task must be the owner of the involved list.

INPUTS

list - a pointer to the system queue header
node - the node to enqueue. This must be a full featured list with type, priority and name fields.

SEE ALSO

AddHead, AddTail, Insert, Remove, RemHead, RemTail

1.45 exec.library/FindName

NAME

FindName -- find a system list node with a given name

SYNOPSIS

```
node = FindName(start, name)
D0,Z          A0      A1
```

```
struct Node *FindName(struct List *, STRPTR);
```

FUNCTION

Traverse a system list until a node with the given name is found. To find multiple occurrences of a string, this function may be called with a node starting point.

No arbitration is done for access to the list! If multiple tasks access the same list, an arbitration mechanism such as SignalSemaphores must be used.

INPUTS

start - a list header or a list node to start the search
(if node, this one is skipped)
name - a pointer to a name string terminated with NULL

RESULTS

node - a pointer to the node with the same name else
zero to indicate that the string was not found.

1.46 exec.library/FindPort

NAME

FindPort -- find a given system message port

SYNOPSIS

```
port = FindPort(name)
D0          A1
```

```
struct MsgPort *FindPort(STRPTR);
```

FUNCTION

This function will search the system message port list for a port with the given name. The first port matching this name will be returned. No arbitration of the port list is done. This function MUST be protected with A Forbid()/Permit() pair!

EXAMPLE

```
#include <exec/types.h>
struct MsgPort *FindPort();

ULONG SafePutToPort(message, portname)
struct Message *message;
STRPTR          portname;
{
    struct MsgPort *port;
```



```

    Forbid();
    port = FindPort(portname);
    if (port)
        PutMsg(port,message);
    Permit();
    return((ULONG)port); /* If zero, the port has gone away */
}

```

INPUT

name - name of the port to find

RETURN

port - a pointer to the message port, or zero if not found.

1.47 exec.library/FindResident

NAME

FindResident - find a resident module by name

SYNOPSIS

```

resident = FindResident(name)
D0                      A1

```

```

struct Resident *FindResident(STRPTR);

```

FUNCTION

Search the system resident tag list for a resident tag ("ROMTag") with the given name. If found return a pointer to the resident tag structure, else return zero.

Resident modules are used by the system to pull all its parts together at startup. Resident tags are also found in disk based devices and libraries.

INPUTS

name - pointer to name string

RESULT

resident - pointer to the resident tag structure or zero if none found.

SEE ALSO

exec/resident.h, InitResident

1.48 exec.library/FindSemaphore

NAME

FindSemaphore -- find a given system signal semaphore

SYNOPSIS

```

signalSemaphore = FindSemaphore(name)

```

D0

A1

```
struct SignalSemaphore *FindSemaphore(STRPTR);
```

FUNCTION

This function will search the system signal semaphore list for a semaphore with the given name. The first semaphore matching this name will be returned.

This function does not arbitrate for access to the semaphore list, surround the call with a Forbid()/Permit() pair.

INPUT

name - name of the semaphore to find

RESULT

semaphore - a pointer to the signal semaphore, or zero if not found.

1.49 exec.library/FindTask

NAME

FindTask -- find a task with the given name or find oneself

SYNOPSIS

```
task = FindTask(name)
D0      A1
```

```
struct Task *FindTask(STRPTR);
```

FUNCTION

This function will check all task queues for a task with the given name, and return a pointer to its task control block. If a NULL name pointer is given a pointer to the current task will be returned.

Finding oneself with a NULL for the name is very quick. Finding a task by name is very system expensive, and will disable interrupts for a long time. Since a task may remove itself at any time, a Forbid()/Permit() pair may be needed to ensure the pointer returned by FindTask() is still valid when used.

INPUT

name - pointer to a name string

RESULT

task - pointer to the task (or Process)

1.50 exec.library/Forbid

NAME

Forbid -- forbid task rescheduling.

SYNOPSIS

```
Forbid()
```

```
void Forbid(void);
```

FUNCTION

Prevents other tasks from being scheduled to run by the dispatcher, until a matching Permit() is executed, or this task is scheduled to Wait(). Interrupts are NOT disabled.

DO NOT USE THIS CALL WITHOUT GOOD JUSTIFICATION. THIS CALL IS DANGEROUS!

RESULTS

The current task will not be rescheduled as long as it is ready to run. In the event that the current task enters a wait state, other tasks may be scheduled. Upon return from the wait state, the original task will continue to run without disturbing the Forbid().

Calls to Forbid() nest. In order to restore normal task rescheduling, the programmer must execute exactly one call to Permit() for every call to Forbid().

WARNING

In the event of a task entering a Wait() after a Forbid(), the system "breaks" the forbidden state and runs normally until the task which called Forbid() is rescheduled. If caution is not taken, this can cause subtle bugs, since any device or DOS call will (in effect) cause your task to wait.

Forbid() is not useful or safe from within interrupt code (All interrupts are always higher priority than tasks, and interrupts are allowed to break a Forbid()).

NOTE

This call is guaranteed to preserve all registers.

SEE ALSO

Permit, Disable, ObtainSemaphore, ObtainSemaphoreShared

1.51 exec.library/FreeEntry

NAME

```
FreeEntry -- free many regions of memory
```

SYNOPSIS

```
FreeEntry(memList)
```

```
A0
```

```
void FreeEntry(struct MemList *);
```

FUNCTION

This function takes a memList structure (as returned by AllocEntry) and frees all the entries.

INPUTS

memList -- pointer to structure filled in with MemEntry
 structures

SEE ALSO

AllocEntry

1.52 exec.library/FreeMem

NAME

FreeMem -- deallocate with knowledge

SYNOPSIS

FreeMem(memoryBlock, byteSize)
 A1 D0

void FreeMem(void *,ULONG);

FUNCTION

Free a region of memory, returning it to the system pool from which it came. Freeing partial blocks back into the system pool is unwise.

NOTE

If a block of memory is freed twice, the system will Guru. The Alert is AN_FreeTwice (\$01000009). If you pass the wrong pointer, you will probably see AN_MemCorrupt \$01000005. Future versions may add more sanity checks to the memory lists.

INPUTS

memoryBlock - pointer to the memory block to free
byteSize - the size of the desired block in bytes. (The operating system will automatically round this number to a multiple of the system memory chunk size)

SEE ALSO

AllocMem

1.53 exec.library/FreeSignal

NAME

FreeSignal -- free a signal bit

SYNOPSIS

FreeSignal(signalNum)
 D0

void FreeSignal(BYTE);

FUNCTION

This function frees a previously allocated signal bit for reuse. This call must be performed while running in the same task in which

the signal was allocated.

WARNING

Signals may not be allocated or freed from exception handling code.

NOTE

Starting with V37, an attempt to free signal -1 is harmless.

INPUTS

signalNum - the signal number to free {0..31}.

1.54 exec.library/FreeTrap

NAME

FreeTrap -- free a processor trap

SYNOPSIS

```
FreeTrap(trapNum)
    D0
```

```
void FreeTrap(ULONG);
```

FUNCTION

This function frees a previously allocated trap number for reuse. This call must be performed while running in the same task in which the trap was allocated.

WARNING

Traps may not be allocated or freed from exception handling code.

INPUTS

trapNum - the trap number to free {of 0..15}

1.55 exec.library/FreeVec

NAME

FreeVec -- return AllocVec() memory to the system (V36)

SYNOPSIS

```
FreeVec(memoryBlock)
    A1
```

```
void FreeVec(void *);
```

FUNCTION

Free an allocation made by the AllocVec() call. The memory will be returned to the system pool from which it came.

NOTE

If a block of memory is freed twice, the system will Guru. The Alert is AN_FreeTwice (\$01000009). If you pass the wrong pointer, you will probably see AN_MemCorrupt \$01000005. Future versions may

add more sanity checks to the memory lists.

INPUTS

memoryBlock - pointer to the memory block to free, or NULL.

SEE ALSO

AllocVec

1.56 exec.library/GetCC

NAME

GetCC -- get condition codes in a 68010 compatible way.

SYNOPSIS

```
conditions = GetCC()  
D0
```

```
UWORD GetCC(void);
```

FUNCTION

The 68000 processor has a "MOVE SR,<ea>" instruction which gets a copy of the processor condition codes.

On the 68010,20 and 30 CPUs, "MOVE SR,<ea>" is privileged. User code will trap if it is attempted. These processors need to use the "MOVE CCR,<ea>" instruction instead.

This function provides a means of obtaining the CPU condition codes in a manner that will make upgrades transparent. This function is VERY short and quick.

RESULTS

conditions - the 680XX condition codes

NOTE

This call is guaranteed to preserve all registers. This function may be implemented as code right in the jump table.

1.57 exec.library/GetMsg

NAME

GetMsg -- get next message from a message port

SYNOPSIS

```
message = GetMsg(port)  
D0      A0
```

```
struct Message *GetMsg(struct MsgPort *);
```

FUNCTION

This function receives a message from a given message port. It provides a fast, non-copying message receiving mechanism. The

received message is removed from the message port.

This function will not wait. If a message is not present this function will return zero. If a program must wait for a message, it can `Wait()` on the signal specified for the port or use the `WaitPort()` function. There can only be one task waiting for any given port.

Getting a message does not imply to the sender that the message is free to be reused by the sender. When the receiver is finished with the message, it may `ReplyMsg()` it back to the sender.

Getting a signal does NOT always imply a message is ready. More than one message may arrive per signal, and signals may show up without messages. Typically you must loop to `GetMsg()` until it returns zero, then `Wait()` or `WaitPort()`.

INPUT

port - a pointer to the receiver message port

RESULT

message - a pointer to the first message available. If there are no messages, return zero.
Callers must be prepared for zero at any time.

SEE ALSO

`PutMsg`, `ReplyMsg`, `WaitPort`, `Wait`, `exec/ports.h`

1.58 exec.library/InitCode

NAME

`InitCode` - initialize resident code modules (internal function)

SYNOPSIS

```
InitCode(startClass, version)
          D0          D1
```

```
void InitCode(ULONG,ULONG);
```

FUNCTION

(This function may be ignored by application programmers)

Call `InitResident()` for all resident modules in the `ResModules` array with the given `startClass` and with versions equal or greater than that specified. The `segList` parameter is passed as zero.

Resident modules are used by the system to pull all its parts together at startup. Modules are initialized in a prioritized order.

Modules that do not have a `startclass` should be of priority -120. `RTF_AFTERDOS` modules should start at -100 (working down).

INPUTS

`startClass` - the class of code to be initialized:

```

        BITDEF RT,COLDSTART,0
        BITDEF RT,SINGLETASK,1 ;ExecBase->ThisTask==0 (V36 only)
        BITDEF RT,AFTERDOS,2 ;(V36 only)
version - a major version number

```

SEE ALSO

ResidentTag (RT) structure definition (resident.h)

1.59 exec.library/InitResident

NAME

InitResident - initialize resident module

SYNOPSIS

```

object = InitResident(resident, segList)
D0                      A1          D1

```

```

APTR InitResident(struct Resident *,ULONG);

```

FUNCTION

Initialize a ROMTag. ROMTags are used to link system modules together. Each disk based device or library must contain a ROMTag structure in the first code hunk.

Once the validity of the ROMTag is verified, the RT_INIT pointer is jumped to with the following registers:

```

D0 = 0
A0 = segList
A6 = ExecBase

```

INPUTS

```

resident - Pointer to a ROMTag
segList  - SegList of the loaded object, if loaded from disk.
           Libraries & Devices will cache this value for later
           return at close or expunge time. Pass NULL for ROM
           modules.

```

RESULTS

```

object - Return value from the init code, usually the library
        or device base. NULL for failure.

```

AUTOINIT FEATURE

An automatic method of library/device base and vector table initialization is also provided by InitResident(). The initial code hunk of the library or device should contain "MOVEQ #-1,d0; RTS;". Following that must be an initialized Resident structure with RTF_AUTOINIT set in rt_Flags, and an rt_Init pointer which points to four longwords. These four longwords will be used in a call to MakeLibrary();

- The size of your library/device base structure including initial Library or Device structure.
- A pointer to a longword table of standard, then library specific function offsets, terminated with -1L.

(short format offsets are also acceptable)

- Pointer to data table in exec/InitStruct format for initialization of Library or Device structure.
- Pointer to library initialization function, or NULL.

Calling sequence:

```
D0 = library base
A0 = segList
A6 = ExecBase
```

This function must return in D0 the library/device base to be linked into the library/device list. If the initialization function fails, the device memory must be manually deallocated, then NULL returned in D0.

SEE ALSO

exec/resident.i, FindResident

1.60 exec.library/InitSemaphore

NAME

InitSemaphore -- initialize a signal semaphore

SYNOPSIS

```
InitSemaphore(signalSemaphore)
    A0
```

```
void InitSemaphore(struct SignalSemaphore *);
```

FUNCTION

This function initializes a signal semaphore and prepares it for use. It does not allocate anything, but does initialize list pointers and the semaphore counters.

Semaphores are often used to protect critical data structures or hardware that can only be accessed by one task at a time. After initialization, the address of the SignalSemaphore may be made available to any number of tasks. Typically a task will try to ObtainSemaphore(), passing this address in. If no other task owns the semaphore, then the call will lock and return quickly. If more tasks try to ObtainSemaphore(), they will be put to sleep. When the owner of the semaphore releases it, the next waiter in turn will be woken up.

Semaphores are often preferable to the old-style Forbid()/Permit() type arbitration. With Forbid()/Permit() *all* other tasks are prevented from running. With semaphores, only those tasks that need access to whatever the semaphore protects are subject to waiting.

INPUT

```
signalSemaphore -- a signal semaphore structure (with all fields
    set to zero before the call)
```

SEE ALSO

```
ObtainSemaphore(), ObtainSemaphoreShared(), AttemptSemaphore(),
ReleaseSemaphore(), exec/semaphores.h
```

1.61 exec.library/InitStruct

NAME

InitStruct - initialize memory from a table

SYNOPSIS

```
InitStruct(initTable, memory, size);
           A1          A2          D0

void InitStruct(struct InitStruct *, APTR, ULONG);
```

FUNCTION

Clear a memory area, then set up default values according to the data and offset values in the initTable. Typically only assembly programs take advantage of this function, and only with the macros defined in "exec/initializers.i".

The initialization table has byte commands to

```
      |a      ||byte|      |given||byte|      |once      |
load |count||word| into |next ||rptr| offset, |repetitively |
      |long|
```

Not all combinations are supported. The offset, when specified, is relative to the memory pointer provided (Memory), and is initially zero. The initialization data (InitTable) contains byte commands whose 8 bits are interpreted as follows:

ddssnnnn

```
dd  the destination type (and size):
    00 no offset, use next destination, nnnn is count
    01 no offset, use next destination, nnnn is repeat
    10 destination offset is in the next byte, nnnn is count
    11 destination offset is in the next 24-bits, nnnn is count
ss  the size and location of the source:
    00 long, from the next two aligned words
    01 word, from the next aligned word
    10 byte, from the next byte
    11 ERROR - will cause an ALERT (see below)
nnnn the count or repeat:
    count the (number+1) of source items to copy
    repeat the source is copied (number+1) times.
```

initTable commands are always read from the next even byte. Given destination offsets are always relative to the memory pointer (A2).

The command %00000000 ends the InitTable stream: use %00010001 if you really want to copy one longword without a new offset.

24 bit APTR not supported for 68020 compatibility -- use long.

INPUTS

initTable - the beginning of the commands and data to init Memory with. Must be on an even boundary unless only byte initialization is done. End table with "dc.b 0" or "dc.w 0".

memory - the beginning of the memory to initialize. Must be on an even boundary if size is specified.

size - the size of memory, which is used to clear it before initializing it via the initTable. If Size is zero, memory is not cleared before initializing.

size must be an even number.

SEE ALSO

exec/initializers.i

1.62 exec.library/Insert

NAME

Insert -- insert a node into a list

SYNOPSIS

```
Insert(list, node, listNode)
      A0      A1      A2
```

```
void Insert(struct List *, struct Node *, struct Node *);
```

FUNCTION

Insert a node into a doubly linked list AFTER a given node position. Insertion at the head of a list is possible by passing a zero value for listNode, though the AddHead function is slightly faster for that special case.

WARNING

This function does not arbitrate for access to the list. The calling task must be the owner of the involved list.

INPUTS

list - a pointer to the target list header
node - the node to insert
listNode - the node after which to insert

SEE ALSO

AddHead, AddTail, Enqueue, RemHead, Remove, RemTail

1.63 exec.library/MakeFunctions

NAME

MakeFunctions -- construct a function jump table

SYNOPSIS

```
tableSize = MakeFunctions(target, functionArray, funcDispBase)
      D0                                A0      A1      A2
```

```
ULONG MakeFunctions (APTR, APTR, APTR);
```

FUNCTION

A low level function used by MakeLibrary to build jump tables of the type used by libraries, devices and resources. It allows the table to be built anywhere in memory, and can be used both for initialization and replacement. This function also supports function pointer compression by expanding relative displacements into absolute pointers.

The processor instruction cache is cleared after the table building.

INPUT

destination - the target address for the high memory end of the function jump table. Typically this will be the library base pointer.

functionArray - pointer to an array of function pointers or function displacements. If funcDispBase is zero, the array is assumed to contain absolute pointers to functions. If funcDispBase is not zero, then the array is assumed to contain word displacements to functions. In both cases, the array is terminated by a -1 (of the same size as the actual entry).

funcDispBase - pointer to the base about which all function displacements are relative. If zero, then the function array contains absolute pointers.

RESULT

tableSize - size of the new table in bytes (for LIB_NEGSIZE).

SEE ALSO

exec/MakeLibrary

1.64 exec.library/MakeLibrary

NAME

MakeLibrary -- construct a library

SYNOPSIS

```
library = MakeLibrary(vectors, structure, init, dSize, segList)
D0                      A0      A1      A2      D0      D1
```

```
struct Library *MakeLibrary
                      (APTR, struct InitStruct *, APTR, ULONG, BPTR);
```

FUNCTION

This function is used for constructing a library vector and data area. The same call is used to make devices. Space for the library is allocated from the system's free memory pool. The data portion of the library is initialized. init may point to a library specific entry point.

NOTE

Starting with V36, the library base is longword adjusted. The lib_PosSize and lib_NegSize fields of the library structure are adjusted to match.

INPUTS

vectors - pointer to an array of function pointers or function displacements. If the first word of the array is -1, then the array contains relative word displacements (based off of vectors); otherwise, the array contains absolute function pointers. The vector list is terminated by a -1 (of the same size as the pointers).

structure - points to an "InitStruct" data region. If NULL, then it will not be used.

init - If non-NULL, an entry point that will be called before adding the library to the system. Registers are as follows:

```
d0 = libAddr    ;Your Library Address
a0 = segList    ;Your AmigaDOS segment list
a6 = ExecBase   ;Address of exec.library
```

The result of the init function must be the library address, or NULL for failure. If NULL, the init point must manually deallocate the library base memory (based on the sizes stored in lib_PosSize and lib_NegSize).

dSize - the size of the library data area, including the standard library node data. This must be at least sizeof(struct Library).

segList - pointer to an AmigaDOS SegList (segment list). This is passed to a library's init code, and is used later for removing the library from memory.

RESULT

library - the reference address of the library. This is the address used in references to the library, not the beginning of the memory area allocated. If the library vector table require more system memory than is available, this function will return NULL.

SEE ALSO

InitStruct, InitResident, exec/initializers.i

1.65 exec.library/ObtainSemaphore

NAME

ObtainSemaphore -- gain exclusive access to a semaphore

SYNOPSIS

```
ObtainSemaphore(signalSemaphore)
    A0
```

```
void ObtainSemaphore(struct SignalSemaphore *);
```

FUNCTION

Signal semaphores are used to gain exclusive access to an object. ObtainSemaphore is the call used to gain this access. If another user currently has the semaphore locked the call will block until the object is available.

If the current task already has locked the semaphore and attempts to lock it again the call will still succeed. A "nesting count" is incremented each time the current owning task of the semaphore calls ObtainSemaphore(). This counter is decremented each time ReleaseSemaphore() is called. When the counter returns to zero the semaphore is actually released, and the next waiting task is called.

A queue of waiting tasks is maintained on the stacks of the waiting tasks. Each will be called in turn as soon as the current task releases the semaphore.

Signal Semaphores are different than Procure()/Vacate() semaphores. The former requires less CPU time, especially if the semaphore is not currently locked. They require very little set up and user thought. The latter flavor of semaphore make no assumptions about how they are used -- they are completely general. Unfortunately they are not as efficient as signal semaphores, and require the locker to have done some setup before doing the call.

INPUT

signalSemaphore -- an initialized signal semaphore structure

NOTE

This function preserves all registers (see BUGS).

BUGS

Until V37, this function could destroy A0.

SEE ALSO

ObtainSemaphoreShared(), InitSemaphore(), ReleaseSemaphore(), AttemptSemaphore(), ObtainSemaphoreList()

1.66 exec.library/ObtainSemaphoreList

NAME

ObtainSemaphoreList -- get a list of semaphores.

SYNOPSIS

```
ObtainSemaphoreList(list)
                    A0
```

```
void ObtainSemaphoreList(struct List *);
```

FUNCTION

Signal semaphores may be linked together into a list. This function takes a list of these semaphores and attempts to lock all of them at once. This call is preferable to applying ObtainSemaphore() to each element in the list because it attempts to lock all the elements simultaneously, and won't deadlock if someone is attempting to lock

in some other order.

This function assumes that only one task at a time will attempt to lock the entire list of semaphores. In other words, there needs to be a higher level lock (perhaps another signal semaphore...) that is used before someone attempts to lock the semaphore list via `ObtainSemaphoreList()`.

Note that deadlocks may result if this call is used AND someone attempts to use `ObtainSemaphore()` to lock more than one semaphore on the list. If you wish to lock more than semaphore (but not all of them) then you should obtain the higher level lock (see above)

INPUT

`list` -- a list of signal semaphores

SEE ALSO

`InitSemaphore()`, `ReleaseSemaphoreList()`

1.67 `exec.library/ObtainSemaphoreShared`

NAME

`ObtainSemaphoreShared` -- gain shared access to a semaphore (V36)

SYNOPSIS

```
ObtainSemaphoreShared(signalSemaphore)
                        a0
```

```
void ObtainSemaphoreShared(struct SignalSemaphore *);
```

FUNCTION

A lock on a signal semaphore may either be exclusive, or shared. Exclusive locks are granted by the `ObtainSemaphore()` and `AttemptSemaphore()` functions. Shared locks are granted by `ObtainSemaphoreShared()`. Calls may be nested.

Any number of tasks may simultaneously hold a shared lock on a semaphore. Only one task may hold an exclusive lock. A typical application is a list that is often read, but only occasionally written to.

Any exclusive locker will be held off until all shared lockers release the semaphore. Likewise, if an exclusive lock is held, all potential shared lockers will block until the exclusive lock is released. All shared lockers are restarted at the same time.

EXAMPLE

```
ObtainSemaphoreShared(ss);
/* read data */
ReleaseSemaphore(ss);

ObtainSemaphore(ss);
/* modify data */
ReleaseSemaphore(ss);
```

NOTES

While this function was added for V36, the feature magically works with all older semaphore structures.

A task owning a shared lock must not attempt to get an exclusive lock on the same semaphore.

INPUT

signalSemaphore -- an initialized signal semaphore structure

NOTE

This call is guaranteed to preserve all registers, starting with V37 exec.

RESULT

SEE ALSO

InitSemaphore(), ReleaseSemaphore()

1.68 exec.library/OldOpenLibrary

NAME

OldOpenLibrary -- obsolete OpenLibrary

SYNOPSIS

```
library = OldOpenLibrary(libName)
D0                                A1
```

```
struct Library *OldOpenLibrary(APTR);
```

FUNCTION

The 1.0 release of the Amiga system had an incorrect version of OpenLibrary that did not check the version number during the library open. This obsolete function is provided so that object code compiled using a 1.0 system will still run.

This exactly the same as "OpenLibrary(libName,0L);"

INPUTS

libName - the name of the library to open

RESULTS

library - a library pointer for a successful open, else zero

SEE ALSO

CloseLibrary

1.69 exec.library/OpenDevice

NAME

OpenDevice -- gain access to a device

SYNOPSIS

```
error = OpenDevice(devName, unitNumber, iORequest, flags)
D0          A0          D0          A1          D1
```

```
BYTE OpenDevice(STRPTR,ULONG,struct IORequest *,ULONG);
```

FUNCTION

This function opens the named device/unit and initializes the given I/O request block. Specific documentation on opening procedures may come with certain devices.

The device may exist in memory, or on disk; this is transparent to the OpenDevice caller.

A full path name for the device name is legitimate. For example "test:devs/fred.device". This allows the use of custom devices without requiring the user to copy the device into the system's DEVS: directory.

NOTES

All calls to OpenDevice should have matching calls to CloseDevice!

Devices on disk cannot be opened until after DOS has been started.

As of V36 tasks can safely call OpenDevice, though DOS may open system requesters (e.g., asking the user to insert the Workbench disk if DEVS: is not online). You must call this function from a DOS Process if you want to turn off DOS requesters.

INPUTS

devName - requested device name

unitNumber - the unit number to open on that device. The format of the unit number is device specific. If the device does not have separate units, send a zero.

iORequest - the I/O request block to be returned with appropriate fields initialized.

flags - additional driver specific information. This is sometimes used to request opening a device with exclusive access.

RESULTS

error - Returns a sign-extended copy of the io_Error field of the IORequest. Zero if successful, else an error code is returned.

BUGS

AmigaDOS file names are not case sensitive, but Exec lists are. If the library name is specified in a different case than it exists on disk, unexpected results may occur.

Prior to V36, tasks could not make OpenDevice calls requiring disk access (since tasks are not allowed to make dos.library calls). Now OpenDevice is protected from tasks.

SEE ALSO

CloseDevice, DoIO, SendIO, CheckIO, AbortIO, WaitIO

1.70 exec.library/OpenLibrary

NAME

OpenLibrary -- gain access to a library

SYNOPSIS

```
library = OpenLibrary(libName, version)
D0                      A1          D0
```

```
struct Library *OpenLibrary(STRPTR, ULONG);
```

FUNCTION

This function returns a pointer to a library that was previously installed into the system. If the requested library exists, and if the library version is greater than or equal to the requested version, then the open will succeed.

The device may exist in memory, or on disk; this is transparent to the OpenDevice caller. Only Processes are allowed to call OpenLibrary (since OpenLibrary may in turn call dos.library).

A full path name for the library name is legitimate. For example "wp:libs/wp.library". This allows the use of custom libraries without requiring the user to copy the library into the system's LIBS: directory.

NOTES

All calls to OpenLibrary should have matching calls to CloseLibrary!

Libraries on disk cannot be opened until after DOS has been started.

As of V36 tasks can safely call OpenLibrary, though DOS may open system requesters (e.g., asking the user to insert the Workbench disk if LIBS: is not online). You must call this function from a DOS Process if you want to turn off DOS requesters.

INPUTS

libName - the name of the library to open

version - the version of the library required.

RESULTS

library - a library pointer for a successful open, else zero

BUGS

AmigaDOS file names are not case sensitive, but Exec lists are. If the library name is specified in a different case than it exists on disk, unexpected results may occur.

Prior to V36, tasks could not make OpenLibrary calls requiring disk access (since tasks are not allowed to make dos.library calls).

Now OpenLibrary is protected from tasks.

The version number of the resident tag in disk based library must match the version number of the library, or V36 may fail to load it.

SEE ALSO

CloseLibrary

1.71 exec.library/OpenResource

NAME

OpenResource -- gain access to a resource

SYNOPSIS

```
resource = OpenResource(resName)
D0                                A1
```

```
APTR OpenResource(STRPTR);
```

FUNCTION

This function returns a pointer to a resource that was previously installed into the system.

There is no CloseResource() function.

INPUTS

resName - the name of the resource requested.

RESULTS

resource - if successful, a resource pointer, else NULL

1.72 exec.library/Permit

NAME

Permit -- permit task rescheduling.

SYNOPSIS

```
Permit()
```

```
void Permit(void);
```

FUNCTION

Allow other tasks to be scheduled to run by the dispatcher, after a matching Forbid() has been executed.

RESULTS

Other tasks will be rescheduled as they are ready to run. In order to restore normal task rescheduling, the programmer must execute exactly one call to Permit() for every call to Forbid().

NOTE

This call is guaranteed to preserve all registers.

SEE ALSO

Forbid, Disable, Enable

1.73 exec.library/Procure

NAME

Procure -- bid for a message lock (semaphore)

SYNOPSIS

```
result = Procure(semaphore, bidMessage)
```

```
D0                      A0          A1
```

```
BYTE Procure(struct Semaphore *, struct Message *);
```

FUNCTION

This function is used to obtain a message based semaphore lock. If the lock is immediate, Procure() returns a true result, and the bidMessage is not used. If the semaphore is already locked, Procure() returns false, and the task must wait for the bidMessage to arrive at its reply port.

Straight "Semaphores" use the message system. They are therefore queueable, and users may wait on several of them at the same time. This makes them more powerful than "Signal Semaphores"

INPUT

semaphore - a semaphore message port. This port is used to queue all pending lockers. This port should be initialized with the PA_IGNORE option, as the MP_SigTask field is used for a pointer to the current locker message (not a task). New semaphore ports must also have the SM_BIDS word initialized to -1. If the semaphore is public, it should be named, its priority set, and the added with AddPort. Message port priority is often used for anti-deadlock locking conventions.

RESULT

result - true when the semaphore is free. In such cases no waiting needs to be done. If false, then the task should wait at its bidMessage reply port.

BUGS

Procure() and Vacate() do not have proven reliability.

SEE ALSO

Vacate()

1.74 exec.library/PutMsg

NAME

PutMsg -- put a message to a message port

SYNOPSIS

```
PutMsg(port, message)
      A0      A1
```

```
void PutMsg(struct MsgPort *, struct Message *);
```

FUNCTION

This function attaches a message to the end of a given message port. It provides a fast, non-copying message sending mechanism.

Messages can be attached to only one port at a time. The message body can be of any size or form. Because messages are not copied, cooperating tasks share the same message memory. The sender task must not recycle the message until it has been replied by the receiver. Of course this depends on the message handling conventions setup by the involved tasks. If the ReplyPort field is non-zero, when the message is replied by the receiver, it will be sent back to that port.

Any one of the following actions can be set to occur when a message is put:

1. no special action
2. signal a given task (specified by MP_SIGTASK)
3. cause a software interrupt (specified by MP_SIGTASK)

The action is selected depending on the value found in the MP_FLAGS of the destination port.

IMPLEMENTATION

1. Sets the LN_TYPE field to "NT_MESSAGE".
2. Attaches the message to the destination port.
3. Performs the specified arrival action at the destination.

INPUT

port - pointer to a message port
message - pointer to a message

SEE ALSO

GetMsg, ReplyMsg, exec/ports.h

1.75 exec.library/RawDoFmt

NAME

RawDoFmt -- format data into a character stream.

SYNOPSIS

```
NextData = RawDoFmt (FormatString, DataStream, PutChProc, PutChData);
d0              a0              a1              a2              a3
```

```
APTR RawDoFmt (STRPTR, APTR, void (*) (), APTR);
```

FUNCTION

perform "C"-language-like formatting of a data stream, outputting the result a character at a time. Where % formatting commands are

found in the FormatString, they will be replaced with the corresponding element in the DataStream. %% must be used in the string if a % is desired in the output.

Under V36, RawDoFmt() returns a pointer to the end of the DataStream (The next argument that would have been processed). This allows multiple formatting passes to be made using the same data.

INPUTS

FormatString - a "C"-language-like NULL terminated format string, with the following supported % options:

%[flags][width.limit][length]type

flags - only one allowed. '-' specifies left justification.
width - field width. If the first character is a '0', the field will be padded with leading 0's.
. - must follow the field width, if specified
limit - maximum number of characters to output from a string. (only valid for %s).
length - size of input data defaults to WORD for types d, x, and c, 'l' changes this to long (32-bit).
type - supported types are:
 b - BSTR, data is 32-bit BPTR to byte count followed by a byte string, or NULL terminated byte string. A NULL BPTR is treated as an empty string. (Added in V36 exec)
 d - decimal
 u - unsigned decimal (Added in V37 exec)
 x - hexadecimal
 s - string, a 32-bit pointer to a NULL terminated byte string. In V36, a NULL pointer is treated as an empty string
 c - character

DataStream - a stream of data that is interpreted according to the format string. Often this is a pointer into the task's stack.

PutChProc - the procedure to call with each character to be output, called as:

```
PutChProc(Char, PutChData);
D0-0:8 A3
```

the procedure is called with a NULL Char at the end of the format string.

PutChData - a value that is passed through to the PutChProc procedure. This is untouched by RawDoFmt, and may be modified by the PutChProc.

EXAMPLE

```
;
; Simple version of the C "sprintf" function. Assumes C-style
; stack-based function conventions.
;
; long eyecount;
```

```

;   eyecount=2;
;   sprintf(string,"%s have %ld eyes.\"", "Fish", eyecount);
;
; would produce "Fish have 2 eyes." in the string buffer.
;
XDEF _sprintf
XREF _AbsExecBase
XREF _LVORawDoFmt
_sprintf:      ; ( ostring, format, {values} )
               movem.l a2/a3/a6, -(sp)

               move.l 4*4(sp), a3      ;Get the output string pointer
               move.l 5*4(sp), a0      ;Get the FormatString pointer
               lea.l 6*4(sp), a1      ;Get the pointer to the DataStream
               lea.l stuffChar(pc), a2
               move.l _AbsExecBase, a6
               jsr    _LVORawDoFmt(a6)

               movem.l (sp)+, a2/a3/a6
               rts

;----- PutChProc function used by RawDoFmt -----
stuffChar:
               move.b d0, (a3)+      ;Put data to output string
               rts

```

WARNING

This Amiga ROM function formats word values in the data stream. If your compiler defaults to longs, you must add an "l" to your % specifications. This can get strange for characters, which might look like "%lc".

The result of RawDoFmt() is **ONLY** valid in V36 and later releases of EXEC. Pre-V36 versions of EXEC have "random" return values.

SEE ALSO

Documentation on the C language "printf" call in any C language reference book.

1.76 exec.library/ReleaseSemaphore

NAME

ReleaseSemaphore -- make signal semaphore available to others

SYNOPSIS

```
ReleaseSemaphore(signalSemaphore)
               A0
```

```
void ReleaseSemaphore(struct SignalSemaphore *);
```

FUNCTION

ReleaseSemaphore() is the inverse of ObtainSemaphore(). It makes the semaphore lockable to other users. If tasks are waiting for the semaphore and this task is done with the semaphore then the next waiting task is signalled.

Each `ObtainSemaphore()` call must be balanced by exactly one `ReleaseSemaphore()` call. This is because there is a nesting count maintained in the semaphore of the number of times that the current task has locked the semaphore. The semaphore is not released to other tasks until the number of releases matches the number of obtains.

Needless to say, havoc breaks out if the task releases more times than it has obtained.

INPUT

`signalSemaphore` -- an initialized signal semaphore structure

NOTE

This call is guaranteed to preserve all registers.

SEE ALSO

`InitSemaphore()`, `ObtainSemaphore()`, `ObtainSemaphoreShared()`

1.77 **exec.library/ReleaseSemaphoreList**

NAME

`ReleaseSemaphoreList` -- make a list of semaphores available

SYNOPSIS

```
ReleaseSemaphoreList(list)
                        A0
```

```
void ReleaseSemaphoreList(struct List *);
```

FUNCTION

`ReleaseSemaphoreList()` is the inverse of `ObtainSemaphoreList()`. It releases each element in the semaphore list.

Needless to say, havoc breaks out if the task releases more times than it has obtained.

INPUT

`list` -- a list of signal semaphores

SEE ALSO

`ObtainSemaphoreList()`

1.78 **exec.library/RemDevice**

NAME

`RemDevice` -- remove a device from the system

SYNOPSIS

```
RemDevice(device)
                A1
```



```
void RemDevice(struct Device *);
```

FUNCTION

This function calls the device's EXPUNGE vector, which requests that a device delete itself. The device may refuse to do this if it is busy or currently open. This is not typically called by user code.

There are certain, limited circumstances where it may be appropriate to attempt to specifically flush a certain device.

Example:

```
/* Attempts to flush the named device out of memory. */
#include <exec/types.h>
#include <exec/execbase.h>

void FlushDevice(name)
STRPTR name;
{
    struct Device *result;

    Forbid();
    if(result=(struct Device *)FindName(&SysBase->DeviceList,name))
        RemDevice(result);
    Permit();
}
```

INPUTS

device - pointer to a device node

SEE ALSO

AddLibrary

1.79 exec.library/RemHead

NAME

RemHead -- remove the head node from a list

SYNOPSIS

```
node = RemHead(list)
D0          A0
```

```
struct Node *RemHead(struct List *);
```

FUNCTION

Get a pointer to the head node and remove it from the list. Assembly programmers may prefer to use the REMHEAD macro from "exec/lists.i".

WARNING

This function does not arbitrate for access to the list. The calling task must be the owner of the involved list.

INPUTS

list - a pointer to the target list header

RESULT

node - the node removed or zero when empty list

SEE ALSO

AddHead, AddTail, Enqueue, Insert, Remove, RemTail

1.80 exec.library/RemIntServer

NAME

RemIntServer -- remove an interrupt server from a server chain

SYNOPSIS

```
RemIntServer(intNum, interrupt)
            D0      A1
```

```
void RemIntServer(ULONG, struct Interrupt *);
```

FUNCTION

This function removes an interrupt server node from the given server chain.

If this server was the last one on this chain, interrupts for this chain are disabled.

INPUTS

intNum - the Paula interrupt bit (0..14)
interrupt - pointer to an interrupt server node

BUGS

Before V36 Kickstart, the feature that disables the interrupt would not function. For most server chains this does not cause a problem.

SEE ALSO

AddIntServer, hardware/intbits.h

1.81 exec.library/RemLibrary

NAME

RemLibrary -- remove a library from the system

SYNOPSIS

```
RemLibrary(library)
            A1
```

```
void RemLibrary(struct Library *);
```

FUNCTION

This function calls the library's EXPUNGE vector, which requests that a library delete itself. The library may refuse to do this if

it is busy or currently open. This is not typically called by user code.

There are certain, limited circumstances where it may be appropriate to attempt to specifically flush a certain Library. Example:

```
/* Attempts to flush the named library out of memory. */
#include <exec/types.h>
#include <exec/execbase.h>

void FlushLibrary(name)
STRPTR name;
{
    struct Library *result;

    Forbid();
    if(result=(struct Library *)FindName(&SysBase->LibList,name))
        RemLibrary(result);
    Permit();
}
```

INPUTS

library - pointer to a library node structure

1.82 exec.library/Remove

NAME

Remove -- remove a node from a list

SYNOPSIS

```
Remove(node)
    A1
```

```
void Remove(struct Node *);
```

FUNCTION

Unlink a node from whatever list it is in. Nodes that are not part of a list must not be passed to this function! Assembly programmers may prefer to use the REMOVE macro from "exec/lists.i".

WARNING

This function does not arbitrate for access to the list. The calling task must be the owner of the involved list.

INPUTS

node - the node to remove

SEE ALSO

AddHead, AddTail, Enqueue, Insert, RemHead, RemTail

1.83 exec.library/RemPort

NAME

RemPort -- remove a message port from the system

SYNOPSIS

```
RemPort (port)
        A1
```

```
void RemPort (struct MsgPort *);
```

FUNCTION

This function removes a message port structure from the system's message port list. Subsequent attempts to rendezvous by name with this port will fail.

INPUTS

port - pointer to a message port

SEE ALSO

AddPort, FindPort

1.84 exec.library/RemResource

NAME

RemResource -- remove a resource from the system

SYNOPSIS

```
RemResource (resource)
        A1
```

```
void RemResource (APTR);
```

FUNCTION

This function removes an existing resource from the system resource list. There must be no outstanding users of the resource.

INPUTS

resource - pointer to a resource node

SEE ALSO

AddResource

1.85 exec.library/RemSemaphore

NAME

RemSemaphore -- remove a signal semaphore from the system

SYNOPSIS

```
RemSemaphore (signalSemaphore)
        A1
```

```
void RemSemaphore (struct SignalSemaphore *);
```

FUNCTION

This function removes a signal semaphore structure from the system's signal semaphore list. Subsequent attempts to rendezvous by name with this semaphore will fail.

INPUTS

signalSemaphore -- an initialized signal semaphore structure

SEE ALSO

AddSemaphore, FindSemaphore

1.86 exec.library/RemTail

NAME

RemTail -- remove the tail node from a list

SYNOPSIS

```
node = RemTail(list)
D0          A0
```

```
struct Node *RemTail(struct List *);
```

FUNCTION

Remove the last node from a list, and return a pointer to it. If the list is empty, return zero. Assembly programmers may prefer to use the REMTAIL macro from "exec/lists.i".

WARNING

This function does not arbitrate for access to the list. The calling task must be the owner of the involved list.

INPUTS

list - a pointer to the target list header

RESULT

node - the node removed or zero when empty list

SEE ALSO

AddHead, AddTail, Enqueue, Insert, Remove, RemHead, RemTail

1.87 exec.library/RemTask

NAME

RemTask -- remove a task from the system

SYNOPSIS

```
RemTask(task)
          A1
```

```
void RemTask(struct Task *);
```

FUNCTION

This function removes a task from the system. Deallocation of resources should have been performed prior to calling this function. Removing some other task is very dangerous. Generally is is best to arrange for tasks to call `RemTask(0L)` on themselves.

`RemTask` will automagically free any memory lists attached to the task's `TC_MENTRY` list.

INPUTS

`task` - pointer to the task node representing the task to be removed. A zero value indicates self removal, and will cause the next ready task to begin execution.

BUGS

Before V36 if `RemTask()` was called on a task other than the current task, and that task was created with `amiga.lib/CreateTask`, there was a slight chance of a crash. The problem can be hidden by bracketing `RemTask()` with `Forbid()/Permit()`.

SEE ALSO

`AddTask`, `exec/AllocEntry`, `amiga.lib/DeleteTask`

1.88 exec.library/ReplyMsg

NAME

`ReplyMsg` -- put a message to its reply port

SYNOPSIS

```
ReplyMsg(message)
    A1
```

```
void ReplyMsg(struct Message *);
```

FUNCTION

This function sends a message to its reply port. This is usually done when the receiver of a message has finished and wants to return it to the sender (so that it can be re-used or deallocated, whatever).

This call may be made from interrupts.

INPUT

`message` - a pointer to the message

IMPLEMENTATION

- 1> Places `"NT_REPLYMSG"` into `LN_TYPE`.
- 2> Puts the message to the port specified by `MN_REPLYPORT`. If there is no replyport, sets `LN_TYPE` to `"NT_FREEMSG"` (use this feature only with extreme care).

SEE ALSO

`GetMsg`, `PutMsg`, `exec/ports.h`

1.89 exec.library/SendIO

NAME

SendIO -- initiate an I/O command

SYNOPSIS

```
SendIO(iORequest)
      A1
```

```
void SendIO(struct IORequest *);
```

FUNCTION

This function requests the device driver start processing the given I/O request. The device will return control without waiting for the I/O to complete.

The `io_Flags` field of the `IORequest` will be set to zero before the request is sent. See `BeginIO()` for more details.

INPUTS

`iORequest` - pointer to an I/O request, or a device specific extended `IORequest`.

SEE ALSO

`DoIO`, `CheckIO`, `WaitIO`, `AbortIO`

1.90 exec.library/SetExcept

NAME

SetExcept -- define certain signals to cause exceptions

SYNOPSIS

```
oldSignals = SetExcept(newSignals, signalMask)
      D0                      D0          D1
```

```
ULONG SetExcept(ULONG,ULONG);
```

FUNCTION

This function defines which of the task's signals will cause a private task exception. When any of the signals occurs the task's exception handler will be dispatched. If the signal occurred prior to calling `SetExcept`, the exception will happen immediately.

The user function pointed to by the task's `tc_ExceptCode` gets called as:

```
newExceptSet = <exceptCode>(signals, exceptData), SysBase
      D0                      D0          A1          A6
```

`signals` - The set of signals that caused this exception. These Signals have been disabled from the current set of signals that can cause an exception.

`exceptData` - A copy of the task structure `tc_ExceptData` field.

newExceptSet - The set of signals in NewExceptSet will be re-enabled for exception generation. Usually this will be the same as the Signals that caused the exception.

INPUTS

newSignals - the new values for the signals specified in signalMask.
 signalMask - the set of signals to be effected

RESULTS

oldSignals - the prior exception signals

EXAMPLE

Get the current state of all exception signals:
 SetExcept(0,0)
 Change a few exception signals:
 SetExcept(\$1374,\$1074)

SEE ALSO

Signal, SetSignal

1.91 exec.library/SetFunction

NAME

SetFunction -- change a function vector in a library

SYNOPSIS

```
oldFunc = SetFunction(library, funcOffset, funcEntry)
D0                      A1          A0.W          D0

APTR SetFunction(struct Library *,LONG,APTR);
```

FUNCTION

SetFunction is a functional way of changing where vectors in a library point. They are changed in such a way that the checksumming process will never falsely declare a library to be invalid.

WARNING

If you use SetFunction on a function that can be called from interrupts, you are obligated to provide your own arbitration.

NOTE

SetFunction cannot be used on non-standard libraries like pre-V36 dos.library. Here you must manually Forbid(), preserve all 6 original bytes, set the new vector, SumLibrary(), then Permit().

INPUTS

library - a pointer to the library to be changed
 funcOffset - the offset of the function to be replaced
 funcEntry - pointer to new function

RESULTS

oldFunc - pointer to the old function that was just replaced

1.92 exec.library/SetIntVector

NAME

SetIntVector -- set a new handler for a system interrupt vector

SYNOPSIS

```
oldInterrupt = SetIntVector(intNumber, interrupt)
D0                                D0          A1
```

```
struct Interrupt *SetIntVector(ULONG, struct Interrupt *);
```

FUNCTION

This function provides a mechanism for setting the system interrupt vectors. These are non-sharable; setting a new interrupt handler disconnects the old one. Installed handlers are responsible for processing, enabling and clearing the interrupt. Note that interrupts may have been left in any state by the previous code.

The IS_CODE and IS_DATA pointers of the Interrupt structure will be copied into a private place by Exec. A pointer to the previously installed Interrupt structure is returned.

When the system calls the specified interrupt code, the registers are setup as follows:

```
D0 - scratch
D1 - scratch (on entry: active
             interrupts -> equals INTENA & INTREQ)

A0 - scratch (on entry: pointer to base of custom chips
             for fast indexing)
A1 - scratch (on entry: Interrupt's IS_DATA pointer)

A5 - jump vector register (scratch on call)
A6 - Exec library base pointer (scratch on call)

all other registers must be preserved
```

INPUTS

intNum - the Paula interrupt bit number (0..14). Only non-chained interrupts should be set. Use AddIntServer() for server chains.

interrupt - a pointer to an Interrupt structure containing the handler's entry point and data segment pointer. A NULL interrupt pointer will remove the current interrupt and set illegal values for IS_CODE and IS_DATA.

By convention, the LN_NAME of the interrupt structure must point a descriptive string so that other users may identify who currently has control of the interrupt.

RESULT

A pointer to the prior interrupt structure which had control

of this interrupt.

SEE ALSO

AddIntServer(), exec/interrupts.i, hardware/intbits.i

1.93 exec.library/SetSignal

NAME

SetSignal -- define the state of this task's signals

SYNOPSIS

```
oldSignals = SetSignal(newSignals, signalMask)
D0                      D0                      D1
```

```
ULONG SetSignal(ULONG, ULONG);
```

FUNCTION

This function can query or modify the state of the current task's received signal mask. Setting the state of signals is considered dangerous. Reading the state of signals is safe.

INPUTS

newSignals - the new values for the signals specified in signalSet.
signalMask - the set of signals to be affected.

RESULTS

oldSignals - the prior values for all signals

EXAMPLES

Get the current state of all signals:

```
SetSignal(0L, 0L);
```

Clear the CTRL-C signal:

```
SetSignal(0L, SIGBREAKF_CTRL_C);
```

Check if the CTRL-C signal was pressed:

```
#include <libraries/dos.h>
```

```
/* Check & clear CTRL_C signal */
```

```
if(SetSignal(0L, SIGBREAKF_CTRL_C) & SIGBREAKF_CTRL_C)
{
    printf("CTRL-C pressed!\n");
}
```

SEE ALSO

Signal, Wait

1.94 exec.library/SetSR

NAME

SetSR -- get and/or set processor status register

SYNOPSIS

```
oldSR = SetSR(newSR, mask)
D0          D0      D1
```

```
ULONG SetSR(ULONG, ULONG);
```

FUNCTION

This function provides a means of modifying the CPU status register in a "safe" way (well, how safe can a function like this be anyway?). This function will only affect the status register bits specified in the mask parameter. The prior content of the entire status register is returned.

INPUTS

newSR - new values for bits specified in the mask.
All other bits are not effected.
mask - bits to be changed

RESULTS

oldSR - the entire status register before new bits

EXAMPLES

```
To get the current SR:
    currentSR = SetSR(0,0);
To change the processor interrupt level to 3:
    oldSR = SetSR($0300,$0700);
Set processor interrupts back to prior level:
    SetSR(oldSR,$0700);
```

1.95 exec.library/SetTaskPri

NAME

SetTaskPri -- get and set the priority of a task

SYNOPSIS

```
oldPriority = SetTaskPri(task, priority)
D0-0:8          A1      D0-0:8
```

```
BYTE SetTaskPri(struct Task *,LONG);
```

FUNCTION

This function changes the priority of a task regardless of its state. The old priority of the task is returned. A reschedule is performed, and a context switch may result.

To change the priority of the currently running task, pass the result of FindTask(0); as the task pointer.

INPUTS

task - task to be affected
priority - the new priority for the task

RESULT

oldPriority - the tasks previous priority

1.96 exec.library/Signal

NAME

Signal -- signal a task

SYNOPSIS

```
Signal(task, signals)
    A1      D0
```

```
void Signal(struct Task *,ULONG);
```

FUNCTION

This function signals a task with the given signals. If the task is currently waiting for one or more of these signals, it will be made ready and a reschedule will occur. If the task is not waiting for any of these signals, the signals will be posted to the task for possible later use. A signal may be sent to a task regardless of whether its running, ready, or waiting.

This function is considered "low level". Its main purpose is to support multiple higher level functions like PutMsg.

This function is safe to call from interrupts.

INPUT

task - the task to be signalled
signals - the signals to be sent

SEE ALSO

Wait, SetSignal

1.97 exec.library/StackSwap

NAME

StackSwap - EXEC supported method of replacing task's stack (V37)

SYNOPSIS

```
StackSwap(newStack)
    A0
```

```
VOID StackSwap(struct StackSwapStruct *);
```

FUNCTION

This function will, in an EXEC supported manner, swap the stack of your task with the given values in StackSwap. The StackSwapStruct structure will then contain the values of the old stack such that the old stack can be restored. This function is new in V37.

NOTE

If you do a stack swap, only the new stack is set up. This function does not copy the stack or do anything else other than set up the new stack for the task. It is generally required that you restore your stack before exiting.

INPUTS

`newStack` - A structure that contains the values for the new upper and lower stack bounds and the new stack pointer. This structure will have its values replaced by those in you task such that you can restore the stack later.

RESULTS

`newStack` - The structure will now contain the old stack. This means that `StackSwap(foo); StackSwap(foo);` will effectively do nothing.

SEE ALSO

`AddTask`, `RemTask`, `exec/tasks.h`

1.98 exec.library/SumKickData

NAME

`SumKickData` -- compute the checksum for the Kickstart delta list

SYNOPSIS

```
checksum = SumKickData()  
D0
```

```
ULONG SumKickData(void);
```

FUNCTION

The Amiga system has some ROM (or Kickstart) resident code that provides the basic functions for the machine. This code is unchangeable by the system software. This function is part of a support system to modify parts of the ROM.

The ROM code is linked together at run time via ROMTags (also known as Resident structures, defined in `exec/resident.h`). These tags tell Exec's low level boot code what subsystems exist in which regions of memory. The current list of ROMTags is contained in the `ResModules` field of `ExecBase`. By default this list contains any ROMTags found in the address ranges `$F80000-$FFFFFF` and `$F00000-$F7FFFF`.

There is also a facility to selectively add or replace modules to the ROMTag list. These modules can exist in RAM, and the memory they occupy will be deleted from the memory free list during the boot process. `SumKickData()` plays an important role in this run-time modification of the ROMTag array.

Three variables in `ExecBase` are used in changing the ROMTag array: `KickMemPtr`, `KickTagPtr`, and `KickChecksum`. `KickMemPtr` points to a

linked list of MemEntry structures. The memory that these MemEntry structures reference will be allocated (via AllocAbs) at boot time. The MemEntry structure itself must also be in the list.

KickTagPtr points to a long-word array of the same format as the ResModules array. The array has a series of pointers to ROMTag structures. The array is either NULL terminated, or will have an entry with the most significant bit (bit 31) set. The most significant bit being set says that this is a link to another long-word array of ROMTag entries. This new array's address can be found by clearing bit 31.

KickChecksum has the result of SumKickData(). It is the checksum of both the KickMemPtr structure and the KickTagPtr arrays. If the checksum does not compute correctly then both KickMemPtr and KickTagPtr will be ignored.

If all the memory referenced by KickMemPtr can't be allocated then KickTagPtr will be ignored.

There is one more important caveat about adding ROMTags. All this ROMTag magic is run very early on in the system -- before expansion memory is added to the system. Therefore any memory in this additional ROMTag area must be addressable at this time. This means that your ROMTag code, MemEntry structures, and resident arrays cannot be in expansion memory. There are two regions of memory that are acceptable: one is chip memory, and the other is "Ranger" memory (memory in the range between \$C00000-\$D80000).

Remember that changing an existing ROMTag entry falls into the "heavy magic" category -- be very careful when doing it. The odd are that you will blow yourself out of the water.

NOTE

SumKickData was introduced in the 1.2 release

RESULT

Value to be stuffed into ExecBase->KickChecksum.

WARNING

After writing to KickChecksum, you should push the data cache. This prevents potential problems with large copyback style caches. A call to CacheClearU will do fine.

SEE ALSO

InitResident, FindResident

1.99 exec.library/SumLibrary

NAME

SumLibrary -- compute and check the checksum on a library

SYNOPSIS

```
SumLibrary(library)
    A1
```

```
void SumLibrary(struct Library *);
```

FUNCTION

SumLibrary computes a new checksum on a library. It can also be used to check an old checksum. If an old checksum does not match, and the library has not been marked as changed, then the system will call Alert().

This call could also be periodically made by some future system-checking task.

INPUTS

library - a pointer to the library to be changed

NOTE

An alert will occur if the checksum fails.

SEE ALSO

SetFunction

1.100 exec.library/SuperState

NAME

SuperState -- enter supervisor state with user stack

SYNOPSIS

```
oldSysStack = SuperState()  
D0
```

```
APTR SuperState(void);
```

FUNCTION

Enter supervisor mode while running on the user's stack. The user still has access to user stack variables. Be careful though, the user stack must be large enough to accommodate space for all interrupt data -- this includes all possible nesting of interrupts. This function does nothing when called from supervisor state.

RESULTS

oldSysStack - system stack pointer; save this. It will come in handy when you return to user state. If the system is already in supervisor mode, oldSysStack is zero.

SEE ALSO

UserState/Supervisor

1.101 exec.library/Supervisor

NAME

Supervisor -- trap to a short supervisor mode function

SYNOPSIS

```
result = Supervisor(userFunc)
Rx      A5
```

```
ULONG Supervisor(void *);
```

FUNCTION

Allow a normal user-mode program to execute a short assembly language function in the supervisor mode of the processor. Supervisor() does not modify or save registers; the user function has full access to the register set. All rules that apply to interrupt code must be followed. In addition, no system calls are permitted. The function must end with an RTE instruction.

EXAMPLE

```
;Obtain the Exception Vector base. 68010 or greater only!
MOVECtrap:   movec.l VBR,d0 ;$4e7a,$0801
             rte
```

INPUTS

userFunc - A pointer to a short assembly language function ending in RTE. The function has full access to the register set.

RESULTS

result - Whatever values the userFunc left in the registers.

SEE ALSO

SuperState, UserState

1.102 exec.library/TypeOfMem

NAME

TypeOfMem -- determine attributes of a given memory address

SYNOPSIS

```
attributes = TypeOfMem(address)
D0          A1
```

```
ULONG TypeOfMem(void *);
```

FUNCTION

Given a RAM memory address, search the system memory lists and return its memory attributes. The memory attributes are similar to those specified when the memory was first allocated: (eg. MEMF_CHIP and MEMF_FAST).

This function is usually used to determine if a particular block of memory is within CHIP space.

If the address is not in known-space, a zero will be returned. (Anything that is not RAM, like the ROM or expansion area, will return zero. Also the first few bytes of a memory area are used up by the MemHeader.)

INPUT

address - a memory address

RESULT

attributes - a long word of memory attribute flags.
If the address is not in known RAM, zero is returned.

SEE ALSO

AllocMem()

1.103 exec.library/UserState

NAME

UserState -- return to user state with user stack

SYNOPSIS

UserState(sysStack)
D0

void UserState(APTR);

FUNCTION

Return to user state with user stack, from supervisor state with user stack. This function is normally used in conjunction with the SuperState function above.

This function must not be called from the user state.

INPUT

sysStack - supervisor stack pointer

BUGS

This function is broken in V33/34 Kickstart. Fixed in V1.31 setpatch.

SEE ALSO

SuperState/Supervisor

1.104 exec.library/Vacate

NAME

Vacate -- release a message lock (semaphore)

SYNOPSIS

Vacate(semaphore)
A0

void Vacate(struct Semaphore *);

FUNCTION

This function releases a previously locked semaphore (see the Procure() function).
If another task is waiting for the semaphore, its bidMessage will be sent to its reply port.

INPUT

semaphore - the semaphore message port representing the semaphore to be freed.

BUGS

Procure() and Vacate() do not have proven reliability.

SEE ALSO

Procure

1.105 exec.library/Wait

NAME

Wait -- wait for one or more signals

SYNOPSIS

```
signals = Wait(signalSet)
D0                      D0
```

```
ULONG Wait(ULONG);
```

FUNCTION

This function will cause the current task to suspend waiting for one or more signals. When one or more of the specified signals occurs, the task will return to the ready state, and those signals will be cleared.

If a signal occurred prior to calling Wait(), the wait condition will be immediately satisfied, and the task will continue to run without delay.

CAUTION

This function cannot be called while in supervisor mode or interrupts! This function will break the action of a Forbid() or Disable() call.

INPUT

signalSet - The set of signals for which to wait.
Each bit represents a particular signal.

RESULTS

signals - the set of signals that were active

1.106 exec.library/WaitIO

NAME

WaitIO -- wait for completion of an I/O request

SYNOPSIS

```
error = WaitIO(ioRequest)
D0                      A1
```

```
BYTE WaitIO(struct IORequest *);
```

FUNCTION

This function waits for the specified I/O request to complete, then removes it from the replyport. If the I/O has already completed, this function will return immediately.

This function should be used with care, as it does not return until the I/O request completes; if the I/O never completes, this function will never return, and your task will hang. If this situation is a possibility, it is safer to use the Wait() function. Wait() will return when any of a specified set of signal is received. This is how I/O timeouts can be properly handled.

WARNING

If this IORequest was "Quick" or otherwise finished BEFORE this call, this function drops through immediately, with no call to Wait(). A side effect is that the signal bit related the port may remain set. Expect this.

When removing a known complete IORequest from a port, WaitIO() is the preferred method. A simple Remove() would require a Disable/Enable pair!

INPUTS

ioRequest - pointer to an I/O request block

RESULTS

error - zero if successful, else an error is returned
(a sign extended copy of io_Error).

SEE ALSO

DoIO, SendIO, CheckIO, AbortIO

1.107 exec.library/WaitPort

NAME

WaitPort -- wait for a given port to be non-empty

SYNOPSIS

```
message = WaitPort(port)
D0                      A0
```

```
struct Message *WaitPort(struct MsgPort *);
```

FUNCTION

This function waits for the given port to become non-empty. If necessary, the Wait() function will be called to wait for the port signal. If a message is already present at the port, this function will return immediately. The return value is always a pointer to the first message queued (but it is not removed from the queue).

CAUTION

More than one message may be at the port when this returns. It is

proper to call the GetMsg() function in a loop until all messages have been handled, then wait for more to arrive.

To wait for more than one port, combine the signal bits from each port into one call to the Wait() function, then use a GetMsg() loop to collect any and all messages. It is possible to get a signal for a port WITHOUT a message showing up. Plan for this.

INPUT

port - a pointer to the message port

RETURN

message - a pointer to the first available message

SEE ALSO

GetMsg