

`Load Procedure. Ignores new records that match old ones.

```

DEFAULT FILE([PeopleArchive])
SET CHANNEL(10;"Names")
While (OK=1)
  CREATE RECORD
  RECEIVE RECORD
  If (OK=1)
    xCode:=[PeopleArchive]KeyCode
    PUSH RECORD
    SEARCH BY INDEX([PeopleArchive]Code=xCode)
    If (Records in selection=0)
      POP RECORD
      SAVE RECORD
    Else
      POP RECORD
    End if
  End if
End while
SET CHANNEL(11)

```

With this procedure we can perform actions before we just blindly stuff data into the database. Notice that once the variable "xCode" has been assigned from a field of the new record, the new record is pushed onto the record stack (**PUSH RECORD**). This allows us to search using "xCode" without losing the record just created. In the example we check to see if the record exists and if it does we ignore the new one.

The following example shows how to replace the old record with new ones.

`Load Procedure. Replaces old records with new records.

```

DEFAULT FILE([PeopleArchive])
SET CHANNEL(10;"Names")
While (OK=1)
  CREATE RECORD
  RECEIVE RECORD
  If (OK=1)
    xCode:=[PeopleArchive]KeyCode
    PUSH RECORD
    SEARCH BY INDEX([PeopleArchive]Code=xCode)
    DELETE SELECTION `Will do nothing if no records are selected.
    POP RECORD
    SAVE RECORD
  End if
End while
SET CHANNEL(11)

```

