

# NEXTSTEP for Intel Processors

**Title:** S3 Graphics Support Under NEXTSTEP

**Entry Number:** 1329

**Last Modified:** <<Date November 15, 1995>>

**Valid for:** Release 3.1

## **Product Vendor:**

Digital Equipment Corporation

Digital Drive, Mail Stop MK01-2J25

Merrimack, NH 03054

USA

+1 (800) 438 4316 USA toll-free phone

+1 (800) 388 3228 faxback system

+1 (508) 496 8800 bulletin board system

+1 (800) 524 5694 USA fax

Dell Computer Corporation

11209 Metric Blvd.

Austin, Texas 78758

USA

+1 (800) 247 6821 USA toll-free phone

+1 (800) 950 1329 faxback system

+1 (512) 728 8528 bulletin board system

011 31 20 684 9291 Europe phone

011 866 2 391 2100 SE Asia phone  
011 81 3 5420 5353 Japan phone  
+1 (800) 727 8320 USA fax

Hewlett Packard  
3000 Hanover St.  
Palo Alto, CA 94304  
USA

+1 (800) 752-0900 USA toll-free phone  
+1 (415) 857 1501 international phone  
+1 (800) 333 1917 faxback system  
+1 (408) 553 3500 bulletin board system  
+1 (415) 857 5518 fax

**Keywords:** S3, Video, Graphics, Driver

## **Description:**

The NEXTSTEP Release 3.1 S3 display driver supports the integrated S3 graphics chipset on the Dell M series, the Dell L series, and the DEC MTE d2 series. Refer to the NEXTSTEP Hardware Compatibility Guide (NeXTanswers document1002\_Hardware\_Compatagility\_Guide , and1157\_Hardware\_Compatability\_Guide\_Plain\_Text\_Version) for more information on S3 support on all of these systems.

Add-on cards with integrated S3 graphics are not currently supported. NeXT plans to support some of these cards in future releases of the S3 display driver.

## **Release 3.3:**

See NeXTanswer document 1002\_3.3\_Intel\_Hardware\_Compatibility\_Guide.rtf

**System Requirements for Release 3.1 S3 Graphics Driver**

DEC MTE-d2 system: 1 MB VRAM supports 800x600 w/ Localbus S3-805  
DEC MTE-d2 system: 1 MB VRAM supports 800x600 w/ Localbus S3-928  
DEC MTE-d2 system: 2 MB VRAM supports 1024x768 w/ Localbus S3-928  
DEC MTE-d2 system: 4 MB VRAM supports 1280x1024 w/ Localbus S3-928  
*[DEC MTE-d2 (S3 805 and S3 928 versions): driver update required]*

Dell 450DE/2 DGX: 2MB VRAM supports 1120 x 832 16 bit color  
Dell ME, L, M Series: 1 MB VRAM supports 800x600 16 bit color, or  
1 MB VRAM supports 1024x768 8 bit grayscale

HP N and NI series: 1 MB VRAM supports 800x600 16 bit color  
HP Vectra XM series: 1 MB VRAM supports 800x600 16 bit color  
HP Vectra XM series: 2 MB VRAM supports 1024x768 16 bit color  
*[HP Vectra XM series: driver update required.]*

**Release 3.1:**

Update 1 of the S3 graphics driver is now available from NeXTanswers via anonymous FTP (ftp.next.com) or email (nextanswers@next.com). Request document numbers 1332\_S3Driver.pkg.compressed and 1331\_S3Driver.ReadMe. This update provides enhanced functionality and several systems on the Hardware Compatibility Guide require it to utilize their full graphics potential under NEXTSTEP. This driver is included with the NEXTSTEP Release 3.2 User CD.

**S3 Driver Update 1 System Support**

**S3 86C8051Based Display Adapters**  
**With an AT&T 20C491 or 20C492 RAMDAC**

System	8-bit Grayscale	16-bit Color
DEC 466d2 MTE w/805	1024X768 1MB VRAM 60, 70, or 72 Hz	800x600 1MB VRAM 60 Hz

DELL ME Series	1024X768 1MB VRAM 60, 70, or 72 Hz	800x600 1MB VRAM 60 Hz
HP N, NI Series	1024X768 1MB VRAM 60, 70, or 72 Hz	800x600 1MB VRAM 60 Hz
IBM ValuePoint S, D, T	1024X768 1MB VRAM 60, 70, or 72 Hz	800x600 1MB VRAM 60 Hz

**S3 86C9281Based Display Adapters  
With a BT 485 RAMDAC**

System	8-bit Grayscale	16-bit Color
HP Vectra XM	1024X768 1MB VRAM 60, 70, or 72 Hz 1280x1024 2MB VRAM 60 Hz	800x600 1MB VRAM 60 Hz 1024x768 2MB VRAM 60 or 72 Hz
DEC 466d2 MTE w/928	1024X768 1MB VRAM 60, 70, or 72 Hz  1280x1024 2MB VRAM 60 Hz	800x600 1MB VRAM 60 Hz  1024x768 2MB VRAM 72 Hz  1280x1024 4MB VRAM 60 Hz

**Setup and Installation:**

**Known Problems:**

**Release 3.1 and 3.2:**

- 7
- Update 1 of the S3 driver may produce fuzzy graphics when used on a DEC MTE 466-d2 (S3 928 version) in1024x768 16-bit color at 60 Hz.