

Q: I'm sending mail via UUCP. Things work *great* from my mail server (which is also my UUCP gateway). From a mail client, though, I get error messages indicating the remote UUCP machine is unknown. The bounce message looks like this:

Date: Mon, 13 Apr 92 13:11:11 CDT
From: Mailer-Agent (NeXT Mail Agent)
Subject: Returned mail: Unable to deliver mail
To: amm

----- Transcript of session follows -----

554 rhino!sandy... Never heard of UUCP host rhino

----- Unsent message follows -----

1/4

What's going on here?

A: One likely source of the problem is that **sendmail** might not have an uptodate notion of the known UUCP connections. If you've added the remote machine (**rhino** in the example, above) and neither rebooted the server nor restarted the **sendmail**

process on the server, then **sendmail** doesn't know about the new connection.

A **sendmail** daemon process is started when the system boots, by **/etc/rc**. When **sendmail** starts up, it runs the command **uuname** to determine the known UUCP connections. (At least, it does this with all the standard configuration files NeXT ships.) The **uuname** command is run *only once*. It is this **sendmail** daemon that handles all the mail coming from the client machines.

So, why does mail originating locally work? A new **sendmail** process is run for each locally-originating message; this new **sendmail** process runs its own instance of **uuname** when it starts. Since **uuname** for the new **sendmail** process has been run after the new system's addition to **L.sys**, the new **sendmail** knows about the new system.

QA835

Valid for 2.0, 3.0, 3.1