

NEXTSTEP for Intel Processors

Title: Installing from PCCard Devices

Entry Number: 1985

Creation Date: August 29 1995

Last Updated: <<Date May 15, 1996>>

Procedure Valid for Release: 3.3

Keywords: installation, pcmcia, floppy, adaptec, 6x60, 6360, xircom, cogent, boot, image

Overview

This NeXTanswer describes how you can use PCCard (PC/MCIA) devices to install NEXTSTEP onto your computer either a CD-ROM drive or a network.

Procedure

Installing from PCCard SCSI

- 1 Download the following floppyimages from NeXTanswers:
1984_3.3_PCCard_Install_Floppy.floppyimage
2145_3.3_Core_Drivers.floppyimage
1923_3.3_Additional_Drivers.floppyimage
Follow the instructions in NeXTanswer
1921_Creating_FDs_From_Images_Under_NEXTSTEP_and_DOS.rtf make
floppies from these images
- 2 Use these new floppies as the Install and Driver floppies for installation.

- 3 Follow the installation instructions in your NEXTSTEP Installation Guide
- 4 After you have completed the installation, you need to manually copy the three drivers
- Intel824X0.config
PCIC.config
PCMCIABus.config
- from the private/Drivers/i386 directory on your floppy to the /private/Drivers/i386 directory on your hard disk. These files already exist on your hard disk; overwrite them.
- 6 Launch Configure.app and make sure you have these new drivers configured properly. They should be configured as:
- Intel 824X0 PCI HostBridge (v3.31)
Intel 82365 PCMCIA Adapter (v3.31)
PCMCIA Bus Support (v3.31)

Installing from PCCard Ethernet

- 1 Download the following floppyimages from NeXTanswers:
- 1984_3.3_PCCard_Install_Floppy.floppyimage
2145_3.3_Core_Drivers.floppyimage
1923_3.3_Additional_Drivers.floppyimage
- Follow the instructions in NeXTanswer
1921_Creating_FDs_From_Images_Under_NEXTSTEP_and_DOS.rtf make
floppies from these images
- 2 Use these new floppies as the Network Install and Driver floppies for installation. The Additional Drivers Floppy does not contain network drivers, so you will have to download the network driver you need and add it to the floppy.
- 3 When you first start up the computer with the PCCard Install Floppy, type

config=netinstall

at the **boot:** prompt.

4 Follow the regular instructions for network installation.

5 After you have completed the installation, you need to manually copy the three drivers

Intel824X0.config
PCIC.config
PCMCIABus.config

from the private/Drivers/i386 directory on your floppy to the /private/Drivers/i386 directory on your hard disk. These files already exist on your hard disk; overwrite them.

6 Launch Configure.app and make sure you have these new drivers configured properly. They should be configured as:

Intel 824X0 PCI HostBridge (v3.31)
Intel 82365 PCMCIA Adapter (v3.31)
PCMCIA Bus Support (v3.31)

See Also:

1921_Creating_FDs_From_Images_Under_NEXTSTEP_and_DOS.rtf
1761_Adaptec_6x60_chipset_add-on_and_integrated__Driver_Overview.rtf
1791_Intel_82595_Chipset_Driver_Overview.rtf
1746_Xircom_Performance_Series_Driver_Overview.rtf