

NEXTSTEP for Intel Processors

Title: NEC PowerMate DX2/66e

Entry Number: 1333

Last Updated: <<Date June 13 1995>>

Product Vendor:

NEC Technologies, Inc.
1414 Massachusetts Ave,
Boxborough MA 01719
USA

+1 (800) 632 4636 USA toll-free phone - sales and information

+1 (800) 366 0476 USA toll-free faxback system

+1 (800) 388 8888 USA toll-free phone - support

+1 (508) 264 8000 international phone

+1 (508) 635 4706 bulletin board system

WWW: <http://www.nec.com/>

Keywords: NEC, PowerMate, ECU, EISA

Usage Commentary:

The NEC PowerMate Series provides an EISA bus with five EISA slots, integrated VGA for 640 x 480 two bit grayscale graphics and processor speeds of 33, 50 and 66 MHz. Supported EISA graphics adapters may be added to this system to provide higher resolution and color capabilities.

Setup and Installation:

The following ECU settings were recorded from a NEC PowerMate DX2/66e. This system successfully installed and ran NEXTSTEP Release 3.1 for Intel Processors onto an internal 435MB Seagate SCSI hard disk using a DPT 2012, Bus Logic BT-747, Adaptec 1542B and Adaptec 1542C SCSI controllers. An ATI Ultra Pro EISA graphics card provides the system with 1024 x 768 16 bit color.

EISA Configuration Utility Setup

System - NEC PowerMate DX2/66e System Board

Shadowing Options:

Video BIOS Shadow...	Enabled
System BIOS Shadow...	Enabled

Caching Options:

Global Caching...	Global Enabled
Video BIOS Cache...	Enabled
System BIOS Cache...	Enabled

Integrated Peripheral:

Parallel Port Address...	378h-37Fh, IRQ7 (Edge Triggered)
Serial Port 1 Address...	3F8h-3FFh, IRQ4 (Edge Triggered)
Serial Port 2 Address...	Disabled

Floppy Diskette Control Options:

Floppy Boot...	Enable
Floppy Write Protect...	Disable

IDE Hard Disk Controller...	Integrated IDE Hard Disk Controller: Disabled
-----------------------------	--

Typematic Rate...	Maximum
-------------------	---------

Mouse Port...	Enable
---------------	--------

Concurrent Mode & Decoupled Refresh...	Enable
--	--------

---Hardware Configuration---

Floppy Diskette Drive A...	1.44 MB- 3.5 inch
----------------------------	-------------------

Floppy Diskette Drive B...	Not Installed
Hard Disk Drive 0...	Not Installed
Hard Disk Drive 1...	Not Installed
User Defined Hard Drive Type	
Number of Cylinders...	0
Number of Heads...	0
Number of Sectors per Track...	0
Write Precomp...	0
Landing Zone...	0
Base Memory...	640 KB
Extended Memory...	15360
Keyboard Error Messages...	Suppressed
Numlock state at boot...	Numlock ON at boot
---Video Features ---	
Video Card...	EGA or VGA
Local/ISA Bus Video...	Local Bus Video
Monitor Display Type...	Color monitor attached
Automatic Scan Rate Detect...	Enable Automatic detect

Motherboard Jumper Settings

Jumpers **15A1**, **16L2**, and **17K3** are disabled.

Known Problems: