
NSMutableParagraphStyle

Inherits From:	NSParagraphStyle : NSObject
Conforms To:	NSCoding (NSParagraphStyle) NSCopying (NSParagraphStyle) NSMutableCopying (NSParagraphStyle) NSObject (NSObject)
Declared In:	AppKit/NSParagraphStyle.h

Class Description

NSMutableParagraphStyle adds methods to its superclass, NSParagraphStyle, for changing the values of the sub-attributes in a paragraph style attribute. See the NSParagraphStyle and NSAttributedString specifications for more information.

Method Types

Setting tab stops	<ul style="list-style-type: none">– setTabStops:– addTabStop:– removeTabStop:
Setting other style information	<ul style="list-style-type: none">– setParagraphStyle:– setAlignment:– setFirstLineHeadIndent:– setHeadIndent:– setTailIndent:– setLineBreakMode:– setMaximumLineHeight:– setMinimumLineHeight:– setLineSpacing:– setParagraphSpacing:

Instance Methods

addTabStop:

– (void)**addTabStop:**(NSTextTab *)*tabStop*

Adds *tabStop* to the receiver.

See also: – **removeTabStop:**, – **setTabStops:**, – **tabStops** (NSParagraphStyle)

removeTabStop:

– (void)**removeTabStop:**(NSTextTab *)*tabStop*

Removes the first text tab whose location and type are equal to those of *tabStop*.

See also: – **addTabStop:**, – **setTabStops:**, – **tabStops** (NSParagraphStyle)

setAlignment:

– (void)**setAlignment:**(NSTextAlignment)*alignment*

Sets the alignment of the receiver to *alignment*, which may be one of:

NSLeftTextAlignment
NSRightTextAlignment
NSCenterTextAlignment
NSJustifiedTextAlignment
NSNaturalTextAlignment

See also: – **alignment** (NSParagraphStyle)

setFirstLineHeadIndent:

– (void)**setFirstLineHeadIndent:**(float)*aFloat*

Sets the distance in points from the leading margin of a text container to the beginning of the paragraph's first line to *aFloat*. This value must be nonnegative.

See also: – **setHeadIndent:**, – **setTailIndent:**, – **firstLineHeadIndent** (NSParagraphStyle)

setHeadIndent:

– (void)**setHeadIndent:**(float)*aFloat*

Sets the distance in points from the leading margin of a text container to the beginning of lines other than the first to *aFloat*. This value must be nonnegative.

See also: – **setFirstLineHeadIndent:**, – **setTailIndent:**, – **headIndent** (NSParagraphStyle)

setLineBreakMode:

– (void)**setLineBreakMode:**(NSLineBreakMode)*mode*

Sets the mode used to break lines in a layout container to *mode*, which may be one of:

NSLineBreakByWordWrapping
NSLineBreakByCharWrapping
NSLineBreakByClipping
NSLineBreakByTruncatingHead
NSLineBreakByTruncatingTail
NSLineBreakByTruncatingMiddle

See the description of **lineBreakMode** in the NSParagraphStyle class specification for descriptions of these values.

setLineSpacing:

– (void)**setLineSpacing:**(float)*aFloat*

Sets the space in points added between lines within the paragraph to *aFloat*. This value must be nonnegative.

See also: – **setMaximumLineHeight:**, – **setMinimumLineHeight:**, – **setParagraphSpacing:**, – **lineSpacing** (NSParagraphStyle)

setMaximumLineHeight:

– (void)**setMaximumLineHeight:**(float)*aFloat*

Sets the maximum height that any line in the paragraph style will occupy, regardless of the font size or size of any attached graphic, to *aFloat*. Glyphs and graphics exceeding this height will overlap neighboring lines; however, a maximum height of zero implies no line height limit. This value must be nonnegative.

Note: Although this limit applies to the line itself, line spacing adds extra space between adjacent lines.

See also: – **setMinimumLineHeight:**, – **setLineSpacing:**, – **maximumLineHeight** (NSParagraphStyle)



setMinimumLineHeight:

– (void)**setMinimumLineHeight:(float)aFloat**

Sets the minimum height that any line in the paragraph style will occupy, regardless of the font size or size of any attached graphic, to *aFloat*. This value must be nonnegative.

See also: – **setMaximumLineHeight:**, – **setLineSpacing:**, – **minimumLineHeight** (NSParagraphStyle)



setParagraphSpacing:

– (void)**setParagraphSpacing:(float)aFloat**

Sets the space added at the end of the paragraph to separate it from the following paragraph to *aFloat*. This value must be nonnegative.

See also: – **setLineSpacing:**, – **paragraphSpacing** (NSParagraphStyle)



setParagraphStyle:

– (void)**setParagraphStyle:(NSParagraphStyle *)aStyle**

Replaces the sub-attributes of the receiver with those in *aStyle*.



setTabStops:

– (void)**setTabStops:(NSArray *)tabStops**

Replaces the tab stops in the receiver with *tabStops*.

See also: – **addTabStop:**, – **removeTabStop:**, – **tabStops** (NSParagraphStyle)



setTailIndent:

– (void)**setTailIndent:(float)aFloat**

Sets the distance in points from the margin of a text container to the end of lines to *aFloat*. If positive, this is the distance from the leading margin (for example, the left margin in left-to-right text). If zero or negative, it's the distance from the trailing margin.

For example, to create a paragraph style that fits exactly in a 2-inch wide container, set its head indent to 0.0 and its tail indent to 0.0. To create a paragraph style with quarter-inch margins, set its head indent to 0.25 and its tail indent to –0.25.

See also: – **setHeadIndent:**, – **setFirstLineHeadIndent:**, – **tailIndent** (NSParagraphStyle)