

## **Buddy API 3.4**

Buddy API contains an Xtra for use with Macromedia Director and Authorware and a UCD for use with Authorware which allows access to Windows API functions.

**[Installation](#)**

**[Distributing your applications](#)**

**[Loading Buddy API Functions](#)**

**[What's new in this release](#)**

Buddy API contains the following the following functions:

**[Information functions](#)**

**[File functions](#)**

**[Registration functions](#)**

**[System functions](#)**

**[Window functions](#)**

**[Alphabetical function list](#)**

**[Contents](#)**

## Installation

Buddy API contains 3 files -

Budapi.x32	32 bit Xtra
Budapi.u32	32 bit u32
Budapi.hlp	this help file

With Version 3.4, development of the 16 bit version has stopped. This version and all future versions will be released as 32 bit only. You can download the last 16 bit version (3.31) from <http://www.mods.com.au/budapi/download.htm>. This help file includes information about the 16 bit version.

### **Xtra installation**

The Xtra version can be used with Director 5, 6, 7 or 8 and Authorware 4 or 5. Place the Xtra into the Xtras folder inside your Director folder or Authorware folder. The u32 file is not used in the Xtra version.

### **U32 installation**

The u32 version can only be used with Authorware - any version. Place the u32 file into your Authorware folder. The Xtra files are not used.

### **Important Information**

You should carefully read the following terms and conditions before using this software. Your use of this software indicates your acceptance of these terms and conditions.

### **Disclaimer of Warranty**

This software and the accompanying files are provided "as is" and without warranties as to performance of merchantability or any other warranties whether expressed or implied.

The user must assume the entire risk of using Buddy API.

### **Copyright**

Buddy API Copyright © 1995-1999 Gary Smith  
All rights reserved.

### **Contact**

Gary Smith  
Internet: [gary@mods.com.au](mailto:gary@mods.com.au)

The latest version of Buddy API is available at

<http://www.buddyapi.com>

27th April 2000

### **Contents**

## Loading Buddy Functions

### **Xtra - Director**

After placing the Xtra in your Xtras folder and restarting Director, the Buddy API functions will become available for use. All the functions are global functions and can be called without using the lingo **openxlib** or **new** commands. You can enter code as provided in this help file in any Director script. You can also test the functions in the Message window.

### **Xtra - Authorware**

After placing the Xtra in your Xtras folder and restarting Authorware, the Buddy API functions will become available for use. You can type the code directly into a calculation icon. The list of functions can be viewed by selecting 'Functions' from the 'Window' menu, then choosing 'Xtra BudAPI' from the category list.

### **U32 - Authorware**

To load the required function, select Functions from the Window menu. Then select the name of your file in the Category drop-down list - it will usually be the last one in the list. Click the Load button. A file dialog box will appear - locate the file Budapi.u32. Click "OK".

Another dialog box will appear. This will contain the names of all the functions contained in BudAPI. Click on the desired entry (or entries), then click the 'Load' button.

To use the function, place a calculation icon on the flowline, then type in the code as provided in the examples.

### **Contents**

## Distributing your applications

### Xtra distribution

Previous versions of Buddy API consisted of two files - an Xtra and a DLL. This version does not contain the dll file.

There are a number of ways the Xtra can be distributed with your projector.

You can place the Xtra in a folder called Xtras in the same folder as your application. This is the recommended method, particularly if your application will run from a slow medium such as CD-ROM. This method will provide the fastest loading application, because the Xtra will not need to be extracted every time your application runs.

In Director 6 and later, you can embed the Xtra into the projector. Embedding the Xtra in Director 6 and 6.5 is not recommended - these versions of Director have problems in this area. Embedding in Director 7 and 8 is much more reliable. To embed the xtra, you need to manually add it to the list of Xtras to be embedded. Choose the Modify -> Movie -> Xtras menu. A dialog box will appear. Click the Add button, and select budapi.x32. In Director 7/8, make sure that the *Include in projector* option is checked. In Director 6/6.5, you also need to check the *Check movie for xtras* option when creating a projector. If you want to make a Director 6/6.5 16 bit projector and embed the Xtra, you will need to add this line to the xtrainfo.txt file located in the Director folder.

```
[#nameW32:"Budapi.x32", #nameW16:"Budapi.x16", #nameFAT:"Buddy API Xtra", #type:#lingo]
```

### U32 distribution

When distributing Buddy API with your application, you need to place the u32 file in the same folder as your packaged file.

### Contents

## Function list

**A - D**

**E - F**

**G - P**

**R - S**

**T - X**

**ActivateWindow**

activates the specified window

**ActiveWindow**

returns the active window

**AddSysItems**

adds System menu, min and max boxes

**Aw2Window**

returns the Authorware presentation window

**ChildWindowList**

returns a list a window's child windows

**CloseApp**

closes the application owning a window

**CloseWindow**

closes a window

**CommandArgs**

returns the command line arguments the application was started with

**CopyFile**

copies a file.

**CopyText**

copies text to the clipboard

**CopyXFiles**

copies multiple files with wildcard matching.

**CpuInfo**

gets information (type, speed) about the processor installed

**CreateFolder**

creates a new folder

**CreatePMGroup**

creates a Program Manager or Start Menu group

**CreatePMIcon**

creates a Program Manager or Start Menu icon

**DecryptText**

decrypts a text string

**DeleteFile**

deletes a file

**DeleteFolder**

deletes an empty folder

**DeletePMGroup**

deletes a Program Manager or Start Menu group

**DeletePMIcon**

deletes a Program Manager or Start Menu icon

**DeleteReg**

deletes Registry entry

**DeleteXFiles**

deletes files with wildcard matching

**DisableDiskErrors**

disables the 'Drive not ready' error message

**DisableKeys**

disables/enables key presses

**DisableMouse**

disables/enables mouse clicks

**DisableScreenSaver**

disables/enables the screen saver

**DisableSwitching**

disables/enables task switching

**DiskInfo**

gets information (type, size, name, number) about a disk

**Information functions**

**File functions**

**Registration functions**

**System functions**

**Window functions**

**Contents**

## Function list

### A - D

### E - F

### G - P

### R - S

### T - X

#### EncryptFile

encrypts/decrypts a file

#### EncryptText

encrypts a text string

#### ExitWindows

exits or restarts Windows

#### FileAge

returns the age of a file

#### FileAttributes

returns the attributes of a file

#### FileDate

returns the date of a file

#### FileExists

checks whether a file exists

#### FileList

returns a list of files in a folder.

#### FileSize

returns the size of a file

#### FileVersion

returns the version of a file.

#### FindApp

finds the application associated with a file type

#### FindClose

finishes a search started with baFindFirstFile

#### FindDrive

searches all drives for a specified file

#### FindFirstFile

searches for the first file matching a specification

#### FindNextFile

searches for the next file matching a specification

#### FindWindow

finds a window with given title or class

#### FlushIni

forces Windows to write an ini file to disk.

#### FolderList

returns a list of folders in a folder.

#### FontList

returns a list of installed fonts

#### FontStyleList

returns a list of available styles for a truetype font

#### FontInstalled

checks whether a font is installed

#### FolderExists

checks whether a folder exists

#### FreeCursor

allows the cursor to move anywhere on the screen

### Information functions

#### File functions

#### Registration functions

### System functions

#### Window functions

### Contents

## Function list

### A - D

### E - F

### G - P

### R - S

### T - X

#### GetFilename

displays a file selection dialog.

#### GetFolder

displays a folder selection dialog.

#### GetVolume

gets the current sound volume of wave and midi files and audio CD

#### GetWindow

returns a window related to another window

#### HideTaskBar

shows/hides the Win95 task bar

#### InstallFont

installs TrueType or bitmap font

#### KeyBeenPressed

checks whether a key has been pressed

#### KeysDown

checks whether a key is being held down

#### MakeShortcut

creates a Win95/NT shortcut

#### MakeShortcutEx

creates a Win95/NT shortcut

#### MemoryInfo

gets information about system memory

#### MoveWindow

moves/resizes a window

#### MsgBox

shows standard Windows message box

#### NextActiveWindow

returns the next window to become active

#### OpenFile

opens a file using it's associated program

#### OpenURL

opens a URL using the default browser

#### PasteText

pastes text from the clipboard

#### PlaceCursor

positions the cursor

#### PMLconList

returns list of icons in a Program Manager or Start Menu group

#### PMGroupList

returns list of Program Manager or Start Menu groups

#### PMSubGroupList

returns list of Start Menu groups inside another group

#### Previous

checks whether a previous instance is running

#### PrinterInfo

returns information about the installed printer

#### PrintFile

prints a file using it's associated program

#### Information functions

#### File functions

#### Registration functions

#### System functions

#### Window functions

#### Contents

## Function list

### A - D

### E - F

### G - P

### R - S

### T - X

<u>ReadIni</u>	reads Windows ini file
<u>ReadRegNumber</u>	reads Registry number value
<u>ReadRegString</u>	reads Registry string value
<u>RecycleFile</u>	places a file in the Win95/NT recycle bin.
<u>RefreshDesktop</u>	refreshes the desktop icons
<u>RegKeyList</u>	returns a list of sub-keys inside a registry key
<u>RegValueList</u>	returns a list of values inside a registry key
<u>RemoveSystems</u>	removes System menu, min and max boxes
<u>RenameFile</u>	renames a file or folder
<u>ResolveShortcut</u>	returns the file a shortcut points to
<u>RestrictCursor</u>	restricts the cursor to a specific screen area
<u>RunProgram</u>	runs an external program
<u>ScreenInfo</u>	gets information (width, height, etc) of the screen
<u>ScreenSaverTime</u>	sets the screen saver time out
<u>SendKeys</u>	sends simulated key presses to the active window
<u>SendMsg</u>	sends a windows message to a window
<u>SetCurrentDir</u>	changes the DOS current directory
<u>SetDisplay</u>	sets the screen size and depth
<u>SetFileAttributes</u>	sets the attributes of a file
<u>SetPattern</u>	sets the desktop pattern
<u>SetPrinter</u>	changes settings for the default printer
<u>SetScreenSaver</u>	sets the screen saver
<u>SetSystemTime</u>	sets the system time/date
<u>SetVolume</u>	sets the volume of wave and midi files and audio CD
<u>SetWallpaper</u>	sets the desktop wallpaper
<u>SetWindowDepth</u>	sets the z-order depth of a window
<u>SetWindowState</u>	minimises, maximises, hides a window
<u>SetWindowTitle</u>	set the caption of a window
<u>Shell</u>	executes a file
<u>ShortFileName</u>	returns the DOS version of a Win95 long file name
<u>Sleep</u>	pauses the calling Director/Authorware program
<u>SoundCard</u>	checks whether a sound card is installed
<u>StageHandle</u>	returns the Director stage window
<u>SysFolder</u>	returns location of system folders (windows, system, temp, etc)
<u>SystemTime</u>	returns the current system time/date

### Information functions

### File functions

### Registration functions

### System functions

### Window functions

### Contents

## Function list

[A - D](#)

[E - F](#)

[G - P](#)

[R - S](#)

[T - X](#)

[TempFileName](#)

returns a temporary file name guaranteed not to exist

[Version](#)

returns version info (Windows, NT, DOS, QuickTime, VFW)

[WaitForWindow](#)

waits until a specified window is in a specified state

[WaitTillActive](#)

waits until a specified window becomes the active one

[WindowDepth](#)

gets the z-order depth of a window

[WindowExists](#)

checks that a window handle is valid

[WindowInfo](#)

returns info (state, size, position, title, class) of a window

[WindowList](#)

returns a list of all windows with given title or class

[WindowToBack](#)

sends a window to the back of other windows

[WindowToFront](#)

brings a window to the front of other windows

[WinHandle](#)

returns the main Director or Authorware presentation window

[WinHelp](#)

shows a Windows help file

[WriteIni](#)

writes an entry to a Windows ini file

[WriteRegNumber](#)

writes number value to the Registry

[WriteRegString](#)

writes string value to the Registry

[XCopy](#)

copies multiple files with wildcard matching, including sub-directories.

[XDelete](#)

deletes files with wildcard matching, including sub-directories

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Registration functions](#)

[Contents](#)

## Information functions

<a href="#"><u>Version</u></a>	returns version info (Windows, NT, DOS, QuickTime, VFW)
<a href="#"><u>SysFolder</u></a>	returns location of system folders (windows, system, temp, etc)
<a href="#"><u>CpuInfo</u></a>	gets information (type, speed) about the processor installed
<a href="#"><u>DiskInfo</u></a>	gets information (type, size, name, number) about a disk
<a href="#"><u>MemoryInfo</u></a>	gets information about system memory
<a href="#"><u>FindApp</u></a>	finds the application associated with a file type
<a href="#"><u>ReadIni</u></a>	reads Windows ini file
<a href="#"><u>WriteIni</u></a>	writes an entry to a Windows ini file
<a href="#"><u>FlushIni</u></a>	forces Windows to write an ini file to disk.
<a href="#"><u>ReadRegString</u></a>	reads Registry string value
<a href="#"><u>WriteRegString</u></a>	writes string value to the Registry
<a href="#"><u>ReadRegNumber</u></a>	reads Registry number value
<a href="#"><u>WriteRegNumber</u></a>	writes number value to the Registry
<a href="#"><u>DeleteReg</u></a>	deletes Registry entry
<a href="#"><u>RegKeyList</u></a>	returns a list of sub-keys inside a registry key
<a href="#"><u>RegValueList</u></a>	returns a list of values inside a registry key
<a href="#"><u>SoundCard</u></a>	checks whether a sound card is installed
<a href="#"><u>FontInstalled</u></a>	checks whether a font is installed
<a href="#"><u>FontList</u></a>	returns a list of installed fonts
<a href="#"><u>FontStyleList</u></a>	returns a list of available styles for a truetype font
<a href="#"><u>CommandArgs</u></a>	returns the command line arguments the application was started with
<a href="#"><u>Previous</u></a>	checks whether a previous instance is running
<a href="#"><u>ScreenInfo</u></a>	gets information (width, height, etc) of the screen

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## Version

**Description:** baVersion returns a string containing version information.

**Usage:** Result = baVersion( VersionType )

**Arguments:** String.  
VersionType is the type of version you are interested in.  
Can be one of the following:  
"os" the current operating system  
"windows" windows version  
"nt" version of Windows NT  
"dos" DOS version  
"vfw" Video for Windows version  
"qt" QuickTime 2 version  
"qt3" QuickTime 3 version

**Returns:** String.  
Returns the version information requested.  
The return for "os" will be either "Win16", "Win95", "Win98", "WinNT" or "Win2000".

**Examples:** Director:  
`set WinVer = baVersion( "windows" )`

Authorware:  
`WinVer := baVersion( "windows" )`

**Notes:** The NT information is provided to enable programs to tell whether or not they are running under Windows NT. For example, baVersion( "windows" ) will return 4.0 for both Windows 95 and Windows NT 4.0 under 32 bit. If the program is running under NT, then baVersion( "nt" ) will also return 4.0, but will return 0 if running under Windows 95.  
This function also allows 16 bit programs to tell what version of NT they are running under. A 16 bit program running under NT will return 3.10 for baVersion( "windows" ), but baVersion( "nt" ) will return the correct NT version.

Here is a table of the possible baVersion return values:

	Win 3.1	Win 95	Win 98	Win NT	Win2000
16 bit "windows"	3.0, 3.10	3.95	3.98	3.10	3.10
16 bit "nt"	0	0	0	3.1 - 4.0	5.0
16 bit "dos"	3.0 - 6.22	7.0	7.10	5.0	5.0
32 bit "windows"	--	4.0	4.10	3.51, 4.0	5.0
32 bit "nt"	--	0	0	3.51, 4.0	5.0
32 bit "dos"	--	0	0	0	0

Apple made considerable changes to QuickTime between versions 2 and 3, and both may co-exist on the same system. "qt" will report the version of QuickTime prior to version 3. The version of QuickTime returned will match the Xtra/UCD version used - the 16bit Xtra/UCD will return the version of 16 bit QuickTime; the 32 bit will return the version of 32 bit QuickTime. "qt3" returns the version of QuickTime 3 or later. "qt3" is only available in 32 bit.

[Information functions](#)  
[File functions](#)

[System functions](#)  
[Window functions](#)

**Alphabetical function list**

**Contents**

## CpuInfo

**Description:** baCpuInfo returns information about the processor installed.

**Usage:** Result = baCpuInfo( InfoType )

**Arguments:** String.  
InfoType is the type of information to get. Can be:  
"vendor" the processor manufacturer  
"type" returns the type of processor  
"model" the model of the processor  
"stepping" the stepping revision number  
"speed" the speed of the processor in MHz

**Returns:** Integer or string depending on the InfoType.  
See the Notes section for details on interpreting the return.

**Examples:** Director:  
`set Cpu = baCpuInfo( "type" )`

Authorware:  
`Cpu := baCpuInfo( "type" )`

**Notes:** The "vendor" option returns a string containing the name of the manufacturer of the processor. This will be a 12 character string, the most common returns will be "GenuineIntel", "AuthenticAMD" and "CryixInstead" but there will be others for chips from IBM, Compaq, DEC and others.

This function contains identification code from Intel and AMD and is only reliable with those processors. Other brands will report that they are equivalent to an Intel processor, but that will not necessarily be a valid comparison.

To determine the actual processor model, you need to interpret both the "type" and "model" options. The "type" option will identify a general family of processor eg: 486, Pentium or K6. The "model" option will give specific information about the model within a particular family. "stepping" is the revision number of a specific model, and will not generally be useful. Refer to the following table to determine a processor.

### Intel CPUs

Description	Type	Model
486 DX	4	0, 1
486 SX	4	2
486 DX2	4	3, 7
486 SL	4	4
486 SX2	4	5
486 DX4	4	8
Pentium	5	1, 2
Pentium Overdrive	5	3
Pentium MMX	5	4
Pentium Pro	6	1
Pentium II (r1)	6	3
Pentium II (r2)	6	5
Celeron (r1)	6	5
Celeron (r2)	6	6
Pentium III	6	7

Note that the first release of the Celeron has the same numbers as the second

Pentium II release.

**AMD CPUs**

Description	Type	Model
AMD K5	5	<6
AMD K6	5	6, 7
AMD K6-II	5	8
AMD K6-III	5	9
AMD K7 Athlon	6	

The "speed" returned is only an approximation within a variation of about 10%. If the processor has been overclocked, the speed it is running at will be returned. Intel specifically warn against quoting this number to users, because it can not be guaranteed to be accurate. Use this number as a guide only.

In the 16 bit Xtra, only Intel processors are supported.

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## SysFolder

**Description:** baSysFolder gets the location of a special Windows directory.

**Usage:** Result = baSysFolder( Folder )

**Arguments:** string.  
Folder is the name of the folder to return. Can be one of the following:

"windows"	returns the Windows folder
"system"	the System folder
"system16"	the System folder for 16 bit files
"system32"	the System folder for 32 bit files
"temp"	the folder used for temporary files
"current"	the current DOS directory

These additional folders are available in 32 bit.

"desktop"	the desktop folder
"common desktop"	the common desktop folder for all users
"groups"	the program groups folder in the start menu
"common groups"	the common program groups folder for all users
"start menu"	the start menu folder
"common start menu"	the common start menu for all users
"personal"	the users personal documents folder
"favorites"	the users favorites folder
"startup"	the 'Start Up' program group folder
"recent"	the 'Recent documents' folder
"sendto"	the 'Send To' folder
"network"	the 'Network Neighborhood' folder
"fonts"	the 'Fonts' folder
"shellnew"	the new documents template folder
"program files"	the program files folder
"common files"	the common folder in the program files folder

**Returns:** String.  
Returns the requested folder.

**Examples:** Director:  
set WinDir = baSysFolder( "windows" )

Authorware:  
WinDir := baSysFolder( "windows" )

**Notes:** The string that is returned will have a "\ " at the end.  
The "system16" and "system32" options are for use with Windows NT. On other versions of windows, they will return the same as "system". These options allow a 16 bit exe to get the windows\system32 folder; and a 32 bit exe to get the windows\system folder.

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)



## FindApp

- Description:** baFindApp returns the application associated with a file type.
- Usage:** Result = baFindApp( Extension )
- Arguments:** String.  
Extension is the extension of the file type.
- Returns:** String.  
Returns the full path name to the application. Returns an empty string if the extension is not associated with or a program, or the associated program does not exist.
- Examples:** Director:  
`set Notepad = baFindApp( "txt" )`
- Authorware:  
`Notepad := baFindApp( "txt" )`
- Notes:** In 32bit Windows, Microsoft guidelines state that if a program registers a file extension, and the path to the executable file is a long file name, then that name must be included in quotes. If an installation program doesn't follow these guidelines, then this function may fail. Specifically, if the path name to the executable contains a space, then this function will not be able to return the path to the executable. Adobe Acrobat Reader 3 is one program that does not register itself correctly - it does not place quotes around the executable name in the registry. The baFindApp function has been written around this particular problem with Acrobat, and will use other methods to locate Acrobat if it is asked to find the app associated with "pdf" files.

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## ReadIni

**Description:** baReadIni gets a string from a Windows ini file.

**Usage:** Result = baReadIni( Section, Keyname, Default, IniFile )

**Arguments:** String, string, string, string.  
Section is the section name of the ini file.  
Keyname is the name of the key  
Default is the string that is returned if the file, section or key doesn't exist.  
IniFile is the name if the ini file to use.

**Returns:** String.  
Returns the value associated with the Keyname. If the IniFile, Section or Keyname doesn't exist, then the return will be the Default string.

**Examples:** Director:  
`set Name = baReadIni( "CurrentUser", "UserName", "Error", "Userdat.ini" )`

Authorware:  
`Name := baReadIni( "CurrentUser", "UserName", "Error", "Userdat.ini" )`

**Notes:** An entry in a Windows ini file has the following format :

```
[Section]  
Keyname=string
```

This function will return the string after the equals sign. When using this function, the Section name you use should not include the square brackets around the name. The Keyname should not include the equals sign. For example the ini file for the example above might look something like this

```
[CurrentUser]  
UserName=Gary Smith  
Password=myspw  
ModulesCompleted=4
```

The IniFile can be in any directory. If the IniFile is not in the Windows directory, then the full path name to the file must be supplied. The ini file does not have to have an .ini extension: any extension can be used.

This function returns a maximum of 2000 characters.

**See also:** [baWriteIni](#)  
[baFlushIni](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## WriteIni

**Description:** baWriteIni writes a string into a Windows ini file.

**Usage:** Result = baWriteIni( Section, Keyname, NewValue, IniFile )

**Arguments:** String, string, string, string.  
Section is the section name of the ini file.  
Keyname is the name of the key  
NewValue is the string to write into the file.  
IniFile is the name of the ini file to use.

**Returns:** Integer.  
Returns 1 if the function was successful, else 0.

**Examples:** Director:  
set OK = baWriteIni( "CurrentUser", "UserName", "Gary Smith", "Userdat.ini" )

Authorware:  
OK := baWriteIni( "CurrentUser", "UserName", "Gary Smith", "Userdat.ini" )

**Notes:** An entry in a Windows ini file has the following format :

```
[Section]
Keyname=string
```

This function will write the string after the equals sign. When using this function, the Section name you use should not include the square brackets around the name. The Keyname should not include the equals sign. For example the ini file for the example above might look something like this

```
[CurrentUser]
UserName=Gary Smith
Password=mypw
ModulesCompleted=4
```

The IniFile can be in any directory. If the IniFile is not in the Windows directory, then the full path name to the file must be supplied. The ini file does not have to have an .ini extension: any extension can be used. If the ini file does not exist, then it will be created.

On Win95, strings written to an ini file can not contain a tab character.

**See also:** [baReadIni](#)  
[baFlushIni](#)

[Information functions](#)  
[File functions](#)

[System functions](#)  
[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FlushIni

**Description:** baFlushIni forces Windows to write an ini file to disk.

**Usage:** baFlushIni( Filename )

**Arguments:** String.  
Filename is the name of the ini file to flush.

**Returns:** Void.

**Examples:** Director:  
`baFlushIni( the moviePath & "data.ini" )`

Authorware:  
`baFlushIni( FileLocation ^ "data.ini" )`

**Notes:** This function is for use with the other ini file functions. When Windows writes an ini file it keeps it cached for a short time. This does not cause problems when using only the ini functions. However, if you want to write an ini file, then immediately do something else with it, say, encrypt it, then you should use this function to force Windows to write the file to disk before you use it.

eg.  
`baWriteIni( "data", "password", pw, iniFile )` -- write ini file  
`baFlushIni( iniFile )` -- force it to disk  
`baEncryptFile( iniFile, key )` -- encrypt it

This functions is not needed if you are only using baWriteIni and baReadIni on your ini files.

**See also:** [baReadIni](#)  
[baWriteIni](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## ReadRegString

**Description:** baReadRegString gets a string from the Windows Registry.

**Usage:** Result = baReadRegString( KeyName, ValueName, Default, Branch )

**Arguments:** String, string, string, string.  
KeyName is the name of the key.  
ValueName is the name of the value. Under 16 bit, this value is ignored.  
Default is the string that is returned if the key/value doesn't exist.  
Branch is the branch of the registry to use. Can be one of the following:  
"HKEY\_CLASSES\_ROOT"  
"HKEY\_CURRENT\_USER"  
"HKEY\_LOCAL\_MACHINE"  
"HKEY\_USERS"  
HKEY\_CURRENT\_USER  
HKEY\_DYN\_DATA  
Under 16 bit, only the HKEY\_CLASSES\_ROOT branch is accessible - the Branch setting is ignored.

**Returns:** String.  
Returns the value associated with the Keyname. If the Keyname doesn't exist, then the return will be the Default string.

**Examples:** Director:  
`set Name = baReadRegString( "Courses\Computers\101", "CurrentUser", "Error", "HKEY_CLASSES_ROOT" )`

Authorware:  
`Name := baReadRegString( "Courses\Computers\101", "CurrentUser", "Error", "HKEY_CLASSES_ROOT" )`

**Notes:** A Registry entry consists of keys and sub-keys, similar to the directories and sub-directories in the Windows file system. 32 bit Windows adds Values to the registry. These can be thought of as files within the key. These Values are not available under 16 bit - the ValueName argument is ignored.

To get the (Default) value of a key in 32 bit use an empty string for the ValueName argument.

In 16 bit, this function can only obtain values from keys located in the HKEY\_CLASSES\_ROOT branch of the Registry.

Under Windows 3.1, the KeyName can not contain any spaces.

This function returns a maximum of 2000 characters.

**See also:** [baWriteRegString](#)  
[baReadRegNumber](#)  
[baWriteRegNumber](#)  
[baDeleteReg](#)  
[baRegKeyList](#)  
[baRegValueList](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## WriteRegString

**Description:** baWriteRegString writes a string into the Windows Registry.

**Usage:** Result = baWriteRegString( KeyName, ValueName, Data, Branch )

**Arguments:** String, string, string, string  
KeyName is the name of the key.  
ValueName is the name of the value. In 16 bit this value is ignored.  
Data is the string to write into the registry.  
Branch is the branch of the registry to use. Can be one of the following:  
"CLASSES\_ROOT"  
"HKEY\_CURRENT\_USER"  
"HKEY\_LOCAL\_MACHINE"  
"HKEY\_USERS"  
HKEY\_CURRENT\_USER  
HKEY\_DYN\_DATA  
Under 16 bit Windows, only the HKEY\_CLASSES\_ROOT branch is accessible - the Branch setting is ignored.

**Returns:** Integer.  
Returns 1 if the function is successful, otherwise 0.

**Examples:** Director:  
set OK = baWriteRegString( "Courses\Computers\101", "CurrentUser", "Gary Smith" ,  
"HKEY\_CLASSES\_ROOT" )

Authorware:  
OK := baWriteRegString( "Courses\Computers\101", "CurrentUser", "Gary Smith" ,  
"HKEY\_CLASSES\_ROOT" )

**Notes:** A Registry entry consists of keys and sub-keys, similar to the directories and sub-directories in the Windows file system. 32 bit Windows adds Values to the registry. These can be thought of as files within the key. These Values are not available under 16 bit - the ValueName argument is ignored.

To set the (Default) value of a key in 32 bit use an empty string for the ValueName argument.

Also in 16 bit, this function can only obtain values from keys located in the HKEY\_CLASSES\_ROOT branch of the Registry.

Under Windows 3.1, the KeyName can not contain any spaces.

**See also:** [baReadRegString](#)  
[baReadRegNumber](#)  
[baWriteRegNumber](#)  
[baDeleteReg](#)  
[baRegKeyList](#)  
[baRegValueList](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

## Contents

## ReadRegNumber

**Description:** baReadRegNumber gets a number from the Windows Registry.

**Usage:** Result = baReadRegNumber( KeyName, ValueName, Default, Branch )

**Arguments:** String, string, integer, string.  
KeyName is the name of the key.  
ValueName is the name of the value.  
Default is the string that is returned if the key/value doesn't exist.  
Branch is the branch of the registry to use. Can be one of the following:  
"HKEY\_CLASSES\_ROOT"  
"HKEY\_CURRENT\_USER"  
"HKEY\_LOCAL\_MACHINE"  
"HKEY\_USERS"  
HKEY\_CURRENT\_USER  
HKEY\_DYN\_DATA

**Returns:** Integer.  
Returns the value associated with the Keyname. If the Keyname doesn't exist, then the return will be the Default value.

**Examples:** Director:  
set Name = baReadRegNumber( "Courses\Computers", "Course", 0, "HKEY\_CLASSES\_ROOT" )

Authorware:  
Name := baReadRegNumber( "Courses\Computers", "Course", 0, "HKEY\_CLASSES\_ROOT" )

**Notes:** This function does not work in 16 bit - the 16 bit registry can not contain numbers. If used in 16 bit, the Default value will always be returned.

A Registry entry consists of keys and sub-keys, similar to the directories and sub-directories in the Windows file system. 32 bit Windows adds Values to the registry. These can be thought of as files within the key.

**See also:** [baReadRegString](#)  
[baWriteRegString](#)  
[baWriteRegNumber](#)  
[baDeleteReg](#)  
[baRegKeyList](#)  
[baRegValueList](#)

[Information functions](#)  
[File functions](#)

[System functions](#)  
[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## WriteRegNumber

**Description:** baWriteRegNumber writes a number into the Windows Registry.

**Usage:** Result = baWriteRegNumber( KeyName, ValueName, NewData, Branch )

**Arguments:** String, string, integer, string.  
KeyName is the name of the key.  
ValueName is the name of the value.  
NewData is the number that will be written to the registry.  
Branch is the branch of the registry to use. Can be one of the following:  
"HKEY\_CLASSES\_ROOT"  
"HKEY\_CURRENT\_USER"  
"HKEY\_LOCAL\_MACHINE"  
"HKEY\_USERS"  
HKEY\_CURRENT\_USER  
HKEY\_DYN\_DATA

0tx1701

**Returns:** Integer.  
Returns 1 if the function is successful, otherwise 0.

**Examples:** Director:  
set OK = baWriteRegNumber( "Courses\Computers", "Course", 101 ,  
"HKEY\_CLASSES\_ROOT" )

Authorware:  
OK := baWriteRegNumber( "Courses\Computers", "Course", 101 ,  
"HKEY\_CLASSES\_ROOT" )

**Notes:** This function does not work in 16 bit - the 16 bit registry can not contain numbers. If used in 16 bit, the function does nothing.

A Registry entry consists of keys and sub-keys, similar to the directories and sub-directories in the Windows file system. 32 bit Windows adds Values to the registry. These can be thought of as files within the key.

**See also:** [baReadRegString](#)  
[baWriteRegString](#)  
[baReadRegNumber](#)  
[baDeleteReg DeleteReg>Main](#)  
[baRegKeyList](#)  
[baRegValueList](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## DeleteReg

**Description:** baDeleteReg deletes a key or value from the Windows Registry.

**Usage:** Result = baDeleteReg( KeyName, ValueName, Branch )

**Arguments:** String, string, string.  
KeyName is the name of the key.  
ValueName is the name of the value. A empty string will delete the entire KeyName.  
Branch is the branch of the registry to use. Can be one of the following:  
"HKEY\_CLASSES\_ROOT"  
"HKEY\_CURRENT\_USER"  
"HKEY\_LOCAL\_MACHINE"  
"HKEY\_USERS"  
HKEY\_CURRENT\_USER  
HKEY\_DYN\_DATA

**Returns:** Integer.  
Returns 1 if the function is successful, otherwise 0.

**Examples:** Director:  
set OK = baDeleteReg( "Courses\Computers", "Course", "HKEY\_CLASSES\_ROOT" )

Authorware:  
OK := baDeleteReg( "Courses\Computers", "Course", HKEY\_CLASSES\_ROOT" )

**Notes:** In 16 bit, the ValueName and Branch parameters are ignored - the 16 bit registry can not have values or branches.  
Under Windows NT, a Key can only be deleted if it is empty. Under Windows 95 or 3.1, all sub keys will also be deleted.

**See also:** [baReadRegString](#)  
[baWriteRegString](#)  
[baReadRegNumber](#)  
[baReadRegNumber](#)  
[baRegKeyList](#)  
[baRegValueList](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## RegKeyList

**Description:** baRegKeyList returns a list of sub-keys inside a registry key.

**Usage:** Result = baRegKeyList( KeyName, Branch )

**Arguments:** String, string.  
KeyName is the name of the key.  
Branch is the branch of the registry to use. Can be one of the following:  
"HKEY\_CLASSES\_ROOT"  
"HKEY\_CURRENT\_USER"  
"HKEY\_LOCAL\_MACHINE"  
"HKEY\_USERS"  
HKEY\_CURRENT\_USER  
HKEY\_DYN\_DATA

**Returns:** List (Xtra) or String (UCD).  
Returns a list of the keys, or an empty list/string if the key doesn't exist or is empty.

**Examples:** Director:  
`set keyList = baRegKeyList( "Software\Adobe", "HKEY_LOCAL_MACHINE" )`

Authorware:  
`keyList := baRegKeyList( "Software\Adobe", "HKEY_LOCAL_MACHINE" )`

**Notes:** The 16 bit version can only read from the HKEY\_CLASSES\_ROOT branch.

**See also:** [baReadRegString](#)  
[baWriteRegString](#)  
[baReadRegNumber](#)  
[baReadRegNumber](#)  
[baDeleteReg](#)  
[baRegValueList](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## RegValueList

**Description:** baRegValueList returns a list of values inside a registry key.

**Usage:** Result = baRegValueList( KeyName, Branch )

**Arguments:** String, string.  
KeyName is the name of the key.  
Branch is the branch of the registry to use. Can be one of the following:  
"HKEY\_CLASSES\_ROOT"  
"HKEY\_CURRENT\_USER"  
"HKEY\_LOCAL\_MACHINE"  
"HKEY\_USERS"  
HKEY\_CURRENT\_USER  
HKEY\_DYN\_DATA

**Returns:** List (Xtra) or String (UCD).  
Returns a list of the keys, or an empty list/string if the key doesn't exist or is empty.

**Examples:** Director:  
set valueList = baRegValueList( "Netscape\Netscape Navigator",  
"HKEY\_LOCAL\_MACHINE" )

Authorware:  
valueList := baRegValueList( "Software\Adobe", "HKEY\_LOCAL\_MACHINE" )

**Notes:** This function is not available in the 16 bit version - the 16 bit registry can not contain values.

**See also:** [baReadRegString](#)  
[baWriteRegString](#)  
[baReadRegNumber](#)  
[baReadRegNumber](#)  
[baDeleteReg](#)  
[baRegKeyList](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## Previous

**Description:** baPrevious checks whether a previous instance of a projector or packaged file is running.

**Usage:** Result = baPrevious( Activate )

**Arguments:** Integer.  
If Activate is true, the previous instance is activated and brought to the front.

**Returns:** Integer.  
Returns the window handle of the previous instance if one is running, else 0.

**Examples:** Director:  
`if baPrevious( true ) <> 0 then quit`

Authorware:  
`if baPrevious( true ) <> 0 then quit(0)`

**Notes:** Both Director and Authorware open their display windows before scripts are executed. This means that the window of the second instance will appear before the previous one can be activated.

Under Windows NT, this function will only find the first instance opened. For example, if you open three copies of a projector, then quit the first one, baPrevious in the third projector will return 0 - it can not recognise the second projector as a previous instance. Under Windows 95 and 3.1, the third projector will be able to identify the second projector as a previous instance.

If you are running a full screen Director projector use this script to activate the previous instance. The example given above will make the stage move to a new position.

```
set wnd = baPrevious( false )
if wnd <> 0 then
    baWindowToFront( wnd )
    quit
end if
```

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## SoundCard

**Description:** baSoundCard checks whether a sound card is installed.

**Usage:** Result = baSoundCard()

**Arguments:** Void.

**Returns:** Integer.  
Returns 1 if a sound card is installed, else 0.

**Examples:** Director:  
set Sound = baSoundCard( )

Authorware:  
Sound := baSoundCard( )

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FontInstalled

**Description:** baFontInstalled reports whether or not a TrueType or Bitmap font is installed.

**Usage:** Result = baFontInstalled( FontName, Style )

**Arguments:** String, string.  
FontName is the name of the font family eg "Arial".  
Style is the specific style eg "Bold". Use an empty string ("") to see if the basic font is installed. The style is ignored if FontName is a Bitmap font.

**Returns:** Integer.  
Returns 1 if the font is presently installed, otherwise 0.

**Examples:** Director:  
set FontOK = baFontInstalled( "Arial", "Bold Italic" )

Authorware:  
FontOK := baFontInstalled( "Arial", "Bold Italic" )

**Notes:** If you ask for a specific font style, then the function will only return true if that style is present. For example, if you ask for "Arial", "Bold" and only the normal Arial is installed, this function will return 0. Some fonts may have different names for the styles, eg "Black" for bold and "Oblique" for italic. You must use the names built into the font.

**See also:** [baFontStyleList](#)  
[baFontList](#)  
[baInstallFont](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FontList

**Description:** baFontList returns a list of all installed fonts.

**Usage:** Result = baFontList( FontType )

**Arguments:** String.  
FontType is the type of fonts to list. Can be:  
"All" all fonts  
"TrueType" only true type fonts  
"Bitmap" only bitmap fonts  
"Device" only device or printer fonts  
"Vector" only vector fonts

**Returns:** List (Xtra) or String (UCD)  
Returns the list of fonts found.

**Examples:** Director:  
set ttList = baFontList( "TrueType" )

Authorware:  
fontList := baFontList( "All" )

**Notes:** Postscript fonts handled by ATM are listed as device fonts.  
The UCD version returns a string with each font on a separate line.

**See also:** [baFontStyleList](#)  
[baFontInstalled](#)  
[baInstallFont](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FontStyleList

**Description:** baFontStyleList returns a list of available styles for a truetype font.

**Usage:** Result = baFontStyleList( FontName )

**Arguments:** String.  
FontName is the name of the font.

**Returns:** List (Xtra) or String (UCD)  
Returns the list of font styles found.

**Examples:** Director:  
set styleList = baFontStyleList( "Arial" )  
  
Authorware:  
styleList := baFontStyleList( "Arial" )

**Notes:** This function is only applicable to truetype fonts - other types of fonts will return an empty list or string. Only styles that are actually installed will be returned. Styles created on-the-fly by Windows will not.  
The UCD version returns a string with each font on a separate line.

**See also:** [baFontList](#)  
[baFontInstalled](#)  
[baInstallFont](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## CommandArgs

- Description:** baCommandArgs returns the arguments the application was started with.
- Usage:** Result = baCommandArgs( )
- Arguments:** Void.
- Returns:** String.  
Returns the command line arguments, or an empty string if there were none.
- Examples:** Director:  
`set Args = baCommandArgs( )`
- Authorware:  
`Args := baCommandArgs( )`

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## DiskInfo

**Description:** baDiskInfo returns the information about a disk.

**Usage:** Result = baDiskInfo( Drive, InfoType )

**Arguments:** String, string  
Drive is the letter of the drive to get the information of.  
InfoType is the type of information to get. Can be:  
"type" returns the type of drive  
"name" returns the volume name  
"size" returns the size of the disk in Kb  
"free" returns the amount of free space in Kb  
"number" returns the serial number of the disk

**Returns:** Depends on InfoType.

"type" string  
The type of drive. Can be:  
"Hard" Fixed hard drive.  
"Floppy" Floppy disk drive.  
"CD-ROM" CD-ROM drive.  
"Network" Network drive.  
"Removable" Removable drive eg Zip, Syquest.  
"RAM" RAM drive.  
"Invalid" Drive doesn't exist, or is of unknown type.

"name" string  
The name of the disk or an empty string if the disk doesn't exist.

"size" integer  
The size of the disk in Kb, or 0 if the disk doesn't exist.

"free" integer  
The amount of free space on the disk in Kb, or 0 if the disk doesn't exist.

"number" integer  
The serial number of the disk, or 0 if the disk doesn't exist.

**Examples:** Director:  
set Size = baDiskInfo( "a", "size" )  
set Label = baDiskInfo( "k", "name" )

Authorware:  
Size := baDiskInfo( "c", "size" )  
Label := baDiskInfo( "k", "name" )

**Notes:** The original Windows API DriveType function reported that a CD-ROM drive was a remote (network) drive when used under Windows 3.1. This function has been altered to report correctly.  
The 32 bit version reports Floppy drives as Removable.  
The 16 bit Xtra/UCD will give inaccurate results on drives greater than 2gb. The 32 bit Xtra/U32 will report the correct size and free space when used on FAT32 or NTFS drives greater than 2gb.

**See also:** [baFindDrive](#)

[Information functions](#)

[File functions](#)

[Alphabetical function list](#)

[Contents](#)

[System functions](#)

[Window functions](#)

## MemoryInfo

**Description:** baMemoryInfo returns information about system memory.

**Usage:** Result = baMemoryInfo( InfoType )

**Arguments:** String.  
InfoType is the type of information to get. Can be:  
"ram"            the amount of physical ram installed  
"free ram"       the amount of physical ram not being used  
"swap"           the size of the current swap file  
"free swap"      the amount of the swap file not being used

**Returns:** Integer.  
Returns the information in bytes.

**Examples:** Director:  
set ram = baMemoryInfo( "ram" )  
  
Authorware:  
free := baMemoryInfo( "free ram" )

**Notes:** The "free swap" option is not available in the 16 bit version.  
The "swap" option in the 16 bit version when running under Windows 95 will return the smaller of the physical ram or the swap file size.

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## ScreenInfo

**Description:** baScreenInfo returns information about the screen.

**Usage:** Result = baScreenInfo( InfoType )

**Arguments:** String.  
The type of information to get. Can be:

"height"	the height of the screen in pixels
"width"	the width of the screen in pixels
"depth"	the colour depth of the screen in bits
"fontheight"	the height of the system font in pixels
"titlebar height"	the height of the system title bars
"menubar height"	the height of system menus

**Returns:** Integer.

**Examples:** Director:  
`set ScrHgt = baScreenInfo( "height" )`

Authorware:  
`ScrHgt := baScreenInfo( "height" )`

**Notes:** The values that are returned will be accurate even if the screen size is changed while the projector or packaged file is running.

**See also:** [baSetDisplay](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## System functions

<u>DisableDiskErrors</u>	disables the 'Drive not ready' error message
<u>DisableKeys</u>	disables/enables key presses
<u>DisableMouse</u>	disables/enables mouse clicks
<u>DisableSwitching</u>	disables/enables task switching
<u>DisableScreenSaver</u>	disables/enables the screen saver
<u>ScreenSaverTime</u>	sets the screen saver time out
<u>SetScreenSaver</u>	sets the screen saver
<u>SetWallpaper</u>	sets the desktop wallpaper
<u>SetPattern</u>	sets the desktop pattern
<u>SetDisplay</u>	sets the screen size and depth
<u>ExitWindows</u>	exits or restarts Windows
<u>RunProgram</u>	runs an external program
<u>WinHelp</u>	shows a Windows help file
<u>MsgBox</u>	shows standard Windows message box
<u>Sleep</u>	pauses the calling Director/Authorware program
<u>HideTaskBar</u>	shows/hides the Win95 task bar
<u>SetCurrentDir</u>	changes the DOS current directory
<u>CopyText</u>	copies text to the clipboard
<u>PasteText</u>	pastes text from the clipboard
<u>EncryptText</u>	encrypts a text string
<u>DecryptText</u>	decrypts a text string
<u>PlaceCursor</u>	positions the cursor
<u>RestrictCursor</u>	restricts the cursor to a specific screen area
<u>FreeCursor</u>	allows the cursor to move anywhere on the screen
<u>SetVolume</u>	sets the volume of wave and midi files and audio CD
<u>GetVolume</u>	gets the current sound volume of wave and midi files and audio CD
<u>InstallFont</u>	installs TrueType or bitmap font
<u>KeysDown</u>	checks whether a key is being held down
<u>KeyBeenPressed</u>	checks whether a key has been pressed
<u>CreatePMGroup</u>	creates a Program Manager or Start Menu group
<u>DeletePMGroup</u>	deletes a Program Manager or Start Menu group
<u>PMGroupList</u>	returns list of Program Manager or Start Menu groups
<u>PMSubGroupList</u>	returns list of Start Menu groups inside another group
<u>CreatePMLicon</u>	creates a Program Manager or Start Menu icon
<u>DeletePMLicon</u>	deletes a Program Manager or Start Menu icon
<u>PMLiconList</u>	returns list of icons in a Program Manager or Start Menu group
<u>SystemTime</u>	returns the current system time/date
<u>SetSystemTime</u>	sets the system time/date
<u>PrinterInfo</u>	returns information about the installed printer
<u>SetPrinter</u>	changes settings for the default printer
<u>RefreshDesktop</u>	refreshes the desktop icons

Information functions

System functions

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## DisableDiskErrors

- Description:** baDisableDiskErrors allows you to suppress the Windows 'drive not ready' error message.
- Usage:** baDisableDiskErrors( State )
- Arguments:** Integer.  
State determines whether or not the error messages are shown. Can be either true or false.
- Returns:** Void.
- Examples:** Director:  
`baDisableDiskErrors( true )`
- Authorware:  
`baDisableDiskErrors( true )`
- Notes:** This function disables the 'drive not ready' error message that occurs when Windows tries to access a file when there isn't a disk in the drive. This is a system wide setting and you should enable the disk errors again as soon as possible after disabling them.

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## DisableKeys

- Description:** baDisableKeys allows you to disable key presses.
- Usage:** Result = baDisableKeys( Disable , WindowHandle )
- Arguments:** Integer, integer.  
WindowHandle is the handle of the window to disable. To disable the keys on all windows, use 0.  
If Disable is true, key presses will be disabled.  
If Disable is false, key presses will be enabled again - the WindowHandle argument is ignored.
- Returns:** Integer.  
When disabling the keys, returns 1 if the function was successful, otherwise 0.  
When enabling the keys, will always return 1.
- Examples:** Director:  
`set KeysOff = baDisableKeys( true , baWinHandle() )`
- Authorware:  
`KeysOff := baDisableKeys( true , baWinHandle() )`
- Notes:** If you disable the keys using this function, make sure that you enable the function before your application quits.

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## DisableMouse

**Description:** baDisableMouse allows you to disable mouse clicks.

**Usage:** Result = baDisableMouse( Disable , WindowHandle )

**Arguments:** Integer, integer.  
WindowHandle is the handle of the window to disable. To disable clicks on all windows, use 0.  
If Disable is true, mouse clicks will be disabled.  
If Disable is false, mouse clicks will be enabled again - the WindowHandle argument is ignored.

**Returns:** Integer.  
When disabling the mouse, returns 1 if the function was successful, otherwise 0.  
When enabling the mouse, will always return 1.

**Examples:** Director:  
`set MouseOff = baDisableMouse( true , baWinHandle() )`

Authorware:  
`MouseOff := baDisableMouse( true , baWinHandle() )`

**Notes:** If you disable the mouse using this function, make sure that you enable the function before your application quits.  
Note that the cursor will still be visible and movable.

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## DisableSwitching

**Description:** baDisableSwitching disables the task switching keys - Alt-Tab, Alt-Esc, and Ctrl-Esc. On Windows 95, the Ctrl-Alt-Del command is also disabled.

**Usage:** baDisableSwitching( On )

**Arguments:** Integer.  
If On is true, then task switching will be disabled.

**Returns:** Void

**Examples:** Director:  
[baDisableSwitching\( true \)](#)

Authorware:  
[baDisableSwitching\( true \)](#)

**Notes:** If you disable switching, you should restore it again before your application quits. If you fail to do so, under Windows 95 the system keys will remain disabled. Under Windows 3.1, at best there will be loss of system resources; more likely, a complete system crash.

For this function to work, you must first set the Director property exitLock to true. Add this code [set the exitLock to true](#) before you call this function. This will also mean that your user can not quit the application using Alt-F4, Esc, etc.

Under Windows 95, if a password protected screen saver is activated after this function is called, task switching will be possible after the password has been entered.

This function will not work under Windows NT.

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## DisableScreenSaver

**Description:** baDisableScreenSaver allows you to enable/disable the screen saver.

**Usage:** Result = baDisableScreenSaver( State )

**Arguments:** Integer.  
State can be either true or false.

**Returns:** Integer.  
Returns 1 if the screen saver was previously active, or 0 if it was inactive.

**Examples:** Director:  
set OldSS = baDisableScreenSaver( false )

Authorware:  
OldSS := baDisableScreenSaver( false )

**Notes:** This function does not actually start the screen saver. It just determines whether or not the screen saver will appear after its time out period has passed. If your user has previously elected not to have a screen saver active, then this function will have no effect.

**See also:** [baScreenSaverTime](#)  
[baSetScreenSaver](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## ScreenSaverTime

**Description:** baScreenSaverTime allows you to set the screen saver time out.

**Usage:** Result = baScreenSaverTime( Time )

**Arguments:** Integer.  
Time is the value to set the screen saver time out to, in seconds.

**Returns:** Integer.  
Returns the previous time out value.

**Examples:** Director:  
set OldTime = baScreenSaverTime( 120 )

Authorware:  
OldTime := baScreenSaverTime( 120 )

**See also:** [baDisableScreenSaver](#)  
[baSetScreenSaver](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## SetScreenSaver

**Description:** baSetScreenSaver allows you to set the screen saver file.

**Usage:** Result = baSetScreenSaver( FileName )

**Arguments:** String.  
FileName is the file name of the screen saver.

**Returns:** String.  
Returns the file name of the previous screen saver.

**Examples:** Director:  
set OldSS = baSetScreenSaver( "c:\windows\ss.scr" )

Authorware:  
OldSS := baSetScreenSaver( "c:\windows\ss.scr" )

**Notes:** You should use the full path name of the screen saver. A empty string will disable screen saving. This function will also enable the screen saver.

**See also:** [baDisableScreenSaver](#)  
[baScreenSaverTime](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## SetWallpaper

**Description:** baSetWallpaper allows you to set the desktop wallpaper.

**Usage:** Result = baSetWallpaper( FileName , Tile )

**Arguments:** String, integer  
FileName is the file name of the wallpaper.  
If Tile is true, the wallpaper will be tiled.

**Returns:** String.  
Returns the file name of the previous wallpaper.

**Examples:** Director:  
set Old = baSetWallpaper( "c:\windows\arcade.bmp" )

Authorware:  
Old := baSetWallpaper( "c:\\windows\\arcade.bmp" )

**Notes:** You should use the full path name of the wallpaper. A empty string will remove the wallpaper.

**See also:** [baSetPattern](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## SetPattern

**Description:** baSetPattern allows you to set the desktop pattern.

**Usage:** Result = baSetPattern( Name , Pattern )

**Arguments:** String, string.  
Name is the name of the pattern.  
Pattern is a string containing the pattern.

**Returns:** String.  
Returns the previous pattern.

**Examples:** Director:  
set Old = baSetPattern( "Bricks" , "187 95 174 93 186 117 234 245" )

Authorware:  
Old := baSetPattern( "Bricks" , "187 95 174 93 186 117 234 245" )

**Notes:** The standard Windows patterns are listed in the control.ini file.

**See also:** [baSetWallpaper](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## SetDisplay

**Description:** baSetDisplay sets the screen size and depth.

**Usage:** Result = baSetDisplay( Width , Height , Depth , Mode , Force )

**Arguments:** Integer, integer, integer, string, integer.  
Width is the new width of the screen in pixels.  
Height is the new height of the screen in pixels.  
Depth is the new depth of the screen in bits.  
Mode is the way in which the new display is set. Can be:  
"temp" temporarily change the display settings.  
"perm" permanently change the display settings.  
"test" tests whether the display can be set without restarting.  
If Force is true, forces the display to change.

**Returns:** Integer.  
Returns 0 if the display was changed or can be changed without restarting.  
Returns 1 if Windows will need to be restarted for the change to take effect.  
Returns less than 0 if another error occurred, eg invalid screen size.

**Examples:** Director:  
set OK = baSetDisplay( 640 , 480 , 8 , "temp" , false )

Authorware:  
OK := baSetDisplay( 640 , 480 , 8 , "temp" , false )

**Notes:** This function will not work under Windows 3.1 - it will always return 0.  
Not all display cards and drivers support screen changing without restarting.  
The force option is not officially supported by Microsoft. It forces the display to change without restarting. This may work correctly with some video cards and drivers, but can cause palette problems on others, and crash the system on some. You are advised to only use this option on known hardware and after extensive testing.  
If you use the "temp" mode, then the user's preferred screen display will be returned when the system is restarted. You can not set a "temp" mode unless it can be changed without restarting Windows.

**See also:** [baScreenInfo](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## ExitWindows

**Description:** baExitWindows exits or restarts Windows.

**Usage:** baExitWindows( Option )

**Arguments:** String.  
Option is the type of exit. Can be:  
"reboot" reboots the system  
"restart" restarts Windows  
"logoff" logs off Windows  
"shutdown" shuts down the system

**Returns:** Void.

**Examples:** Director:  
baExitWindows( "reboot" )

Authorware:  
baExitWindows( "reboot" )

**Notes:** Not all versions of Windows support all the restarting options. If a particular function is not available, then another mode will be substituted according to the following table. The system security settings may prohibit some of these options from operating.

	<b>Windows 3.1</b>	<b>Windows 95</b>	<b>Windows NT</b>
16 bit "reboot"	reboot	reboot	logoff
16 bit "restart"	restart	restart	logoff
16 bit "shutdown"	restart	shutdown	logoff
16 bit "logoff"	restart	logoff	logoff
32 bit "reboot"	--	reboot	reboot
32 bit "restart"	--	restart	reboot
32 bit "shutdown"	--	shutdown	shutdown
32 bit "logoff"	--	logoff	logoff

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## RunProgram

**Description:** baRunProgram runs an external application and can optionally wait until the other program quits before continuing.

**Usage:** Result = baRunProgram( Program , State, Wait )

**Arguments:** String, string, integer.  
Program is the name of the program to run.  
State is how the program is to appear. Can be one of the following:  
"Normal" shows in its usual state.  
"Hidden" is not visible.  
"Maximised" shows as a maximised window.  
"Minimised" shows as an minimised icon.

Wait determines whether the Authorware program continues, or if it waits for the external program to finish before continuing. Can be either true or false.

**Returns:** Integer.  
In 16 bit, returns the instance handle of the program. If this is greater than 31, then the program started successfully. In 32 bit, returns a meaningless number greater than 31. If the return is less than 32, then an error occurred. Some possible error numbers are listed here.

- 0 System was out of memory, executable file was corrupt, or relocations were invalid.
- 1 Unspecified error.
- 2 File was not found.
- 3 Path was not found.
- 5 Attempt was made to dynamically link to a task, or there was a sharing or network-protection error.
- 6 Library required separate data segments for each task.
- 8 There was insufficient memory to start the application.
- 10 Windows version was incorrect.
- 11 Executable file was invalid. Either it was not a Windows application or there was an error in the .EXE image.
- 12 Application was designed for a different operating system.
- 13 Application was designed for MS-DOS 4.0.
- 14 Type of executable file was unknown.
- 15 Attempt was made to load a real-mode application (developed for an earlier version of Windows).
- 16 Attempt was made to load a second instance of an executable file containing multiple data segments that were not marked read-only.
- 19 Attempt was made to load a compressed executable file. The file must be decompressed before it can be loaded.
- 20 Dynamic-link library (DLL) file was invalid. One of the DLLs required to run this application was corrupt.
- 21 Application requires 32-bit extensions.

**Examples:** Director:  
set OK = baRunProgram( "Notepad.exe", "maximised", false )

Authorware:  
OK := baRunProgram( "Notepad.exe", "maximised", false )

**Notes:** Where possible, the complete path to the program should be specified. If a path is not provided, then Windows searches for the file in the following order:

- 1 The current directory.
- 2 The Windows directory.
- 3 The Windows system directory.
- 4 The directory containing the executable file for the current task.

- 5 The directories listed in the PATH environment variable.
- 6 The directories mapped in a network.

You are not limited to supplying just an executable file name; you can add any other command line parameters that the executable supports. For example, to load the Adobe Acrobat Reader with mydoc.pdf, use the following call:  
baRunProgram( "acroread.exe mydoc.pdf", "maximised", false )

To print an Acrobat file, you can use  
baRunProgram( "acroread.exe /p mydoc.pdf", "Hidden", true )

If used with the Wait option, this function will not return control to Authorware/Director until the jumped to program has quit. If your user switches back to the Authorware program, it will appear to have frozen. You may choose to display an on-screen message to inform your user of this. You can also use the [WaitTillActive](#) function to pause execution until the Authorware/Director window becomes active again.

**See also:**

[baWaitTillActive](#)  
[baWaitForWindow](#)  
[baNextActiveWindow](#)  
[baOpenFile](#)  
[baShell](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## Shell

**Description:** baShell executes a file.

**Usage:** Result = baShell( Operation, Filename, Args, WorkDir, State )

**Arguments:** String, string, string, string, string.  
Operation is the action to perform on the file.  
Filename is the name of the file the shortcut will point to.  
Args is any command line arguments to use.  
WorkDir is the working directory to set.  
State is the state to start the program in.

**Returns:** Integer.  
Returns a number larger than 32 if successful.  
Returns an error code. If the return is less than 32 than an error occurred.

Possible errors include:

- 0 System was out of memory.
- 2 File was not found.
- 3 Path was not found.
- 5 Sharing or network-protection error.
- 6 Library required separate data segments for each task.
- 8 There was insufficient memory to start the application.
- 10 Windows version was incorrect.
- 11 Executable file was invalid. Either it was not a Windows application or there was an error in the .EXE image.
- 12 Application was designed for a different operating system.
- 13 Application was designed for MS-DOS 4.0.
- 14 Type of executable file was unknown.
- 15 Attempt was made to load a real-mode application (developed for an earlier version of Windows).
- 16 Attempt was made to load a second instance of an executable file containing multiple data segments that were not marked read-only.
- 19 Attempt was made to load a compressed executable file. The file must be decompressed before it can be loaded.
- 20 Dynamic-link library (DLL) file was invalid. One of the DLLs required to run this application was corrupt.
- 21 Application requires 32-bit extensions.
- 26 A sharing violation occurred.
- 27 The filename association is incomplete or invalid.
- 29 The DDE transaction failed.
- 30 The DDE transaction could not be completed because other DDE transactions were being processed.
- 31 There is no application associated with the given filename

**Examples:** Director:  

```
set ok = baShell( "open", "c:\windows\notepad.exe", "myfile.txt" , "", "normal" )  
set ok = baShell( "edit", "myfile.htm" , "", "", "normal" )
```

Authorware:  

```
set ok = baShell( "open", "myfile.doc", "" , "", "normal" )
```

**Notes:** This function can execute either a document or a program file. If it opens a document file, the Args parameter is ignored. The Operation can be any action that is registered with the document type, most commonly 'open' and 'print'. If the specified action is not registered to the document, the function will return 31. Only the 'open' action works on program files.

**See also:** [baOpenFile](#)  
[baPrintFile](#)  
[baRunProgram](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## WinHelp

**Description:** baWinHelp displays a windows Help file.

**Usage:** Result = baWinHelp(Cmd, HelpFile, Data )

**Arguments:** String, string, string.

Cmd is the help file command. Can be one of the following:

"Contents" shows the Contents page.

"Context" shows the page with the "Data" context number.

"PopUp" shows the page with the "Data" context number in a pop-up window.

"Show" shows the topic found that matches "Data" if there is one exact match. If there is more than one match, then the Search dialog box is displayed. If there is no exact match, then an error message will appear.

"Search" shows the topic found that matches "Data" if there is one exact match. If there is more than one match, then the Search dialog box is displayed. If there is no match, then the Search dialog box appears.

"Quit" closes the Help file.

"Help" shows the Help-On-Help page.

"Macro" executes the Help macro named in "Data".

HelpFile is the name of the Help file to display. This should include the complete path to the help file.

Data is a string containing extra information. This will vary according to the Cmd used.

Note that even if a number is required, this must be passed as a string.

"Contents" Data should be "".

"Context" Data is the context number, eg "4".

"PopUp" Data is the context number, eg "4".

"Show" Data is the topic string to show, eg "About BudAPI".

"Search" Data is the topic string to search for, eg "About BudAPI".

"Quit" Data should be "".

"Help" Data should be "".

"Macro" Data should be the name of the macro to execute, eg "PlayMovie".

**Returns:** Integer.

Returns 1 if successful, else 0. Not finding the Help file is not considered a failure.

**Examples:** Director:

```
set OK = WinHelp( "Show", the pathName & "myhelp.hlp", "Flowers" )
```

```
set OK = WinHelp( "Quit", the pathName & "myhelp.hlp", "" )
```

Authorware:

```
OK := WinHelp( "Show", FileLocation ^ "myhelp.hlp", "Flowers" )
```

```
OK := WinHelp( "Quit", FileLocation ^ "myhelp.hlp", "" )
```

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## MsgBox

**Description:** baMsgBox displays a standard Windows MessageBox

**Usage:** Result = baMsgBox( Message, Caption, Buttons, Icon, DefButton )

**Arguments:** String, string, string, string, integer.  
Message is the message to display. This can contain more than one line.  
Caption is the caption to show in the Title bar.  
Buttons is the type of buttons to display. This can be one of the following:

"OK"  
"OKCancel"  
"RetryCancel"  
"AbortRetryIgnore"  
"YesNo"  
"YesNoCancel"

Icon is the type of icon to display. This can be one of the following:

"Stop"  
"Information"  
"Question"  
"Exclamation"  
"NoIcon"

DefButton is the number of the default (selected) button. Can be 1, 2, or 3 depending on the number of buttons. The button on the left hand side is 1.

**Returns:** String.  
Returns the name of the button clicked eg "OK" or "Ignore".

**Examples:** Director:  
set Answer = baMsgBox( "Is this is a test message?", "A question" , "YesNo",  
"Question" , 1 )  
if Answer = "Yes" then baMsgBox("Correct!" , "The answer", "OK", "Information", 1)

Authorware:  
Answer := baMsgBox( "Is this is a test message?", "A question" , "YesNo", "Question" ,  
1 )  
if Answer = "Yes" then baMsgBox("Correct!" , "The answer", "OK", "Information", 1)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## Sleep

**Description:** baSleep pauses the calling Director/Authorware program.

**Usage:** baSleep( milliSecs )

**Arguments:** Integer.  
milliSecs is the time to sleep for, in thousandths of a second.

**Returns:** Void.

**Examples:** Director:  
baSleep( 200 )

Authorware:  
baSleep( 200 )

**Notes:** This function is most useful for 'lowering' the priority of Director to allow other programs a larger slice of available processing time - for example when playing a mpeg movie. Calling this function in a loop such as in a on exitFrame handler, will give other processes a chance to run while still allowing Director to process events such as mouse clicks. Larger numbers will give other programs more time, but slow down Director responses. Values between 50 and 200 would be a good starting point for experimentation.  
This function is available in 16 bit, but its' effectiveness is limited because 16 bit Windows has limited multitasking abilities.

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## HideTaskBar

**Description:** baHideTaskBar shows/hides the Win95 task bar.

**Usage:** Result = baHideTaskBar( Hide )

**Arguments:** Integer.  
If Hide is true, the task bar is hidden, else it will be visible.

**Returns:** Integer.  
Returns the previous state of the task bar - 1 if it is visible, 0 if it isn't.

**Examples:** Director:  
`set showing = baHideTaskBar( true )`

Authorware:  
`showing := baHideTaskBar( true )`

**Notes:** This function will not change the users task bar settings - the 'Always on top' and 'Auto hide' settings.

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## SetCurrentDir

**Description:** baSetCurrentDir sets the current directory.

**Usage:** Result = baSetCurrentDir( Dir )

**Arguments:** String.  
Dir is the full path name of the directory to make current.

**Returns:** Integer.  
Returns 1 if successful, else 0.

**Examples:** Director:  
set OK = baSetCurrentDir( "c:\temp" )

Authorware:  
OK := baSetCurrentDir( "c:\\temp" )

**Notes:** This function is useful when running external programs using the [RunProgram](#) function. Some programs, particularly DOS ones, require the current directory to be set first. The current directory can be retrieved using the [SysFolder](#) function.

**See also:** [SysFolder](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## CopyText

- Description:** baCopyText copies text to the clipboard.
- Usage:** Result = baCopyText( ClipText )
- Arguments:** String.  
ClipText is the text to copy to the clipboard.
- Returns:** Integer.  
Returns 1 if the function is successful, otherwise 0.
- Examples:** Director:  
set OK = baCopyText( UserName )
- Authorware:  
OK := baCopyText( UserName )
- See also:** [baPasteText](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## PasteText

**Description:** baPasteText copies text from the clipboard.

**Usage:** Result = baPasteText()

**Arguments:** Void.

**Returns:** String.  
Returns the text currently in the clipboard. If the clipboard is empty or unavailable, returns an empty string.

**Examples:** Director:  
set ClipText = baPasteText()

Authorware:  
ClipText := baPasteText()

**See also:** [baCopyText](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## EncryptText

**Description:** baEncryptText encrypts a text string.

**Usage:** Result = baEncryptText( String , Key )

**Arguments:** String, string.  
String is the text to encrypt.  
Key is the string to use as the encryption key.

**Returns:** String.  
Returns the encrypted string.

**Examples:** Director:  
set text = baEncryptText( "MyPassword" , "This is my key" )

Authorware:  
test := baEncryptText( "MyPassword" , "This is my key" )

**Notes:** This function uses an xor routine to encrypt the text. To decrypt the text, use the [baDecryptText](#) function using the same key. This will return the original text. As well as encrypting the text, this function also puts the text through a uuencode type function to ensure that the encrypted string contains only printable characters. This means that the encrypted string will not be the same length as the original string. The maximum size of the string that can be encrypted is 2000 characters.

**See also:** [baDecryptText](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## DecryptText

**Description:** baDecryptText decrypts a string encrypted with [baEncryptText](#)

**Usage:** Result = baDecryptText( String , Key )

**Arguments:** String, string.  
String is the text to decrypt.  
Key is the string that was used as the encryption key.

**Returns:** String.  
Returns the decrypted string.

**Examples:** Director:  
set text = baDecryptText( "MyEncryptedPassword" , "This is my key" )

Authorware:  
text := baDecryptText( "MyEncryptedPassword" , "This is my key" )

**See also:** [baEncryptText](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## PlaceCursor

**Description:** baPlaceCursor positions the cursor on the screen.

**Usage:** baPlaceCursor( X, Y )

**Arguments:** Integer, integer.  
X an Y is the new position of the cursor, measured from the top left corner of the screen.

**Returns:** Void.

**Examples:** Director:  
baPlaceCursor( 200 , 300 )

Authorware:  
baPlaceCursor( 200 , 300 )

**See also:** [baRestrictCursor](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## RestrictCursor

- Description:** baRestrictCursor restricts the cursor to a specified part of the screen.
- Usage:** baRestrictCursor( Left, Top, Right, Bottom )
- Arguments:** Integer, integer, integer, integer.  
Left, Top, Right, Bottom define the rectangle that the cursor will be restricted to. They are measured in pixels from the top left corner of the screen.
- Returns:** Void.
- Examples:** Director:  
baRestrictCursor( 100, 100, 200, 200 )  
  
Authorware:  
baRestrictCursor( 100, 100, 200, 200 )
- Notes:** Use the [baFreeCursor](#) function to return the cursor to its normal state.
- See also:** [baFreeCursor](#)  
[baPlaceCursor](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FreeCursor

**Description:** baFreeCursor allows the cursor to move anywhere on the screen. It is used to free the cursor after using [baRestrictCursor](#).

**Usage:** baFreeCursor()

**Arguments:** Void.

**Returns:** Void.

**Examples:** Director:  
[baFreeCursor\(\)](#)

Authorware:  
[baFreeCursor\(\)](#)

**See also:** [baRestrictCursor](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## SetVolume

**Description:** baSetVolume sets the volume level of the sound card for wave files and audio CD.

**Usage:** Result = baSetVolume( Device, Volume )

**Arguments:** String, integer.  
Device is the device to change. Can be:

"master"	sets the master volume
"wave"	sets the volume of wave and video files
"cd"	sets the volume of audio CD playback
"midi"	sets the volume of an external midi device
"synth"	sets the volume of the internal FM synthesizer
"master mute"	controls the master mute
"wave mute"	controls the wave mute
"cd mute"	controls the CD mute
"synth mute"	controls the built-in synthesizer mute

Volume is the volume level to set. The volume level can be between 0 (silence) and 100 (maximum). For the mute devices, Volume can be either 1 for mute on, or 0 for mute off.

**Returns:** Integer.  
Returns 1 if successful, else 0.

**Examples:** Director:  
`set OK = baSetVolume( "cd" , 50 )`

Authorware:  
`OK := baSetVolume( "cd" , 50 )`

**Notes:** Not all sound cards support this function. some cards will only support some of the device types. They will return 0 if the function is not supported.

The function will set the volume on the first sound card found.

The master volume and the mute options are only available under 32 bit, and then only if the system has a mixer device installed.

Some sound cards do not set the volume precisely. For example, if you set the volume to 50, then call the [baGetVolume](#) function, it may return 48 or 49.

**See also:** [baGetVolume](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## GetVolume

**Description:** baGetVolume gets the current volume level of wave files and audio CD.

**Usage:** Result = baGetVolume( Device )

**Arguments:** String.  
Device is the device to get the volume of. Can be:

"master"	gets the master volume
"wave"	gets the volume of wave and video files
"cd"	gets the volume of audio CD playback
"midi"	gets the volume of an external midi device
"synth"	gets the volume of the internal FM synthesizer
"master mute"	gets the master mute state
"wave mute"	gets the wave mute state
"cd mute"	gets the CD mute state
"synth mute"	gets the built-in synthesizer mute state

**Returns:** Integer.  
Returns the volume of the requested device. The volume level can be between 0 (silence) and 100 (maximum). The mute options will return 1 if the mute is on, or 0 if it isn't.  
Returns -1 if the function is not supported.

**Examples:** Director:  
`set Volume = baGetVolume( "wave" )`

Authorware:  
`Volume := baGetVolume( "wave" )`

**Notes:** Not all sound cards support this function. Some cards will only support some of the device types. They will return -1 if the function is not supported.

The function will get the volume from the first sound card found.

The master volume and the mute options are only available under 32 bit, and then only if the system has a mixer device installed.

If the left and right channels are at different levels, then the average of the two is returned.

Some sound cards do not set the volume precisely. For example, if you set the volume to 50 using the [baSetVolume](#) function, then call this function, it may return an 48 or 49.

**See also:** [baSetVolume](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## InstallFont

**Description:** baInstallFont installs a TrueType or Bitmap font.

**Usage:** Result = baInstallFont( FontFile , FontName )

**Arguments:** FontFile is the .ttf or .fon file to install.  
FontName is the name of the font.

**Returns:** Integer.  
Returns 0 if font installs OK. Otherwise returns one of:

- 1 A font file with that name already exists.
- 2 The font file was not found.
- 3 Error copying font file.
- 4 Windows couldn't install the font.
- 5 The font file is an invalid name.

**Examples:** Director:  
`set OK = baInstallFont( "arialb.ttf" , "Arial Bold" )`

Authorware:  
`OK := baInstallFont( "arialb.ttf" , "Arial Bold" )`

**Notes:** Most fonts are copyrighted material. You should not install a font unless you are legally allowed to do so.  
The name of the font should be taken from the Fonts Control Panel. The name that Windows identifies the font to applications is taken from information inside the font file, not the name you give it.  
You should use the [FontInstalled](#) command to check whether or not a particular font is already installed before you try to install a new copy.  
Director does not rebuild it's font list after it has been started. This means that the font will not be available to the projector that installed it unless it is restarted. All versions of Authorware should be able to use the font immediately. There is usually no need to restart Windows.

**See also:** [baFontInstalled](#)  
[baFontStyleList](#)  
[baFontList](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## KeyIsDown

**Description:** baKeyIsDown checks whether a key is currently down.

**Usage:** Result = baKeyIsDown( Key )

**Arguments:** Integer.  
Key is the virtual key code of the key to test.

**Returns:** Integer.  
Returns 1 if Key is being held down, else 0.

**Examples:** Director:  
set KeyDown = baKeyIsDown( 65 ) -- check if the "a" key is down

Authorware:  
KeyDown := baKeyIsDown( 65 ) -- check if the "a" key is down

**Notes:** A list of [Virtual Key Codes](#) is supplied. Some of these keys are not available in different versions of Windows.

**See also:** [baKeyBeenPressed](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## KeyBeenPressed

- Description:** baKeyBeenPressed checks whether a key has been pressed since the last time the function was called.
- Usage:** Result = baKeyBeenPressed( Key )
- Arguments:** Integer.  
Key is the virtual key code of the key to test.
- Returns:** Integer.  
Returns 1 if Key has been pressed since the last time the function was called, else 0.
- Examples:** Director:  
`set KeyBeenPressed = baKeyBeenPressed( 65 ) -- check if the "a" key has been pressed`
- Authorware:  
`KeyBeenPressed := baKeyBeenPressed( 65 ) -- check if the "a" key has been pressed`
- Notes:** A list of [Virtual Key Codes](#) is supplied. Some of these keys are not available in different versions of Windows.  
This function tracks key presses in all applications, not just yours.
- See also:** [baKeysIsDown](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## CreatePMGroup

**Description:** baCreatePMGroup makes a Program Manager or Start Menu group.

**Usage:** Result = baCreatePMGroup( Group )

**Arguments:** String.  
Group is the name of the group to create.

**Returns:** Integer.  
Returns 1 if successful, else 0.

**Examples:** Director:  
set OK = baCreatePMGroup( "Multimedia World" )  
  
Authorware:  
OK := baCreatePMGroup( "Multimedia World" )

**See also:** [baDeletePMGroup](#)  
[baPMGroupList](#)  
[baCreatePMIcon](#)  
[baDeletePMIcon](#)  
[baPMIconList](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## SystemTime

**Description:** baSystemTime returns the current time/date.

**Usage:** Result = baSystemTime( Format )

**Arguments:** String.  
Format is the time/date format to return.

**Returns:** String.  
Returns the requested time/date.

**Examples:** Director:  
`set theTime = baSystemTime( "date" )`

Authorware:  
`theTime := baSystemTime( "Today is %A" )` -- returns the day eg "Today is Tuesday"

**Notes:** There are two predefined formats - "time" and "date"  
"time" will return the current time in 24 hour format with leading zeros - hours, minutes and seconds eg "230412". It will always be 6 characters long.  
"date" will return the date in year, month, day eg "19980321". It will always be 8 characters long,  
Other formatting is available. Any of these constants will be replaced by the appropriate time/date - any other characters will be returned as is.

%a Abbreviated weekday name  
%A Full weekday name  
%b Abbreviated month name  
%B Full month name  
%d Day of month as decimal number (1 - 31)  
%0d Day of month with leading 0  
%H Hour in 24-hour format (0 - 23)  
%0H Hour in 24-hour format with leading 0  
%j Day of year as decimal number (1 - 366)  
%0j Day of year as decimal number with leading 0  
%m Month as decimal number (1 - 12)  
%0m Month as decimal number with leading 0  
%M Minute as decimal number (0 - 59)  
%0M Minute as decimal number with leading 0  
%S Second as decimal number (0 - 59)  
%0S Second as decimal number with leading 0  
%w Weekday as decimal number (0 - 6; Sunday is 0)  
%y Year without century, as decimal number (00 - 99)  
%Y Year with century, as decimal number

Examples:  
"%d %B, %Y" "2 June, 1998"  
"It is %M past %H on %A" "It is 23 past 10 on Tuesday"  
"The time is %H:%0M:%0S" "The time is 14:25:04"

**See also:** [baSetSystemTime](#)

[Information functions](#)

[File functions](#)

[Alphabetical function list](#)

[Contents](#)

[System functions](#)

[Window functions](#)

## SetSystemTime

**Description:** baSetSystemTime sets the current time/date.

**Usage:** Result = baSetSystemTime( Format, NewTime )

**Arguments:** String, string.  
Format is the time/date format to set. Can be either "time" or "date".  
NewTime is the time/date to set.

**Returns:** Integer.  
Returns 1 if successful, otherwise 0.

**Examples:** Director:  
set ok = baSetSystemTime( "date", "19980523" ) - sets the date to 23 June 1998

Authorware:  
set ok = baSetSystemTime( "time", "102300" ) - sets the time to 23 past 10

**Notes:** The format for the time or date must be as follows:  
"time" is in 24 hour format with leading zeros - hours, minutes and seconds and must be 6 characters  
"date" is in year, month, day with leading zeros and must be 8 characters long,  
The "date" and "time" formats are the same as those returned by [baSystemTime](#)

**See also:** [baSystemTime](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## PrinterInfo

**Description:** baPrinterInfo returns information about the installed printers.

**Usage:** Result = baPrinterInfo( Info )

**Arguments:** String.  
Info is the type of information required.

Can be

"installed"	returns full list of installed printers, drivers and ports
"list"	list of the names of installed printers
"default"	the current default printer
"orientation"	the orientation of the default printer
"paper"	the current paper size of the default printer
"papers"	the list of paper sizes supported by the default printer
"papername"	the name of the current paper of the default printer
"papernames"	the list of paper names of the default printer
"paperlength"	the length of the paper in the default printer in 1/1000 mm
"paperwidth"	the width of the paper in the default printer in 1/1000 mm
"copies"	the number of copies to print

**Returns:** Depends on Info type.

Xtra: "installed", "list", "papers", "papernames" return a list;  
"default", "orientation", "paper", "papername" return a string;  
"paperlength", "paperwidth" and "copies" return an integer.  
UCD: always returns a string.

**Examples:** Director:  
`set printer = baPrinterInfo( "default" )`

Authorware:  
`printerList := baPrinterInfo( "list" )`

**Notes:** The "installed" info type returns a list (Xtra) or a string (UCD) - one list element or line for each printer. Each element will consist of the printer name, then the driver, then the port, all separated by commas. eg.

[`"EPSON Stylus COLOR 400, EPS400, LPT1:"`, `"Acrobat PDFWriter, PDFWRITR, DISK:"`] (Xtra)  
`"EPSON Stylus COLOR 400, EPS400, LPT1:\rAcrobat PDFWriter, PDFWRITR, DISK:"` (UCD)

The "list" Info type returns a list with just the printer names. eg  
[`"EPSON Stylus COLOR 400"`, `"Acrobat PDFWriter"`]

The "orientation" Info type will return "Landscape", "Portrait" or "Unknown".

The "paper" Info type returns the size of the selected paper. It will be one of the following values:

`"Letter"`, `"LetterSmall"`, `"Tabloid"`, `"Ledger"`, `"Legal"`, `"Statement"`, `"Executive"`, `"A3"`, `"A4"`, `"A4Small"`, `"A5"`, `"B4"`, `"B5"`, `"Folio"`, `"Quarto"`, `"10x14"`, `"11x17"`, `"Note"`, `"Envelope9"`, `"Envelope10"`, `"Envelope11"`, `"Envelope12"`, `"Envelope14"`, `"CSheet"`, `"DSheet"`, `"ESheet"`, `"EnvelopeDL"`, `"EnvelopeC5"`, `"EnvelopeC3"`, `"EnvelopeC4"`, `"EnvelopeC6"`, `"EnvelopeC65"`, `"EnvelopeB4"`, `"EnvelopeB5"`, `"EnvelopeB6"`, `"EnvelopeItaly"`, `"EnvelopeMonarch"`, `"EnvelopePersonal"`, `"FanFoldUS"`, `"FanFoldStdGerman"`, `"FanFoldLegalGermany"`, `"User"`, `"Unknown"`.

The "papers" info type returns a list (Xtra) or string( UCD) of the paper sizes supported

by the default printer.

The "papername" type returns the name of the selected paper as shown by the printer driver.

The "papernames" type returns a list of the papers supported by the default printer, as listed by the printer driver.

The "paper" option uses paper sizes pre-defined by Windows. Printer drivers may define their own page sizes and names - if the selected paper is a printer-defined size, the function will return "Unknown".

The "papername" will return the name of the paper as displayed by the printer driver - this will be the name the user sees in printer setup dialog boxes.

**See also:** [baSetPrinter](#)

[Information functions](#)

[File functions](#)

[Alphabetical function list](#)

[Contents](#)

[System functions](#)

[Window functions](#)

## SetPrinter

**Description:** baSetPrinter changes settings for the default printer.

**Usage:** Result = baSetPrinter( Info, Data )

**Arguments:** String, any (Xtra) or string (UCD)  
Info is the type of information to set.

Can be

"default" set the current default printer (string)  
"orientation" the orientation of the default printer (string)  
"paper" the selected paper size of the default printer (string)  
"papername" the name of the selected paper of the default printer (string)  
"copies" the number of copies to print (integer - Xtra, string - UCD)

Data is the data to set - the format depends on the info type. The UCD version will always be a string.

**Returns:** Integer  
Returns 1 if successful, otherwise 0.

**Examples:** Director:  
set ok = baSetPrinter( "default", "Epson 400 Stylus Color" )  
set ok = baSetPrinter( "copies", 2 )

Authorware:  
ok := baSetPrinter( "orientation", "landscape" )  
ok := baSetPrinter( "copies", "2" )

**Notes:** The "default" option only requires the name of the printer, not the port or driver.  
The "paper" option uses the same names as the [baPrinterInfo](#) "paper".  
The "papername" option uses the same names as the [baPrinterInfo](#) "papername".

**See also:** [baPrinterInfo](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## RefreshDesktop

- Description:** baRefreshDesktop refreshes the desktop icons.
- Usage:** baRefreshDesktop( Wait )
- Arguments:** Integer.  
If Wait is true, then the function will wait until the update is complete before returning.
- Returns:** Void.
- Examples:** Director:  
[baRefreshDesktop\( true \)](#)
- Authorware:  
[baRefreshDesktop\( false \)](#)
- Notes:** This function would typically be used after making registry changes that affect the icons displayed by files, such as changing a file association.  
This function only works in the 32 bit Xtra/UCD. If used in 16 bit, it will do nothing.

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## DeletePMGroup

**Description:** baDeletePMGroup deletes a Program Manager or Start Menu group.

**Usage:** Result = baDeletePMGroup( Group )

**Arguments:** String.  
Group is the name of the group to delete.

**Returns:** Integer.  
Returns 1 if successful, else 0.

**Examples:** Director:  
set OK = baDeletePMGroup( "Multimedia World" )

Authorware:  
OK := baDeletePMGroup( "Multimedia World" )

**Notes:** The group does not have to be empty for it to be deleted.

**See also:** [baCreatePMGroup](#)  
[baPMGroupList](#)  
[baCreatePMIcon](#)  
[baDeletePMIcon](#)  
[baPMIconList](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## PMGroupList

**Description:** baPMGroupList returns a list of all Program Manager or Start Menu groups.

**Usage:** Result = baPMGroupList( )

**Arguments:** Void.

**Returns:** List (Xtra) or String (UCD).  
Returns a list or string containing all Program Manager groups.

**Examples:** Director:  
`set GroupList = baPMGroupList( )`

Authorware:  
`GroupList := baPMGroupList( )`

**Notes:** The return for the UCD version is a string with each group on a separate line. You can use the Authorware GetLine function to retrieve each group.

**See also:** [baPMSubGroupList](#)  
[baCreatePMGroup](#)  
[baDeletePMGroup](#)  
[baCreatePMIcon](#)  
[baDeletePMIcon](#)  
[baPMIconList](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## **PMSubGroupList**

**Description:** baPMSubGroupList returns a list of Start Menu groups inside another group.

**Usage:** Result = baPMSubGroupList(GroupName )

**Arguments:** GroupName.  
Group is the name of the group to get the list of

**Returns:** List (Xtra) or String (UCD).  
Returns a list or string containing the groups.

**Examples:** Director:  
`set GroupList = baPMSubGroupList("Accessories")`  
  
Authorware:  
`GroupList := baPMSubGroupList("Accessories ")`

**Notes:** This function returns the groups inside a group. These 'nested groups' are only possible in Windows 95/NT, and this function is only available in the 32 bit Xtra/UCD. If used in 16 bit, it will return an empty string/list.  
To get the contents of a group inside a group, place a "\" between the groups ("\" in Authorware) eg  
`baPMSubGroupList("Accessories\Multimedia")`.

The return for the UCD version is a string with each group on a separate line. You can use the Authorware GetLine function to retrieve each group.

**See also:** [baPMGroupList](#)  
[baCreatePMGroup](#)  
[baDeletePMGroup](#)  
[baCreatePMIcon](#)  
[baDeletePMIcon](#)  
[baPMIconList](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## CreatePMIcon

**Description:** baCreatePMIcon creates a Program Manager or Start Menu icon.

**Usage:** Result = baCreatePMIcon( Command, Title, Icon, IconNumber )

**Arguments:** String, string, string, integer.  
Command is the command line to use in the icon.  
Title is the name that appears under the icon.  
Icon is the name of the icon to use.  
IconNumber is the number of the icon to use.

**Returns:** Integer.  
Returns 1 if successful, else 0.

**Examples:** Director:  
set OK = baCreatePMIcon( "d:\mterms.exe", "Multimedia Terms", "d:\mterms.ico", 0 )

Authorware:  
OK := baCreatePMIcon( "d:\mterms.exe", "Multimedia Terms", " d:\mterms.ico", 0 )

**Notes:** The icon will be added to the active Program Manager group. To ensure that the group you want to add the icon to is active, you should always call [baCreatePMGroup](#) before you use this function (even if the group already exists). This will make the group the active one. If you are adding multiple icons, you only need to make one call to [baCreatePMGroup](#) before you start adding.  
If you create a group, and want to add icons to it, you should allow enough time for Windows to create the group before you try to add an icon to it. A wait of one second should be enough, but slow machines running Win95 may take longer.

The Icon parameter can be either an .ico, .exe or .dll file. If the file is a .ico, then the IconNumber parameter is ignored. If it is a .exe or .dll file, then the IconNumber is the number of the icon in that file to use. If the Icon is an empty string (""), then the first icon in the Command .exe file will be used.

For example:

[baCreatePMIcon\( "d:\mterms.exe", "Multimedia Terms", "", 0 \)](#)  
will use the default icon for d:\mterms.exe.

[baCreatePMIcon\( "d:\mterms.exe", "Multimedia Terms", "d:\mterms.ico", 0 \)](#)  
will use the d:\mterms.ico icon.

[baCreatePMIcon\( "d:\mterms.exe", "Multimedia Terms", "c:\windows\moreicons.dll", 5 \)](#)  
will use the fifth icon in moreicons.dll.

**See also:** [baCreatePMGroup](#)  
[baDeletePMGroup](#)  
[baPMGroupList](#)      [baPMSubGroupList](#)  
[baDeletePMIcon](#)  
[baPMIconList](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

**Alphabetical function list**

**Contents**

## DeletePMIcon

**Description:** baDeletePMIcon deletes a Program Manager or Start Menu icon.

**Usage:** Result = baDeletePMIcon( Icon )

**Arguments:** String.  
Icon is the name of the icon to delete.

**Returns:** Integer.  
Returns 1 if successful, else 0.

**Examples:** Director:  
set OK = baDeletePMIcon( "Multimedia Terms" )

Authorware:  
OK := baDeletePMIcon( "Multimedia Terms" )

**Notes:** The icon will be deleted from the active Program Manager group. To ensure that the group you want to delete the icon from is active, you should always call [baCreatePMGroup](#) before you use this function (even if the group already exists). This will make the group the active one. If you are deleting multiple icons, you only need to make one call to [baCreatePMGroup](#) before you start deleting.

**See also:** [baCreatePMGroup](#)  
[baDeletePMGroup](#)  
[baPMGroupList](#)  
[baPMSubGroupList](#)  
[baCreatePMIcon](#)  
[baPMIconList](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## PMIconList

**Description:** baPMIconList returns a list containing all the icons in a Program Manager group.

**Usage:** Result = baPMIconList( Group )

**Arguments:** String.  
Group is the name of the group to get the icons of.

**Returns:** List (Xtra) or String (UCD).  
Returns a list or string containing all the icons in Group.  
If Group does not exist or it empty, then an empty list or string will be returned.

**Examples:** Director:  
set IconList = baPMIconList( "Macromedia" )

Authorware:  
IconList := baPMIconList( "Macromedia" )

**Notes:** The return for the UCD version is a string with each icon on a separate line. You can use the Authorware GetLine function to retrieve each group.  
In 32 bit, you can also get the contents of a nested group, by placing a "\" ("\" in Authorware) between the groups. eg baPMIconList( "Accessories\Multimedia" ) will get the contents of the Multimedia group, inside the Accessories group.

**See also:** [baCreatePMGroup](#)  
[baDeletePMGroup](#)  
[baPMGroupList](#)  
[baPMSubGroupList](#)  
[baCreatePMIcon](#)  
[baDeletePMIcon](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## File functions

<a href="#"><u>FileAge</u></a>	returns the age of a file
<a href="#"><u>FileExists</u></a>	checks whether a file exists
<a href="#"><u>FolderExists</u></a>	checks whether a folder exists
<a href="#"><u>CreateFolder</u></a>	creates a new folder
<a href="#"><u>DeleteFolder</u></a>	deletes an empty folder
<a href="#"><u>RenameFile</u></a>	renames a file or folder
<a href="#"><u>DeleteFile</u></a>	deletes a file
<a href="#"><u>DeleteXFiles</u></a>	deletes files with wildcard matching
<a href="#"><u>XDelete</u></a>	deletes files with wildcard matching, including sub-directories
<a href="#"><u>FileDate</u></a>	returns the date of a file
<a href="#"><u>FileSize</u></a>	returns the size of a file
<a href="#"><u>FileAttributes</u></a>	returns the attributes of a file
<a href="#"><u>SetFileAttributes</u></a>	sets the attributes of a file
<a href="#"><u>RecycleFile</u></a>	places a file in the Win95/NT recycle bin.
<a href="#"><u>CopyFile</u></a>	copies a file.
<a href="#"><u>CopyXFiles</u></a>	copies multiple files with wildcard matching.
<a href="#"><u>XCopy</u></a>	copies multiple files with wildcard matching, including sub-directories.
<a href="#"><u>FileVersion</u></a>	returns the version of a file.
<a href="#"><u>FileList</u></a>	returns a list of files in a folder.
<a href="#"><u>FolderList</u></a>	returns a list of folders in a folder.
<a href="#"><u>GetFilename</u></a>	displays a file selection dialog.
<a href="#"><u>GetFolder</u></a>	displays a folder selection dialog.
<a href="#"><u>FindFirstFile</u></a>	searches for the first file matching a specification
<a href="#"><u>FindNextFile</u></a>	searches for the next file matching a specification
<a href="#"><u>FindClose</u></a>	finishes a search started with baFindFirstFile
<a href="#"><u>EncryptFile</u></a>	encrypts/decrypts a file
<a href="#"><u>FindDrive</u></a>	searches all drives for a specified file
<a href="#"><u>Shell</u></a>	executes a file
<a href="#"><u>OpenFile</u></a>	opens a file using it's associated program
<a href="#"><u>OpenURL</u></a>	opens a URL using the default browser
<a href="#"><u>PrintFile</u></a>	prints a file using it's associated program
<a href="#"><u>ShortFileName</u></a>	returns the DOS version of a Win95 long file name
<a href="#"><u>TempFileName</u></a>	returns a temporary file name guaranteed not to exist
<a href="#"><u>MakeShortcut</u></a>	creates a Win95/NT shortcut
<a href="#"><u>MakeShortcutEx</u></a>	creates a Win95/NT shortcut
<a href="#"><u>ResolveShortcut</u></a>	returns the file a shortcut points to

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FileAge

**Description:** baFileAge returns the date of a file in seconds.

**Usage:** Result = baFileAge( FileName )

**Arguments:** String  
FileName is the file to get the age of.

**Returns:** Integer.  
Returns the age of the file in seconds.

**Examples:** Director:  
set Age = baFileAge( "student.dat" )

Authorware:  
Age := baFileAge( "student.dat" )

**Notes:** The number returned is the number of seconds since an arbitrary date. The number means little by itself, but can be used to compare the dates of two files. The file with higher number is the newer file. For example:  
if baFileAge( "c:\data\student.dat" ) > baFileAge( "a:\student.dat" ) then  
-- file on "C" drive is newer than the one on "A" drive.

**See also:** [baFileDate](#)  
[baFileVersion](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FileExists

**Description:** baFileExists reports whether or not a specific file exists.

**Usage:** Result = baFileExists( FileName )

**Arguments:** String.  
FileName is the name of the file. It should include the full path name.

**Returns:** Integer.  
Returns 1 if the file exists, otherwise 0.

**Examples:** Director:  
set File = baFileExists( the pathname & "test.dat" )

Authorware:  
File := baFileExists( FileLocation ^ "test.dat" )

**See also:** [baRenameFile](#)  
[baFolderExists](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FolderExists

**Description:** baFolderExists checks whether or not a folder exists.

**Usage:** Result = baFolderExists( FolderName )

**Arguments:** String  
FolderName is the folder to check for.

**Returns:** Integer.  
Returns 1 if the folder exists, else 0.

**Examples:** Director:  
set OK = baFolderExists( "c:\data" )

Authorware:  
OK := baFolderExists( "c:\\data" )

**See also:** [baCreateFolder](#)  
[baDeleteFolder](#)  
[baFileExists](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## CreateFolder

**Description:** baCreateFolder creates a new folder.

**Usage:** Result = baCreateFolder( FolderName )

**Arguments:** String  
FolderName is the folder to create.

**Returns:** Integer.  
Returns 1 if the folder was successfully created or already exists, else 0.

**Examples:** Director:  
set OK = baCreateFolder( "c:\data\courses" )

Authorware:  
OK := baCreateFolder( "c:\data\courses" )

**Notes:** This function will create any intermediate folders that are needed. For example, baCreateFolder( "c:\data\courses\biology" ) will create "c:\data", then "c:\data\courses", then "c:\data\courses\biology".

**See also:** [baFolderExists](#)  
[baDeleteFolder](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## DeleteFolder

**Description:** baDeleteFolder deletes an empty folder.

**Usage:** Result = baDeleteFolder( FolderName )

**Arguments:** String  
FolderName is the folder to delete.

**Returns:** Integer.  
Returns 1 if the folder was successfully deleted or doesn't exist, else 0.

**Examples:** Director:  
set OK = baDeleteFolder( "c:\data" )

Authorware:  
OK := baDeleteFolder( "c:\\data" )

**Notes:** This function will only delete a folder that doesn't contain any files or sub-directories.

**See also:** [baFolderExists](#)  
[baCreateFolder](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## RenameFile

**Description:** baRenameFile renames a file or folder.

**Usage:** Result = baRenameFile( FileName , NewName )

**Arguments:** String  
FileName is the file/folder to rename.  
NewName is the new name for the file/folder.

**Returns:** Integer.  
Returns 1 if the file was successfully renamed, else 0.

**Examples:** Director:  
`set OK = baRenameFile( "c:\data\student.dat" , "c:\data\student.bak" )`  
  
Authorware:  
`OK := baRenameFile( "c:\data\student.dat" , "c:\data\student.bak" )`

**Notes:** This function will fail if a file called NewName already exists. The full path name to both the FileName and the NewName should be given.  
You can also move a file or folder to a different folder if the destination file is on the same drive as the source file. eg: `baRenameFile( "c:\data\student.dat" , "c:\temp\student.dat" )` moves student.dat file from c:\data to c:\temp.

**See also:** [baFileExists](#)  
[baDeleteFile](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## DeleteFile

**Description:** baDeleteFile deletes a file.

**Usage:** Result = baDeleteFile( FileName )

**Arguments:** String  
FileName is the file to delete.

**Returns:** Integer.  
Returns 1 if the file was successfully deleted or doesn't exist, else 0.

**Examples:** Director:  
set OK = baDeleteFile( "c:\data\student.bak" )

Authorware:  
OK := baDeleteFile( "c:\\data\\student.bak" )

**See also:** [baDeleteXFiles](#)  
[baRenameFile](#)  
[baRecycleFile](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## DeleteXFiles

**Description:** baDeleteXFiles deletes files with wildcard matching.

**Usage:** Result = baDeleteXFiles( DirName , FileSpec )

**Arguments:** String, string.  
DirName is the folder to delete the files from.  
FileSpec determines what files are deleted.

**Returns:** Integer.  
Returns 1 if all the matching files were successfully deleted or if DirName doesn't exist, else 0.

**Examples:** Director:  
set OK = baDeleteXFiles( "c:\data" , "\*.bak" )

Authorware:  
OK := baDeleteXFiles( "c:\\data" , "\*.bak" )

**Notes:** The FileSpec argument follows normal DOS wildcard rules. A \* means match any character in the file name.  
So \*.\* deletes all files in the directory; \*.bmp deletes all files with a .bmp extension;  
T\*.\* deletes all files starting with the letter T.

**See also:** [baDeleteFile](#)  
[baFileExists](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## XDelete

- Description:** baXDelete deletes files with wildcard matching, including sub-directories.
- Usage:** Result = baXDelete( DirName , FileSpec )
- Arguments:** String, string.  
DirName is the folder to delete the files from.  
FileSpec determines what files are deleted.
- Returns:** Integer.  
Returns 1 if all the matching files were successfully deleted or if DirName doesn't exist, else 0.
- Examples:** Director:  
set OK = baXDelete( "c:\data" , "\*.bak" )  
  
Authorware:  
OK := baXDelete( "c:\data" , "\*.bak" )
- Notes:** Any empty directories that are left will also be deleted.  
The FileSpec argument follows normal DOS wildcard rules. A \* means match any character in the file name.  
So \*.\* deletes all files in the directory; \*.bmp deletes all files with a .bmp extension;  
T\*. \* deletes all files starting with the letter T.
- See also:** [baDeleteFile](#)  
[baDeleteXFiles](#)  
[baFileExists](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FileDate

**Description:** baFileDate returns the date of a file as a string.

**Usage:** Result = baFileDate( FileName , DateFormat , TimeFormat )

**Arguments:** String, string, string  
FileName is the file to get the date of.  
DateFormat is the desired format of the date,  
TimeFormat is the desired format of the time.

**Returns:** String.  
Returns the date of the file, or an empty string if the file doesn't exist.

**Examples:** Director:  
set OK = baFileDate( "c:\data\student.dat" , "dd-mm-yy" , "hh:nn:ss" )

Authorware:  
OK := baFileDate( "c:\data\student.dat" , "dd-mm-yy" , "hh:nn:ss" )

**Notes:** The date format can consist of "d" for day, "m" for month, "y" for year.  
The time format can consist of "h" for hours, "n" for minutes, "s" for seconds. (Note the "n" for minutes.)  
A single letter ("d") returns the exact number eg "5".  
A double letter ("dd") returns the number with a leading zero if required eg "05".  
A triple letter ("ddd") returns the short name eg "Mon".  
A quad letter ("dddd") returns the full name eg "Monday".  
Any letters other than those listed above will returned as is - they can be used for separators eg "dd-mm-yy" returns "05-11-97"; "d mmmm, yyyy" returns "5 November, 1997"  
If the format is an empty string, then the date or time will not be returned.

**See also:** [baFileAge](#)  
[baFileVersion](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FileSize

- Description:** baFileSize returns the size of a file.
- Usage:** Result = baFileSize( FileName )
- Arguments:** String.  
FileName is the file to get the size of.
- Returns:** Integer.  
Returns the size of the file in bytes, or -1 if the file doesn't exist.
- Examples:** Director:  
set size = baFileSize( "c:\data\student.dat" )
- Authorware:  
size := baFileSize( "c:\\data\\student.dat" )

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FileAttributes

**Description:** baFileAttributes returns the attributes of a file.

**Usage:** Result = baFileAttributes( FileName )

**Arguments:** String.  
FileName is the file to get the attributes of.

**Returns:** String.  
Returns a string containing all the the attributes that are set.  
Can be any combination of:  
"r" read-only  
"a" archive  
"h" hidden  
"s" system  
Returns an empty string if FileName doesn't exist.

**Examples:** Director:  
`set att = baFileAttributes( "c:\data\student.dat" )`

Authorware:  
`att := baFileAttributes( "c:\data\student.dat" )`

**Notes:** You can use the Director **contains** or Authorware **Find** function to test whether a particular attribute is set. eg.

if Find( "r" , baFileAttributes( FileName ) ) <> 0 then -- file is read only

if baFileAttributes( FileName ) contains "r" then -- file is read only

**See also:** [baSetFileAttributes](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## SetFileAttributes

**Description:** baSetFileAttributes sets the attributes of a file.

**Usage:** Result = baSetFileAttributes( FileName , Attributes )

**Arguments:** String, string.  
FileName is the file to get the attributes of.  
Attributes are the attributes to set.  
Can be any combination of:  
"r" read-only  
"a" archive  
"h" hidden  
"s" system  
An empty string removes all attributes.

**Returns:** Integer.  
Returns 1 if successful, else 0.

**Examples:** Director:  
set OK = baSetFileAttributes( "c:\data\student.dat" , "rh" ) -- make file hidden and read-only

Authorware:  
OK := baSetFileAttributes( "c:\data\student.dat" , "" ) -- clear all attributes

**See also:** [baFileAttributes](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## RecycleFile

**Description:** baRecycleFile places a file in the Win95/NT recycle bin.

**Usage:** Result = baRecycleFile( FileName )

**Arguments:** String  
FileName is the file to recycle.

**Returns:** Integer.  
Returns 1 if the file was successfully recycled or doesn't exist, else 0.

**Examples:** Director:  
set OK = baRecycleFile( "c:\data\student.bak" )

Authorware:  
OK := baRecycleFile( "c:\\data\\student.bak" )

**Notes:** This function only works in 32 bit. If used in 16 bit, the file will be immediately deleted.

**See also:** [baDeleteFile](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## CopyFile

**Description:** baCopyFile copies a file.

**Usage:** Result = baCopyFile( SourceFile , DestFile , Overwrite )

**Arguments:** String, string, string.  
SourceFile is the file to copy.  
DestFile is the name to copy it to.  
Overwrite determines how the copy is done. Can be:  
"Always" always copies the file  
"IfNewer" copies the file if SourceFile is newer than DestFile  
"IfNotExist" copies only if DestFile does not already exist

**Returns:** Integer.  
Returns 0 if the file was copied successfully, otherwise one of these:  
1 Invalid Source file name  
2 Invalid Dest file name  
3 Error reading the Source file  
4 Error writing the Dest file  
5 Couldn't create directory for Dest file  
6 Dest file exists  
7 Dest file is newer than Source file

**Examples:** Director:  
set OK = baCopyFile( "c:\data\student.dat" , "c:\data\backup\student.dat" , "IfNewer" )

Authorware:  
OK := baCopyFile( "c:\data\student.dat" , "c:\data\backup\student.dat" , "IfNewer" )

**Notes:** By default, this function will not overwrite an existing file if that file is marked as read-only. However, by adding "+" to the "Always" and "IfNewer" options (eg "Always+" or "IfNewer+"), the files will be overwritten if they are read-only.

A return value of 6 (Dest file exists) can only be returned when Overwrite is "IfNotExist".

A return value of 7 (Dest file is newer than Source file) can only be returned when Overwrite is "IfNewer". The other return values can be returned for all Overwrite options.

The "IfNewer" option operates as follows: if both files have internal version numbers, then these numbers are used for comparison, otherwise the dates of the two files are used for comparison.

The DestFile must contain the full name of the file, not just the name of the folder it is being copied to.

The 16 bit version will not copy system or hidden files, but the 32 bit version can. The 16 bit version will return 1 if you attempt to copy a hidden file.

The new file will be set to archive and not read-only.

**See also:** [baCopyXFiles](#)  
[baXCopy](#)

[Information functions](#)  
[File functions](#)

[System functions](#)  
[Window functions](#)

**Alphabetical function list**

**Contents**

## CopyXFiles

**Description:** baCopyXFiles copies multiple files from one folder to another folder, with wildcard matching.

**Usage:** Result = baCopyXFiles( SourceDir , DestDir , FileSpec , Overwrite )

**Arguments:** String, string, string, string.  
SourceDir is the folder to copy from.  
DestDir is the folder to copy to.  
FileSpec determines what files are copied.  
Overwrite determines how the copy is done. Can be:  
"Always" always copies the file  
"IfNewer" copies the file if SourceFile is newer than DestFile  
"IfNotExist" copies only if DestFile does not already exist

**Returns:** Integer.  
Returns 0 if all the files were copied successfully, otherwise one of these:  
1 Invalid SourceDir name  
2 Invalid DestDir file name  
3 Error reading a Source file  
4 Error writing a Dest file  
5 Couldn't create directory for Dest files  
6 Dest file exists  
7 Dest file is newer than Source file  
8 No files matched the specified wildcard

**Examples:** Director:  
set OK = baCopyXFiles( "c:\data" , "d:\backup" , "\*.dat" , "IfNewer" )

Authorware:  
OK := baCopyXFiles( "c:\data" , "d:\backup" , "\*.dat" , "IfNewer" )

**Notes:** By default, this function will not overwrite an existing file if that file is marked as read-only. However, by adding "+" to the "Always" and "IfNewer" options (eg "Always+" or "IfNewer+"), the files will be overwritten if they are read-only.

The return value will not be 0 if any file is not copied. For example, if you specify baCopyXFiles( "c:\data" , "d:\backup" , "\*" , "IfNewer" ) and any of the files in c:\data are newer than the ones in d:\backup, the return result will be 7 (Dest file is newer than Source). A result of 0 will be returned only if none of the files in c:\data is newer than d:\backup.

The FileSpec argument follows normal DOS wildcard rules. A \* means match any character in the file name.  
So \*.\* copies all files; \*.bmp copies all files with a .bmp extension; T.\* copies all files starting with the letter T.

A return value of 6 (Dest file exists) can only be returned when Overwrite is "IfNotExist".

A return value of 7 (Dest file is newer than Source file) can only be returned when Overwrite is "IfNewer". The other return values can be returned for all Overwrite options.

The "IfNewer" option operates as follows: if both files have internal version numbers, then these numbers are used for comparison, otherwise the dates of the two files are used for comparison.

The 16 bit version can not copy system or hidden files, but the 32 bit version can. The new files will be set to archive and not read-only.

**See also:** [baCopyFile](#)  
[baXCopy](#)

[Information functions](#)

[File functions](#)

[Alphabetical function list](#)

[Contents](#)

[System functions](#)

[Window functions](#)

## XCopy

**Description:** baXCopy copies multiple files from one folder to another folder, with wildcard matching, including sub-directories.

**Usage:** Result = baCopyX( SourceDir , DestDir , FileSpec , Overwrite, MakeDir )

**Arguments:** String, string, string, string, integer.  
SourceDir is the folder to copy from.  
DestDir is the folder to copy to.  
FileSpec determines what files are copied.  
Overwrite determines how the copy is done. Can be:  
"Always" always copies the file  
"IfNewer" copies the file if SourceFile is newer than DestFile  
"IfNotExist" copies only if DestFile does not already exist  
If MakeDir is true, any empty directories will be created.

**Returns:** Integer.  
Returns 0 if all the files were copied successfully, otherwise one of these:

- 1 Invalid SourceDir name
- 2 Invalid DestDir file name
- 3 Error reading a Source file
- 4 Error writing a Dest file
- 5 Couldn't create directory for Dest files
- 6 Dest file exists
- 7 Dest file is newer than Source file
- 8 No files matched the specified wildcard

**Examples:** Director:  
set OK = baXCopy( "c:\data" , "d:\backup" , "\*.dat " , "IfNewer" , true )

Authorware:  
OK := baXCopy( "c:\data" , "d:\backup" , "\*.\*" , "Always" , false )

**Notes:** By default, this function will not overwrite an existing file if that file is marked as read-only. However, by adding "+" to the "Always" and "IfNewer" options (eg "Always+" or "IfNewer+"), the files will be overwritten if they are read-only.

The return value will not be 0 if any file is not copied. For example, if you specify baXCopy( "c:\data" , "d:\backup" , "\*.\*" , "IfNewer" ) and any of the files in c:\data are newer than the ones in d:\backup, the return result will be 7 (Dest file is newer than Source). A result of 0 will be returned only if none of the files in c:\data is newer than d:\backup.

The FileSpec argument follows normal DOS wildcard rules. A \* means match any character in the file name.

So \*.\* copies all files; \*.bmp copies all files with a .bmp extension; T\*. \* copies all files starting with the letter T.

A return value of 6 (Dest file exists) can only be returned when Overwrite is "IfNotExist".

A return value of 7 (Dest file is newer than Source file) can only be returned when Overwrite is "IfNewer". The other return values can be returned for all Overwrite options.

The "IfNewer" option operates as follows: if both files have internal version numbers, then these numbers are used for comparison, otherwise the dates of the two files are used for comparison.

The 16 bit version can not copy system or hidden files, but the 32 bit version can. The new files will be set to archive and not read-only.

**See also:** [baCopyFile](#)  
[baCopyXFiles](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FileVersion

- Description:** baFileVersion returns a string containing the version of a file.
- Usage:** Result = baFileVersion( FileName )
- Arguments:** String.  
FileName is the name of the file to obtain version information of.
- Returns:** String.  
Returns the version of the file. If the file doesn't contain version information or doesn't exist, then an empty string is returned.
- Examples:** Director:  
`set AcroVer = baFileVersion( "c:\acroread\acroread.exe" )`
- Authorware:  
`AcroVer := baFileVersion( "c:\acroread\acroread.exe" )`
- Notes:** The version of a 32 bit file (dll, exe, etc) is not available to a 16 bit exe under Windows NT.
- See also:** [baFileDate](#)  
[baFileAge](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FileList

**Description:** baFileList returns a list of files in a folder.

**Usage:** Result = baFileList( Folder, FileSpec )

**Arguments:** String, string.  
Folder is the name of the folder to list.  
FileSpec is the pattern of files to match.

**Returns:** List (Xtra) or String (UCD).  
Returns the list of matching files. If Folder doesn't exist, then an empty list/string is returned.

**Examples:** Director:  
set Files = baFileList( "c:\windows", "\*.\*" )

Authorware:  
Files := baFileList( "c:\\temp", "\*.bmp" )

**See also:** [baFolderList](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FolderList

- Description:** baFolderList returns a list of folders in a folder.
- Usage:** Result = baFolderList( Folder )
- Arguments:** String.  
Folder is the name of the folder to list.
- Returns:** List (Xtra) or String (UCD).  
Returns the list of folders. If Folder doesn't exist, then an empty list/string is returned.
- Examples:** Director:  
set Folders = baFolderList( "c:\windows" )
- Authorware:  
Files := baFolderList( "c:\\temp" )
- See also:** [baFileList](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## GetFilename

**Description:** baGetFilename displays a file dialog box and returns the filename selected.

**Usage:** Result = baGetFilename( Operation, StartDir, Filename, Filter, Flags, Instruction, NoFolders, X, Y )

**Arguments:** String, string, string, string, integer, string, integer, integer, integer.  
Operation is the type of dialog to show. Can be "open" or "save".  
StartDir is the initial directory. Use "" for the current directory.  
Filename is the initial file name to display.  
Filter is the type of files to display. Use "" to show all files.  
Flags modifies the behaviour of the dialog.  
Instruction is the instruction to display to the user.  
If NoFolders is true, the folder selection controls will not be shown.  
X is horizontal position of the dialog.  
Y is the vertical position of the dialog.

**Returns:** String.  
Returns the file name selected, or "" if the user cancelled.

**Examples:** Director:  
`set filename = baGetFilename( "save", "c:\temp", "newfile.txt", "Text files|.txt", 0, "Save new file", false, 100, 100 )`

Authorware:  
`file := baGetFilename( "open", "c:\temp", "", "", 0, "Select data file to open", true, -1, 0 )`

**Notes:** The filter argument consists of a series of strings separated by "|" characters. The strings are divided into pairs, the first half of a pair is the description that appears in the drop down box, the second half is the wildcard for the files. Separate multiple wildcards with semi-colons.

"Text files|.txt" -- shows only text files

"Text files|.txt|All files|\*.\*" -- allows the user to display either text files or all files

"Images|.bmp;\*.tif;\*.jpg" -- shows different image files

Setting the NoFolders option to true will mean that the user will not be able to change the initial directory, and folders will not be shown.

The X and Y values are the number of pixels from the top left corner of the screen. Set X to -1 to position the dialog in the center of the calling Director/Authorware window. Set X to -2 to position the dialog in the center of the screen.

The flags argument allows you to change the way the dialog box looks and behaves. It can be the combination of any of these values.

- 1 OFN\_READONLY  
Causes the Read Only check box to be checked initially when the dialog box is created.
- 2 OFN\_OVERWRITEPROMPT  
Causes the Save As dialog box to generate a message box if the selected file already exists. The user must confirm whether to overwrite the file.
- 4 OFN\_HIDEREADONLY  
Hides the Read Only check box.
- 8 OFN\_NOCHANGEDIR  
Restores the current directory to its original value if the user changed the directory

	while selecting a file.
32	OFN_ADDEXTENSION If the user enters a name without an extension, the first extension listed in the Filter argument will be added to the end of the returned filename.
512	OFN_ALLOWMULTISELECT Specifies that the File Name list box allows multiple selections.
2048	OFN_PATHMUSTEXIST Specifies that the user can type only valid paths and filenames. If this flag is used and the user types an invalid path and filename in the File Name entry field, the dialog box function displays a warning in a message box.
4096	OFN_FILEMUSTEXIST Specifies that the user can type only names of existing files in the File Name entry field. If this flag is specified and the user enters an invalid name, the dialog box procedure displays a warning in a message box.
8192	OFN_CREATEPROMPT Specifies that the dialog box function should ask whether the user wants to create a file that does not currently exist.
32768	OFN_NOREADONLYRETURN Specifies that the returned file does not have the Read Only check box checked and is not in a write-protected directory.
131072	OFN_NONETWORKBUTTON Hides and disables the Network button.
262144	OFN_NOLONGNAMES Specifies that long filenames are not displayed in the File Name list box. This value is ignored if OFN_EXPLORER is set.

These values are available in 32 bit only

524288	OFN_EXPLORER Creates an Open or Save As dialog box that uses user-interface features similar to the Windows Explorer.
1048576	OFN_NODEREFERENCELINKS Directs the dialog box to return the path and filename of the selected shortcut (.LNK) file. If this value is not given, the dialog box returns the path and filename of the file <i>referenced by</i> the shortcut.
2097152	OFN_LONGNAMES Causes the Open or Save As dialog box to display long filenames. If this flag is not specified, the dialog box displays filenames in 8.3 format. This value is ignored if OFN_EXPLORER is set.

To use these values, add the appropriate values together eg  
OFN\_CREATEPROMPT + OFN\_HIDEREADONLY + OFN\_NONETWORKBUTTON

If OFN\_ALLOWMULTISELECT is selected and the user selects more than one file, the return will be a series of strings, separated by returns. The first line will be the directory selected, the remaining lines will be the selected filenames. In Director, use "the line of" function to retrieve each line. In Authorware, use the "GetLine" function.

The OFN\_EXPLORER flag can not be used with the NoFolders option.

To make it easier to enter the constants, here are some scripts:

```
Director:
set OFN_READONLY = 1
set OFN_OVERWRITEPROMPT = 2
set OFN_HIDEREADONLY = 4
set OFN_NOCHANGEDIR = 8
set OFN_ALLOWMULTISELECT = 512
set OFN_PATHMUSTEXIST = 2048
set OFN_FILEMUSTEXIST = 4096
set OFN_CREATEPROMPT = 8192
set OFN_NOREADONLYRETURN = 32768
```

```
set OFN_NONETWORKBUTTON = 131072
set OFN_NOLONGNAMES = 262144
-- 32 bit only
set OFN_EXPLORER = 524288
set OFN_NODEREFERENCELINKS = 1048576
set OFN_LONGNAMES = 2097152
```

Authorware:

```
OFN_READONLY := 1
OFN_OVERWRITEPROMPT := 2
OFN_HIDEREADONLY := 4
OFN_NOCHANGEDIR := 8
OFN_ALLOWMULTISELECT := 512
OFN_PATHMUSTEXIST := 2048
OFN_FILEMUSTEXIST := 4096
OFN_CREATEPROMPT := 8192
OFN_NOREADONLYRETURN := 32768
OFN_NONETWORKBUTTON := 131072
OFN_NOLONGNAMES := 262144
-- 32 bit only
OFN_EXPLORER := 524288
OFN_NODEREFERENCELINKS := 1048576
OFN_LONGNAMES := 2097152
```

**See also:**      [baGetFolder](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## GetFolder

**Description:** baGetFolder displays a directory dialog box and returns the folder selected..

**Usage:** Result = baGetFolder( StartDir, Instruction, Flags, Caption, X, Y )

**Arguments:** String, string, integer, string, integer, integer.  
StartDir is the initial directory. Use "" for the current directory.  
Instruction is the instruction to display to the user.  
Flags modifies the behaviour of the dialog.  
Caption is the caption of the dialog.  
X is the horizontal position of the dialog.  
Y is the vertical position of the dialog.

**Returns:** String.  
Returns the folder selected, or "" if the user cancelled.

**Examples:** Director:  
set folder = baGetFolder( "c:\temp", "Please select a folder to install into:", 1, "Select a folder", -1, 0 )

Authorware:  
folder := baGetFolder( "c:\\temp", "Select installation directory", 0, "", 200, 200 )

**Notes:** The flags argument allows you to change the way the dialog box looks and behaves. The following flags are defined.

- 1 ODN\_EXPLORER  
Makes the dialog box a 32 bit Explorer style. If this style is not available, for example if running under Windows 3.1, then a 16 bit style dialog will be shown. The 16 bit Xtra/UCD ignores this style - it will always show the 16 bit style dialog.
- 2 ODN\_NEWBUTTON  
Displays a New button to allow the user to create a new folder. This style is only available with the 16 bit style dialog. It cannot be combined with ODN\_EXPLORER.

The Caption argument is only used if a 32 bit dialog box is used. If it is an empty string, then the default "Browse for Folder" will be displayed.

The X and Y values are the number of pixels from the top left corner of the screen. Set X to -1 to position the dialog in the center of the calling Director/Authorware window. Set X to -2 to position the dialog in the center of the screen.

**See also:** [baGetFilename](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FindFirstFile

**Description:** baFindFirstFile searches for the first file matching a specification.

**Usage:** Result = baFindFirstFile( StartDir, FileSpec )

**Arguments:** String, string.  
StartDir is the directory to start searching in.  
FileSpec is the pattern to search for.

**Returns:** String  
Returns the full path to the first file found

**Examples:** Director:  
set file = baFindFirstFile( "c:\", "netscape.exe" ) -- searches drive c for netscape.exe

Authorware:  
file := baFindFirstFile( "c:\windows", "\*.ttf" ) -- searches for fonts

**Notes:** All sub-directories of the starting directory will be included in the search. This function can be used with baFindNextFile to find all files. When you are finished finding all the files you are interested in, you must call baFindClose to free memory allocated by baFindFirstFile.

Here are examples of searching the C drive for all copies of "netscape.exe"

Director:

```
set fileList = [] -- a list to contain the found files
set file = baFindFirstFile( "c:\", "netscape.exe" )
-- loop through all found files and add to the list
repeat while file <> ""
    append( fileList, file )
    set file = baFindNextFile()
end repeat
baFindClose()
```

Authorware Xtra:

```
fileList := [] -- a list to contain the found files
file := baFindFirstFile( "c:\", "netscape.exe" )
repeat while file <> ""
    AddLinear( fileList, file )
    file := baFindNextFile()
end repeat
baFindClose()
```

Authorware UCD:

```
fileList := ""
file := baFindFirstFile( "c:\", "netscape.exe" )
repeat while file <> ""
    -- add names to fileList with returns between file names
    if fileList = "" then
```

```
        fileList := file
    else
        fileList := fileList ^ Return ^ file
    end if
    -- get next file
    file := baFindNextFile()
end repeat
baFindClose()
```

**See also:** [baFindNextFile](#)  
[baFindClose](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FindNextFile

**Description:** baFindNextFile continues a search started with baFindFirstFile.

**Usage:** Result = baFindNextFile( )

**Arguments:** Void

**Returns:** String  
Returns the full path to the next file found

**Examples:** Director:  
set file = baFindNextFile( )

Authorware:  
file := baFindNextFile( )

**Notes:** You must call baFindFirstFile before calling this function. baFindFirstFile sets up the search criteria, and allocates the required memory. When you are finished finding all the files you are interested in, you should call baFindClose to free memory allocated by baFindFirstFile.

**See also:** [baFindFirstFile](#)  
[baFindClose](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FindClose

**Description:** baFindClose finishes a search started with baFindFirstFile.

**Usage:** baFindClose()

**Arguments:** Void

**Returns:** Void

**Examples:** Director:  
baFindClose()

Authorware:  
baFindClose()

**Notes:** This function frees memory allocated by baFindFirstFile. After calling this function, you must call baFindFirstFile to start a new search.

**See also:** [baFindFirstFile](#)  
[baFindNextFile](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## EncryptFile

**Description:** baEncryptFile encrypts/decrypts a file.

**Usage:** Result = baEncryptFile( FileName , Key )

**Arguments:** String, string.  
FileName is the file to encrypt/decrypt.  
Key is the string to use as the encryption key.

**Returns:** Integer.  
Returns 1 if successful, else 0.

**Examples:** Director:  
set OK = baEncryptFile( "d:\results.dat" , "This is my key" )

Authorware:  
OK := baEncryptFile( "d:\results.dat" , "This is my key" )

**Notes:** This function uses an xor routine to encrypt a file. To decrypt the file, run the function again using the same key. This will return it to it's original state.

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FindDrive

**Description:** baFindDrive searches all drives looking for a specified file.

**Usage:** Result = baFindDrive( StartDrive, FileName )

**Arguments:** String, string.  
StartDrive is the letter of the drive to start searching on.  
FileName is the name of the file to search for.

**Returns:** String.  
Returns the letter of the Drive where the file was found. If the file is not found, returns an empty string.

**Examples:** Director:  
set Drive = baFindDrive( "c", "myfile.id" )

Authorware:  
Drive := baFindDrive( "c", "myfile.id" )

**Notes:** The StartDrive option can be used to avoid searching floppy disks.  
The FileName can consist of a pathname as well as the filename. For example, FindDrive( "c", "data\avi\cn232.avi" ) will search for "c:\data\avi\cn232.avi", "d:\data\avi\cn232.avi", "e:\data\avi\cn232.avi", etc. If a path is not included, then the root directory of the drive will be used in the search. The search is done in alphabetical order.  
This function can be used to search for content that is stored separately from the main packaged file eg on a CD or network drive.

**See also:** [baDiskInfo](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## OpenFile

**Description:** baOpenFile opens a document, using the program that the file is associated with.

**Usage:** Result = baOpenFile( FileName , State )

**Arguments:** String, string.  
FileName is the name of the file to open. The full path name should be supplied.  
State is the window state to open the file with.  
Can be one of these:  
"Normal" shows in its usual state.  
"Hidden" is not visible.  
"Maximised" shows as a maximised window.  
"Minimised" shows as an minimised icon.

**Returns:** Integer.  
Returns an error code. If the return is less than 32 than an error occurred.  
Possible errors include:

- 0 System was out of memory.
- 2 File was not found.
- 3 Path was not found.
- 5 Sharing or network-protection error.
- 6 Library required separate data segments for each task.
- 8 There was insufficient memory to start the application.
- 10 Windows version was incorrect.
- 11 Executable file was invalid. Either it was not a Windows application or there was an error in the .EXE image.
- 12 Application was designed for a different operating system.
- 13 Application was designed for MS-DOS 4.0.
- 14 Type of executable file was unknown.
- 15 Attempt was made to load a real-mode application (developed for an earlier version of Windows).
- 16 Attempt was made to load a second instance of an executable file containing multiple data segments that were not marked read-only.
- 19 Attempt was made to load a compressed executable file. The file must be decompressed before it can be loaded.
- 20 Dynamic-link library (DLL) file was invalid. One of the DLLs required to run this application was corrupt.
- 21 Application requires 32-bit extensions.
- 26 A sharing violation occurred.
- 27 The filename association is incomplete or invalid.
- 29 The DDE transaction failed.
- 30 The DDE transaction could not be completed because other DDE transactions were being processed.
- 31 There is no application associated with the given filename

**Examples:** Director:  
set OK = baOpenFile( the pathName & "test.txt" , "maximised" )

Authorware:  
OK := baOpenFile( FileLocation ^ "test.txt" , "maximised" )

**See also:** [baPrintFile](#)  
[baShell](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

**Alphabetical function list**

**Contents**

## OpenURL

**Description:** baOpenURL opens an internet document, using the default browser.

**Usage:** Result = baOpenURL( URL , State )

**Arguments:** String, string.  
URL is the name of the document to open.  
State is the window state to open the browser with.  
Can be one of these:  
"Normal" shows in its usual state.  
"Hidden" is not visible.  
"Maximised" shows as a maximised window.  
"Minimised" shows as an minimised icon.

**Returns:** Integer.  
Returns 1 if successful, else 0. Success means that there is a browser associated with .htm files, and it can be started. If opening a local HTML file under Windows 95 the function will fail if the file does not exist; under Windows 3.1, the browser will open with an error message, but the function will return 1.

**Examples:** Director:  
set OK = baOpenURL( "http://www.macromedia.com" , "maximised" )

Authorware:  
OK := baOpenURL( "http://www.macromedia.com" , "maximised" )

**Notes:** The URL can be any valid internet URL. The function will also work with local HTML files, however using the OpenFile function will be more reliable.  
This function has been written for use with Netscape Navigator and Microsoft Internet Explorer, but it may work with other browsers.

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## PrintFile

**Description:** baPrintFile prints a document, using the program that the file is associated with.

**Usage:** Result = baPrintFile( FileName )

**Arguments:** String.  
FileName is the name of the file to print. The full path name should be supplied.

**Returns:** Integer.  
Returns an error code. If the return is less than 32 than an error occurred.

Possible errors include:

- 0 System was out of memory.
- 2 File was not found.
- 3 Path was not found.
- 5 Sharing or network-protection error.
- 6 Library required separate data segments for each task.
- 8 There was insufficient memory to start the application.
- 10 Windows version was incorrect.
- 11 Executable file was invalid. Either it was not a Windows application or there was an error in the .EXE image.
- 12 Application was designed for a different operating system.
- 13 Application was designed for MS-DOS 4.0.
- 14 Type of executable file was unknown.
- 15 Attempt was made to load a real-mode application (developed for an earlier version of Windows).
- 16 Attempt was made to load a second instance of an executable file containing multiple data segments that were not marked read-only.
- 19 Attempt was made to load a compressed executable file. The file must be decompressed before it can be loaded.
- 20 Dynamic-link library (DLL) file was invalid. One of the DLLs required to run this application was corrupt.
- 21 Application requires 32-bit extensions.
- 26 A sharing violation occurred.
- 27 The filename association is incomplete or invalid.
- 29 The DDE transaction failed.
- 30 The DDE transaction could not be completed because other DDE transactions were being processed.
- 31 There is no application associated with the given filename extension.

**Examples:** Director:  
set OK = baPrintFile( the pathName & "test.txt" )

Authorware:  
OK := baPrintFile( FileLocation ^ "test.txt" )

**See also:** [baOpenFile](#)  
[baShell](#)

[Information functions](#)  
[File functions](#)

[System functions](#)  
[Window functions](#)

[Alphabetical function list](#)

## Contents

## ShortFileName

**Description:** baShortFileName returns the DOS 8.3 name of a Windows 95 long filename.

**Usage:** Result = baShortFileName(LongFileName )

**Arguments:** String.  
LongFileName is the name of the file. You must supply the full path name to the file.

**Returns:** String.  
Returns the file name in DOS format. If the file doesn't exist, then the return will be an empty string.

**Examples:** Director:  
set ShortName = baShortFileName( "c:\Program Files\Accessories\Wordpad.exe" )

Authorware:  
ShortName := baShortFileName( "c:\\Program Files\\Accessories\\Wordpad.exe" )

**Notes:** In 16 bit, this function works in Windows 95; but under Windows 3.x or NT the function will return the FileName exactly the same as it was.

Under 32 bit, the function will work under 95 or NT.

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## TempFileName

**Description:** baTempFileName returns a temporary file name that is guaranteed not to exist.

**Usage:** Result = baTempFileName( Prefix )

**Arguments:** String.  
Prefix is a string of up to 3 characters that is used to generate the filename.

**Returns:** String.  
Returns the file name, including the path.

**Examples:** Director:  
set FileName = TempFileName( "gaz" )

Authorware:  
FileName := TempFileName( "gaz" )

**Notes:** Under 16 bit, the file name will consist of the path name, a tilde "~" followed by the prefix, then a four digit number, with a ".tmp" extension; eg "c:\temp\~gaz1257.tmp". The file will not be created.

Under 32 bit, the file name will consist of the path name, followed by the prefix, then a number, with a ".tmp" extension; eg "c:\temp\gaz12453.tmp" An empty file with that name will be created.

The baTempFileName function gets the temporary file path as follows::

- 16 bit:**
1. The path specified by the TEMP environment variable
  2. Root directory of the first hard disk, if TEMP is not defined.
- 32 bit:**
1. The path specified by the TMP environment variable.
  2. The path specified by the TEMP environment variable, if TMP is not defined.
  3. The current directory, if both TMP and TEMP are not defined.

Files created using file names returned by this function are not automatically deleted when Windows shuts down.

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## MakeShortcut

**Description:** baMakeShortcut creates a Windows 95/NT shortcut.

**Usage:** Result = baMakeShortcut( FileName , Path , Title )

**Arguments:** String, string, string.  
FileName is the file that the shortcut will point to.  
Path is the folder that the shortcut will be created in.  
Title is the name of the shortcut.

**Returns:** Integer.  
Returns 1 if successful, else 0.

**Examples:** Director:  
set OK = baMakeShortcut( "d:\mworld.exe" , "c:\windows\desktop" , "Multimedia World" )

Authorware:  
OK := baMakeShortcut( "d:\mworld.exe" , "c:\windows\desktop" , "Multimedia World" )

**Notes:** This function is only available in the 32 bit version running under Windows 95 or NT 4. If used in 16 bit or under earlier versions of NT, it will do nothing and return 0.

**See also:** [baMakeShortcutEx](#)  
[baResolveShortcut](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## MakeShortcutEx

- Description:** baMakeShortcutEx creates a Windows 95/NT shortcut.
- Usage:** Result = baMakeShortcutEx( FileName, Path, Title, Args, WorkDir, Icon, IconNumber, Hotkey, State )
- Arguments:** String, string, string, string, string, string, integer, integer, string.  
Filename is the name of the file the shortcut will point to.  
Path is the folder to create the shortcut in.  
Title is the name of the shortcut.  
Args is any command line arguments to use.  
WorkDir is the working directory to set.  
Icon is the name of the icon file.  
IconNumber is the number of the icon in Icon to use.  
Hokey is the virtual key code of the hotkey to assign to the shortcut.  
State is the state to start the program in. Can be "normal", "min", "max"
- Returns:** Integer.  
Returns 1 if successful, else 0.
- Examples:** Director:  
`set ok = baMakeShortcutEx( "c:\windows\notepad.exe", "c:\temp", "My Notepad", "", "c:\windows", "c:\windows\moricons.dll", 12, 65, "normal" )`  
  
Authorware:  
`ok := baMakeShortcutEx( "c:\window\notepad.exe", baSysFolder( "desktop" ), "My Document", docpath ^ "theFile.txt", "", "", 0, 65, "max" )`
- Notes:** This function is only available in the 32 bit version running under Windows 95 or NT 4. If used in 16 bit or under earlier versions of NT, it will do nothing and return 0. This function is an extended version of [baMakeShortcut](#). Only the first three arguments are required - if any of the others are an empty string or 0, they will be ignored.
- The Icon parameter can be either an .ico, .exe or .dll file. If the file is a .ico, then the IconNumber parameter is ignored. If it is a .exe or .dll file, then the IconNumber is the number of the icon in that file to use. If the Icon is an empty string (""), then the first icon in the Command .exe file will be used.
- The Hotkey is a number that represents the virtual key code to use as the hotkey. The actual hotkey will be Ctrl + Alt + the key. eg a value of 65 will produce a hotkey of Ctrl+Alt+A. If the value is negative then Shift will also be used. eg -66 will produce Ctrl+Alt+Shift+B. A list of [Virtual Key Codes](#) is supplied.
- See also:** [baMakeShortcut](#)  
[baResolveShortcut](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

## Contents

## ResolveShortcut

- Description:** baResolveShortcut returns the file a Window 95/NT shortcut. points to.
- Usage:** Result = baResolveShortcut( Shortcut )
- Arguments:** String.  
Shortcut is the name of the shortcut.
- Returns:** String.  
Returns the file name, or an empty string if the shortcut doesn't exist or isn't a shortcut.
- Examples:** Director:  
set filename = baResolveShortcut( "c:\temp\My Shortcut" )
- Authorware:  
\_\_ filename := baResolveShortcut( "c:\\temp\\My Shortcut" )
- Notes:** This function is only available in the 32 bit version running under Windows 95 or NT 4. If used in 16 bit or under earlier versions of NT, it will do nothing and return an empty string.  
The file extension fo shortcuts is .lnk, which Windows does not display. It does not matter whether or not you include this extension in your shortcut name.
- See also:** [baMakeShortcut](#)  
[baMakeShortcutEx](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## Window functions

<a href="#"><u>WindowInfo</u></a>	returns info (state, size, position, title, class) of a window
<a href="#"><u>FindWindow</u></a>	finds a window with given title or class
<a href="#"><u>WindowList</u></a>	returns a list of all windows with given title or class
<a href="#"><u>ChildWindowList</u></a>	returns a list a window's child windows
<a href="#"><u>ActiveWindow</u></a>	returns the active window
<a href="#"><u>CloseWindow</u></a>	closes a window
<a href="#"><u>CloseApp</u></a>	closes the application owning a window
<a href="#"><u>SetWindowState</u></a>	minimises, maximises, hides a window
<a href="#"><u>ActivateWindow</u></a>	activates the specified window
<a href="#"><u>SetWindowTitle</u></a>	set the caption of a window
<a href="#"><u>MoveWindow</u></a>	moves/resizes a window
<a href="#"><u>WindowToFront</u></a>	brings a window to the front of other windows
<a href="#"><u>WindowToBack</u></a>	sends a window to the back of other windows
<a href="#"><u>WindowDepth</u></a>	gets the z-order depth of a window
<a href="#"><u>SetWindowDepth</u></a>	sets the z-order depth of a window
<a href="#"><u>WaitForWindow</u></a>	waits until a specified window is in a specified state
<a href="#"><u>WaitTillActive</u></a>	waits until a specified window becomes the active one
<a href="#"><u>NextActiveWindow</u></a>	returns the next window to become active
<a href="#"><u>WindowExists</u></a>	checks that a window handle is valid
<a href="#"><u>GetWindow</u></a>	returns a window related to another window
<a href="#"><u>SendKeys</u></a>	sends simulated key presses to the active window
<a href="#"><u>SendMsg</u></a>	sends a windows message to a window
<a href="#"><u>AddSysItems</u></a>	adds System menu, min and max boxes
<a href="#"><u>RemoveSysItems</u></a>	removes System menu, min and max boxes
<a href="#"><u>WinHandle</u></a>	returns the main Director or Authorware presentation window
<a href="#"><u>StageHandle</u></a>	returns the Director stage window
<a href="#"><u>Aw2Window</u></a>	returns the Authorware presentation window

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## WindowInfo

**Description:** baWindowInfo returns information about a window.

**Usage:** Result = baWindowInfo( WindowHandle , InfoType )

**Arguments:** Integer, string  
WindowHandle is the handle of the window.  
InfoType is the type of information required. Can be one of the following:

"title"	the caption of the window
"class"	the class name of the window
"state"	the present state of the window. Return can be:
"hidden"	the window is hidden
"min"	minimised
"max"	maximised
"normal"	normal state
"text"	the window's text
"left"	the left edge of the window in pixels
"right"	the right edge
"top"	the top edge of the window in pixels
"bottom"	the bottom edge
"height"	the height of the window
"width"	the width of the window
"client height"	the height of the client area of the window
"client width"	the width of the client area of the window

**Returns:** String.  
Returns the information requested, or "Invalid" if the window doesn't exist..

**Examples:** Director:  
`set State = baWindowInfo( Window, "state" )`

Authorware:  
`State := baWindowInfo( Window, "state" )`

**Notes:** The "text" option can be used to retrieve the text in an edit control window.

**See also:** [baSetWindowTitle](#)  
[baMoveWindow](#)  
[baSetWindowState](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## FindWindow

**Description:** baFindWindow returns the handle of a window. This handle can then be used in other window management functions.

**Usage:** Result = baFindWindow( Class, Title )

**Arguments:** String, string.  
Class is the class name of the window.  
Title is the text in the window's caption.  
The function can use either or both arguments. If one of the arguments is blank, then only the other argument will be used in searching for the window.

**Returns:** Integer.  
Returns the window handle. If the window isn't found, then returns 0.

**Examples:** Director:  
`set WinHandle = baFindWindow( "" , "Calculator" )`

Authorware:  
`WinHandle := baFindWindow( "" , "Calculator" )`

**Notes:** A window handle is an number that Windows uses to identify windows. Every window has a unique handle. You can use this handle to manipulate the window; bring it to the front, close it, etc.  
Every window also has a class name. This is assigned by the programmer, and can be used to find a specific window. For example, the Class window for the main MS Word window is "OpusApp". To find the handle for the Word window, you could use FindWindow( "OpusApp", "" ).  
If you know the text in the window's caption, you can use this to find the window. For example, FindWindow( "" , "Notepad - mydoc.txt" ).

**See also:** [baWindowList](#)  
[baGetWindow](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## WindowList

**Description:** baWindowList returns a list of the handles of open windows. These handles can then be used in other window management functions.

**Usage:** Result = baWindowList( Class , Caption , MatchCaption )

**Arguments:** String, string, integer.  
Class is the Class name of the windows to find.  
Caption is the Caption of the windows to find.  
If MatchCaption is true, then Caption must match the window caption exactly (apart from case). If it is false, then any window which contains Caption will be returned. If Caption is an empty string, then MatchCaption is ignored.  
The function can use either or both Class and Caption arguments. If one of the arguments is empty, then only the other argument will be used in searching for the windows.

**Returns:** List (Xtra) or String (UCD).  
Returns a list or string of all matching window handles.

**Examples:** Director:  
`set WndList = baWindowList( "" , "Netscape" , false ) -- return list of all windows with a caption containing "Netscape"`

Authorware:  
`WndList := baWindowList( "Notepad" , "" , false ) -- return list of all Notepad windows`

**Notes:** The return for the UCD version is a string with each window handle on a separate line. You can use the Authorware GetLine function to retrieve each window handle. The windows will be listed in front-to-back order - the first window in the list will be the one at the front, while the last one in the list will be behind all other windows in the list.

**See also:** [baFindWindow](#)  
[baChildWindowList](#)  
[baGetWindow](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## ChildWindowList

**Description:** baChildWindowList returns a list of a window's child windows.

**Usage:** Result = baChildWindowList( ParentWnd, Class, Caption, MatchCaption )

**Arguments:** Integer, string, string, integer.  
ParentWnd is the window to get the children of.  
Class is the class of child windows to include.  
Caption is the window title of child windows to include.  
If MatchCaption is true, then Caption must match the window caption exactly (apart from case). If it is false, then any window which contains Caption will be returned. If Caption is an empty string, then MatchCaption is ignored.  
The function can use either or both Class and Caption arguments. If one of the arguments is empty, then only the other argument will be used in searching for the windows.

**Returns:** List (Xtra) or String (UCD).  
Returns a list or string of all found window handles.

**Examples:** Director:  
`set wndList = baChildWindowList( 1234, "", "", 0 ) -- return list of all child windows of window 1234`

Authorware:  
`wndList := baChildWindowList( 1234, "Edit", "", 0 ) -- return list of all edit controls of window 1234`

**Notes:** The return for the UCD version is a string with each window handle on a separate line. You can use the Authorware GetLine function to retrieve each window handle. This function will return all child windows of the parent window and all its' children.

**See also:** [baFindWindow](#)  
[baWindowList](#)  
[baGetWindow](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## ActiveWindow

**Description:** baActiveWindow returns the handle of the currently active window.

**Usage:** Result = baActiveWindow()

**Arguments:** Void.

**Returns:** Integer.  
Returns the handle of the active window.

**Examples:** Director:  
`set WinHandle = baActiveWindow()`

Authorware:  
`WinHandle := baActiveWindow()`

**Notes:** Under some conditions, this function can return 0. This would typically happen during the time an application starts up - the app may have control, but not yet opened its main window. Do not use a loop such as this:

```
set wnd = 0
baRunProgram( "other.exe" , "normal" , false )
repeat while wnd <> baWinHandle()
    set wnd = baActiveWindow() -- ActiveWindow could return 0
end repeat
```

In the case above, it is possible that wnd will equal 0, not the window handle of the new application. A better way to achieve this is to use the baNextActiveWindow function.

**See also:** [baNextActiveWindow](#)  
[baWaitForWindow](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## CloseWindow

**Description:** baCloseWindow closes the specified window.

**Usage:** Result = baCloseWindow( WinHandle )

**Arguments:** Integer.  
WinHandle is the handle of the window to close.

**Returns:** Integer.  
Returns 1 if successful, otherwise 0.

**Examples:** Director:  
set OK = baCloseWindow( WinHandle )

Authorware:  
OK := baCloseWindow( WinHandle )

**See also:** [baCloseApp](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## CloseApp

**Description:** baCloseApp closes the application owning a specified window.

**Usage:** Result = baCloseApp( WinHandle )

**Arguments:** Integer.  
WinHandle is the handle of the window to close.

**Returns:** Void.

**Examples:** Director:  
[baCloseApp\( WinHandle \)](#)

Authorware:  
[baCloseApp\( WinHandle \)](#)

**Notes:** Not all applications react kindly to being closed by other applications, and may leave the system unstable - particularly in 16 bit Windows. If you use this function, be sure to test thoroughly. If possible, use the [baCloseWindow](#) function instead.

**See also:** [baCloseWindow](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## SetWindowTitle

**Description:** baSetWindowTitle sets the title of a specified window.

**Usage:** baSetWindowTitle( WinHandle, Title )

**Arguments:** Integer, string.  
WinHandle is the handle of the window to change the title of.  
Title is the string to change the window title to.

**Returns:** Void.

**Examples:** Director:  
baSetWindowTitle( Window, "Module 1" )  
  
Authorware:  
baSetWindowTitle( Window, "Module 1" )

**Notes:** If the WinHandle is 0, or is not the valid handle of a window, then the function will act on the active window.

**See also:** [baWindowInfo](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

llang2057

[Contents](#)

## MoveWindow

**Description:** baMoveWindow moves or resizes the specified window.

**Usage:** baMoveWindow( WinHandle, Left , Top , Width , Height , Activate )

**Arguments:** Integer, integer, integer, integer, integer, integer.  
WinHandle is the handle of the window to move.  
Left is the new left position of the window.  
Top is the new top position of the window.  
Width is the new width of the window.  
Height is the new height of the window.  
If Activate is true then the window will be activated.

**Returns:** Void.

**Examples:** Dirlor:  
`baMoveWindow( Wnd, 20 , 20 , 400 , 400 , true )`

Authorware:  
`baMoveWindow( Wnd, 20 , 20 , 400 , 400 , true )`

**Notes:** If both Left and Top arguments are -1, then the windows current position will not be changed.  
If both Width and Height are -1, then the windows current size will not be changed.

**See also:** [baWindowInfo](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## WindowToFront

**Description:** baWindowToFront brings the specified window to the front of all other windows.

**Usage:** Result = baWindowToFront( WinHandle )

**Arguments:** Integer.  
WinHandle is the handle of the window to bring to the front. To bring the Director or Authorware window to the front, use the baWinHandle() function.

**Returns:** Integer.  
Returns 1 if successful, otherwise 0.

**Examples:** Director:  
set OK = baWindowToFront( baWinHandle() )

Authorware:  
OK := baWindowToFront( baWinHandle() )

**See also:** [baWindowToBack](#)  
[baWindowDepth](#)  
[baSetWindowDepth](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## WindowToBack

**Description:** baWindowToBack sends the specified window to the back of all other windows.

**Usage:** Result = baWindowToBack( WinHandle )

**Arguments:** Integer.  
WinHandle is the handle of the window to send to the back. To send the Director or Authorware window to the back, use the baWinHandle() function.

**Returns:** Integer.  
Returns 1 if successful, otherwise 0.

**Examples:** Director:  
set OK = baWindowToBack( baWinHandle() )

Authorware:  
OK := baWindowToBack( baWinHandle() )

**See also:** [baWindowToFront](#)  
[baWindowDepth](#)  
[baSetWindowDepth](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## WindowDepth

**Description:** baWindowDepth gets the z-order depth of the specified window.

**Usage:** Result = baWindowDepth( WinHandle )

**Arguments:** Integer.  
WinHandle is the handle to get the depth of.

**Returns:** Integer.  
Returns the depth, or 0 if WinHandle doesn't exist.

**Examples:** Director:  
`set depth = baWindowDepth( baWinHandle() )`

Authorware:  
`depth := baWindowDepth( baWinHandle() )`

**Notes:** Only windows that are visible are counted in the depth. If a window's state is hidden, then it will be ignored by this function. Windows that are set as topmost or stay-on-top will be counted before normal windows - even if they are minimised.

**See also:** [baSetWindowDepth](#)  
[baWindowToFront](#)  
[baWindowToBack](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## SetWindowDepth

**Description:** baSetWindowDepth sets the z-order depth of the specified window.

**Usage:** baSetWindowDepth( WinHandle , Depth )

**Arguments:** Integer, integer.  
WinHandle is the handle to set the depth of.  
Depth is the new depth to set the window to.

**Returns:** Void.

**Examples:** Director:  
baSetWindowDepth( baWinHandle() , 2 ) -- sets the Director window to below the top window, but in front of all other windows

Authorware:  
baSetWindowDepth( 3124 , 5 )

**Notes:** Setting a depth greater than the number of visible windows is allowed - the window will be sent to the back of all other windows.

**See also:** [baWindowDepth](#)  
[baWindowToFront](#)  
[baWindowToBack](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## GetWindow

**Description:** baGetWindow gets a window that is related to another window.

**Usage:** Result = baGetWindow( WindowHandle , Relation )

**Arguments:** Integer, string.  
WindowHandle is the handle of the window.  
Relation is the type of relationship to look for. Can be one of the following:

"child"	gets the first child window
"first"	gets the first window
"last"	gets the last window
"next"	gets the next window
"previous"	gets the previous window
"owner"	gets the window's owner
"parent"	gets the window's parent

**Returns:** Integer.  
Returns the handle of the found window, or 0 if the requested window could not be found.

**Examples:** Director:  
set wnd = baGetWindow( 2349 , "parent" )

Authorware:  
wnd := baGetWindow( 2349 , "parent" )

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## WaitForWindow

**Description:** baWaitForWindow waits until a window is in a specified state, with an optional timeout.

**Usage:** Result = baWaitForWindow( WinHandle , State , TimeOut )

**Arguments:** Integer, string, integer  
WinHandle is the handle of the window to wait for.  
State is the state to wait for. Can be:  
    "inactive"    waits until the window is inactive  
    "active"     waits until the window is active  
    "closed"     waits until the window is closed  
TimeOut is the maximum amount of time to wait in ticks. A tick is equal to 1/60th of a second. If TimeOut is 0, the function will wait indefinitely.

**Returns:** Integer.  
Returns 0 if the window doesn't exist, or the timeout occurs before the window reaches the specified state.  
Returns 1 if the window reached the specified state.

**Examples:** Director:  
`set OK = baWaitForWindow( baWinHandle() , "active" , 300 ) -- waits for the Director window to become active, for a maximum of 5 seconds`

Authorware:  
`OK := baWaitForWindow( 3248, "closed" , 600 ) -- waits for the window 3248 to be closed, for a maximum of 10 seconds`

**Notes:** The "inactive" option is useful for waiting until the Director/Authorware window is inactive after starting another program. When the Director/Authorware window is no longer active, then the other program has opened and has focus.  
For example, here is some code to open a readme file in Authorware, and wait until the user has finished with it.

```
if baOpenFile( "readme.txt" , "normal" ) > 32 then -- open readme file
    wnd := baNextActiveWindow( 0 ) -- get handle of Notepad window
    baWaitForWindow( baWinHandle() , "active" , 0 ) -- wait till the Authorware
window is active i.e. Notepad has been closed or user switched back to Authorware
    if baWindowExists( wnd ) then baCloseWindow( wnd ) -- close Notepad
    end if
end if
```

**See also:** [baWaitTillActive](#)  
[baNextActiveWindow](#)  
[baActiveWindow](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)



## WaitTillActive

**Description:** baWaitTillActive pauses execution until a specified window becomes the active one.

**Usage:** baWaitTillActive( WindowHandle )

**Arguments:** Integer.  
WindowHandle is the handle of the window to wait for.

**Returns:** Void.

**Examples:** Director:  
[baWaitTillActive\( baWinHandle\(\) \)](#) -- wait till Director window becomes the active one

Authorware:  
[baWaitTillActive\( baWinHandle\(\) \)](#) -- wait till Authorware window becomes the active one

**Notes:** This function is mainly intended to be used with the [RunProgram](#) function. The RunProgram function can pause execution until the jumped to program quits. This may cause a problem if the user switches back to the Authorware program without quitting the jumped to program. If you use the RunProgram without the pause option, you can use this function (after a short wait) to resume the program if the user switches back to it.  
This function is provided for compatibility with older versions. New applications should use the [baWaitForWindow](#) function.

**See also:** [baWaitForWindow](#)  
[baNextActiveWindow](#)  
[baActiveWindow](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## NextActiveWindow

**Description:** baNextActiveWindow returns the next window to become active.

**Usage:** Result = baNextActiveWindow( TimeOut )

**Arguments:** Integer  
TimeOut is the maximum amount of time to wait in ticks. A tick is equal to 1/60th of a second. If TimeOut is 0, the function will wait indefinitely.

**Returns:** Integer.  
Returns the handle of the next active window.  
Returns 0 if the timeout occurs before another window becomes active.

**Examples:** Director:  
set wnd = baNextActiveWindow( 300 ) -- waits for the next window to become active, for a maximum of 5 seconds

Authorware:  
wnd := baNextActiveWindow( 600 )

**Notes:** This function will not operate with versions of Authorware earlier than 3.0.

The next active window is defined as the next window that isn't the window of the Director/Authorware calling program, or a dialog box or a splash screen. It would be typically used after a baRunProgram or baOpenFile call to get the handle of the window the program opens, and is particularly useful for applications such as Netscape and Acrobat that open splash screens.

Here is an example of opening an Acrobat file in Director, and closing it when the user is finished with it.

```
if baOpenFile( "readme.pdf" , "normal" ) > 32 then -- open acrobat file
    set wnd = baNextActiveWindow( 0 ) -- get handle of Acrobat window
    baWaitForWindow( baWinHandle() , "active" , 0 ) -- wait till the Director window
is active i.e. Acrobat has been closed or user switched back to Director
    if baWindowExists( wnd ) then baCloseWindow( wnd ) -- close Acrobat
    end if
end if
```

**See also:** [baWaitTillActive](#)  
[baWaitForWindow](#)  
[baActiveWindow](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## WindowExists

**Description:** baWindowExists checks if a window handle is valid.

**Usage:** Result = baWindowExists( WinHandle )

**Arguments:** Integer.  
WindowHandle is the handle of the window to check for.

**Returns:** Integer.  
Returns 1 if the window exists, else 0.

**Examples:** Director:  
set OK = baWindowExists( 3248 )

Authorware:  
OK := baWindowExists( 3248 )

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## SendKeys

**Description:** baSendKeys sends a series of keystrokes to the active window.

**Usage:** Result = baSendKeys( Keys )

**Arguments:** String.  
Keys is the string of keys to send. See the notes section for a full description.

**Returns:** Integer.  
Returns an error code.  
0 success.  
1 invalid character in string  
2 window unavailable  
3 unknown error  
4 another SendKeys function is still under way

**Examples:** Director:  
set OK = baSendKeys( "hello" ) -- sends "hello"  
set OK = baSendKeys( "^C" ) -- sends Control C  
set OK = baSendKeys( "{F1}" ) -- sends the F1 key  
set OK = baSendKeys( "fname.txt{ENTER}" ) -- sends "fname.txt" then Enter

Authorware:  
OK := baSendKeys( "hello" ) -- sends "hello"  
OK := baSendKeys( "^C" ) -- sends Control C  
OK := baSendKeys( "{F1}" ) -- sends the F1 key  
OK := baSendKeys( "fname.txt{ENTER}" ) -- sends "fname.txt" then Enter

**Notes:** The string sent can contain any alphanumeric character.  
Use "@" for the Alt key, "~" for the Shift key, and "^" for the Control key. If you need to send these actual keys, use a combination of Shift and the required letter eg to send "@" use "~2".

Other special keys can be sent as follows: (include the curly brackets)

```
{F1}, {F2}, etc to {F12}  
{INSERT}  
{DELETE}  
{HOME}  
{END}  
{PGUP}  
{PGDN}  
{TAB}  
{ENTER}  
{BKSP}  
{PRTSC}  
{ESCAPE}  
{LEFT}  
{RIGHT}  
{UP}  
{DOWN}
```

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

## Contents

## SendMsg

**Description:** baSendMsg sends a Windows message to a window.

**Usage:** Result = baSendMsg( WindowHandle , Message , wParam , lParam , Wait )

**Arguments:** Integer, integer, integer, integer, integer.  
WindowHandle is the handle of the window to send the message to.  
Message is the message to send.  
wParam is additional message information.  
lParam is additional message information.  
If Wait is true, execution is paused until the window processes the message.

**Returns:** Integer.  
If Wait is true, the return value specifies the result of the message processing and depends on the message sent.  
If Wait is false, returns 1 if the message was successfully posted to the window, else 0.

**Examples:** Director:  
set Result = baSendMsg( 65535, 26 , 0, 0, true ) -- send a WM\_WININCHANGE message to all windows.

Authorware:  
Result := baSendMsg( 65535, 26, 0, 0, true )

**Notes:** To use this function, you will need access to Windows API information about messages.

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## AddSystems

**Description:** baAddSystems is a function which adds the system menu, minimise and maximise buttons to a window.

**Usage:** baAddSystems( WindowHandle, SystemMenu, MinBox, MaxBox )

**Arguments:** Integer, integer, integer, integer.  
WindowHandle is the handle of the window to change.  
If SystemMenu is true, the system menu is added.  
If MinBox is true, the minimize button is added.  
If MaxBox is true, the maximize button is added.

**Returns:** Void.

**Examples:** Director:  
`baAddSystems(baWinHandle() , false , true , false )`

Authorware:  
`baAddSystems(baWinHandle() , false , true , false )`

**Notes:** Use this function with care. Some windows do not react kindly to having their window style changed. Some windows will ignore this call.  
This function is limited in 32 bit Windows - only the Director/Authorware window can be changed, and you can only have all the items or none of the items.

**See also:** [baRemoveSystems](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## RemoveSysItems

**Description:** baRemoveSysItems is a function which removes the system menu, minimise and maximise buttons from a window.

**Usage:** baRemoveSysItems( WindowHandle, SystemMenu, MinBox, MaxBox )

**Arguments:** Integer, integer, integer, integer.  
WindowHandle is the handle of the window to change.  
If SystemMenu is true, the system menu is removed.  
If MinBox is true, the minimize button is removed.  
If MaxBox is true, the maximize button is removed.

**Returns:** Void.

**Examples:** Director:  
`baRemoveSysItems(1356 , true , false , false ) -- remove the system menu from window 1356`

Authorware:  
`baRemoveSysItems(1356 , true , false , false ) -- remove the system menu from window 1356`

**Notes:** Use this function with care. Some windows do not react kindly to having their window style changed. Some windows will ignore this call.  
This function is limited in 32 bit Windows - only the Director/Authorware window can be changed, and you can only have all the items or none of the items.

**See also:** [baAddSysItems](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## WinHandle

**Description:** baWinHandle returns the main Director window or the Authorware presentation window.

**Usage:** Result = baWinHandle()

**Arguments:** Void.

**Returns:** Integer.

**Examples:** Director:  
`set Win = baWinHandle()`

Authorware:  
`Win := baWinHandle()`

**Notes:** Use this function to get the Director window for use with the other window manipulation functions.

In the UCD version, this function returns the Authorware presentation window when packaged, but the main Authorware window during authoring. When using Buddy window functions on the Authorware window, you should use baWinHandle() rather than the system WindowHandle variable.

This is necessary because in authoring mode, the presentation window is a child of the main Authorware window. This causes problems with functions that rely on a specific window being active, because Windows thinks the active window is actually the main Authorware window, not the presentation window. By using this function instead of the system WindowHandle variable, you can create a file that behaves correctly in both authoring and runtime modes.

For example, if the presentation window is active, **baActiveWindow()** and **WindowHandle** will not be the same during authoring, but will be when packaged. However, **baActiveWindow()** and **baWinHandle()** will be the same in both authoring and packaged modes.

The baWinHandle function only works in version 3.0 or later of Authorware - use the [baAw2Window](#) function in earlier versions.

**See also:** [baStageHandle](#)  
[baAw2Window](#)

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## StageHandle

**Description:** baStageHandle returns the Director stage window.

**Usage:** Result = baStageHandle()

**Arguments:** Void.

**Returns:** Integer.

**Examples:** Director:  
`set Win = baStageHandle()`

Authorware:  
N/A

**Notes:** Use this function to get the Director stage window. You should use [baWinHandle](#) if you want to use the other Buddy window manipulation functions on the Director window.

If used in Authorware, this function will return the main presentation window.

**See also:** [baWinHandle](#)

[Information functions](#)

[File functions](#)

[Alphabetical function list](#)

[Contents](#)

[System functions](#)

[Window functions](#)

## Aw2Window

- Description:** baAw2Window returns the handle of the Authorware presentation window.
- Usage:** Result = baAw2Window( WindowHandle )
- Arguments:** Integer.  
WindowHandle is the system Authorware variable.
- Returns:** Integer.  
Returns the handle of the Authorware presentation window when packaged; the handle of the main Authorware window when authoring..
- Examples:** Director:  
[Not available](#)
- Authorware:  
[WinHandle := baAw2Window\( WindowHandle \)](#)
- Notes:** This function is not available in the Xtra version. The [baWinHandle](#) function can be used to retrieve this value in the Xtra version.
- This function will work in all versions of Authorware, however Versions 3.0 or later of Authorware should use the [baWinHandle](#) function.
- See also:** [baWinHandle](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## SetWindowState

**Description:** baSetWindowState allows you to manipulate the specified window.

**Usage:** baSetWindowState( WinHandle, State )

**Arguments:** Integer, string.

WinHandle is the handle of the window to change. To change the Director or Authorware window, use the baWinHandle() function.

State is the window's new state. Can be one of the following:

"Hidden"	Hides the window and passes activation to another window.
"Restored"	Activates and displays a window. If the window is minimized or maximized, it is restored to its original size and position.
"Normal"	Activates a window and displays it in its current size and position.
"Maximised"	Activates a window and displays it as a maximized window.
"Minimised"	Activates a window and displays it as an icon.
"MinNotActive"	Displays a window as an icon. The window that is currently active remains active.
"NotActive"	Displays a window in its current state. The window that is currently active remains active.
"ShowNotActive"	Displays a window in its most recent size and position. The window that is currently active remains active.
"StayOnTop"	Makes the window stay on top of all other windows.
"DontStayOnTop"	Allows the window to go behind other windows.

**Returns:** Void.

**Examples:** Director:  
baSetWindowState( baWinHandle(), "StayOnTop" )

Authorware:  
baSetWindowState( baWinHandle(), "StayOnTop" )

**Notes:** If the WinHandle is 0, or is not the valid handle of a window, then the function will act on the active window.

**See also:** [baWindowInfo](#)  
[baActivateWindow](#)

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## ActivateWindow

**Description:** baActivateWindow activates the specified window.

**Usage:** Result = baActivateWindow( WinHandle )

**Arguments:** Integer.  
WinHandle is the handle of the window to activate. To activate the Director or Authorware window, use the baWinHandle() function.

**Returns:** Integer.  
Returns 1 if successful, otherwise 0.

**Examples:** Director:  
set OK = baActivateWindow( baWinHandle() )

Authorware:  
OK := baActivateWindow( baWinHandle() )

**Notes:** Microsoft has introduced a change to the way this function operates under Win 98 and NT 5. If your user is presently typing in a window, then you can not force another window to become the active one. Instead, the button for that window will flash on the Taskbar to alert the user that a program needs attention.

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## Virtual Key Codes

vk\_BackSpace = 8  
vk\_Shift = 16  
vk\_Pause = 19  
vk\_Space = 32  
vk\_End = 35  
vk\_Up = 38  
vk\_PrintScreen = 44

vk\_Tab = 9  
vk\_Control = 17  
vk\_CapsLock = 20  
vk\_PageUp = 33  
vk\_Home = 36  
vk\_Right = 39  
vk\_Insert = 45

vk\_Return = 13  
vk\_Alt = 18  
vk\_Escape = 27  
vk\_PageDown = 34  
vk\_Left = 37  
vk\_Down = 40  
vk\_Delete = 46

vk\_0 = 48  
vk\_3 = 51  
vk\_6 = 54  
vk\_9 = 57

vk\_1 = 49  
vk\_4 = 52  
vk\_7 = 55

vk\_2 = 50  
vk\_5 = 53  
vk\_8 = 56

vk\_A = 65  
vk\_D = 68  
vk\_G = 71  
vk\_J = 74  
vk\_M = 77  
vk\_P = 80  
vk\_S = 83  
vk\_V = 86  
vk\_Y = 89

vk\_B = 66  
vk\_E = 69  
vk\_H = 72  
vk\_K = 75  
vk\_N = 78  
vk\_Q = 81  
vk\_T = 84  
vk\_W = 87  
vk\_Z = 90

vk\_C = 67  
vk\_F = 70  
vk\_I = 73  
vk\_L = 76  
vk\_O = 79  
vk\_R = 82  
vk\_U = 85  
vk\_X = 88

vk\_LWin = 91 \*  
vk\_NumPad0 = 96  
vk\_NumPad3 = 99  
vk\_NumPad6 = 102  
vk\_NumPad9 = 105  
vk\_Subtract = 109

vk\_RWin = 92 \*  
vk\_NumPad1 = 97  
vk\_NumPad4 = 100  
vk\_NumPad7 = 103  
vk\_Multiply = 106  
vk\_Decimal = 110

vk\_Apps = 93 \*  
vk\_NumPad2 = 98  
vk\_NumPad5 = 101  
vk\_NumPad8 = 104  
vk\_Add = 107  
vk\_Divide = 111

vk\_F1 = 112  
vk\_F4 = 115  
vk\_F7 = 118  
vk\_F10 = 121  
vk\_F13 = 124  
vk\_F16 = 127

vk\_F2 = 113  
vk\_F5 = 116  
vk\_F8 = 119  
vk\_F11 = 122  
vk\_F14 = 125

vk\_F3 = 114  
vk\_F6 = 117  
vk\_F9 = 120  
vk\_F12 = 123  
vk\_F15 = 126

vk\_NumLock = 144  
vk\_RShift = 161 \*\*  
vk\_LAlt = 164 \*\*  
vk\_Equals = 187  
vk\_Period = 190  
vk\_RightBrace = 221

vk\_ScrollLock = 145  
vk\_LControl = 162 \*\*  
vk\_RAlt = 165 \*\*  
vk\_Comma = 188  
vk\_Slash = 191  
vk\_LeftBrace = 219

vk\_LShift = 160 \*\*  
vk\_RControl = 163 \*\*  
vk\_SemiColon = 186  
vk\_UnderScore = 189  
vk\_BackSlash = 220  
vk\_Apostrophe = 222

\* Available in 95/NT4 only

\*\* Available in NT only

**KeysDown**

**KeyBeenPressed**

**Contents**

## Registration functions

<a href="#"><u>About</u></a>	shows information about Buddy API
<a href="#"><u>Register</u></a>	registers Buddy API
<a href="#"><u>SaveRegistration</u></a>	saves your registration information
<a href="#"><u>GetRegistration</u></a>	retrieves your registration information
<a href="#"><u>Functions</u></a>	retrieves the number of functions you are licenced to use

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## About

**Description:** baAbout shows information about Buddy API.

**Usage:** baAbout()

**Arguments:** Void.

**Returns:** Void.

**Examples:** Director:  
[baAbout\(\)](#)

Authorware:  
[baAbout\(\)](#)

**Notes:** This function displays a message box showing the version of Buddy API, who the version is registered to, and the number of functions licenced for use.

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## Register

**Description:** baRegister registers Buddy API.

**Usage:** Result = baRegister( UserName , RegNumber )

**Arguments:** String, integer.  
UserName is the user name you received when you registered.  
RegNumber is your registration number.

**Returns:** Integer.  
Returns the number of functions licenced for use.

**Examples:** Director:  
`set funcs = baRegister( "My name" , 111111 )`

Authorware:  
`funcs := baRegister( "My name" , 111111 )`

**Notes:** You need to use this function before you call any other Buddy functions. For Director, the best place to do this is in your startMovie handler. In Authorware, place this into a calculation icon near the start of the flowline.

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## SaveRegistration

**Description:** baSaveRegistration saves your Buddy API registration information

**Usage:** Result = baSaveRegistration( UserName , RegNumber )

**Arguments:** String, integer.  
UserName is the user name you received when you registered.  
RegNumber is your registration number.

**Returns:** Integer.  
Returns 1 if successfully saved, else 0.

**Examples:** Director:  
set OK = baSaveRegistration( "My name" , 111111 )

Authorware:  
OK := baSaveRegistration( "My name" , 111111 )

**Notes:** This function is designed to be used with the [baGetRegistration](#) function to make it easier for you to enter your registration code. In Director, you can use the Message window to save the information.  
The function is only available in authoring mode.  
This function is not included in the UCD version.

[Information functions](#)

[System functions](#)

[File functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## GetRegistration

**Description:** baGetRegistration retrieves your Buddy API registration information

**Usage:** Result = baGetRegistration( )

**Arguments:** Void.

**Returns:** String.  
Returns your registration information.

**Examples:** Director:  
`set regstring = baGetRegistration( )`

Authorware:  
`regstring := baGetRegistration( )`

**Notes:** This function is designed to be used with the [baSaveRegistration](#) function to make it easier for you to enter your registration code. The function also places the registration information on the clipboard ready to be pasted into the desired handler or calculation icon. In Director, you can use the Message window to get the information. The function is only available in authoring mode. This function is not included in the UCD version.

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## Functions

**Description:** baFunctions returns the number of functions you are licenced to use

**Usage:** Result = baFunctions( )

**Arguments:** Void.

**Returns:** Integer.  
Returns the number of licenced functions.

**Examples:** Director:  
`set number = baFunctions( )`

Authorware:  
`number := baFunctions( )`

**Notes:** This function is not included in the UCD version.

[Information functions](#)

[File functions](#)

[System functions](#)

[Window functions](#)

[Alphabetical function list](#)

[Contents](#)

## What's new in this release

### The following changes are new in version 3.4

Development of the 16 bit version has now stopped.

The .dll file has now been removed and the Xtra is delivered as a single file.

baVersion changed to report "Win2000".

There was a limit of 500 total characters in the returned filenames in baGetFilename when used with a multiple selection dialog. This has been increased to 12000 characters.

### The following bugs are fixed in version 3.4

CpuInfo would sometimes report the incorrect value for AMD processors.

The number option for DiskInfo could return -1 if the serial number of the disk was a large number. This number is now returned as a float.

### The following changes were new in version 3.31

Considerable changes made to the window handling functions for compatability with Director 7.02.

"vendor" and "model" options added for CpuInfo, and support for AMD chips added.

"client rect" and client "width" added to WindowInfo.

"menubar height" and "titlebar height" added to ScreenInfo

"common desktop", "common startup", "common start menu", "common groups" options added to SysFolder.

ReadRegString changed under NT so that a (Default) value with no value set returns an empty string rather than the passed in Default value

### The following bugs were fixed in version 3.31

Under Windows NT, using FileExists on a file would prevent DeleteFolder subsequently deleting the folder containing the file.

### The following changes were new in version 3.3

The Xtra version now contains an embedded copy of the DLL, and is distributed as a single file.

The GetFolder function has an option to allow the creation of a new folder.

The GetFilename function has the OFN\_ADDEXTENSION option added.

Some internal changes to the FindApp function to work around problems with applications that are not registered correctly in the registry.

The XCopy and CopyXFiles functions now retain the case of the original file names in 32 bit.

FileList and FolderList now return the filenames with the same case as the original filenames in 32 bit.

An option to overwrite existing read-only files was added to the file copying functions.

### The following bugs were fixed in version 3.3

FindFirstFile could report the wrong path to the file, if the second file found was in the same folder as the first file found.

XCopy crashed when copying a file which had an embedded version resource, and the "IfNewer" option is specified, and the file already exists in the destination folder.

bagetFilename showed a truncated dialog box when the stage/presentation window was smaller than about 350 pixels and the OFN\_EXPLORER flag was used.

### The following functions were new in version 3.2

#### FlushIni

forces Windows to write an ini file to disk.

#### FindFirstFile

searches for the first file matching a specification

#### FindNextFile

searches for the next file matching a specification

<u><a href="#">FindClose</a></u>	finishes a search started with baFindFirstFile
<u><a href="#">XCopy</a></u>	copies multiple files with wildcard matching, including sub-directories.
<u><a href="#">XDelete</a></u>	deletes files with wildcard matching, including sub-directories
<u><a href="#">FontList</a></u>	returns a list of installed fonts
<u><a href="#">FontStyleList</a></u>	returns a list of available styles for a truetype font
<u><a href="#">MakeShortcutEx</a></u>	creates a Win95/NT shortcut
<u><a href="#">ResolveShortcut</a></u>	returns the file a shortcut points to
<u><a href="#">RegKeyList</a></u>	returns a list of sub-keys inside a registry key
<u><a href="#">RegValueList</a></u>	returns a list of values inside a registry key
<u><a href="#">ChildWindowList</a></u>	returns a list a window's child windows
<u><a href="#">GetFilename</a></u>	displays a file selection dialog.
<u><a href="#">GetFolder</a></u>	displays a folder selection dialog.
<u><a href="#">Sleep</a></u>	pauses the calling Directof/Authorware program
<u><a href="#">SystemTime</a></u>	returns the current system time/date
<u><a href="#">SetSystemTime</a></u>	sets the system time/date
<u><a href="#">PrinterInfo</a></u>	returns information about the installed printer
<u><a href="#">SetPrinter</a></u>	changes settings for the default printer
<u><a href="#">Shell</a></u>	executes a file
<u><a href="#">RefreshDesktop</a></u>	refreshes the desktop icons

### Changes to existing functions in 3.2:

baVersion( "os" ) will return "Win98" on Windows 98

baVersion( "windows" ) will return "4.10" (32 bit) and "3.98" (16 bit) on Windows 98

baVersion( "qt3" ) will return the version of QuickTime 3 installed (32 bit only)

baGetVolume/SetVolume have been changed to use the Win32 mixer functions if they are available.

Some new options are now available. These new options are 32 bit only.

These are:

"master"	controls the master volume
"master mute"	controls the master mute
"wave mute"	controls the wave mute
"cd mute"	controls the CD mute
"synth mute"	controls the built-in synthesizer mute

### Bugs fixed in 3.2

baFileVersion failed on Word 97 and PowerPoint 97.

baCopyFile failed when copying to the root directory of a drive (introduced in 3.12 release).

baCommandArgs could cut off the first letter of the argument if you define a file type to be associated with your projector/application, and a file of that type in a folder with a long file name is double-clicked in Explorer.

baFindApp failed when used on NT if the user did not have write access to the system folder.

### The following functions were added in version 3.12

<u><a href="#">FileList</a></u>	returns a list of files in a folder.
<u><a href="#">FolderList</a></u>	returns a list of folders in a folder.
<u><a href="#">MemoryInfo</a></u>	gets information about system memory

**Changes to existing functions:**

baShortFileName now works correctly under Windows 3.1.

Under NT, the registry functions now comply with the current user's security settings.

**The following functions were added in version 3.11**

**PMSubGroupList** returns list of groups inside another Start Menu group  
**DeleteReg** deletes Registry entry

**Changes to existing functions:**

baFolderExists failed if used on an empty floppy disk, or an empty directory on a Novell server. This also caused baCopyFile to fail. This has been fixed.

baMovewindow did not work as documented in the help file. Using -1 for the new position now keeps the windows current position.

baSendKeys has the cursor keys added - LEFT, RIGHT, DOWN, UP.

The free and size options for baDiskInfo have been updated to work with FAT32 drives larger than 2 gb.

baCopyXFiles now gives more 'time slices' to the system during the copy, This allows Windows and Director to update their displays more frequently.

**The following functions were added in version 3.1**

**PMGroupList** returns list of Program Manager or Start Menu groups  
**PMIconList** returns list of icons in a Program Manager or Start Menu group  
**WindowList** returns a list of all windows with given title or class  
**WaitForWindow** waits until a specified window is in a specified state  
**NextActiveWindow** returns the next window to become active  
**WindowExists** checks that a window handle is valid  
**WindowDepth** gets the z-order depth of a window  
**SetWindowDepth** sets the z-order depth of a window  
**CloseApp** closes the application owning a window  
**StageHandle** returns the Director stage window  
**Aw2Window** returns the Authorware presentation window  
**FileSize** returns the size of a file  
**FileAttributes** returns the attributes of a file  
**SetFileAttributes** sets the attributes of a file  
**Functions** retrieves the number of functions you are licenced to use

**Changes to existing functions in version 3.1:**

baFileExists now reports hidden files as existing in the 16 bit Xtra and UCD.

baFindApp checks if Acrobat Reader 3 has been installed into a folder containing a space and uses a different method to locate it if it does.

baSetScreenSaver converts the long file name of a screen saver in Windows 95 to a short file name before installing it.

**Changes in version 3.03:**

Added "restart" option to baExitWindows for 32 bit Xtra and UCD in Windows 95.

Internal changes to baCopyFile and baInstallFont to provide consistency between 16 and 32 bit versions.

**Changes in version 3.02:**

Added baWinHandle to UCD version..

**Bugs fixed in version 3.01:**

The Director window did not redraw itself during baWaitTillActive.

The window functions (baMoveWindow, baActivateWindow, etc) did not always work correctly in Windows NT with the 32 bit Xtra.

**Other changes in version 3.01:**

The maximum size string returned by the baReadIni and baReadRegString functions increased to 2000 characters.

**[Contents](#)**

