
NSIgnoreMisspelledWords

Adopted By: NSText

Declared In: AppKit/NSSpellProtocol.h

Protocol Description

Implement this protocol to have the Ignore button in the Spelling panel function properly. The Ignore button allows the user to accept a word that the spelling checker believes is misspelled. In order for this action to update the “ignored words” list for the document being checked, the `NSIgnoreMisspelledWords` protocol must be implemented.

This protocol is necessary because a list of ignored words is useful only if it pertains to the entire document being checked, but the spelling checker (`NSSpellChecker` object) does not check the entire document for spelling at once. The spelling checker returns as soon as it finds a misspelled word. Thus, it checks only a subset of the document at any one time. The user usually wants to check the entire document, and so usually several spelling checks are run in succession until no misspelled words are found. This protocol allows the list of ignored words to be maintained per-document, even though the spelling checks are not run per-document.

The `NSIgnoreMisspelledWords` protocol specifies a method, **`ignoreSpelling:`**, which should be implemented like this:

```
- (void)ignoreSpelling:(id)sender
{
    [[NSSpellChecker sharedSpellChecker] ignoreWord:[sender selectedCell]
        stringValue] inSpellDocumentWithTag:myDocumentTag];
}
```

The second argument to the `NSSpellChecker` method **`ignoreWord:inSpellDocumentWithTag:`** is a tag that the `NSSpellChecker` can use to distinguish the documents being checked. (See the discussion of “Matching a List of Ignored Words With the Document It Belongs To” in the description of the `NSSpellChecker` class.) Once the `NSSpellChecker` has a way to distinguish the various documents, it can append new ignored words to the appropriate list.

To make the ignored words feature useful, the application must store a document's ignored words list with the document. See the `NSSpellChecker` class description for more information.

Instance Methods

ignoreSpelling:

– (void)**ignoreSpelling:**(id)*sender*

Implement to allow an application to ignore misspelled words on a document-by-document basis. This message is sent by the NSSpellChecker instance to the object whose text is being checked.

Implement this method by using the code shown in the protocol description.