
This chapter describes the Objective-C language and discusses the principles of object-oriented programming as they're implemented in Objective-C. It covers all the basic features that the language adds to standard C. The next chapter continues the discussion by taking up more advanced and less commonly used language features.

Objective-C syntax is a superset of standard C syntax, and its compiler works for both C and Objective-C source code. The compiler recognizes Objective-C source files by a ".m" extension, just as it recognizes files containing only standard C syntax by a ".c" extension. The Objective-C language is fully compatible with ANSI standard C.

Objective-C can also be used as an extension to C++. At first glance, this may seem superfluous since C++ is itself an object-oriented extension of C. But C++ was designed primarily as "a better C," and not necessarily as a full-featured object-oriented language. It lacks some of the possibilities for object-oriented design that dynamic typing and dynamic binding bring to Objective-C. At the same time, it has useful language features not found in Objective-C. When you use the two languages in combination, you can assign appropriate roles to the features found in each and take advantage of what's best in both.

Because object-oriented programs postpone many decisions from compile time to run time, object-oriented languages depend on a run-time system for executing the compiled code. The run-time system for the Objective-C language is discussed in Chapter 4. This chapter and the next present the language, but touch on important elements of the run-time system as they're important for understanding language features. NeXT has modified the GNU C compiler to compile Objective-C, and NeXT provides its own run-time system.

Objects

As the name implies, object-oriented programs are built around *objects*. An object associates data with the particular operations that can use or affect that data. In Objective-C, these operations are known as the object's *methods*; the data they affect are its *instance variables*. In essence, an object bundles a data structure (instance variables) and a group of procedures (methods) into a self-contained programming unit.

For example, if you are writing a drawing program that allows a user to create images composed of lines, circles, rectangles, text, bit-mapped images, and so forth, you might create classes for many of the basic shapes that a user will be

able to manipulate. A Rectangle object, for instance, might have instance variables that identify the position of the rectangle within the drawing along with its width and its height. Other instance variables could define the rectangle's color, whether or not it is to be filled, and a line pattern that should be used to display the rectangle. A Rectangle would have methods to set the rectangle's position, size, color, fill status, and line pattern, along with a method that causes the rectangle to display itself.

In Objective-C, an object's instance variables are internal to the object; you get access to an object's state only through the object's methods. For others to find out something about an object, there has to be a method to supply the information. For example, a Rectangle would have methods that reveal its size and its position.

Moreover, an object sees only the methods that were designed for it; it can't mistakenly perform methods intended for other types of objects. Just as a C function protects its local variables, hiding them from the rest of the program, an object hides both its instance variables and its method implementations.

id

In Objective-C, objects are identified by a distinct data type, `id`. This type is defined as a pointer to an object—in reality, a pointer to the object's data (its instance variables). Like a C function or an array, an object is identified by its address. All objects, regardless of their instance variables or methods, are of type `id`.

```
id anObject;
```

For the object-oriented constructs of Objective-C, such as method return values, `id` replaces `int` as the default data type. (For strictly C constructs, such as function return values, `int` remains the default type.)

The keyword `nil` is defined as a null object, an `id` with a value of 0. `id`, `nil`, and the other basic types of Objective-C are defined in the header file `objc.h`, which is located in the `objc` subdirectory of `/NextDeveloper/Headers`.

Dynamic Typing

The `id` type is completely nonrestrictive. By itself, it yields no information about an object, except that it is an object.

But objects aren't all the same. A Rectangle won't have the same methods or instance variables as an object that represents a bit-mapped image. At some

point, a program needs to find more specific information about the objects it contains—what the object’s instance variables are, what methods it can perform, and so on. Since the `id` type designator can’t supply this information to the compiler, each object has to be able to supply it at run time.

This is possible because every object carries with it an `isa` instance variable that identifies the object’s *class*—what kind of object it is. Every `Rectangle` object would be able to tell the run-time system that it is a `Rectangle`. Every `Circle` can say that it is a `Circle`. Objects with the same behavior (methods) and the same kinds of data (instance variables) are members of the same class.

Objects are thus *dynamically typed* at run time. Whenever it needs to, the run-time system can find the exact class that an object belongs to, just by asking the object. Dynamic typing in Objective-C serves as the foundation for dynamic binding, discussed later.

The `isa` pointer also enables objects to introspect about themselves as objects. The compiler doesn’t discard much of the information it finds in source code; it arranges most of it in data structures for the run-time system to use. Through `isa`, objects can find this information and reveal it at run time. An object can, for example, say whether it has a particular method in its repertoire and what the name of its superclass is.

Object classes are discussed in more detail under “Classes” below.

It’s also possible to give the compiler information about the class of an object by statically typing it in source code using the class name. Classes are particular kinds of objects, and the class name can serve as a type name. See “Class Types” later in this chapter and “Static Options” in Chapter 3.

Messages

To get an object to do something, you send it a *message* telling it to apply a method. In Objective-C, *message expressions* are enclosed in square brackets:

```
[receiver message]
```

The receiver is an object, and the message tells it what to do. In source code, the message is simply the name of a method and any arguments that are passed to it. When a message is sent, the run-time system selects the appropriate method from the receiver’s repertoire and invokes it.

For example, this message tells the `myRect` object to perform its `display` method, which causes the rectangle to display itself:

```
[myRect display];
```

Methods can also take arguments. The imaginary message below tells `myRect` to set its location within the window to coordinates (30.0, 50.0):

```
[myRect setOrigin:30.0 :50.0];
```

Here the method name, `setOrigin:`, has two colons, one for each of its arguments. The arguments are inserted after the colons, breaking the name apart. Colons don't have to be grouped at the end of a method name, as they are here. Usually a keyword describing the argument precedes each colon. The `setWidth:height:` method, for example, takes two arguments:

```
[myRect setWidth:10.0 height:15.0];
```

Methods that take a variable number of arguments are also possible, though they're somewhat rare. Extra arguments are separated by commas after the end of the method name. (Unlike colons, the commas aren't considered part of the name.) In the following example, the imaginary `makeGroup:` method is passed one required argument (`group`) and three that are optional:

```
[receiver makeGroup:group, memberOne, memberTwo, memberThree];
```

Like standard C functions, methods can return values. The following example sets the variable `isFilled` to YES if `myRect` is drawn as a solid rectangle, or NO if it's drawn in outline form only.

```
BOOL isFilled;  
isFilled = [myRect isFilled];
```

Note that a variable and a method can have the same name.

One message can be nested inside another. Here one rectangle is set to the color of another:

```
[myRect setPrimaryColor:[otherRect primaryColor]];
```

A message to `nil` also is valid, as long as the message returns an object; if it does, a message sent to `nil` will return `nil`. If the message sent to `nil` returns anything other than an object, the return value is undefined.

The Receiver's Instance Variables

A method has automatic access to the receiving object's instance variables. You don't need to pass them to the method as arguments. For example, the `primaryColor` method illustrated above takes no arguments, yet it can find the primary color for `otherRect` and return it. Every method assumes the receiver and its instance variables, without having to declare them as arguments.

This convention simplifies Objective-C source code. It also supports the way object-oriented programmers think about objects and messages. Messages are sent to receivers much as letters are delivered to your home. Message arguments bring information from the outside to the receiver; they don't need to bring the receiver to itself.

A method has automatic access only to the receiver's instance variables. If it requires information about a variable stored in another object, it must send a message to the object asking it to reveal the contents of the variable. The `primaryColor` and `isFilled` methods shown above are used for just this purpose.

See “Defining A Class” for more information on referring to instance variables.

Polymorphism

As the examples above illustrate, messages in Objective-C appear in the same syntactic positions as function calls in standard C. But, because methods “belong to” an object, messages behave differently than function calls.

In particular, an object has access only to the methods that were defined for it. It can't confuse them with methods defined for other kinds of objects, even if another object has a method with the same name. This means that two objects can respond differently to the same message. For example, each kind of object sent a `display` message could display itself in a unique way. A `Circle` and a `Rectangle` would respond differently to identical instructions to track the cursor.

This feature, referred to as *polymorphism*, plays a significant role in the design of object-oriented programs. Together with dynamic binding, it permits you to write code that might apply to any number of different kinds of objects, without your having to choose at the time you write the code what kinds of objects they

might be. They might even be objects that will be developed later, by other programmers working on other projects. If you write code that sends a `display` message to an `id` variable, any object that has a `display` method is a potential receiver.

Dynamic Binding

A crucial difference between function calls and messages is that a function and its arguments are joined together in the compiled code, but a message and a receiving object aren't united until the program is running and the message is sent. Therefore, the exact method that will be invoked to respond to a message can only be determined at run time, not when the code is compiled.

The precise method that a message invokes depends on the receiver. Different receivers may have different method implementations for the same method name (polymorphism). For the compiler to find the right method implementation for a message, it would have to know what kind of object the receiver is—what class it belongs to. This is information the receiver is able to reveal at run time when it receives a message (dynamic typing), but it's not available from the type declarations found in source code.

The selection of a method implementation happens at run time. When a message is sent, a run-time messaging routine looks at the receiver and at the method named in the message. It locates the receiver's implementation of a method matching the name, "calls" the method, and passes it a pointer to the receiver's instance variables. (For more on this routine, see "How Messaging Works" below.)

The method name in a message thus serves to "select" a method implementation. For this reason, method names in messages are often referred to as *selectors*.

This *dynamic binding* of methods to messages works hand-in-hand with polymorphism to give object-oriented programming much of its flexibility and power. Since each object can have its own version of a method, a program can achieve a variety of results, not by varying the message itself, but by varying just the object that receives the message. This can be done as the program runs; receivers can be decided "on the fly" and can be made dependent on external factors such as user actions.

When executing code based upon the Application Kit, for example, users determine which objects receive messages from menu commands like Cut, Copy, and Paste. The message goes to whatever object controls the current selection. An object that displays editable text would react to a `copy` message differently than an object that displays scanned images. An object that

represents a set of shapes would respond differently than a Rectangle. Since messages don't select methods (methods aren't bound to messages) until run time, these differences are isolated in the methods that respond to the message. The code that sends the message doesn't have to be concerned with them; it doesn't even have to enumerate the possibilities. Each application can invent its own objects that respond in their own way to copy messages.

Objective-C takes dynamic binding one step further and allows even the message that's sent (the method selector) to be a variable that's determined at run time. This is discussed in the section on "How Messaging Works."

Classes

An object-oriented program is typically built from a variety of objects. A program based on the OpenStep software frameworks might use NSMatrix objects, NSWindow objects, NSDictionary objects, NSFont objects, NSText objects, and many others. Programs often use more than one object of the same kind or *class*—several NSArray or NSWindows, for example.

In Objective-C, you define objects by defining their class. The class definition is a prototype for a kind of object; it declares the instance variables that become part of every member of the class, and it defines a set of methods that all objects in the class can use.

The compiler creates just one accessible object for each class, a *class object* that knows how to build new objects belonging to the class. (For this reason it's traditionally called a "factory object.") The class object is the compiled version of the class; the objects it builds are *instances* of the class. The objects that will do the main work of your program are instances created by the class object at run time.

All instances of a class have access to the same set of methods, and they all have a set of instance variables cut from the same mold. Each object gets its own instance variables, but the methods are shared.


By convention, class names begin with an uppercase letter (such as "Rectangle"); the names of instances typically begin with a lowercase letter (such as "myRect").

Inheritance

Class definitions are additive; each new class that you define is based on another class through which it *inherits* methods and instance variables. The new class

simply adds to or modifies what it inherits. It doesn't need to duplicate inherited code.

Inheritance links all classes together in a hierarchical tree with a single class at its root. When writing code that is based upon the Foundation framework, that root class is typically `NSObject`. Every class (except a root class) has a *superclass* one step nearer the root, and any class (including a root class) can be the superclass for any number of *subclasses* one step farther from the root. The figure below illustrates the hierarchy for a few of the classes used in the drawing program.



This figure shows that the `Square` class is a subclass of the `Rectangle` class, the `Rectangle` class is a subclass of `Shape`, `Shape` is a subclass of `Graphic`, and `Graphic` is a subclass of `NSObject`. Inheritance is cumulative. So a `Square` object has the methods and instance variables defined for `Rectangle`, `Shape`, `Graphic`, and `NSObject`, as well as those defined specifically for `Square`. This is simply to say that a `Square` object isn't only a `Square`, it's also a `Rectangle`, a `Shape`, a `Graphic`, and an `NSObject`.

Every class but `NSObject` can thus be seen as a specialization or an adaptation of another class. Each successive subclass further modifies the cumulative total of what's inherited. The `Square` class defines only the minimum needed to turn a `Rectangle` into a `Square`.

When you define a class, you link it to the hierarchy by declaring its superclass; every class you create must be the subclass of another class (unless you define a new root class). Plenty of potential superclasses are available. `OPENSTEP` includes the `NSObject` class and several software frameworks containing definitions for more than 125 additional classes. Some are classes that you can use “off the shelf”—incorporate into your program as is. Others you might want to adapt to your own needs by defining a subclass.

Some framework classes define almost everything you need, but leave some specifics to be implemented in a subclass. You can thus create very sophisticated objects by writing only a small amount of code, and reusing work done by the programmers of the framework.

The NSObject Class

NSObject, being a root class, doesn't have a superclass. In OpenStep, it's in the inheritance path for every other class. That's because it defines the basic framework for Objective-C objects and object interactions. It imparts to the classes and instances that inherit from it the ability to behave as objects and cooperate with the run-time system.

A class that doesn't need to inherit any special behavior from another class is nevertheless made a subclass of the NSObject class. Instances of the class must at least have the ability to behave like Objective-C objects at run time. Inheriting this ability from the NSObject class is much simpler and much more reliable than reinventing it in a new class definition.

Note: Implementing a new root class is a delicate task and one with many hidden hazards. The class must duplicate much of what the NSObject class does, such as allocate instances, connect them to their class, and identify them to the run-time system. It's strongly recommended that you use the NSObject class provided with OpenStep as the root class. This manual doesn't explain all the ins and outs that you would need to know to replace it.

Inheriting Instance Variables

When a class object creates a new instance, the new object contains not only the instance variables that were defined for its class, but also the instance variables defined for its superclass, and for its superclass's superclass, all the way back to the root class. Thus, the isa instance variable defined in the NSObject class becomes part of every object. isa connects each object to its class.

The figure below shows some of the instance variables that could be defined for a particular implementation of Rectangle, and where they might come from. Note that the variables that make the object a Rectangle are added to the ones that make it a Shape, and the ones that make it a Shape are added to the ones that make it a Graphic, and so on.

Class	isa;	— declared in NSObject
NSPoint	origin;	— declared in Graphic
NSColor	*primaryColor;	} declared in Shape
Pattern	linePattern;	
...		
float	width;	} declared in Rectangle
float	height;	
BOOL	filled;	
NSColor	*fillColor;	
...		

A class doesn't have to declare instance variables. It can simply define new methods and rely on the instance variables it inherits, if it needs any instance variables at all. For instance, Square might not declare any new instance variables of its own.

Inheriting Methods

An object has access not only to the methods that were defined for its class, but also to methods defined for its superclass, and for its superclass's superclass, all the way back to the root of the hierarchy. For instance, a Square object can use methods defined in the Rectangle, Shape, Graphic, and NSObject classes as well as methods defined in its own class.

Any new class you define in your program can therefore make use of the code written for all the classes above it in the hierarchy. This type of inheritance is a major benefit of object-oriented programming. When you use one of the object-oriented frameworks provided by OPENSTEP, your programs can take advantage of all the basic functionality coded into the framework classes. You have to add only the code that customizes the framework to your application.

Class objects also inherit from the classes above them in the hierarchy. But because they don't have instance variables (only instances do), they inherit only methods.

Overriding One Method With Another

There's one useful exception to inheritance: When you define a new class, you can implement a new method with the same name as one defined in a class farther up the hierarchy. The new method overrides the original; instances of the new class will perform it rather than the original, and subclasses of the new class will inherit it rather than the original.

For example, Graphic defines a **display** method that Rectangle overrides by defining its own version of **display**. The Graphic method is available to all kinds

of objects that inherit from the Graphic class—but not to Rectangle objects, which instead perform the Rectangle version of `display`.

Although overriding a method blocks the original version from being inherited, other methods defined in the new class can skip over the redefined method and find the original (see “Messages to self and super,” below, to learn how).

A redefined method can also incorporate the very method it overrides. When it does, the new method serves only to refine or modify the method it overrides, rather than replace it outright. When several classes in the hierarchy define the same method, but each new version incorporates the version it overrides, the implementation of the method is effectively spread over all the classes.

Although a subclass can override inherited methods, it can’t override inherited instance variables. Since an object has memory allocated for every instance variable it inherits, you can’t override an inherited variable by declaring a new one with the same name. If you try, the compiler will complain.

Abstract Classes

Some classes are designed only so that other classes can inherit from them. These *abstract classes* group methods and instance variables that will be used by a number of different subclasses into a common definition. The abstract class is incomplete by itself, but contains useful code that reduces the implementation burden of its subclasses.

The `NSObject` class is the prime example of an abstract class. Although programs often define `NSObject` subclasses and use instances belonging to the subclasses, they never use instances belonging directly to the `NSObject` class. An `NSObject` instance wouldn’t be good for anything; it would be a generic object with the ability to do nothing in particular.

Abstract classes often contain code that helps define the structure of an application. When you create subclasses of these classes, instances of your new classes fit effortlessly into the application structure and work automatically with other objects.

(Because abstract classes must have subclasses, they’re sometimes also called *abstract superclasses*.)

Class Types

A class definition is a specification for a kind of object. The class, in effect, defines a data type. The type is based not just on the data structure the class defines (instance variables), but also on the behavior included in the definition (methods).

A class name can appear in source code wherever a type specifier is permitted in C—for example, as an argument to the `sizeof` operator:

```
int i = sizeof(Rectangle);
```

Static Typing

You can use a class name in place of `id` to designate an object's type:

```
Rectangle *myRect;
```

Because this way of declaring an object type gives the compiler information about what kind of object it is, it's known as *static typing*. Just as `id` is defined as a pointer to an object, objects are statically typed as pointers to a class. Objects are always typed by a pointer. Static typing makes the pointer explicit; `id` hides it.

Static typing permits the compiler to do some type checking—for example, to warn if an object receives a message that it appears not to be able to respond to—and to loosen some restrictions that apply to objects generically typed `id`. In addition, it can make your intentions clearer to others who read your source code. However, it doesn't defeat dynamic binding or alter the dynamic determination of a receiver's class at run time.

An object can be statically typed to its own class or to any class that it inherits from. For example, since inheritance makes a `Rectangle` a kind of `Graphic`, a `Rectangle` instance could be statically typed to the `Graphic` class:

```
Graphic *myRect;
```

This is possible because a `Rectangle` is a `Graphic`. It's more than a `Graphic` since it also has the instance variables and method capabilities of a `Shape` and a `Rectangle`, but it's a `Graphic` nonetheless. For purposes of type checking, the compiler will consider `myRect` to be an `Graphic`, but at run time it will be treated as a `Rectangle`.

See “Static Options” in the next chapter for more on static typing and its benefits.

Type Introspection

Instances can reveal their types at run time. The `isMemberOfClass:` method, defined in the `NSObject` class, checks whether the receiver is an instance of a particular class:

```
if ( [anObject isMemberOfClass:someClass] )
    . . .
```

The `isKindOfClass:` method, also defined in the `NSObject` class, checks more generally whether the receiver inherits from or is a member of a particular class (whether it has the class in its inheritance path):

```
if ( [anObject isKindOfClass:someClass] )
    . . .
```

The set of classes for which `isKindOfClass:` returns YES is the same set to which the receiver can be statically typed.

Introspection isn't limited to type information. Later sections of this chapter discuss methods that return the class object, report whether an object can respond to a message, and reveal other information.

See the `NSObject` class specification in the *Foundation Framework Reference* for more on `isKindOfClass:`, `isMemberOfClass:`, and related methods.

Class Objects

A class definition contains various kinds of information, much of it about instances of the class:

- The name of the class and its superclass
- A template describing a set of instance variables
- The declaration of method names and their return and argument types
- The method implementations

This information is compiled and recorded in data structures made available to the run-time system. The compiler creates just one object, a *class object*, to represent the class. The class object has access to all the information about the class, which means mainly information about what instances of the class are like. It's able to produce new instances according to the plan put forward in the class definition.

Although a class object keeps the prototype of a class instance, it's not an instance itself. It has no instance variables of its own and it can't perform methods intended for instances of the class. However, a class definition can include methods intended specifically for the class object—*class methods* as opposed to *instance methods*. A class object inherits class methods from the classes above it in the hierarchy, just as instances inherit instance methods.

In source code, the class object is represented by the class name. In the following example, the Rectangle class returns the class version number using a method inherited from the NSObject class:

```
int versionNumber = [Rectangle version];
```

However, the class name stands for the class object only as the receiver in a message expression. Elsewhere, you need to ask an instance or the class to return the class id. Both respond to a class message:

```
id aClass = [anObject class];  
id rectClass = [Rectangle class];
```

As these examples show, class objects can, like all other objects, be typed id. But class objects can also be more specifically typed to the Class data type:

```
Class aClass = [anObject class];  
Class rectClass = [Rectangle class];
```

All class objects are of type Class. Using this type name for a class is equivalent to using the class name to statically type an instance.

Class objects are thus full-fledged objects that can be dynamically typed, receive messages, and inherit methods from other classes. They're special only in that they're created by the compiler, lack data structures (instance variables) of their own other than those built from the class definition, and are the agents for producing instances at run time.

Note: The compiler also builds a “meta-class object” for each class. It describes the class object just as the class object describes instances of the class. But while you can send messages to instances and to the class object, the meta-class object is used only internally by the run-time system.

Creating Instances

A principal function of a class object is to create new instances. This code tells the `Rectangle` class to create a new `Rectangle` instance and assign it to the `myRect` variable:

```
id myRect;  
myRect = [Rectangle alloc];
```

The `alloc` method dynamically allocates memory for the new object's instance variables and initializes them all to 0—all, that is, except the `isa` variable that connects the new instance to its class. For an object to be useful, it generally needs to be more completely initialized. That's the function of an `init` method. Initialization typically follows immediately after allocation:

```
myRect = [[Rectangle alloc] init];
```


This line of code, or one like it, would be necessary before `myRect` could receive any of the messages that were illustrated in previous examples in this chapter. The `alloc` method returns a new instance and that instance performs an `init` method to set its initial state. Every class object has at least one method (like `alloc`) that enables it to produce new objects, and every instance has at least one method (like `init`) that prepares it for use. Initialization methods often take arguments to allow particular values to be passed and have keywords to label the arguments (`initWithPosition:size:`, for example, is a method that might initialize a new `Rectangle` instance), but they all begin with “init”.

Customization With Class Objects

It's not just a whim of the Objective-C language that classes are treated as objects. It's a choice that has intended, and sometimes surprising, benefits for design. It's possible, for example, to customize an object with a class, where the class belongs to an open-ended set. In the Application Kit, for example, an `NSMatrix` object can be customized with a particular kind of `NSCell`.

An `NSMatrix` can take responsibility for creating the individual objects that represent its cells. It can do this when the `NSMatrix` is first initialized and later when new cells are needed. The visible matrix that an `NSMatrix` object draws on-screen can grow and shrink at run time, perhaps in response to user actions. When it grows, the `NSMatrix` needs to be able to produce new objects to fill the new slots that are added.

But what kind of objects should they be? Each `NSMatrix` displays just one kind of `NSCell`, but there are many different kinds. The inheritance hierarchy in the following figure shows some of those provided by the Application Kit. All inherit from the generic `NSCell` class:



When an `NSMatrix` creates new `NSCell` objects, should they be `NSButtonCells` to display a bank of buttons or switches, `NSTextFieldCells` to display fields where the user can enter and edit text, or some other kind of `NSCell`? The `NSMatrix` must allow for any kind of `NSCell`, even types that haven't been invented yet.

One solution to this problem would be to define the `NSMatrix` class as an abstract class and require everyone who uses it to declare a subclass and implement the methods that produce new cells. Because they would be implementing the methods, users of the class could be sure that the objects they created were of the right type.

But this requires others to do work that ought to be done in the `NSMatrix` class, and it unnecessarily proliferates the number of classes. Since an application might need more than one kind of `NSMatrix`, each with a different kind of `NSCell`, it could become cluttered with `NSMatrix` subclasses. Every time you invented a new kind of `NSCell`, you'd also have to define a new kind of `NSMatrix`. Moreover, programmers on different projects would be writing virtually identical code to do the same job, all to make up for `NSMatrix`'s failure to do it.

A better solution, the solution the `NSMatrix` class actually adopts, is to allow `NSMatrix` instances to be initialized with a kind of `NSCell`—with a class object. It defines a `setCellClass:` method that passes the class object for the kind of `NSCell` object an `NSMatrix` should use to fill empty slots:

```
[myMatrix setCellClass:[NSButtonCell class]];
```

The NSMatrix uses the class object to produce new cells when it's first initialized and whenever it's resized to contain more cells. This kind of customization would be impossible if classes weren't objects that could be passed in messages and assigned to variables.

Variables and Class Objects

When you define a new class of objects, you can decide what instance variables they should have. Every instance of the class will have its own copy of all the variables you declare; each object controls its own data.

However, you can't prescribe variables for the class object; there are no "class variable" counterparts to instance variables. Only internal data structures, initialized from the class definition, are provided for the class. The class object also has no access to the instance variables of any instances; it can't initialize, read, or alter them.

Therefore, for all the instances of a class to share data, an external variable of some sort is required. Some classes declare static variables and provide class methods to manage them. (Declaring a variable static in the same file as the class definition limits its scope to just the class—and to just the part of the class that's implemented in the file. Unlike instance variables, static variables can't be inherited by subclasses.)

Static variables help give the class object more functionality than just that of a "factory" producing instances; it can approach being a complete and versatile object in its own right. A class object can be used to coordinate the instances it creates, dispense instances from lists of objects already created, or manage other processes essential to the application. In the limiting case, when you need only one object of a particular class, you can put all the object's state into static variables and use only class methods. This saves the step of allocating and initializing an instance.

Note: It would also be possible to use external variables that weren't declared static, but the limited scope of static variables better serves the purpose of encapsulating data into separate objects.

Initializing a Class Object

If a class object is to be used for anything besides allocating instances, it may need to be initialized just as an instance is. Although programs don't allocate class objects, Objective-C does provide a way for programs to initialize them.

The run-time system sends an `initialize` message to every class object before the class receives any other messages. This gives the class a chance to set up its run-time environment before it's used. If no initialization is required, you don't need

to write an `initialize` method to respond to the message; the `NSObject` class defines an empty version that your class inherits.

If a class makes use of static or global variables, the `initialize` method is a good place to set their initial values. For example, if a class maintains an array of instances, the `initialize` method could set up the array and even allocate one or two default instances to have them ready.

Note that since `initialize` is inherited, it may be called multiple times on behalf of subclasses.

Methods of the Root Class

All objects, classes and instances alike, need an interface to the run-time system. Both class objects and instances should be able to introspect about their abilities and to report their place in the inheritance hierarchy. It's the province of the `NSObject` class to provide this interface.

So that `NSObject`'s methods won't all have to be implemented twice—once to provide a run-time interface for instances and again to duplicate that interface for class objects—class objects are given special dispensation to perform instance methods defined in the root class. When a class object receives a message that it can't respond to with a class method, the run-time system will see if there's a root instance method that can respond. The only instance methods that a class object can perform are those defined in the root class, and only if there's no class method that can do the job.

For more on this peculiar ability of class objects to perform root instance methods, see the `NSObject` class specification in the *Foundation Framework Reference*.

Class Names in Source Code

In source code, class names can be used in only two very different contexts. These contexts reflect the dual role of a class as a data type and as an object:

- The class name can be used as a type name for a kind of object. For example:

```
Rectangle *anObject;  
anObject = [[Rectangle alloc] init];
```

Here `anObject` is statically typed to be a `Rectangle`. The compiler will expect it to have the data structure of a `Rectangle` instance and the instance methods defined and inherited by the `Rectangle` class. Static typing enables

the compiler to do better type checking and makes source code more self-documenting. See “Static Options” in the next chapter for details.

Only instances can be statically typed; class objects can’t be, since they aren’t members of a class, but rather belong to the Class data type.

- As the receiver in a message expression, the class name refers to the class object. This usage was illustrated in several of the examples above. The class name can stand for the class object only as a message receiver. In any other context, you must ask the class object to reveal its id (by sending it a class message). The example below passes the Rectangle class as an argument in an `isKindOfClass:` message.

```
if ( [anObject isKindOfClass:[Rectangle class]] )
    . . .
```

It would have been illegal to simply use the name “Rectangle” as the argument. The class name can only be a receiver.

If you don’t know the class name at compile time but have it as a string at run time, `objc_lookupClass()` will return the class object:

```
char *aBuffer;
. . .
if ( [anObject isKindOfClass:objc_lookupClass(aBuffer)] )
    . . .
```

This function returns `nil` if the string it’s passed is not a valid class name.

Class names compete in the same name space as variables and functions. A class and a global variable can’t have the same name. Class names are about the only names with global visibility in Objective-C.

Defining A Class

Much of object-oriented programming consists of writing the code for new objects—defining new classes. In Objective-C, classes are defined in two parts:

- An *interface* that declares the methods and instance variables of the class and names its superclass

- An *implementation* that actually defines the class (contains the code that implements its methods)

Although the compiler doesn't require it, the interface and implementation are usually separated into two different files. The interface file must be made available to anyone who uses the class. You generally wouldn't want to distribute the implementation file that widely; users don't need source code for the implementation.

A single file can declare or implement more than one class. Nevertheless, it's customary to have a separate interface file for each class, if not also a separate implementation file. Keeping class interfaces separate better reflects their status as independent entities.

Interface and implementation files typically are named after the class. The implementation file has a ".m" suffix, indicating that it contains Objective-C source code. The interface file can be assigned any other extension. Because it's included in other source files, the interface file usually has the ".h" suffix typical of header files. For example, the Rectangle class would be declared in `Rectangle.h` and defined in `Rectangle.m`.

Separating an object's interface from its implementation fits well with the design of object-oriented programs. An object is a self-contained entity that can be viewed from the outside almost as a "black box." Once you've determined how an object will interact with other elements in your program—that is, once you've declared its interface—you can freely alter its implementation without affecting any other part of the application.

The Interface

The declaration of a class interface begins with the compiler directive `@interface` and ends with the directive `@end`. (All Objective-C directives to the compiler begin with "@".)

```
@interface ClassName : ItsSuperclass
{
    instance variable declarations
}
method declarations
@end
```

The first line of the declaration presents the new class name and links it to its superclass. The superclass defines the position of the new class in the inheritance hierarchy, as discussed under "Inheritance" above. If the colon and

superclass name are omitted, the new class is declared as a root class, a rival to the NSObject class.

Following the class declaration, braces enclose declarations of *instance variables*, the data structures that will be part of each instance of the class. Here's a partial list of instance variables that might be declared in the Rectangle class:

```
float width  
float height;  
BOOL filled;  
NSColor *fillColor;
```

Methods for the class are declared next, after the braces enclosing instance variables and before the end of the class declaration. The names of methods that can be used by class objects, *class methods*, are preceded by a plus sign:

```
+ alloc;
```

The methods that instances of a class can use, *instance methods*, are marked with a minus sign:

```
- (void)display;
```

Although it's not a common practice, you can define a class method and an instance method with the same name. A method can also have the same name as an instance variable. This is more common, especially if the method returns the value in the variable. For example, Circle has a *radius* method that could match a *radius* instance variable.

Method return types are declared using the standard C syntax for casting one type to another:

```
- (float)radius;
```

Argument types are declared in the same way:

```
- (void)setRadius:(float)aRadius;
```

If a return or argument type isn't explicitly declared, it's assumed to be the default type for methods and messages—an `id`. The `alloc` method illustrated above returns `id`.

When there's more than one argument, they're declared within the method name after the colons. Arguments break the name apart in the declaration, just as in a message. For example:

```
- (void)setWidth:(float)width height:(float)height;
```

Methods that take a variable number of arguments declare them using a comma and an ellipsis, just as a function would:

```
- makeGroup:group, ...;
```

Importing the Interface

The interface file must be included in any source module that depends on the class interface—that includes any module that creates an instance of the class, sends a message to invoke a method declared for the class, or mentions an instance variable declared in the class. The interface is usually included with the `#import` directive:

```
#import "Rectangle.h"
```

This directive is identical to `#include`, except that it makes sure that the same file is never included more than once. It's therefore preferred and is used in place of `#include` in code examples throughout NeXT documentation.

To reflect the fact that a class definition builds on the definitions of inherited classes, an interface file begins by importing the interface for its superclass:

```
#import "ItsSuperclass.h"

@interface ClassName : ItsSuperclass
{
    instance variable declarations
}
method declarations
@end
```

This convention means that every interface file includes, indirectly, the interface files for all inherited classes. When a source module imports a class interface, it gets interfaces for the entire inheritance hierarchy that the class is built upon.

Note that if there is a “precomp”—a precompiled header—that supports the superclass, you may prefer to import the precomp instead.

Referring to Other Classes

An interface file declares a class and, by importing its superclass, implicitly contains declarations for all inherited classes, from NSObject on down through its superclass. If the interface mentions classes not in this hierarchy, it must import them explicitly or declare them with the @class directive:

```
@class Rectangle, Circle;
```

This directive simply informs the compiler that “Rectangle” and “Circle” are class names. It doesn’t import their interface files.

An interface file mentions class names when it statically types instance variables, return values, and arguments. For example, this declaration

```
- (void)setPrimaryColor:(NSColor *)aColor;
```

mentions the NSColor class.

Since declarations like this simply use the class name as a type and don’t depend on any details of the class interface (its methods and instance variables), the @class directive gives the compiler sufficient forewarning of what to expect. However, where the interface to a class is actually used (instances created, messages sent), the class interface must be imported. Typically, an interface file uses @class to declare classes, and the corresponding implementation file imports their interfaces (since it will need to create instances of those classes or send them messages).

The @class directive minimizes the amount of code seen by the compiler and linker, and is therefore the simplest way to give a forward declaration of a class name. Being simple, it avoids potential problems that may come with importing files that import still other files. For example, if one class declares a statically typed instance variable of another class, and their two interface files import each other, neither class may compile correctly.

The Role of the Interface

The purpose of the interface file is to declare the new class to other source modules (and to other programmers). It contains all the information they need to work with the class (programmers might also appreciate a little documentation).

- The interface file tells users how the class is connected into the inheritance hierarchy and what other classes—inherited or simply referred to somewhere in the class—are needed.
- The interface file also lets the compiler know what instance variables an object contains and programmers know what variables their subclasses will inherit. Although instance variables are most naturally viewed as a matter of the implementation of a class rather than its interface, they must nevertheless be declared in the interface file. This is because the compiler must be aware of the structure of an object where it's used, not just where it's defined. As a programmer, however, you can generally ignore the instance variables of the classes you use, except when defining a subclass.
- Finally, through its list of method declarations, the interface file lets other modules know what messages can be sent to the class object and instances of the class. Every method that can be used outside the class definition is declared in the interface file; methods that are internal to the class implementation can be omitted.

The Implementation

The definition of a class is structured very much like its declaration. It begins with an `@implementation` directive and ends with `@end`:

```
@implementation ClassName : ItsSuperclass
{
    instance variable declarations
}
method definitions
@end
```

However, every implementation file must import its own interface. For example, `Rectangle.m` imports `Rectangle.h`. Because the implementation doesn't need to repeat any of the declarations it imports, it can safely omit:

- The name of the superclass
- The declarations of instance variables

This simplifies the implementation and makes it mainly devoted to method definitions:

```
#import "ClassName.h"

@implementation ClassName
    method definitions
@end
```

Methods for a class are defined, like C functions, within a pair of braces. Before the braces, they're declared in the same manner as in the interface file, but without the semicolon. For example:

```
+ alloc
{
    . . .
}

- (BOOL)isfilled
{
    . . .
}

- (void)setFilled:(BOOL)flag
{
    . . .
}
```

Methods that take a variable number of arguments handle them just as a function would:

```
#import <stdarg.h>

. . .

- getGroup:group, ...
{
    va_list ap;
    va_start(ap, group);
    . . .
}
```

Referring to Instance Variables

By default, the definition of an instance method has all the instance variables of the object within its scope. It can refer to them simply by name. Although the

compiler creates the equivalent of C structures to store instance variables, the exact nature of the structure is hidden. You don't need either of the structure operators ('.' or '->') to refer to an object's data. For example, the following method definition refers to the receiver's tag instance variable:

```
- (void)setFilled:(BOOL)flag
{
    filled = flag;
    . . .
}
```

Neither the receiving object nor its `filled` instance variable is declared as an argument to this method, yet the instance variable falls within its scope. This simplification of method syntax is a significant shorthand in the writing of Objective-C code.

When the instance variable belongs to an object that's not the receiver, the object's type must be made explicit to the compiler through static typing. In referring to the instance variable of a statically typed object, the structure pointer operator ('->') is used.

Suppose, for example, that the `Sibling` class declares a statically typed object, `twin`, as an instance variable:

```
@interface Sibling : NSObject
{
    Sibling *twin;
    int gender;
    struct features *appearance;
}
```

As long as the instance variables of the statically typed object are within the scope of the class (as they are here because `twin` is typed to the same class), a `Sibling` method can set them directly:

```
- makeIdenticalTwin
{
    if ( !twin ) {
        twin = [[Sibling alloc] init];
        twin->gender = gender;
        twin->appearance = appearance;
    }
    return twin;
}
```

The Scope of Instance Variables

Although they're declared in the class interface, instance variables are more a matter of the way a class is implemented than of the way it's used. An object's interface lies in its methods, not in its internal data structures.

Often there's a one-to-one correspondence between a method and an instance variable, as in the following example:

```
- (BOOL)isFilled
{
    return filled;
}
```


But this need not be the case. Some methods might return information not stored in instance variables, and some instance variables might store information that an object is unwilling to reveal.

As a class is revised from time to time, the choice of instance variables may change, even though the methods it declares remain the same. As long as messages are the vehicle for interacting with instances of the class, these changes won't really affect its interface.

To enforce the ability of an object to hide its data, the compiler limits the scope of instance variables—that is, limits their visibility within the program. But to provide flexibility, it also lets you explicitly set the scope at three different levels. Each level is marked by a compiler directive:

Directive	Meaning
@private	The instance variable is accessible only within the class that declares it.
@protected	The instance variable is accessible within the class that declares it and within classes that inherit it.
@public	The instance variable is accessible everywhere.

This is illustrated in the following figure.



A directive applies to all the instance variables listed after it, up to the next directive or the end of the list. In the following example, the `age` and `evaluation` instance variables are private, `name`, `job`, and `wage` are protected, and `boss` is public.

```
@interface Worker : NSObject
{
    char *name;
@private
    int age;
    char *evaluation;
@protected
    id job;
    float wage;
@public
    id boss;
}
```

By default, all unmarked instance variables (like `name` above) are `@protected`.

All instance variables that a class declares, no matter how they're marked, are within the scope of the class definition. For example, a class that declares a `job` instance variable, such as the `Worker` class shown above, can refer to it in a method definition:

```
- promoteTo:newPosition
{
    id old = job;
    job = newPosition;
    return old;
}
```

Obviously, if a class couldn't access its own instance variables, the instance variables would be of no use whatsoever.

Normally, a class also has access to the instance variables it inherits. The ability to refer to an instance variable is usually inherited along with the variable. It makes sense for classes to have their entire data structures within their scope, especially if you think of a class definition as merely an elaboration of the classes it inherits from. The `promoteTo:` method illustrated above could just as well have been defined in any class that inherits the `job` instance variable from the `Worker` class.

However, there are reasons why you might want to restrict inheriting classes from accessing an instance variable:

- Once a subclass accesses an inherited instance variable, the class that declares the variable is tied to that part of its implementation. In later versions, it can't eliminate the variable or alter the role it plays without inadvertently breaking the subclass.

- Moreover, if a subclass accesses an inherited instance variable and alters its value, it may inadvertently introduce bugs in the class that declares the variable, especially if the variable is involved in class-internal dependencies.

To limit an instance variable's scope to just the class that declares it, you must mark it `@private`.

At the other extreme, marking a variable `@public` makes it generally available, even outside of class definitions that inherit or declare the variable. Normally, to get information stored in an instance variable, other objects must send a message requesting it. However, a public instance variable can be accessed anywhere as if it were a field in a C structure.

```
Worker *ceo = [[Worker alloc] init];
ceo->boss = nil;
```

Note that the object must be statically typed.

Marking instance variables `@public` defeats the ability of an object to hide its data. It runs counter to a fundamental principle of object-oriented programming—the encapsulation of data within objects where it's protected from view and inadvertent error. Public instance variables should therefore be avoided except in extraordinary cases.

How Messaging Works

In Objective-C, messages aren't bound to method implementations until run time. The compiler converts a message expression,

```
[receiver message]
```

into a call on a messaging function, `objc_msgSend()`. This function takes the receiver and the name of the method mentioned in the message—that is, the *method selector*—as its two principal arguments:

```
objc_msgSend(receiver, selector)
```

Any arguments passed in the message are also handed to `objc_msgSend()`:

```
objc_msgSend(receiver, selector, arg1, arg2, . . .)
```

The messaging function does everything necessary for dynamic binding:

- It first finds the procedure (method implementation) that the selector refers to. Since the same method can be implemented differently by different classes, the precise procedure that it finds depends on the class of the receiver.
- It then calls the procedure, passing it the receiving object (a pointer to its data), along with any arguments that were specified for the method.
- Finally, it passes on the return value of the procedure as its own return value.

Note: The compiler generates calls to the messaging function. You should never call it directly in the code you write.


The key to messaging lies in the structures that the compiler builds for each class and object. Every class structure includes these two essential elements:

- A pointer to the superclass.
- A class *dispatch table*. This table has entries that associate method selectors with the class-specific addresses of the methods they identify. The selector for the `setOrigin::` method is associated with the address of (the procedure that implements) `setOrigin::`, the selector for the `display` method is associated with `display`'s address, and so on.

When a new object is created, memory for it is allocated, and its instance variables are initialized. First among the object's variables is a pointer to its class structure. This pointer, called `isa`, gives the object access to its class and, through the class, to all the classes it inherits from.

Note: While not strictly a part of the language, the `isa` pointer is required for an object to work with NeXT's run-time system. An object needs to be "equivalent" to a `struct objc_object` (defined in `objc/objc.h`) in whatever fields the structure defines. However, you will rarely if ever need to create your own root object, and objects that inherit from `NSObject` or `NSProxy` automatically have the `isa` variable.

These elements of class and object structure are illustrated in the following figure.



When a message is sent to an object, the messaging function follows the object's `isa` pointer to the class structure where it looks up the method selector in the dispatch table. If it can't find the selector there, `objc_msgSend()` follows the pointer to the superclass and tries to find the selector in its dispatch table. Successive failures cause `objc_msgSend()` to climb the class hierarchy until it reaches the `NSObject` class. Once it locates the selector, it calls the method entered in the table and passes it the receiving object's data structure.

This is the way that method implementations are chosen at run time—or, in the jargon of object-oriented programming, that methods are dynamically bound to messages.

To speed the messaging process, the run-time system caches the selectors and addresses of methods as they are used. There's a separate cache for each class, and it can contain selectors for inherited methods as well as for methods defined in the class. Before searching the dispatch tables, the messaging routine first checks the cache of the receiving object's class (on the theory that a method that was used once may likely be used again). If the method selector is in the cache, messaging is only slightly slower than a function call. Once a program has been running long enough to “warm up” its caches, almost all the messages it sends will find a cached method. Caches grow dynamically to accommodate new messages as the program runs.

Selectors

For efficiency, full ASCII names are not used as method selectors in compiled code. Instead, the compiler writes each method name into a table, then pairs the name with a unique identifier that will represent the method at run time. The run-time system makes sure each identifier is unique: No two selectors are the same, and all methods with the same name have the same selector. Compiled selectors are assigned to a special type, SEL, to distinguish them from other data. Valid selectors are never 0.

A compiled selector contains fields of coded information that aid run-time messaging. You should therefore let the system assign SEL identifiers to methods; it won't work to assign them arbitrarily yourself.

The `@selector()` directive lets Objective-C source code refer to the compiled selector, rather than to the full method name. Here the selector for `setWidth:height:` is assigned to the `setWidthHeight` variable:

```
SEL setWidthHeight;
setWidthHeight = @selector(setWidth:height:);
```

It's most efficient to assign values to SEL variables at compile time with the `@selector()` directive. However, in some cases, a program may need to convert a character string to a selector at run time. This can be done with the `sel_getUid()` function:

```
setWidthHeight = sel_getUid(aBuffer);
```

Conversion in the opposite direction is also possible. The `sel_getName()` function returns a method name for a selector:

```
char *method;  
method = sel_getName(setWidthHeight);
```

These and other run-time functions are described in the OPENSTEP framework reference documentation.

Methods and Selectors

Compiled selectors identify method names, not method implementations. Rectangle's `display` method, for example, will have the same selector as `display` methods defined in other classes. This is essential for polymorphism and dynamic binding; it lets you send the same message to receivers belonging to different classes. If there were one selector per method implementation, a message would be no different than a function call.

A class method and an instance method with the same name are assigned the same selector. However, because of their different domains, there's no confusion between the two. A class could define a `display` class method in addition to a `display` instance method.

Method Return and Argument Types

The messaging routine has access to method implementations only through selectors, so it treats all methods with the same selector alike. It discovers the return type of a method, and the data types of its arguments, from the selector. Therefore, except for messages sent to statically typed receivers, dynamic binding requires all implementations of identically named methods to have the same return type and the same argument types. (Statically typed receivers are an exception to this rule, since the compiler can learn about the method implementation from the class type.)

Although identically named class methods and instance methods are represented by the same selector, they can have different argument and return types.

Varying the Message at Run Time

The `performSelector:`, `performSelector:withObject:`, and `performSelector:withObject:withObject:` methods, defined in the NSObject protocol, take SEL identifiers as their initial arguments. All three methods map directly into the messaging function. For example,

```
[friend performSelector:@selector(gossipAbout:)
    withObject:aNeighbor];
```

is equivalent to:

```
[friend gossipAbout:aNeighbor];
```

These methods make it possible to vary a message at run time, just as it's possible to vary the object that receives the message. Variable names can be used in both halves of a message expression:

```
id    helper = getTheReceiver();
SEL   request = getTheSelector();
[helper performSelector:request];
```

In this example, the receiver (*helper*) is chosen at run time (by the fictitious `getTheReceiver()` function), and the method the receiver is asked to perform (*request*) is also determined at run time (by the equally fictitious `getTheSelector()` function).

Note: `performSelector:` and its companion methods return an `id`. If the method that's performed returns a different type, it should be cast to the proper type. (However, casting won't work for all types; the method should return a pointer or a type compatible with a pointer.)

The Target-Action Paradigm

In its treatment of user-interface controls, the OpenStep Application Kit makes good use of the ability to vary both the receiver and the message.

`NSControls` are graphical devices that can be used to give instructions to an application. Most resemble real-world control devices such as buttons, switches, knobs, text fields, dials, menu items, and the like. In software, these devices stand between the application and the user. They interpret events coming from hardware devices like the keyboard and mouse and translate them into application-specific instructions. For example, a button labeled "Find" would translate a mouse click into an instruction for the application to start searching for something.

The Application Kit defines a template for creating control devices and defines a few "off-the-shelf" devices of its own. For example, the `NSButtonCell` class

defines an object that you can assign to an `NSMatrix` and initialize with a size, a label, a picture, a font, and a keyboard alternative. When the user clicks the button (or uses the keyboard alternative), the `NSButtonCell` sends a message instructing the application to do something. To do this, an `NSButtonCell` must be initialized not just with an image, a size, and a label, but with directions on what message to send and who to send it to. Accordingly, an `NSButtonCell` can be initialized for an *action message*, the method selector it should use in the message it sends, and a *target*, the object that should receive the message.

```
[myButtonCell setAction:@selector(reapTheWind:)];  
[myButtonCell setTarget:anObject];
```

The `NSButtonCell` sends the message using `NSObject`'s `performSelector:withObject:` method. All action messages take a single argument, the `id` of the control device sending the message.

If Objective-C didn't allow the message to be varied, all `NSButtonCells` would have to send the same message; the name of the method would be frozen in the `NSButtonCell` source code. Instead of simply implementing a mechanism for translating user actions into action messages, `NSButtonCells` and other controls would have to constrain the content of the message. This would make it difficult for any object to respond to more than one `NSButtonCell`. There would either have to be one target for each button, or the target object would have to discover which button the message came from and act accordingly. Each time you rearranged the user interface, you'd also have to re-implement the method that responds to the action message. This would be an unnecessary complication that Objective-C happily avoids.

Avoiding Messaging Errors

If an object receives a message to perform a method that isn't in its repertoire, an error results. It's the same sort of error as calling a nonexistent function. But because messaging occurs at run time, the error often won't be evident until the program executes.

It's relatively easy to avoid this error when the message selector is constant and the class of the receiving object is known. As you're programming, you can check to be sure that the receiver is able to respond. If the receiver is statically typed, the compiler will check for you.

However, if the message selector or the class of the receiver varies, it may be necessary to postpone this check until run time. The `respondToSelector:` method, defined in the `NSObject` class, determines whether a potential receiver can

respond to a potential message. It takes the method selector as an argument and returns whether the receiver has access to a method matching the selector:

```
if ( [anObject respondsToSelector:@selector(setOrigin:)] )
    [anObject setOrigin:0.0 :0.0];
else
    fprintf(stderr, "%s can't be placed\n",
        [anObject [NSStringFromClass([anObject class]) cString]])
```

The `respondToSelector:` test is especially important when sending messages to objects that you don't have control over at compile time. For example, if you write code that sends a message to an object represented by a variable that others can set, you should check to be sure the receiver implements a method that can respond to the message.

Note: An object can also arrange to have the messages that it receives forwarded to other objects if it can't respond to them directly itself. In that case, it will appear that the object can't handle the message, even though it responds to it indirectly by assigning it to another object. Forwarding is discussed in Chapter 4, "The Run-Time System."

Hidden Arguments

When the messaging function finds the procedure that implements a method, it calls the procedure and passes it all the arguments in the message. It also passes the procedure two hidden arguments:

- The receiving object
- The selector for the method

These arguments give every method implementation explicit information about the two halves of the message expression that invoked it. They're said to be "hidden" because they aren't declared in the source code that defines the method. They're inserted into the implementation when the code is compiled.

Although these arguments aren't explicitly declared, source code can still refer to them (just as it can refer to the receiving object's instance variables). A method refers to the receiving object as `self`, and to its own selector as `_cmd`. In the example below, `_cmd` refers to the selector for the `strange` method and `self` to the object that receives a `strange` message.

```
- strange
{
    id target = getTheReceiver();
    SEL action = getTheMethod();

    if ( target == self || action == _cmd )
        return nil;
    return [target performSelector:action];
}
```

`self` is the more useful of the two arguments. It is, in fact, the way the receiving object's instance variables are made available to the method definition.

Although it can make your API more confusing, some methods that have no other meaningful return value return `self`, rather than `void`. This enables such messages to be nested in source code. For example, if `setWidthHeight:`, `setFilled:`, and `setFillColor:` all returned `self`, you could write code like the following:

```
[[myRect setWidth:10.0 height:5.0] setFilled:YES]
    setFillColor:Green];
```

`self` is discussed in more detail in the next section.

Messages to self and super

Objective-C provides two terms that can be used within a method definition to refer to the object that performs the method—`self` and `super`.

Suppose, for example, that you define a `reposition` method that needs to change the coordinates of whatever object it acts on. It can invoke the `setOrigin:` method to make the change. All it needs to do is send a `setOrigin:` message to the very same object that the `reposition` message itself was sent to. When you're writing the `reposition` code, you can refer to that object as either `self` or `super`. The `reposition` method could read either:

```
- reposition
{
    . . .
    [self setOrigin:someX :someY];
    . . .
}
```

or:

```
- reposition
{
    . . .
    [super setOrigin:someX :someY];
    . . .
}
```


Here `self` and `super` both refer to the object receiving a `reposition` message, whatever object that may happen to be. The two terms are quite different, however. `self` is one of the hidden arguments that the messaging routine passes to every method; it's a local variable that can be used freely within a method implementation, just as the names of instance variables can be. `super` is a term that substitutes for `self` only as the receiver in a message expression. As receivers, the two terms differ principally in how they affect the messaging process:

- `self` searches for the method implementation in the usual manner, starting in the dispatch table of the receiving object's class. In the example above, it would begin with the class of the object receiving the `reposition` message.
- `super` starts the search for the method implementation in a very different place. It begins in the superclass of the class that defines the method where `super` appears. In the example above, it would begin with the superclass of the class where `reposition` is defined.

Wherever `super` receives a message, the compiler substitutes another messaging routine for `objc_msgSend()`. The substitute routine looks directly to the superclass of the defining class—that is, to the superclass of the class sending the message to `super`—rather than to the class of the object receiving the message.

An Example

The difference between `self` and `super` becomes clear in a hierarchy of three classes. Suppose, for example, that we create an object belonging to a class called `Low`. `Low`'s superclass is `Mid`; `Mid`'s superclass is `High`. All three classes define a method called `negotiate`, which they use for a variety of purposes. In addition, `Mid` defines an ambitious method called `makeLastingPeace`, which also has need of the `negotiate` method. This is illustrated in the following figure:



We now send a message to our Low object to perform the `makeLastingPeace` method, and `makeLastingPeace`, in turn, sends a `negotiate` message to the same Low object. If source code calls this object `self`,

```
- makeLastingPeace
{
    [self negotiate];
    . . .
}
```

the messaging routine will find the version of `negotiate` defined in Low, `self`'s class. However, if source code calls this object `super`,

```
- makeLastingPeace
{
    [super negotiate];
    . . .
}
```

the messaging routine will find the version of `negotiate` defined in `High`. It ignores the receiving object's class (`Low`) and skips to the superclass of `Mid`, since `Mid` is where `makeLastingPeace` is defined. Neither message finds `Mid`'s version of `negotiate`.

As this example illustrates, `super` provides a way to bypass a method that overrides another method. Here it enabled `makeLastingPeace` to avoid the `Mid` version of `negotiate` that redefined the original `High` version.

Not being able to reach `Mid`'s version of `negotiate` may seem like a flaw, but, under the circumstances, it's right to avoid it:

- The author of the `Low` class intentionally overrode `Mid`'s version of `negotiate` so that instances of the `Low` class (and its subclasses) would invoke the redefined version of the method instead. The designer of `Low` didn't want `Low` objects to perform the inherited method.
- In sending the message to `super`, the author of `Mid`'s `makeLastingPeace` method intentionally skipped over `Mid`'s version of `negotiate` (and over any versions that might be defined in classes like `Low` that inherit from `Mid`) to perform the version defined in the `High` class. `Mid`'s designer wanted to use the `High` version of `negotiate` and no other.

`Mid`'s version of `negotiate` could still be used, but it would take a direct message to a `Mid` instance to do it.

Using `super`

Messages to `super` allow method implementations to be distributed over more than one class. You can override an existing method to modify or add to it, and still incorporate the original method in the modification:

```
- negotiate
{
    . . .
    return [super negotiate];
}
```

For some tasks, each class in the inheritance hierarchy can implement a method that does part of the job and pass the message on to `super` for the rest. The `init` method, which initializes a newly allocated instance, is designed to work like this. Each `init` method has responsibility for initializing the instance variables defined in its class. But before doing so, it sends an `init` message to `super` to have the classes it inherits from initialize their instance variables. Each version of `init` follows this same procedure, so classes initialize their instance variables in the order of inheritance:

```
- (id)init
{
    [super init];
    . . .
}
```

It's also possible to concentrate core functionality in one method defined in a superclass, and have subclasses incorporate the method through messages to `super`. For example, every class method that creates a new instance must allocate storage for the new object and initialize its `isa` pointer to the class structure. This is typically left to the `alloc` and `allocWithZone:` methods defined in the `NSObject` class. If another class overrides these methods for any reason (a rare case), it can still get the basic functionality by sending a message to `super`.

Redefining `self`

`super` is simply a flag to the compiler telling it where to begin searching for the method to perform; it's used only as the receiver of a message. But `self` is a variable name that can be used in any number of ways, even assigned a new value.

There's a tendency to do just that in definitions of class methods. Class methods are often concerned, not with the class object, but with instances of the class. For example, a method might combine allocation and initialization of an instance:

```
+ (id)newRect
{
    return [[self alloc] init];
}
```

In such a method, it's tempting to send messages to the instance and to call the instance `self`, just as in an instance method. But that would be an error. `self` and `super` both refer to the receiving object—the object that gets a message telling it

to perform the method. Inside an instance method, `self` refers to the instance; but inside a class method, `self` refers to the class object.

Before a class method can send a message telling `self` to perform an instance method, it must redefine `self` to be the instance:

```
+ (id)newRectofColor:(NSColor *)aColor
{
    self = [[self alloc] init];
    [self setPrimaryColor:aColor];
    return self;
}
```

The method shown above is a class method, so, initially, `self` refers to the class object. It's as the class object that `self` receives the `alloc` message. `self` is then redefined to be the instance that `alloc` returns and `init` initializes. It's as the new instance that it receives the `setPrimaryColor:` message.

To avoid confusion, it's usually better to use a variable other than `self` to refer to an instance inside a class method:

```
+ (id)newRectofColor:(NSColor *)aColor
{
    id newInstance = [[self alloc] init];
    [newInstance setPrimaryColor:aColor];
    return newInstance;
}
```

Note: In these examples, the class method sends messages (`init` and `setPrimaryColor:`) to initialize the instance. It doesn't assign a new value directly to an instance variable as an instance method might have done:

```
linePattern = aPattern;
primaryColor = aColor;
```

Only instance variables of the receiver can be directly set this way. Because the receiver for a class method (the class object) has no instance variables, this syntax can't be used. However, if `newInstance` had been statically typed, something similar would have been possible:

```
newInstance->linePattern = aPattern;
```

See “Referring to Instance Variables” earlier in this chapter for more on when this syntax is permitted.