

# Technote 1128

## Understanding Open Transport Memory Management

By Quinn "The Eskimo!"  
Apple Worldwide Developer Technical Support

---

### CONTENTS

[Introducing OT Memory Management](#)

[Using OT Memory Effectively](#)

[Advanced Topics](#)

[Summary](#)

This Technote describes how Open Transport's interrupt-safe memory management system works, and how you can use it for best effect in your software.

This Technote is directed at advanced programmers writing Open Transport client or kernel code.

---

## Introducing OT Memory Management

Open Transport provides many different interrupt-safe memory allocation routines. These include `OTAllocMem`, `OTAlloc`, `OTAllocSharedClientMem` and `OTAllocPortMem`. In order to know which routines to use in which circumstances -- and how using these routines affects the memory available to Open Transport and the rest of Mac OS -- you need to understand the OT memory management system.

### Pools of Power

OT memory management is layered on top of four classes of **memory pools**:

1. A **client pool** is allocated for each program that calls `InitOpenTransport` (or `InitOpenTransportUtilities`). It is used to satisfy OT memory allocations for that program and it is destroyed when that program calls `CloseOpenTransport` (either explicitly or by an application quitting).
2. The **shared client pool** (also known as the **native pool**) is allocated when the first program calls `InitOpenTransport` (typically this is the AppleTalk protocol stack, early in the boot sequence). This pool is used by the OT client-side libraries for the bulk of their allocation.
3. The **kernel pool** is allocated the first time the OT kernel is loaded. It is used by the OT kernel and its plug-ins (for example, STREAMS modules and drivers).
4. The **port pool** is allocated the first time a program calls `InitOpenTransport` or `InitOpenTransportUtilities`. The pool is used to hold information about ports. It is distinct from the kernel pool, because port scanners can run without loading the kernel, hence without creating the kernel pool.

Open Transport memory pools are implemented by the Apple Shared Library Manager (ASLM) `TStandardPool` class and inherit some attributes from that class:

1. A pool is always allocated within a Mac OS Memory Manager zone.
2. Each pool starts with an initial size.
3. Memory pools are interrupt-safe. You can allocate memory from the OT memory pools at any

time. However, the pool can only grow at system task time. If you allocate memory at interrupt time, the allocation may fail even though there is enough memory in the zone to grow the pool to meet the request.

4. When the pool runs low on memory, the pool expands by allocating memory from the Mac OS Memory Manager at system task time. The pool grows by a percentage factor, known as the **grow by** factor. The amount grown is bounded below by the **minimum grow** amount.
5. The pool starts to grow when the amount of free space in the pool drops below the **low mark**. There is also a **high mark**, which defines when the pool should start to shrink. This feature is used only by the kernel pool.

#### Note:

You can read more about the ASLM memory pool classes in the ASLM Developer's Guide, available as part of the ASLM SDK on the Mac OS SDK CDs.

## Pool Parameters

The following tables gives the basic parameters of the various Open Transport memory pools.

Pool Type	Zone	Initial	Grow By	Min Grow	Low Mark	High Mark
Client [1]	Appl	2K	20%	2K	1K	infinite
Client [2]	System	1K	20%	2K	512	infinite
Shared	System	2K	20%	4K	2K+1	infinite
Kernel	System [3]	2K	20%	34K	34K+1	[4]
Port	System	2K	20%	1K	1K+1	infinite

#### Notes:

1. This row is for client programs that link with the OT application libraries (those whose names end with "App") and who have not called `InitLibraryManager`.
2. This row is for client programs that link with the OT extension libraries (those whose names end with "Extn") and who have not called `InitLibraryManager`.
3. OT explicitly holds (in the virtual memory sense) the memory in the kernel pool. OT does not guarantee to hold the memory in the other pools.
4. The OT kernel pool shrinks and grows depending on a number of factors, which are described below.

## Using OT Memory Effectively

This section describes various hints and tips for using the OT memory management system effectively.

### OT Routines and their Pool Usage

The following table is a summary of the common OT routines that allocate memory, the amount of memory they allocate, and the pool from which they allocate.

<b>Routine</b>	<b>Pool</b>	<b>Approximate Amount</b>
OTAllocMem [1]	Client	depends on size parameter
OTAllocMem [1]	Kernel	depends on size parameter
OTAlloc	Client	depends on ref and fields parameters
OTAllocSharedClientMem	Shared	depends on size parameter
OTAllocPortMem	Port	depends on size parameter
OTOpenEndpoint	Client Shared Port	16 bytes 150 bytes 1 KB
OTStreamOpen	Shared Kernel	40 bytes 1 KB
OTCreateConfiguration	Shared	100 bytes [2]
OTSnd	Kernel	nbytes [3]

### **IMPORTANT:**

These amount are approximate. The values vary depending on the relative complexity of the protocol being used and between versions of Open Transport. **These values are only meant as a guide for analyzing your program's memory needs.**

### **Notes:**

1. OTAllocMem behaves differently depending on the libraries with which you link. If you link with the OT client libraries (for example, OpenTransportLib), OTAllocMem allocates memory from the client pool. If you link with the OT kernel libraries (for example, OpenTptModuleLib), OTAllocMem allocates memory from the kernel pool.
2. The exact size depends on the complexity of the configuration. This value is a lower bound, based on a simple call to OTCreateConfiguration("serial").
3. This memory is consumed only if the endpoint is copying sent data (i.e., ack sends if off), which is the default setting. If no-copy sends are enabled, the routine allocates a much smaller amount of housekeeping memory.

## **Examining Memory Pools in MacsBug**

The above analysis was done empirically, by calling each routine repeatedly while recording the effect on each memory pool. While OT provides no programming interface for measuring the usage of its memory pools, you can easily find the pools in MacsBug.

First, you will need to find the debug version of Open Transport -- available via links on the [OT web page](#) -- and extract the "OT Debugger Prefs" file, included as part of the install package:

```
Open Tpt Debug Installer
Open Transport Installer
Open Transport Files
OT Debugger Prefs
```

You should copy the "OT Debugger Prefs" file to your MacsBug Preferences folder, then restart your machine.

## IMPORTANT:

It is vital that you use the "OT Debugger Prefs" file from a debug install of OT whose version number matches the version of OT you have installed. The "OT Debugger Prefs" file contains MacsBug templates that are automatically generated by the OT build system to match the layout of the fields in the OT data structures. This layout changes from version to version of OT. If you have the wrong version of the "OT Debugger Prefs", you will not get accurate results in MacsBug.

Once you have the "OT Debugger Prefs" file installed, you can use it to find and display the various OT memory pools. The first step is to dump the OT globals. This is done differently on 68K and PowerPC, and is explained in the following sections.

## Dumping OT Globals on PowerPC

On PowerPC, you can dump the OT globals using the following command:

```
>>> dm __gOTGlobal OTGlobal
Displaying OTGlobal at 0006BDA0
0006BDA0 fGestaltValue      0000003F
0006BDA4 f68KDeferredProc  00000000
0006BDA8 fVersion          01308000
[... other stuff deleted ...]
0006BF04 fClientGlobal
0006BF04 fClientList
0006BF04 fHead              005F1714
[... other stuff deleted ...]
0006BF30 fNativePool        00095320
[... other stuff deleted ...]
0006BF8C fKernelGlobal
0006BF8C fKernelPool        0039A4A0
0006BF90 fKernelPoolMaxSize #13421772
[... other stuff deleted ...]
0006BFD4 fPortPool          0037AA90
[... other stuff deleted ...]
```

OT exports the address of the OT globals as a CFM symbol, `__gOTGlobal`. The above command dumps that address using the `OTGlobal` template from the "OT Debugger Prefs" file. As far as memory usage is concerned, there are three fields of interest:

1. `fNativePool` -- This is the address of the shared client pool.
2. `fKernelPool` -- This is the address of the kernel pool.
3. `fClientList.fHead` -- This is the head of the OT client list. You can dump out the first client using the command:

```
>>> dm 5f1714 RegisteredClient
Displaying RegisteredClient at 005F1714
005F1714 fLink
005F1714 fNext              005F15BC
005F1718 fProviders
005F1718 fHead              005F13D0
005F171C fStreams
005F171C fHead              00000000
005F1720 fWhoAmI            070A7134
[... other stuff deleted ...]
```

You can examine the next client by following the `fLink.fNext` field. Your application will be the one whose `fWhoAmI` field points into your application heap. Once you've found your application, you can display its connection to ASLM by dumping its `fWhoAmI` pointer using the

TLibraryManager template, as shown below:

```
>>> dm 70a7134 TLibraryManager
Displaying TLibraryManager at 070A7134
070A7134  __vptr          003873B0
070A7138  fPool           070A6780
070A713C  fLibraryFile       00000000
070A7140  fDefaultPool       070A6780
[... other stuff deleted ...]
```

The address of your client pool is held in the fDefaultPool field.

Given the address of a pool, you can do a number of things with it:

- The following MacsBug command will display some basic information about the pool:

```
>>> dm 70a6780 TMemoryPool
Displaying TMemoryPool at 070A6780
070A6780  __vptr          00386F40
070A6784  fMemList         070A6770
070A6788  fSize            #2408
070A678C  fLowMark         #1797
070A6790  fHighMark        #4294967295
070A6794  fMaxUsed         #352
070A6798  fCurFree         #2056
070A679C  fZone            06F7CF00
070A67A0  fMemType         #1
[... other stuff deleted ...]
```

The fSize field is the total amount of memory in the pool. The fCurFree field is the amount of free memory left in the pool.

- The dumptool dcmd will display the list of memory blocks in the pool, for example:

```
>>> dumptool 70a6780
Allocated Memory
-----
 70a7000( #16)  70a7010( #16)  70a7020( #168)
 70a70c8( #64)  "!"$plnt"
 70a7108( #40)  "!"$slst"
 70a7130( #48)  "!"$lmgr"
Free Memory
-----
 70a67f8(#2056)
```

- The dumprawpool dcmd will display a more detailed list, for example:

```
>>> dumprawpool 70a6780
Allocated Memory
-----
F:  70a67f8(#2056)
A:  70a7000( #16)  70a7010( #16)  70a7020( #168)
A:  70a70c8( #64)  "!"$plnt"
A:  70a7108( #40)  "!"$slst"
A:  70a7130( #48)  "!"$lmgr"
```

## Dumping OT Globals on 68K

On 68K, the procedure is slightly more complex. The first step is to find the address of the OT global. You do this using the following MacsBug command:

### IMPORTANT:

For this to work you will need to install the debug version of OT so that MacsBug can find the `FetchOTGlobal` symbol.

```
>>> hx 2800
The target heap is the System heap at 00002800
>>> il FetchOTGlobal
Disassembling from FetchOTGlobal
FetchOTGlobal
+00000 0015D5E2  LINK      A6,#$0000          | 4E56 0000
+00004 0015D5E6  MOVE.L    $00092434,D0          | 2039 0009 2434
+0000A 0015D5EC  UNLK      A6                    | 4E5E
+0000C 0015D5EE  RTS                          | 4E75
[... other stuff deleted ...]
```

The first command switches the current MacsBug target zone to the system heap. The next command disassembles a function that returns the address of the OT globals. The line at `FetchOTGlobal + 4` moves the address of the OT globals into register D0. In this case, the address of the OT globals is stored in memory location `$00092434`. You can dump the globals using the following MacsBug command:

```
>>> dm 92434^ OTGlobal
Displaying OTGlobal at 000B5050
000B5050  fGestaltValue      0000000F
000B5054  f68KDeferredProc  00238164
000B5058  fVersion          01306007
[... other stuff deleted ...]
```

After dumping the OT globals, you can proceed as in the PowerPC case.

## Controlling Client Pool Parameters

As described above, the OT client pool for an application is allocated in the application heap when you call `InitOpenTransport`. The pool starts very small and grows on demand. However, this behavior is not always optimal. Specifically, if you want to exclusively use the OT memory allocators in your application, you should dedicate your entire application heap to their use. Having the allocators consume your application heap piecemeal is much less efficient than giving it to them in one big chunk.

You can obtain more control over your client pool by using the ASLM programming interface. If you have already initialized a connection to ASLM, `InitOpenTransport` will use it (and its client pool) instead of creating its own. You can use this to control how large your client pool is, where it is allocated, and how it grows.

### Note:

To program with ASLM, you need the ASLM SDK from the Mac OS SDK CDs.

### IMPORTANT:

To call ASLM from 68K C or C++ code, you must be building with the 4-byte integers.

To use this technique, you must call `InitLibraryManager` before calling `InitOpenTransport`. In addition, you must call `CleanupLibraryManager` after calling `CloseOpenTransport`. The prototypes

for these routines are defined in "LibraryManager.h", but they are given below for your convenience.

```
OSErr InitLibraryManager(size_t poolsize, int zoneType, int memType);
void CleanupLibraryManager(void);
```

The additional parameters to `InitLibraryManager` allow you to specify the initial size for your client pool (in bytes), the location of the client pool (typically `kSystemZone`, `kApplicZone`, or `kCurrentZone`), and the type of memory for the client pool (typically `kNormalMemory`; however, if you access the memory when paging is unsafe, `kHoldMemory` may be useful).

The following code snippet demonstrates this technique. It first creates a subsidiary zone within the application heap (whose size is calculated to consume the entire heap, minus some memory for use by the toolbox). It then calls `InitLibraryManager` to connect to ASLM (and establish the client pool in the subsidiary zone) before calling `InitOpenTransport`.

```
static OSStatus InitOpenTransportWithMemoryLimit(void)
{
    OSStatus err;
    SInt32 junkTotalFree;
    SInt32 contigFree;
    SInt32 zoneSize;
    Ptr subsidiaryZone;
    THz oldZone;

    // First call the system Memory Manager to determine the largest
    // contiguous block in the heap.

    PurgeSpace(&junkTotalFree, &contigFree);

    zoneSize = contigFree - kBytesReservedForToolboxInApplicationZone;

    // Allocate the memory for our zone and create a zone in that
    // block. Then init ASLM, telling it to create a pool that
    // takes up the entire zone (minus the ASLM overhead factor)
    // in the current zone, i.e., the zone we just created. Finally,
    // initialize OT. OT will see that we've init'd ASLM and use
    // the pool that ASLM created (in the zone we created) for
    // satisfying OTAllocMem requests.

    subsidiaryZone = NewPtr(zoneSize);
    oldZone = GetZone();

    // InitZone sets the current zone to the newly created zone,
    // so I don't have to do it myself.

    InitZone(nil, 16, subsidiaryZone + zoneSize, subsidiaryZone);
    err = InitLibraryManager(zoneSize - 2048, kCurrentZone, kNormalMemory);
    if (err == noErr) {
        err = InitOpenTransport();
        if (err != noErr) {
            CleanupLibraryManager();
        }
    }
    SetZone(oldZone);

    return err;
}
```

**Note:**

This code is a simplified version (less error checking) of the code used by the DTS sample code `OTStreamLogViewer`. If you use this technique, you should get the real code from that sample.

**Note:**

The above technique is by no means the only one available to you using the ASLM API. You should read the *ASLM Developer's Guide* for more information.

## Advanced Topics

This section describes some of the more advanced issues in the realm of OT memory management. Specifically, the section describes how the OT shared client and kernel pools grow and shrink over time. Before tackling this, you need to learn about another API call you can make to alter the behavior of the OT memory system.

**Note:**

This section of the note is intended for those with an intimate knowledge of the Open Transport architecture. Do not be alarmed if you do not understand it!

### `OTSetMemoryLimits`

The `OTSetMemoryLimits` routine allows software to directly affect the behavior of the OT memory pools. The prototype for the routine is:

```
#ifdef __cplusplus
extern "C" {
#endif

extern OSStatus OTSetMemoryLimits(size_t growSize, size_t maxSize);

#ifdef __cplusplus
}
#endif
```

The `growSize` parameter is the amount by which OT should grow the kernel pool right now. When you call the routine, OT immediately tries to grow the kernel pool by this amount. The `maxSize` parameter is the new maximum size of the kernel pool. OT will never grow the kernel pool larger than this amount.

`OTSetMemoryLimits` also implicitly sets an internal Open Transport variable called `fServerMode`. If you call `OTSetMemoryLimits` with a positive `growSize` value, `fServerMode` is incremented. If you call it with a zero value, `fServerMode` is decremented. If `fServerMode` is non-zero, OT will never downsize the shared client or kernel pools. To be a good citizen, server software should call `OTSetMemoryLimits` with a positive `growSize` when it starts up, and a zero `growSize` when it shuts down.

Finally, if you grow the kernel pool by more than 20 KB, `OTSetMemoryLimits` will also grow the shared client pool by 10% of the `growSize` value.

`OTSetMemoryLimits` is only of use to server software which must handle extremely 'bursty' connection patterns or many connections in parallel. By increasing the maximum size of the kernel pool, the server can handle more connections in parallel. By growing the kernel pool immediately (rather than as each connection is created), the server can handle these parallel connections as soon as it's started, rather than waiting for the kernel pool to grow through usage. By never downsizing the kernel pool, the server can handle many connections simultaneously even after a long period of inactivity.



`OTSetMemoryLimits` must be called at system task time and returns an error result if it can't grow the kernel pool by the specified amount.

### **IMPORTANT:**

Using `OTSetMemoryLimits` will never increase the performance of a single connection. It is only useful for software with dozens of parallel connections. DTS strongly recommends that client software never call `OTSetMemoryLimits`.

### **Note:**

The `OTSetMemoryLimits` routine does not appear in any Open Transport header files. If you use the routine, you must declare the prototype yourself. This is a consequence of the above policy -- general application programs should not call this routine.

### **Note:**

There is an earlier incarnation of `OTSetMemoryLimits`, called `OTSetServerMode`. This routine has been completely subsumed by `OTSetMemoryLimits`.

## **Growing OT Memory Pools**

When OT attempts to grow a pool, it uses a binary back-off algorithm to do so. It starts by attempting to grow the pool by getting one big block of memory from the Mac OS Memory Manager. If a block of that size is not available, it halves the size requested and tries again. This process terminates when either OT has grown the pool the requested amount, or the block size shrinks below 10 KB.

## **Shrinking OT Memory Pools**

ASLM memory pools have the ability to shrink. A memory pool is made up of a number of discontinuous memory blocks that have been allocated from the Mac OS Memory Manager. When a pool is **downsized**, each Mac OS memory block is examined to see if it is empty. If it is, that memory block is released back to the Mac OS Memory Manager.

OT memory pools are downsized at the following points:

- Whenever a client dies (it calls `CloseOpenTransport` or an application quits without calling `CloseOpenTransport`) **and** OT is not in server mode, OT downsizes the shared client and kernel pools.
- Whenever OT unloads the client libraries, it downsizes the shared client pool.
- Whenever OT unloads the kernel (which happens when there are no remaining clients who called `InitOpenTransport`), it downsizes the kernel pool if OT is not in server mode.
- Whenever OT unloads the kernel utilities library (which happens when there are no remaining clients who called `InitOpenTransportUtilities`), OT downsizes the port pool.
- OT downsizes the port pool after it runs port scanners.
- OT downsizes the shared client pool immediately after it runs through the list of configurators calling their `OTSetupConfigurator` or `OTStartupConfigurator` entry points.

## **More Kernel Pool Trivia**

OT maintains a hard limit on the upper bound of the size of the kernel pool. Clients can set this limit using the `OTSetMemoryLimits` routine. This poses the question: What is the initial value for this limit? Out of the box, OT sets this limit to 10% of the physical memory on the machine (as returned by `gestaltPhysicalRAMSize`). This strikes a balance between providing enough buffer space for networking while preventing OT from consuming all the user's memory.

When the kernel is loaded for the first time, OT creates the kernel pool at the initial size specified above. However, each time the kernel loads (including the first time), OT forces the kernel to grow to be at least 96 KB before finishing the load. This mechanism allows the kernel pool to be small while the kernel is unloaded, but grow quickly when the kernel loads.

## Summary

Open Transport provides a reliable, flexible, and interrupt-safe memory management system. By understanding how it works, you can avoid some common pitfalls and still write code that allocates memory at interrupt time. *Finally*.

## Further References

- [Inside Macintosh: Networking With Open Transport](#)
- [Inside Macintosh: Memory](#)
- [Apple Shared Library Manager Developer's Guide](#)
- [Open Transport Web Page](#)

## Downloadables



[Acrobat version of this Note \(152K\).](#)

## Acknowledgments

Thanks to Mark Cookson, Steve Kalkwarf, Rich Kubota and Brad Suinn.

---

---

To send feedback, please use the [Feedback](#) page.

11-May-98

[Technotes](#)

[Previous Technote](#) | [Contents](#) | [Next Technote](#)