

Division 4 Masonry

Estimating Tips

041 Mortar & Masonry Accessories

- The terms *mortar* and *grout* are often used interchangeably, and incorrectly. Mortar is used to bed masonry units, seal the entry of air and moisture, provide architectural appearance, and allow for size variations in the units. Grout is used primarily in reinforced masonry construction and is used to bond the masonry to the reinforcing steel. Common mortar types are M(2500 psi), S(1800 psi), N(750 psi), and O(350 psi), and conform to ASTM C270. Grout is either fine or coarse, conforms to ASTM C476, and in-place strengths generally exceed 2500 psi. Mortar and grout are different components of masonry construction and are placed by entirely different methods. An estimator should be aware of their unique uses and costs.

042 Unit Masonry

- The most common types of unit masonry are brick and concrete masonry. The major classifications of brick are building brick (ASTM C62), facing brick (ASTM C216) and glazed brick, fire brick and pavers. Many varieties of texture and appearance can exist within these classifications, and the estimator would be wise to check local custom and availability within the project area. On repair and remodeling jobs, matching the existing brick may be the most important criteria.
- Brick and concrete block are priced by the piece and then converted into a price per square foot of wall. Openings less than two square feet are generally ignored by the estimator because any savings in units used is offset by the cutting and trimming required.

- All masonry walls, whether interior or exterior, require bracing. The cost of bracing walls during construction should be included by the estimator and this bracing must remain in place until permanent bracing is complete. Permanent bracing of masonry walls is accomplished by masonry itself, in the form of pilasters or abutting wall corners, or by anchoring the walls to the structural frame. Accessories in the form of anchors, anchor slots and ties are used, but their supply and installation can be by different trades. For instance, anchor slots on spandrel beams and columns are supplied and welded in place by the steel fabricator, but the ties from the slots into the masonry are installed by the bricklayer. Regardless of the installation method the estimator must be certain that these accessories are accounted for in pricing.

Reference Numbers

Reference numbers are shown in bold squares at the beginning of some major classifications. These numbers refer to related items in the Reference Section. The reference information may be an estimating procedure, an alternate pricing method or technical information.

Note: Not all subdivisions listed here necessarily appear in this publication.