xlib:window-backing-store, 4-39
xlib:window-bit-gravity, 4-39
xlib:window-border, 4-40
xlib:window-class, 4-40
xlib:window-colormap, 4-40
xlib:window-colormap-installed-p, 4-40
xlib:window-cursor, 4-41
xlib:window-display, 4-41
xlib:window-do-not-propagate-mask, 4-41
xlib:window-equal, 4-41
xlib:window-event-mask, 4-41
xlib:window-gravity, 4-41
xlib:window-id, 4-42
xlib:window-map-state, 4-42
xlib:window-override-redirect, 4-42
xlib:window-p, 4-43
xlib:window-plist, 4-43
xlib:window-priority, 4-43
xlib:window-save-under, 4-43
xlib:window-visual, 4-43
xlib:with-display, 2-29
xlib:with-event-queue, 12-125
xlib:with-gcontext, 5-68
  example, 1-8
xlib:with-server-grabbed, 14-169
xlib:with-state, 4-43
  example, 1-7
xlib:write-bitmap-file, 7-87
xlib:write-resources, 13-167

xlib:query-best-tile, 5-67
xlib:query-colors, 9-105
xlib:query-extension, 15-183
xlib:query-keymap, 14-172
xlib:query-pointer, 12-126
  example, 1-10
xlib:query-tree, 4-46
xlib:queue-event, 12-124

R

xlib:read-bitmap-file, 7-87
xlib:read-resources, 13-166
xlib:recolor-cursor, 10-109
xlib:remove-access-host, 14-180
xlib:remove-from-save-set , 14-178
xlib:reparent-window, 4-46
xlib:reset-screen-saver, 14-180
xlib:rotate-properties, 11-114

S

xlib:screen-backing-stores, 3-32
xlib:screen-black-pixel, 3-32
  example, 1-10
xlib:screen-default-colormap, 3-32
xlib:screen-depths, 3-32
xlib:screen-event-mask-at-open, 3-32
xlib:screen-height, 3-33
xlib:screen-height-in-millimeters, 3-33
xlib:screen-max-installed-maps, 3-33
xlib:screen-min-installed-maps, 3-33
xlib:screen-p, 3-33
xlib:screen-plist, 3-33
xlib:screen-root, 3-33
  example, 1-10
xlib:screen-root-depth, 3-34
xlib:screen-root-visual, 3-34
xlib:screen-save-unders-p, 3-34
xlib:screen-saver, 14-180
xlib:screen-white-pixel, 3-34
  example, 1-10
xlib:screen-width, 3-34
xlib:screen-width-in-millimeters, 3-34
xlib:selection-owner, 11-117
xlib:send-event, 12-125
xlib:set-input-focus, 12-128
xlib:set-modifier-mapping, 14-172
xlib:set-screen-saver, 14-181
xlib:store-color, 9-105
xlib:store-colors, 9-106

T

xlib:text-extents, 8-97
  example, 1-7
xlib:text-width, 8-98
xlib:translate-coordinates, 4-47
xlib:translate-function, 6-78

U

xlib:ungrab-button, 12-133
xlib:ungrab-key, 12-135
xlib:ungrab-keyboard, 12-134
xlib:ungrab-pointer, 12-131
xlib:ungrab-server, 14-169
xlib:uninstall-colormap, 9-103
xlib:unmap-subwindows, 4-49
xlib:unmap-window, 4-49
  example, 1-9

W

xlib:warp-pointer, 12-127
xlib:warp-pointer-if-inside, 12-127
xlib:warp-pointer-relative, 12-127
xlib:warp-pointer-relative-if-inside, 12-128
xlib:window-all-event-masks , 4-38
xlib:window-background, 4-38
xlib:window-backing-pixel, 4-39
xlib:window-backing-planes, 4-39

xlib:image-red-mask, 7-82
xlib:image-width, 7-82
xlib:image-x-hot, 7-82
xlib:image-xy-bitmap-list, 7-83
xlib:image-y-hot, 7-82
xlib:image-z-bits-per-pixel, 7-83
xlib:image-z-pixarray, 7-83
xlib:input-focus, 12-129
xlib:install-colormap, 9-102
xlib:installed-colormaps, 9-102
xlib:intern-atom, 11-112

K

xlib:keyboard-control, 14-172
xlib:keyboard-mapping, 14-175
xlib:keycode-character, 14-176
xlib:keycode-keysym, 14-175
xlib:kill-client, 14-178
xlib:kill-temporary-clients, 14-178

L

xlib:list-extensions, 15-183
xlib:list-font-names, 8-91
xlib:list-fonts, 8-91
xlib:list-properties, 11-114
xlib:lookup-color, 9-105

M

xlib:make-color, 9-100
xlib:make-event-keys, 1-16
xlib:make-event-mask, 1-16
  example, 1-5, 1-6
xlib:make-resource-database, 13-162
xlib:make-state-keys, 1-20
xlib:make-state-mask, 1-20
xlib:map-resource, 13-163
xlib:map-subwindows, 4-49
  example, 1-7
xlib:map-window, 4-48
xlib:max-char-ascent, 8-94
xlib:max-char-attributes, 8-94
xlib:max-char-descent, 8-94
xlib:max-char-left-bearing, 8-94
xlib:max-char-right-bearing, 8-94
xlib:max-char-width, 8-94
xlib:merge-resources, 13-163
xlib:min-char-ascent , 8-95
xlib:min-char-attributes, 8-95
xlib:min-char-descent, 8-95
xlib:min-char-left-bearing, 8-95
xlib:min-char-right-bearing, 8-95
xlib:min-char-width, 8-95
xlib:modifier-mapping, 14-172
xlib:motion-events, 12-127

O

xlib:open-display, 2-23
  example, 1-10
xlib:open-font, 8-90
  example, 1-10

P

xlib:pixmap-display, 4-50
xlib:pixmap-equal, 4-50
xlib:pixmap-id, 4-50
xlib:pixmap-p, 4-51
xlib:pixmap-plist, 4-51
xlib:pointer-control, 14-170
xlib:pointer-mapping, 14-170
xlib:pointer-position, 12-126
xlib:process-event, 12-122
xlib:put-image, 7-86
xlib:put-raw-image, 7-88

Q

xlib:query-best-cursor, 10-109
xlib:query-best-stipple, 5-67

xlib:font-direction, 8-92
xlib:font-display, 8-92
xlib:font-equal, 8-92
xlib:font-id, 8-92
xlib:font-max-byte1, 8-92
xlib:font-max-byte2, 8-92
xlib:font-max-char, 8-93
xlib:font-min-byte1, 8-93
xlib:font-min-byte2, 8-93
xlib:font-min-char, 8-93
xlib:font-name, 8-93
xlib:font-p, 8-93
xlib:font-path, 8-90
xlib:font-plist, 8-93
xlib:font-properties, 8-94
xlib:font-property, 8-94
xlib:force-gcontext-changes, 5-68
xlib:free-colormap, 9-102
xlib:free-colors, 9-104
xlib:free-cursor, 10-108
xlib:free-gcontext, 5-68
xlib:free-pixmap, 4-50

G

xlib:gcontext-arc-mode, 5-55
xlib:gcontext-background, 5-56
  example, 1-6, 1-8
xlib:gcontext-cache-p, 5-56
xlib:gcontext-cap-style, 5-56
xlib:gcontext-clip-x, 5-58
xlib:gcontext-clip-y, 5-58
xlib:gcontext-dash-offset, 5-58
xlib:gcontext-dashes, 5-58
xlib:gcontext-display, 5-59
xlib:gcontext-equal, 5-59
xlib:gcontext-exposures, 5-59
xlib:gcontext-fill-rule, 5-59
xlib:gcontext-fill-style, 5-60
xlib:gcontext-font, 5-61
  example, 1-7, 1-8
xlib:gcontext-foreground, 5-61
  example, 1-8
xlib:gcontext-function, 5-61
xlib:gcontext-id, 5-62
xlib:gcontext-join-style, 5-62
xlib:gcontext-line-style, 5-63
xlib:gcontext-line-width, 5-63
xlib:gcontext-p, 5-64
xlib:gcontext-plane-mask, 5-64
xlib:gcontext-plist, 5-65
xlib:gcontext-stipple, 5-65
xlib:gcontext-subwindow-mode, 5-66
xlib:gcontext-tile, 5-66
xlib:gcontext-ts-x, 5-67
xlib:gcontext-ts-y, 5-67
xlib:get-image, 7-85
xlib:get-property, 11-114
xlib:get-raw-image, 7-87
xlib:get-resources, 13-165
xlib:get-search-resource, 13-166
xlib:get-search-table, 13-165
xlib:global-pointer-position, 12-126
xlib:grab-button, 12-132
xlib:grab-keyboard, 12-133, 12-134
xlib:grab-pointer, 12-130
xlib:grab-server, 14-169

H

xlib:handler-function, 12-122

I

xlib:image-blue-mask, 7-81
xlib:image-depth, 7-81
xlib:image-green-mask, 7-81
xlib:image-height, 7-82
xlib:image-name, 7-82
xlib:image-plist, 7-82

xlib:delete-resource, 13-163
xlib:destroy-subwindows, 4-49
xlib:destroy-window, 4-49
  example, 1-6
xlib:discard-current-event, 12-124
xlib:discard-font-info, 8-90
xlib:display-after-function, 2-29
xlib:display-authorization-data, 2-24
xlib:display-authorization-name, 2-24
xlib:display-bitmap-format, 2-24
xlib:display-byte-order, 2-24
xlib:display-display, 2-24
xlib:display-error-handler, 2-25
xlib:display-finish-output, 2-29
xlib:display-force-output, 2-29
xlib:display-image-lsb-first-p, 2-25
xlib:display-keycode-range, 2-25
xlib:display-max-keycode, 2-26
xlib:display-max-request-length, 2-26
xlib:display-min-keycode, 2-26
xlib:display-motion-buffer-size, 2-26
xlib:display-p, 2-26
xlib:display-pixmap-formats, 2-26
xlib:display-plist, 2-27
xlib:display-protocol-major-version, 2-27
xlib:display-protocol-minor-version, 2-27
xlib:display-protocol-version, 2-27
xlib:display-resource-id-base, 2-27
xlib:display-resource-id-mask , 2-28
xlib:display-roots, 2-28
  example, 1-10
xlib:display-vendor, 2-28
xlib:display-vendor-name, 2-28
xlib:display-version-number, 2-28
xlib:display-xid, 2-28
xlib:draw-arc, 6-74
xlib:draw-arcs, 6-75
xlib:draw-glyph, 6-76
xlib:draw-glyphs, 6-76
xlib:draw-image-glyph, 6-77
xlib:draw-image-glyphs, 6-78
  example, 1-8
xlib:draw-line, 6-72
xlib:draw-lines, 6-72
xlib:draw-point, 6-71
xlib:draw-points, 6-71
xlib:draw-rectangle, 6-73
xlib:draw-rectangles, 6-73
xlib:draw-segments, 6-73
xlib:drawable-border-width, 4-37
xlib:drawable-depth, 4-37
xlib:drawable-display, 4-35
  example, 1-9
xlib:drawable-equal, 4-35
xlib:drawable-height, 4-37
  example, 1-7
xlib:drawable-id, 4-35
xlib:drawable-p, 4-35
xlib:drawable-plist, 4-35
xlib:drawable-root, 4-46
xlib:drawable-width, 4-37
  example, 1-7
xlib:drawable-x, 4-38
  example, 1-7
xlib:drawable-y, 4-38
  example, 1-7

E

xlib:event-case, 12-123
  example, 1-9
xlib:event-cond, 12-123
xlib:event-listen, 12-125

F

xlib:find-atom, 11-112
xlib:font-all-chars-exist-p, 8-91
xlib:font-ascent, 8-91
  example, 1-7, 1-8
xlib:font-default-char, 8-91
xlib:font-descent, 8-92
  example, 1-7

Functions

A

xlib:access-control, 14-179
xlib:access-hosts, 14-179
xlib:activate-screen-saver, 14-180
xlib:add-access-host, 14-179
xlib:add-resource, 13-162
xlib:add-to-save-set, 14-178
xlib:alloc-color, 9-103
xlib:alloc-color-cells, 9-103
xlib:alloc-color-planes, 9-104
xlib:allow-events, 12-158
xlib:atom-name, 11-112

B

xlib:bell, 14-170

C

xlib:change-active-pointer-grab, 12-131
xlib:change-keyboard-control, 14-171
xlib:change-keyboard-mapping, 14-174
xlib:change-pointer-control, 14-169
xlib:change-property, 11-113
xlib:char-ascent, 8-96
xlib:char-attributes, 8-96
xlib:char-descent, 8-96
xlib:char-left-bearing, 8-96
xlib:char-right-bearing, 8-96
xlib:char-width, 8-97
xlib:circulate-window-down, 4-45
xlib:circulate-window-up, 4-46
xlib:clear-area, 6-69
xlib:close-display, 2-30, 5-57
  example, 1-10
xlib:close-down-mode, 14-178
xlib:close-font, 8-90
xlib:color-blue, 9-100
xlib:color-green, 9-100
xlib:color-p, 9-100
xlib:color-red, 9-100
xlib:color-rgb, 9-100
xlib:colormap-display, 9-107
xlib:colormap-equal, 9-107
xlib:colormap-id, 9-107
xlib:colormap-p, 9-107
xlib:colormap-plist, 9-107
xlib:convert-selection, 11-116
xlib:copy-area, 6-70
xlib:copy-colormap-and-free, 9-102
xlib:copy-gcontext, 5-67
xlib:copy-gcontext-components, 5-68
xlib:copy-image, 7-85
xlib:copy-plane, 6-70
xlib:create-colormap, 9-101
xlib:create-cursor, 10-107
xlib:create-gcontext, 5-54
  example, 1-5
xlib:create-glyph-cursor, 10-108
xlib:create-image, 7-83
xlib:create-pixmap, 4-50
xlib:create-window, 4-35
  example, 1-5, 1-6
xlib:cursor-display, 10-109
xlib:cursor-equal, 10-109
xlib:cursor-id, 10-109
xlib:cursor-p, 10-109
xlib:cursor-plist, 10-109

D

xlib:declare-event, 12-157
xlib:define-condition, 16-185
xlib:delete-property, 11-113