

Apple II Technical Notes



Developer Technical Support

AppleTalk

#7: MLIACTV Flag and the Iie Workstation Card

Written by: Mark Day & Dan Strnad
November 1989

This Technical Note describes a problem using the MLIACTV flag with the Iie Workstation Card.

When using the Apple Iie Workstation Card, the MLIACTV flag does not always show that the MLI (or PFI) is active. This inconsistency can cause programs that use the MLIACTV flag to fail when making MLI calls from interrupt routines. Programs can correct for this problem by making all MLI calls through the NewMLI routine listed in this Note and checking the NewMLIActv flag instead of the MLIACTV flag. This approach solves the problem only if **all** MLI calls, including those made by any interrupt routines, are made through this routine.

The following routine is a replacement for the MLI entry point at \$BF00. Programs using this routine can perform a JSR to NewMLI instead, which fixes the problem. Section 6.2.1 of the *ProDOS 8 Technical Reference Manual* details how programs can cause the MLI to return the their routine rather than the routine that originally called it. For programs using this technique that are also using the routine below, the location below labeled NewCmdAddr replaces CmdAdr (\$BF9C). The steps involved in patching the MLI return location still apply, as specified in Section 6.2.1 of the ProDOS 8 Technical Reference.

```
; MLI patch for Apple II Workstation Card  
; by Mark Day  
;
```

```
; code shown is compatible with MPW IIGS cross-assembler
;
; Your program should use the NewMLIActv flag instead of
; MLIACTV ($BF9B), and should JSR NewMLI instead of
; JSR MLI ($BF00).
;

        machine      M6502          ; 6502 code for //e
        longa  off
        longi  off

parmptr  equ    0          ; two bytes on zero page
MLI      equ    $BF00      ; entry to the real MLI

NewMLI proc

        php          ; save old interrupt status to
        pla          ; temporarily disable interrupts
        sta oldp     ; so that NewCmdAddr is always valid
        sei          ; when an interrupting routine sees
                    ; NewMLI active.

        sec
        ror    NewMLIActv  ; NewMLI is now active!
```

```

;
; We need to get the return address from the stack so we can
; get the command number and parameter block address which
; follow the JSR NewMLI, and so we can save NewCmdAddr.
;
        clc
        pla                ; get low byte of parm address - 1
        sta    parmptr
        adc     #4          ; get real return address
        sta    NewCmdAddr
        pla
        sta    parmptr+1    ; save high byte of parm address - 1
        adc     #0
        sta    NewCmdAddr+1 ; save real return address

        lda oldp
        pha
        plp                ; reinstate old interrupt status
;
; Now, we copy the call number and parameter list pointer that followed
; the JSR NewMLI, and copy them after a JSR to the real MLI.
;
        tya                ; save Y on stack
        pha
        ldy     #1          ; offset to command number
        lda     (parmptr),y ; get command number
        sta     NewCmdNum
        iny
        lda     (parmptr),y ; point to parm list ptr (low)
        sta     NewParmPtr
        iny
        lda     (parmptr),y
        sta     NewParmPtr+1
        pla
        tay                ; unstack value of y register
;
; Now, call the real MLI with the user's command and parameter list
; and jump back to our caller.
;
        jsr     MLI          ; call the real MLI
NewCmdNum    dc.b    0        ; command number
NewParmPtr   dc.w    0        ; parameter list pointer

        php
        lsr     NewMLIActv   ; save C because LSR changes it!
                                ; MLI is no longer active
        plp
                                ; restore C
        dc.b    $4C          ; JMP absolute instruction
NewCmdAddr   dc.w    0        ; target of jump, caller's return address

NewMLIActv   dc.b    0        ; $80 bit set if MLI active
oldp         ds.b    1        ; used to preserve processor status

        endp
        end

```

Note that this routine also works on the Apple IIgs, even though the problem with the MLIACTV flag only affects Apple IIe Workstation Cards.

Further Reference

- *AppleShare Programmer's Guide for the Apple IIgs*
- *ProDOS 8 Technical Reference Manual*