

Contents

Figures and Tables / v

Preface / vii

About this note / vii

For more information / vii

1 Macintosh Classic II Hardware / 1

Major features / 2

Design differences / 3

Compatibility issues / 5

 ADB implementation / 5

 SCSI and SCC implementation / 5

 Sound input/output hardware / 6

 No on-board mathematics coprocessor (FPU) / 6

Hardware overview / 7

 Main processor / 7

 EAGLE gate array / 7

 Address decode and memory mapping / 8

 VIAs / 9

 ROM / 9

 Power-on overlay function / 9

 RAM / 10

 Video / 10

 Sound interface / 12

 Sound input feature / 12

 SCC and SCSI interfaces / 13

 SCC / 13

 SCSI / 14

 Hard disk drive dimensions and mounting requirements / 15

 Floppy disk interface / 17

Apple Desktop Bus (ADB) microcontroller /	18
Apple Desktop Bus interface /	19
Real-time clock and parameter RAM /	19
Power-on reset /	20
Keyboard reset and NMI /	20
FPU/ROM connector /	21
Electrical description of the FPU/ROM connector /	22
Physical design guidelines for the FPU/ROM card /	25
FPU/ROM connector power budget /	26

2 Macintosh Classic II Software / 27

The Macintosh Classic II ROM /	28
New MMU code /	28
New video driver /	28
Software-controlled brightness /	29
New and improved SANE package /	29
Modified AppleTalk support /	29
System software /	29

Figures and Tables

1 Macintosh Classic II Hardware / 1

Figure 1-1 Block diagram of the Macintosh Classic II computer
/ 4

Figure 1-2 512 x 342 video timing / 11

Figure 1-3 Envelope requirement for 3.5-inch hard disk drive
/ 16

Figure 1-4 Pinout of FPU/ROM connector / 22

Figure 1-5 Design guide for an FPU/ROM card / 25

Table 1-1 Memory map summary / 8

Table 1-2 ROM address allocations / 9

Table 1-3 Serial port pinout / 14

Table 1-4 Pinouts for internal and external SCSI connectors / 15

Table 1-5 Pinout for internal floppy disk connector / 17

Table 1-6 Pinout for external floppy disk connector / 18

Table 1-7 ADB connector pinout / 19

Table 1-8 Signals on the FPU/ROM connector / 23