

Table 1. IOTracer Version 6.0 Record Formats

<i>field</i>	1	2	3	4	filler	5	6	7	8	9
<i>length</i>	4B (long)	1B (byte)	1B (byte)	4B (long)	2B	4B (long)	4B (long)	4B (long)	4B (long)	4B (long)
<i>offset</i>	0B	4B	5B	6B	—	12B	16B	20B	24B	28B
<i>Record Class 1:</i> <b>Open</b> <b>OpenRF</b> <b>Async Open</b>	start time	<i>type:</i> 0x80 0x84 0xC0	unused	end time	unused	unused	file number	name (0-3)	name (4-7)	name (8-11)
<i>Record Class 2:</i> <b>Read</b> <b>Write</b> <b>Async Read</b> <b>Async Write</b>	start time	<i>type:</i> 0x82 0x83 0xC2 0xC3	unused	end time	unused	unused	file number	no. bytes	unused	unused
<i>Record Class 3:</i> <b>Close</b> <b>Async Close</b>	start time	<i>type:</i> 0x81 0xC1	unused	end time	unused	unused	file number	unused	unused	unused
<i>Record Class 4:</i> <b>Allocate</b> <b>Close Resource</b>	start time	<i>type:</i> 0x85 0xA2	unused	unused	unused	return address	file number	unused	unused	unused
<i>Record Class 5:</i> <b>GetFileInfo</b>	start time	<i>type:</i> 0x87	unused	end time	unused	return address	unused	name (0-3)	name (4-7)	name (8-11)
<i>Record Class 6:</i> <b>Delete</b> <b>Create</b> <b>CreateResFile</b> <b>OpenResFile</b>	start time	<i>type:</i> 0x86 0x88 0xA0 0xA1	unused	unused	unused	return address	unused	name (0-3)	name (4-7)	name (8-11)
<i>Record Class 7:</i> <b>Load Resource</b>	start time	<i>type:</i> 0xA5	unused	unused	unused	return address	unused	unused	unused	unused

	<i>field</i>	1	2	3	4	filler	5	6	7	8	9
	<i>length</i>	4B (long)	1B (byte)	1B (byte)	4B (long)	2B	4B (long)	4B (long)	4B (long)	4B (long)	4B (long)
	<i>offset</i>	0B	4B	5B	6B	—	12B	16B	20B	24B	28B
<i>Record Class 8:</i>											
	<b>GetNamedRes.</b>	start time	<i>type:</i> 0xA4	unused	unused	unused	return address	unused	resource type	unused	unused
<i>Record Class 9:</i>											
	<b>Get Resource GetIndRes.</b>	start time	<i>type:</i> 0xA3 0xA6	unused	unused	unused	return address	unused	resource type	resource id	unused