

TECHNOTE 1086

Power Management & The Energy Saver API

CONTENTS

[Energy Saver Overview](#)

[Energy Services Access](#)

[Energy Services API](#)

[The ESGlobals Structure](#)

[ESLoadPreferences](#)

[ESGetPreferences](#)

[ESSetPreferences](#)

[ESRefreshSettings](#)

[ESSavePreferences](#)

[ESAddNoteProc](#)

[ESRemoveNoteProc](#)

[Energy Saver Notification
Function](#)

[ESRestoreDefaults](#)

[ESGetUnsavedFolder](#)

[ESSetUnsavedFolder](#)

[ESGetINITVersion](#)

[Summary](#)

In an effort to provide a consistent method of controlling the various power conservation hardware and software features implemented on the Macintosh platform, Apple has introduced the Energy Saver system.

In addition to providing developers with a standard way to control power management features such as display sleep/dimming, hard drive spindown, idle shutdown or sleep, the Energy Services API also provides a consistent way to synchronize the Human Interfaces for multiple concurrent applications that need to access these features.

This Note discusses how to communicate with the Macintosh Energy Saver Extension through the Energy Services API and is important for developers who wish to access Mac OS power management features from their applications.

This Note also includes the public interfaces for the Energy Services API.

Energy Saver Overview

Energy Saver provides a consistent method of controlling the various power conservation hardware and software features implemented on the Macintosh platform.

Although the features it supports vary depending on the machines' capabilities, Energy Saver typically attempts to reduce power consumption by controlling such operations as:

- **Display Sleep/Dimming** - by reducing the power requirements to the display monitor.
- **Hard Drive Spindown** - by reducing power by spinning down (removing power) the hard disk drive spindle motor.

- **Idle Shutdown** - by programatically turning off power to the computer without losing any data.
- **Idle Sleep** - Enter a reduced power requirement state from which rapid recovery can be made when waking up. Note that the sleep state differs according to the hardware capabilities present in the machine.
- **Scheduled Startup/Shutdown** - Scheduled startup is used to restart the system at a predetermined time. When used in conjunction with scheduled shutdown, document autosave, and bookmarking, these can offer a substantial savings in energy requirements while providing a convenient means of restarting the system.
- **Document AutoSave** - Document autosave provides the means to automatically save open untitled or unsaved documents at system shutdown time without requiring user intervention or confirmation.
- **Wakeup Sound**- A user-configurable sound to be played when the system is waking up from sleep mode. Since the monitor is typically dimmed, the wake-up sound is the only means of determining if the system is currently active.

Even though the majority of action is handled by either the Mac OS Power Manager or various Macintosh power conservation hardware, the Energy Saver is the method used to provide the user with a mechanism for determining when and how the various actions are to occur.


The Energy Services API also provides a way to synchronize the Human Interfaces for multiple concurrent applications that need to access the power management features.

Components of the Energy Saver

Energy Saver is actually composed of two separate components: a system extension and a control panel.

- **Control panel** - The control panel manipulates the settings that are stored in system memory and a preference file.
- **Energy Saver Extension** - The extension uses the settings stored in the preference file to direct desired energy-saving behavior.

Figure 1 provides an overview of the Energy Saver components.

**FIGURE 1. Energy Saver Overview****Note:**

The Energy Saver control panel is not really a control panel. It is an application with a special signature of 'APPC', which, to the Finder in systems after Systems 7.5.2, is used to allow applications dropped on the System Folder to be automatically placed into the Control Panel.

This allows the developer to construct control panels in the same manner as an application but permits the Finder to do its auto-placement function.

Energy Services Access

Applications can safely use the same mechanism to manipulate the Energy Saver preference file as the Energy Saver control panel. This is accomplished through the Energy Services API. The purpose of this API is to provide homogenous support for high-level power management features that are not provided by the Power Manager, as well as provide standardized preference support for power manager functions that do not have persistent PRAM settings.

The Energy Saver Extension provides auto power on/off features for all Macs with an Egret or Cuda microcontrollers. In addition, it will manage preferences for Screen dimming, Hard disk spin down, sleep mode, and options for all these features. There are calls that can be used to obtain and set the preferences, as well as calls to activate the settings in the preferences passed.

Whenever possible, application developers should use this functionality instead of creating their own from scratch, at least to the extent of updating the preferences, so that other applications and control panels will reflect user choices made in all applications.

Determining If Your Mac Supports the Energy Services API

The proper way to determine if a particular Macintosh model supports the Energy Services API is to use the Gestalt function to check for the '**wnkl**' selector, then check the response for non-nil value. This will indicate that the Energy Services API is loaded.

[illegible]

```
// The following fields let you specify different times of the day
// for startup and shutdown for each individual day.  If you are not
// going to allow specific daily schedules. then set all WU's to
// mainWUTime and all SD fields to mainSDTime.

// Shutdown Time
    unsigned long    SDMonTime;
    unsigned long    SDTueTime;
    unsigned long    SDWedTime;
    unsigned long    SDThuTime;
    unsigned long    SDFriTime;
    unsigned long    SDSatTime;
    unsigned long    SDSunTime;

// Wakeup Time
    unsigned long    WUMonTime;
    unsigned long    WUTueTime;
    unsigned long    WUWedTime;
    unsigned long    WUThuTime;
    unsigned long    WUFriTime;
    unsigned long    WUSatTime;
    unsigned long    WUSunTime;

// Sleep Prefs Info stuff
    short            reserved3;
    short            WUSoundResID;        // ID of the 'snd ' to play on wakeup
    short            reserved4;

// Startup Prefs Info
    short            reserved5;
    short            AppFlags;            // Always set to 0 in new pref file.
    short            NonComplianceFlag;    // Set if machine sleeps over 30 watts

// Shutdown Prefs Info
    short            SDIdleTime;
    short            SDNotifyFlags;        // Notification Options
                                           // 0020 = Notify on Shutdown
                                           // 0001 = Blinking icon
                                           // 0002 = Text message
                                           // 0004 = Play snd
                                           // 0008 = save files
                                           // 8008 = Dont save on sleep

                                           // 0400 = Play snd on Wakeup
                                           // 0800 = Wakeup on Ring detect
                                           // 1000 = Blink pwr light (portables)
                                           // 2000 = mute sounds when asleep

    short            SDNotifyDelayTime;
    short            SDSoundResID;
// ID of the 'snd ' to play on Shutdown
    short            reserved6;
    short            reserved7;

// Energy Saver General prefs info
    long             reserved8;
    Boolean           reserved9;

} ESGlobals, *ESGlobalsPtr, **ESGlobalsHand;
```

ESLoadPreferences

ESLoadPreferences reloads the current settings from the preferences file and updates the Energy Services Globals. It also returns a copy of the settings for your use.

PROTOTYPE

```
OSErr ESLoadPreferences(ESGlobalsPtr thePrefs);
```

thePrefs A pointer to the ESGlobals structure

RESULT CODE

File Read Errors, Memory Errors, ES Errors

IMPORTANT

This is called by the Energy Saver Extension at system startup time. Your application should never have to make this call unless you intend to revert back to the saved preference settings.

ESLoadPreferences will not update the state of the machine. After making this call, you need to call `ESRefreshSettings()` in order to make the read in settings take effect.

ESGetPreferences

ESGetPreferences returns a copy of the current settings for your use. This is the normal call an application will make to get the current user settings for all the energy services information.

PROTOTYPE

```
OSErr ESGetPreferences(ESGlobalsPtr thePrefs);
```

thePrefs A pointer to the ESGlobals structure

RESULT CODE

Memory Errors, ES Errors

ESSetPreferences

ESSetPreferences copies the passed settings to the Energy Services globals.

PROTOTYPE

```
OSErr ESSetPreferences(ESGlobalsPtr thePrefs);
```

thePrefs A pointer to the ESGlobals structure

RESULT CODE

Memory Errors, ES Errors

IMPORTANT

ESSetPreferences will NOT call the Power Manager to make the settings effective, nor will it set new startup and shutdown times. After making this call, you need to call `ESRefreshSettings()` to cause the new settings to take effect.

ESRefreshSettings

ESRefreshSettings will cause the current settings to be activated and will make all necessary power manager calls to cause them to be active. In addition, it will install whatever startup and shutdown tasks need to be installed to act on the current set of notifications.

PROTOTYPE

```
OSErr ESRefreshSettings();
```

RESULT CODE

ES Errors

ESSavePreferences

ESSavePreferences performs three operations: it calls ESSetPreferences() to transfer the passed settings, then ESRefreshSettings() to make them active, and lastly it saves the settings out to the preferences file so they remain consistent over boots. This is the normal call an application will make when it wants to make a persistent update to the Energy services settings.

PROTOTYPE

```
OSErr ESSavePreferences(ESGlobalsPtr thePrefs);
```

thePrefs A pointer to the ESGlobals structure

RESULT CODE

File Errors, Memory Errors, ES Errors

IMPORTANT

When specifying **snd** resources in the WUSoundResID or SDSoundResID field of ESGlobals record, you should ensure that those resources are in the current resource chain. This is important because ESSavePreferences will cause them to be loaded, detached and copied into System Heap.

ESAddNoteProc

You can use the ESAddNoteProc to install an Energy Saver notification response procedure. This notifier can be used to inform your application that the energy saver prefs are being read or written.

PROTOTYPE

```
OSErr ESAddNoteProc(ESNotifyProcPtr theProc, long data);
```

theProc A pointer to a notification response procedure

data A user defined ref to pass to the data procedure

RESULT CODE

ES Errors

SEE ALSO

The Energy Saver Notification and ESRemoveNoteProc function.

ESRemoveNoteProc

You can use the `ESRemoveNoteProc` to remove an Energy Saver notification response procedure.

PROTOTYPE

```
OSErr ESRemoveNoteProc(ESNotifyProcPtr theProc);
```

`theProc` A pointer to a notification response procedure

RESULT CODE

ES Errors

SEE ALSO

The Energy Saver Notification and `ESAddNoteProc` function.

Energy Saver Notification Function

Once installed by the `ESAddNoteProc` function, your notification procedure will be called when any application attempts to access the ES prefs.

The notifier will be called with the selector `xNoteESDataReq` whenever the Energy Saver prefs are being read but before the application is returned to them.

You are also called when someone copies new prefs to the Energy Saver Extension with a `xNoteNewESData` selector. You then get a chance to change the data that they have copied Globals, but you get to it before it is applied.

This allows your application to dynamically update the display of the `ESGlobals` or to filter data values.

PROTOTYPE

```
pascal long MyESNotifyProc (short selector, ESGlobalsPtr theData);
```

`selector` A value indicating the type of activity that has occurred. See the description below for the meaning of this field.

`thePrefs` A pointer to the `ESGlobals` structure

DESCRIPTION

The valid types of activity are:

Value name	Value	Description
<code>xNoteNewESData</code>	1	New <code>ESGlobals</code> written out.
<code>xNoteESDataReq</code>	2	<code>ESGlobals</code> are being requested.

ESRestoreDefaults

ESRestoreDefaults is used to restore the system to the machine-dependent default settings as stored in the extension resource data. Use this call whenever you want to return the Energy Saver back to the installed default settings.

You also get a copy of the ESGlobals so that you can see what those defaults are. Getting the ESGlobals is convenient so that you can update your HI to reflect the current machine state.

One possible use for this is in response to a "Apple Defaults" menu item.

PROTOTYPE

```
OSErr ESRestoreDefaults(ESGlobalsPtr thePrefs);
```

thePrefs A pointer to the ESGlobals structure

RESULT CODE

Memory Errors, ES Errors

ESGetUnsavedFolder

This call is used to retrieve the pathname of the Unsaved Document folder used by the Autosave feature.

PROTOTYPE

```
OSErr ESGetUnsavedFolder(Ptr theString);
```

theString A pointer to a string into which the current pathname of the unsaved document folder will be copied.

RESULT CODE

Memory Errors, ES Errors

ESSetUnsavedFolder

You can use the ESetUnsavedFolder to set the pathname of the Unsaved Document folder used by the Autosave feature.

PROTOTYPE

```
OSErr ESetUnsavedFolder(Ptr theString);
```

theString A pointer to a string which contains the pathname of the unsaved document folder to be used.

RESULT CODE

Memory Errors, ES Errors

ESGetINITVersion

This call is used to retrieve the current version number of the installed Energy Saver extension file. Use this call to verify that the correct version of the Energy Saver extension is being used.

PROTOTYPE

```
OSErr ESGetINITVersion(Handle* theVers);
```

theVers A pointer to the version structure

RESULT CODE

ES Errors

Summary

As the Macintosh platform continues to evolve, the Energy Saver API provides a consistent method of monitoring and controlling power management features. In addition, the Energy Saver API also presents a few interesting opportunities for third-party developer applications.

Further References

- [Inside Macintosh: Devices, Chapter 6, Power Manager Reference](#)
- [Technote 1046: Inside Macintosh: Devices, Power Manager Addenda](#)
- [Technote 1079: Power Management & Servers: Auto Restart From Power Failure](#)

Downloadables



[Acrobat version of this Note \(180K\)](#)



[inhexed version of the Energy Services API files \(38K\)](#)

To contact us, please use the [Contact Us](#) page.
Updated: 20-Dec-96

[Technotes](#)
[Previous Technote](#) | [Contents](#) | [Next Technote](#)