

DAYTime

Inherits From: Object
Conforms To: NXTransport
Declared In: daymisckit/DAYTime.h

Class Description

This documentation is still incomplete, and the class itself is only halfway implemented (no day of week or customized stringValues). Sorry.

DAYTime is used to store a time, accurate from years down to seconds. You can add and subtract DAYTimes from each other and specify how to generate a string value for the time. It can calculate the day of the week for a given date, as well. If used to measure time in a relative sense, then the day of week functions are disabled since they don't make sense semantically. A DAYTime object may easily be initialized or set to the current time on the system clock. It may also be sent bycopy over a distributed objects link and archived to a file.

Instance Variables

BOOL **isRelative**;
long **microsecond**;
long **second**;
long **minute**;
long **hour**;
long **dow**;
long **day**;
long **month**;
long **year**;

isRelative

Whether the DAYTime object is an absolute or relative time.

microsecond

The microsecond (0 ± 999,999).

second

The second (0 ± 59).

minute

The minute (0 ± 59).

hour

The hour (0 ± 23).

dow

The day of the week (-1 ± 6). dow is -1 if the day of the week is unknown; for example, if it has not yet been calculated.

day

The day of the month (0 ± 27/28/29/30).

month

The month (0 ± 11).

year

The year.

Method Types

Initializing and freeing a DAYTime ± init
± initWithCurrentTime

Changing a DAYTime ± setDay:
± setDayOfWeek:
± setHour:
± setMicrosecond:
± setMinute:
± setMonth:
± setRelative:
± setSecond:
± setYear:

Manipulating a DAYTime ± addDays:
± addHours:
± addMicroseconds:
± addMinutes:
± addMonths:
± addSeconds:
± addTime:
± addYears:

- ± calcDayOfWeek
- ± subtractDays:
- ± subtractHours:
- ± subtractMicroseconds:
- ± subtractMinutes:
- ± subtractMonths:
- ± subtractSeconds:
- ± subtractTime:
- ± subtractYears:

Querying attributes

- ± day
- ± dayOfWeek
- ± doubleValue
- ± floatValue
- ± hour
- ± intValue
- ± isRelative
- ± microsecond
- ± minute
- ± month
- ± second
- ± stringValue
- ± year

Archiving

- ± read:
- ± write:

Instance Methods

x

- **x:(x)x**

x. Returns *self*.

See also: **-x:**

x

- **x:(x)x**

x. Returns *self*.

See also: **-x:**