

MATERIAL SAFETY DATA SHEET

COATINGS AND RESINS GROUP

PPG Industries, Inc.

SECTION 1 - CHEMICAL, PRODUCT, AND COMPANY INFORMATION

PRODUCT CODE/IDENTITY: 97-675

REVISION DATE: 11/21/96 (001) 0814

CUSTOMER PART #/NAME: Not applicable

PRODUCT TRADE NAME: METALHIDE 1001 ZINC DUST GREEN

CHEMICAL FAMILY: PIGMENT

EMERGENCY MEDICAL/SPILL INFO: (304) 843-1300 (U.S.) 91-800-00-214 (MEXICO)

TECHNICAL INFORMATION: 1-800-441-9695

PRODUCT SAFETY/MSDS INFORMATION: 4325 ROSANNA DRIVE, P.O. BOX 9 ALLISON PARK, PA 15101 (412) 492-5555

DATE OF MSDS PREPARATION: 01/10/00

PRIMARY HAZARD WARNING

There are no hazardous ingredients in this product as defined by the OSHA Hazard Communication Standard.

THIS MATERIAL SAFETY DATA SHEET HAS BEEN PREPARED IN ACCORDANCE WITH THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200), THE SUPPLIER NOTIFICATION REQUIREMENTS OF SARA TITLE III, SECTION 313, AND OTHER APPLICABLE RIGHT-TO-KNOW REGULATIONS.

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

There are no hazardous ingredients in this product as defined by the OSHA Hazard Communication Standard.

PRODUCT STATUS RELATIVE TO THE U.S. EPA TOXIC SUBSTANCES CONTROL ACT

All chemical substances in this product are listed on the U.S. TSCA Inventory or are otherwise exempt from TSCA Inventory reporting requirements.

SECTION 3 - HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE FROM:

INGESTION: May be harmful if swallowed.

EYE CONTACT: Causes eye irritation.

SKIN CONTACT: May cause slight skin irritation.

INHALATION: Dust may be harmful if inhaled. Dust irritates eyes, nose and throat.

CHRONIC OVEREXPOSURE: Not applicable

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Redness, itching, burning sensation and visual disturbances may indicate excessive eye contact. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Not applicable.

SECTION 4 - FIRST AID MEASURES

INGESTION: If swallowed, do not induce vomiting. Gently wipe out inside mouth to remove any residual material.

EYE CONTACT: In case of eye contact, remove contact lenses and flush eyes immediately with a gentle stream of luke warm water for at least 15 minutes.

SKIN CONTACT: In case of skin contact, flush immediately with plenty of water for at least 15 minutes followed by washing with soap and water.

INHALATION: If affected by inhalation of dust, remove to fresh air. Apply artificial respiration and other support measures as required.

OTHER: If ingestion, any type of overexposure or symptoms of overexposure occur during or following the use of this product, contact a poison control center, emergency room or physician immediately; have Material Safety Data Sheet information available.

SECTION 5 - FIRE FIGHTING MEASURES

FLASHPOINT: Not applicable

FLAMMABLE LIMITS: Lower explosion limit (LEL): Not available

Upper explosion limit (UEL): Not available

EXTINGUISHING MEDIA: Use National Fire Protection Association (NFPA) Class D extinguishers designed to extinguish metal fires.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Contact with moisture or acids may produce hydrogen gas. Dust can form explosive mixture in air.

SPECIAL FIRE FIGHTING PROCEDURES: Smother fire with suitable dry powder. Wear NIOSH approved self-contained breathing apparatus. Do not use water or liquid extinguishing agents.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Return material to container.

WASTE DISPOSAL METHOD: Waste material must be disposed of in accordance with

federal, state, provincial, and local environmental control regulations. Empty containers should be recycled or disposed of through an approved waste management facility.

SECTION 7 - HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Avoid exposure to dampness in storage.

OTHER PRECAUTIONS: Store in cool dry place. Keep tightly sealed when not in use.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT FOR:

EYE PROTECTION: Wear sufficient eye protection to prevent contact with powdered materials.

SKIN PROTECTION: This coating does not pose a skin absorption hazard. Gloves selection should be based on the work task to prevent skin irritation.

RESPIRATORY PROTECTION: Use an appropriate NIOSH-approved particulate filter respirator. Read the respirator manufacturer's instructions and literature carefully to determine the type of airborne contaminants against which the respirator is effective, its limitations, and how it is to be properly fitted and used.

OTHER EQUIPMENT: Clean contaminated clothing and shoes.

VENTILATION REQUIREMENTS: Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients in Section 2 below the lowest suggested exposure limit, and LEL below stated limit, as appropriate.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

[FORMULA VALUES, NOT SALES SPECIFICATIONS]

BOILING RANGE: Not applicable

SOLUBILITY IN WATER: .0 %

VAPOR PRESSURE: N.A. mmHg

WEIGHT/GALLON (LBS): 58.58 (U.S.)

VAPOR DENSITY: Not applicable

pH: Not applicable

% VOLATILE/VOLUME: .010

% SOLIDS BY WEIGHT: 100.00

SPECIFIC GRAVITY: 7.030

EVAPORATION RATE(BuOAc=100): 0

ODOR/APPEARANCE: Non-viscous liquid with an odor characteristic of the ingredients listed in Section 2.

SECTION 10 - STABILITY AND REACTIVITY

This product is normally stable but may undergo hazardous reactions at extremely high temperatures and pressures.

INCOMPATIBILITY (MATERIALS AND CONDITIONS TO AVOID): High concentrations of airborne dust may ignite explosively. All ignition sources should be eliminated when this product is dispersed in air. Avoid contact with moisture, water, high humidity, and acids.

HAZARDOUS DECOMPOSITION PRODUCTS: May produce the following hazardous decomposition products when exposed to extreme heat: oxides of zinc ; Extreme heat includes, but is not limited to, flame cutting, brazing, and welding.

Hazardous Materials Identification System (HMIS) and National Fire Protection Association (NFPA) Ratings:

HMIS Rating		NFPA Rating	
HEALTH	1	HEALTH	1
FLAMMABILITY	1(a)	FLAMMABILITY	1(a)
REACTIVITY	1	INSTABILITY	1

Rating System:0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe, *=Chronic Effects.

(a) The flammability rating printed above applies to this product during normal transportation and storage. However, theoretically, this product can form explosive mixtures at high concentrations of airborne dust. Per NFPA 704 (1996 edition) criteria, such products would be assigned a "flammability" hazard rating of "3" if they are "readily dispersed in air".

Safe handling of this product requires that all of the information on the MSDS be evaluated for specific work environments and conditions of use.

THIS IS THE END OF THE MSDS FOR: 97-675 (00057697.00997-675)

Manufactured and Supplied by:

PPG INDUSTRIES, EAST POINT

1377 OAKLEIGH DRIVE

EAST POINT, GA 30344