



ALDON CORPORATION

MATERIAL SAFETY DATA SHEET

1533 W. Henrietta Rd.
Avon, New York 14414
(716) 226-6177

MSDS No. PP 235
Effective Date April 13, 1999

SECTION V HEALTH HAZARD DATA

PP 235

Threshold Limited Value None established for this mixture (ACGIH 1992-93).

Effects of Overexposure Specific data is not available. This compound is considered to be of low hazard by ingestion or by contact. Exercise appropriate procedures to minimize potential hazards.

Emergency and First Aid Procedures
EYES: Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get medical attention. **SKIN:** Flush thoroughly with water, then wash with mild soap and water. **INGESTION:** If swallowed, if conscious, give one or two glasses of water to drink, induce vomiting and call physician. Never give anything by mouth to an unconscious person.

SECTION VI REACTIVITY DATA

Stability	Unstable		Conditions to Avoid	Excessive temperature and heat.
	Stable	X		

Incompatibility (Materials to Avoid) None known.

Hazardous Decomposition Products Thermal decomposition or burning may produce oxides of phosphorous (PO_x).

Hazardous Polymerization	Conditions to Avoid		Not applicable.
	May Occur	Will Not Occur	
		X	

SECTION VII SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled Flush to sewer with copious amounts of water. Wash spill area with soap and water.

Waste Disposal Method Discharge, treatment, or disposal may be subject to Federal, State or Local laws. These disposal guidelines are intended for the disposal of catalog-size quantities only.

Flush to sewer with copious amounts of water.

SECTION VIII SPECIAL PROTECTION INFORMATION

Respiration Protection (Specify Type) None needed in normal laboratory handling. If misty conditions prevail, work in a ventilation hood or wear a NIOSH/MSHA-approved respirator.

Ventilation	Local Exhaust	None needed.	Special	No.
	Mechanical (General)	None needed.	Other	No.

Protective Gloves Rubber for repeated exposure. **Eye Protection** Chemical safety glasses.

Other Protective Equipment Lab coat, eye wash station, proper gloves.

SECTION IX SPECIAL PRECAUTIONS

Precautions to be Taken in Handling & Storing Store in a cool place. Wash thoroughly after handling. Keep container tightly closed when not in use.

Other Precautions Read label on container before using. Do not wear contact lenses when working with chemicals. Remove and wash contaminated clothing.

For laboratory use only. Not for drug, food or household use. Keep out of reach of children.

Revision No. 3	Date 4/13/99	Approved Michael Raszeja	Chemical Safety Coordinator MR
-----------------------	---------------------	---------------------------------	---------------------------------------

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. * Hazardous Materials Industrial Standards. Printed on recycled paper.

SECTION I NAME 24 HOUR EMERGENCY ASSISTANCE

Product	PHOSPHATE BUFFER 0.1 MOLAR SOL'N	 CHEMTREC 800-424-9300 Day 716-226-6177 NFPA HAZARD RATING LEAST SLIGHT MODERATE HIGH EXTREME 0 1 2 3 4	Health	0
Chemical Synonyms	Phosphate Buffer Solution, pH 6.5		Fire	0
Formula	Mixture. See Section II.		Reactivity	0
Unit Size	up to 3.785 Lt.		HMIS *	
C.A.S. No.	Mixture. See Section II.			

SECTION II INGREDIENTS OF MIXTURES

Principal Component(s)	%	TLV Units
Potassium Phosphate, Monobasic: (CAS No. 7778-77-0)	13.6% (w/v)	None established.
Potassium Phosphate, Dibasic: (CAS No. 7758-11-4)	17.4% (w/v)	None established.
Water: (CAS No. 7732-18-5)	69%	None established.

CAUTION! MAY BE HARMFUL IF SWALLOWED. AVOID CONTACT WITH SKIN AND EYES.

SECTION III PHYSICAL DATA

Melting Point (°F)	Freezes below 0°C (32°F)	Specific Gravity (H₂O = 1)	Approx. 1.1
Boiling Point (°F)	Above 100°C (212°F)	Percent Volatile by Volume (%)	69%
Vapor Pressure (mm Hg)	14 (water).	Evaporation Rate (Water = 1)	< 1
Vapor Density (Air=1)	0.7 (water).		
Solubility in Water	Complete.		
Appearance & Odor	Clear, water white, water solution; no odor.		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used)	Non-flammable.	Flammable Limits in Air % by Volume	NA	Lower	Upper
				-----	-----

Extinguisher Media Use any media suitable for extinguishing supporting fire.

SPECIAL FIREFIGHTING PROCEDURES

Non-flammable. In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Fire or excessive heat may produce hazardous decomposition products.

D.O.T. **NON-REGULATED.**

Approved by U.S. Department of Labor "essentially similar" to form OSHA-20