



ALDON CORPORATION

MATERIAL SAFETY DATA SHEET

1533 W. Henrietta Rd.
Avon, New York 14414
(716) 226-6177

MSDS No. AA 203
Effective Date March 16, 1999

SECTION V HEALTH HAZARD DATA

AA 203

Threshold Limited Value

None established for this mixture.

Effects of Overexposure

May be harmful by ingestion. May cause irritation. To the best of our knowledge, the chemical, physical and toxicological properties have not been thoroughly investigated. Specific data is not available. Exercise appropriate procedures to minimize potential hazards.

Emergency and First Aid Procedures

INGESTION: If swallowed, if conscious, give one or two glasses of water to drink, induce vomiting and call a physician. Never give anything by mouth to an unconscious person. **SKIN:** Flush with water, then wash with mild soap and water. **EYES:** Flush thoroughly with water, lifting upper and lower eyelids occasionally. If irritation develops or persists, get medical attention. **INHALATION AS MIST:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

SECTION VI REACTIVITY DATA

Stability	Unstable	Conditions to Avoid
	Stable	X Excessive temperatures to cause evaporation.

Incompatibility (Materials to Avoid)	Alkalies and water-reactive materials such as oleum: causes exothermic reactions.
--------------------------------------	---

Hazardous Decomposition Products	At temperatures above 760°C (1400°F), yield sulfur oxide gases (SO _x).
----------------------------------	--

Hazardous Polymerization		Conditions to Avoid
May Occur	Will Not Occur	Not applicable.
	X	

SECTION VII SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled	Small spills may be flushed to sewer with copious amounts of water.
---	---

Waste Disposal Method	Discharge, treatment, or disposal may be subject to Federal, State or Local laws. These disposal guidelines are intended for the disposal of catalog-size quantities only.
-----------------------	--

Dissolve in water and flush to sewer with copious amounts of water.

SECTION VIII SPECIAL PROTECTION INFORMATION

Respiration Protection (Specify Type)		None needed in normal laboratory handling. If misty conditions prevail, work in ventilation hood or wear a NIOSH/MSHA-approved dust mask.			
Ventilation	Local Exhaust	Not required.	Special	No.	
	Mechanical (General)	Not required.	Other	No.	

Protective Gloves	Rubber.	Eye Protection	Chemical safety glasses.
-------------------	---------	----------------	--------------------------

Other Protective Equipment	Goggles, lab coat, proper gloves, eye wash station.
----------------------------	---

SECTION IX SPECIAL PRECAUTIONS

Precautions to be Taken in Handling & Storing	Store in a cool, dry place. Wash thoroughly after handling. Keep container tightly closed when not in use.
---	---

Other Precautions	Read label on container before using. Do not wear contact lenses when working with chemicals. Avoid contact with eyes, skin, and mucous membranes. Remove and wash contaminated clothing.
-------------------	---

For laboratory use only. Not for drug, food or household use. Keep out of reach of children.

Revision	No. 1	Date	3/16/99	Approved	Michael Raszeja	Chemical Safety Coordinator	MR
The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. * Hazardous Materials Industrial Standards. Printed on recycled paper.							

SECTION I NAME 24 HOUR EMERGENCY ASSISTANCE

Product	ALUMINUM SULFATE 50% SOLUTION	 CHEMTREC 800-424-9300 Day 716-226-6177 NFPA HAZARD RATING LEAST SLIGHT MODERATE HIGH EXTREME 0 1 2 3 4 HMIS * 0 1 2 3 4
Chemical Synonyms	Aluminium Sulfate Aqueous Solution	
Formula	Mixture.	
Unit Size	up to 55 gal.	
C.A.S. No.	Mixture.	

SECTION II INGREDIENTS OF MIXTURES

Principal Component(s)	%	TLV Units
Aluminum Sulfate: (CAS No. 10043-01-3)	50%	None established.
Water: (CAS No. 7732-18-5)	50%	None established.

CAUTION! MAY BE HARMFUL IF SWALLOWED.

SECTION III PHYSICAL DATA

Melting Point (°F)	Freezes approx. 0°C (32°F)	Specific Gravity (H ₂ O = 1)	Approx. 1.0
Boiling Point (°F)	Approx. 100°C (212°F)	Percent Volatile by Volume (%)	50%
Vapor Pressure (mm Hg)	14 (water).	Evaporation Rate (Water = 1)	Slightly < 1
Vapor Density (Air=1)	0.7 (water).		
Solubility in Water	Complete.		
Appearance & Odor	Clear, water white liquid; no odor.		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used)	Non-flammable.	Flammable Limits in Air % by Volume	N/A	Lower	Upper
Extinguisher Media	Use any media suitable for extinguishing supporting fire.				

SPECIAL FIREFIGHTING PROCEDURES

In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

UNUSUAL FIRE AND EXPLOSION HAZARDS

In fire conditions, water may evaporate from this solution, which may cause hazardous decomposition products to be produced as dust or fume.

D.O.T. NON-REGULATED.

Approved by U.S. Department of Labor "essentially similar" to form OSHA-20