



ALDON CORPORATION

MATERIAL SAFETY DATA SHEET

1533 W. Henrietta Rd.
Avon, New York 14414
(716) 226-6177

MSDS No. AA 385
Effective Date April 14, 1999

SECTION V HEALTH HAZARD DATA

Threshold Limited Value None established.

Effects of Overexposure May cause irritation to eyes. Repeated or prolonged contact with skin may cause irritation. To the best of our knowledge, the chemical, physical and toxicological properties have not been thoroughly investigated. Specific data is not available. Exercise appropriate procedures to minimize potential hazards.

Emergency and First Aid Procedures
EYES: Flush thoroughly with water for 15 minutes, lifting upper and lower eyelids occasionally. If irritation develops or persists, get medical attention. **SKIN:** Flush thoroughly with soap and water. If irritation occurs, get medical attention. **INGESTION:** If conscious, rinse mouth with water. Call physician immediately. Never give anything by mouth to an unconscious person. **INHALATION:** Remove to fresh air.

SECTION VI REACTIVITY DATA

Stability
Unstable
Stable X
Conditions to Avoid Excessive temperature and heat to cause evaporation.

Incompatibility (Materials to Avoid) Avoid mixing with acids, oxidizing materials.

Hazardous Decomposition Products May produce hazardous decomposition products of Carbon monoxide, Carbon dioxide and silicon dioxide.

Hazardous Polymerization
May Occur Will Not Occur X
Conditions to Avoid Not Applicable.

SECTION VII SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled Ventilate area. Absorb spill with vermiculite, sand, earth, paper towels. Place in suitable container for proper disposal. Wash spill area with soap and water.

Waste Disposal Method Discharge, treatment, or disposal may be subject to Federal, State or Local laws. These disposal guidelines are intended for the disposal of catalog-size quantities only.
Dispose of in an approved chemical landfill or contract with a licensed waste disposal service.

SECTION VIII SPECIAL PROTECTION INFORMATION

Respiration Protection (Specify Type) If misty conditions prevail, work in ventilation hood or wear a NIOSH/MSHA approved respirator.

Ventilation
Local Exhaust None required Special No
Mechanical (General) None required Other No

Protective Gloves Rubber **Eye Protection** Chemical Safety Glasses

Other Protective Equipment Apron, lab coat, eye wash station.

SECTION IX SPECIAL PRECAUTIONS

Precautions to be Taken in Handling & Storing Store in a cool, dry area. Wash thoroughly after handling.
Keep container tightly closed when not in use.

Other Precautions Read label on container before using. Do not wear contact lenses when working with chemicals.
Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Remove and wash contaminated clothing.

For laboratory use only. Not for drug, food or household use. Keep out of reach of children.

Revision 1 Date 4/14/99 Approved Michael Raszeja Chemical Safety Coordinator MR

The information contained herein is furnished without warranty of any kind. Employees should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. * Hazardous Materials Industrial Standards. Printed on recycled paper.

SECTION I NAME 24 HOUR EMERGENCY ASSISTANCE

Product	ANTI-STATIC FLUID	 CHEMTREC 800-424-9300 Day 716-226-6177 NFPA HAZARD RATING LEAST SLIGHT MODERATE HIGH EXTREME 0 1 2 3 4 HMIS * HEALTH FIRE REACTIVITY 1 0 0
Chemical Synonyms	N/A	
Formula	Mixture	
Unit Size	up to 55 gal.	
C.A.S. No.	Mixture	

SECTION II INGREDIENTS OF MIXTURES

Principal Component(s)	%	TLV Units
DOW Silicone Emulsion 24: (CAS No. 63148-62-9)	< 1%	None established
Water: (CAS No. 7732-18-5)	> 99%	None established

CAUTION! HARMFUL IF SWALLOWED. MAY CAUSE SKIN AND EYE IRRITATION.

SECTION III PHYSICAL DATA

Melting Point (°F)	Aprox. 0°C (32°F)	Specific Gravity (H ₂ O = 1)	> 1
Boiling Point (°F)	Approx. 100°C (212°F)	Percent Volatile by Volume (%)	> 99%
Vapor Pressure (mm Hg)	14 (water)	Evaporation Rate (=1)	N/A
Vapor Density (Air=1)	0.7 (water)		
Solubility in Water	Soluble		
Appearance & Odor	Colorless liquid; faint odor.		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used)	Non-Flammable	Flammable Limits in Air % by Volume	Lower	Upper
----------------------------------	---------------	--	-------	-------

Extinguisher Media Use any media suitable for extinguishing supporting fire.

SPECIAL FIREFIGHTING PROCEDURES

In fire conditions, wear a NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS

None known.

D.O.T. Non-Regulated.

Approved by U.S. Department of Labor "essentially similar" to form OSHA-20