



ALDON CORPORATION

MATERIAL SAFETY DATA SHEET

1533 W. Henrietta Rd.
Avon, New York 14414
(716) 226-6177

MSDS No. CC 353
Effective Date January 22, 1999

SECTION V HEALTH HAZARD DATA

CC 353

Threshold Limited Value As Cobalt metal, dust or fume: TWA: 0.02 mg/m³ (air) (ACGIH 1992-93).

Effects of Overexposure
EYES: Contact with eyes causes irritation. **SKIN:** Prolonged or repeated exposure causes irritation and may result in an allergic skin reaction.
INGESTION: May cause vomiting, diarrhea, and a sensation of hotness.

Emergency and First Aid Procedures
INGESTION: If conscious, give one or two glasses of water to drink, induce vomiting and call a physician. Never give anything by mouth to an unconscious person. **SKIN:** Flush with water, then wash with mild soap and water. **EYES:** Flush thoroughly with water, lifting upper and lower eyelids occasionally. If irritation develops or persists, get medical attention.
INHALATION AS MIST: Remove to fresh air. If discomfort or illness develops, get medical attention.

SECTION VI REACTIVITY DATA

Stability
Unstable: Stable:
Conditions to Avoid Excessive temperature to cause evaporation.

Incompatibility (Materials to Avoid) Strong oxidizers.

Hazardous Decomposition Products Thermal decomposition or burning may produce cobalt oxide dust, hydrochloric acid or chlorine.

Hazardous Polymerization
May Occur: Will Not Occur:
Conditions to Avoid Not applicable.

SECTION VII SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled Absorb spill in vermiculite, sand, earth, paper towel and place in a suitable container for proper disposal. Wash spill area with soap and water.

Waste Disposal Method Discharge, treatment, or disposal may be subject to Federal, State or Local laws. These disposal guidelines are intended for the disposal of catalog-size quantities only.
Dispose of in an approved chemical landfill or contract with a licensed waste disposal service.

SECTION VIII SPECIAL PROTECTION INFORMATION

Respiration Protection (Specify Type) None needed in normal laboratory handling. If misty conditions prevail, work in ventilation hood or wear a NIOSH/MSHA-approved respirator.

Ventilation
Local Exhaust: Not required: Special: No:
Mechanical (General): Not required: Other: No:

Protective Gloves Rubber. **Eye Protection** Chemical safety glasses.

Other Protective Equipment Lab coat, apron, eye wash station, proper gloves.

SECTION IX SPECIAL PRECAUTIONS

Precautions to be Taken in Handling & Storing Store in a cool place. Wash thoroughly after handling.
Keep container tightly closed when not in use.

Other Precautions Read label on container before using. Do not wear contact lenses when working with chemicals.
Avoid contact with skin and eyes.
Remove and wash contaminated clothing.

For laboratory use only. Not for drug, food or household use. Keep out of reach of children.

Revision No. 1 Date 1/22/99 Approved Michael Raszeja
Chemical Safety Coordinator MR

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. * Hazardous Materials Industrial Standards. Printed on recycled paper.

SECTION I NAME 24 HOUR EMERGENCY ASSISTANCE

Product	COBALTOUS CHLORIDE 0.4 M AQ. SOL'N	 CHEMTREC 800-424-9300 Day 716-226-6177 NFPA HAZARD RATING LEAST SLIGHT MODERATE HIGH EXTREME 0 1 2 3 4 HMIS * 0 1 2 3 4
Chemical Synonyms	Cobalt Chloride, Water Solution	
Formula	Mixture. See Section II.	
Unit Size	up to 4 Lt.	
C.A.S. No.	Mixture. See Section II.	

SECTION II INGREDIENTS OF MIXTURES

Principal Component(s)	%	TLV Units
Cobalt Chloride: (CAS No. 7646-79-9)	9.52%	See Section V.
Water: (CAS No. 7732-18-5)	90.48%	None established.
WARNING! MAY BE HARMFUL IF SWALLOWED.		
MAY CAUSE SKIN IRRITATION.		

SECTION III PHYSICAL DATA

Melting Point (°F)	Freezes approx. 0°C (32°F)	Specific Gravity (H ₂ O = 1)	Approx. 1.0
Boiling Point (°F)	Approx. 100°C (212°F)	Percent Volatile by Volume (%)	90.48%
Vapor Pressure (mm Hg)	14 (water).	Evaporation Rate (Water = 1)	Slightly less than 1.
Vapor Density (Air=1)	0.7 (water).		
Solubility in Water	Complete.		
Appearance & Odor	Clear, water white, water like liquid; no odor.		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used)	Non-flammable.	Flammable Limits in Air % by Volume	NA	Lower	Upper
----------------------------------	----------------	--	----	-------	-------

Extinguisher Media Use any media suitable for extinguishing supporting fire.

SPECIAL FIREFIGHTING PROCEDURES

If involved in fire situation, wear a NIOSH/MSHA-approved self-contained breathing apparatus. Use flooding amounts of water in early stages of fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS

In fire conditions resulting in the evaporation of the water of solution hazardous decomposition products may be produced as dust or fume.

D.O.T. NON-REGULATED.

Approved by U.S. Department of Labor "essentially similar" to form OSHA-20