



MATERIAL SAFETY DATA SHEET

1533 W. Henrietta Rd.
Avon, New York 14414
(716) 226-6177

MSDS No. AA 183
Effective Date January 18, 1999

SECTION V HEALTH HAZARD DATA

AA 183

Threshold Limited Value None established by (ACGIH 1992-93).
Toxicity: LD50: orl-rat 4.28 g/kg as aluminum nitrate.

Effects of Overexposure May be harmful by ingestion. May cause irritation. To the best of our knowledge, the chemical, physical and toxicological properties have not been thoroughly investigated. Specific data is not available.

Emergency and First Aid Procedures
INGESTION: If swallowed, if conscious, give one or two glasses of water to drink, induce vomiting and call a physician. Never give anything by mouth to an unconscious person. **SKIN:** Flush with water, then wash with mild soap and water. **EYES:** Flush thoroughly with water, lifting upper and lower eyelids occasionally. If irritation develops or persists, get medical attention.

SECTION VI REACTIVITY DATA

Stability	Unstable		Conditions to Avoid	Excessive temperature to cause evaporation.
	Stable	X		

Incompatibility (Materials to Avoid) Alkalies.

Hazardous Decomposition Products Thermal decomposition produces aluminum oxide, and nitrogen oxides (NO_x).

Hazardous Polymerization	Conditions to Avoid		Not applicable.
	May Occur	Will Not Occur	
		X	

SECTION VII SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled Absorb with an inert dry material and place in an appropriate container for proper disposal. Wash spill area thoroughly with soap and water.

Waste Disposal Method Discharge, treatment, or disposal may be subject to Federal, State or Local laws. These disposal guidelines are intended for the disposal of catalog-size quantities only.

Dispose of in accordance with federal, state and local regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

Respiration Protection (Specify Type) None needed in normal laboratory handling. If misty conditions prevail, work in ventilation hood or wear a NIOSH/MSHA-approved respirator.

Ventilation	Local Exhaust	Not required.	Special	No.
	Mechanical (General)	Not required.	Other	No.

Protective Gloves Rubber. **Eye Protection** Chemical safety glasses.

Other Protective Equipment Lab coat, apron, eye wash station, proper gloves.

SECTION IX SPECIAL PRECAUTIONS

Precautions to be Taken in Handling & Storing Store in a cool place. Wash thoroughly after handling.
Keep container tightly closed when not in use.

Other Precautions Read label on container before using. Do not wear contact lenses when working with chemicals.

Remove and wash contaminated clothing.

For laboratory use only. Not for drug, food or household use. Keep out of reach of children.

Revision No. 2	Date 1/18/99	Approved Michael Raszeja	Chemical Safety Coordinator MR
-----------------------	---------------------	---------------------------------	---------------------------------------

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. * Hazardous Materials Industrial Standards. Printed on recycled paper.

SECTION I NAME 24 HOUR EMERGENCY ASSISTANCE

Product	ALUMINUM NITRATE, 0.1 MOLAR SOLUTION
Chemical Synonyms	Aluminum Nitrate, Aqueous Solution
Formula	Mixture
Unit Size	up to 4 Lt.
C.A.S. No.	Mixture

CHEMTREC
800-424-9300
Day 716-226-6177

Health	2
Fire	0
Reactivity	1

NFPA HAZARD RATING
LEAST SLIGHT MODERATE HIGH EXTREME
0 1 2 3 4

HMIS *
0 1 2 3 4

SECTION II INGREDIENTS OF MIXTURES

Principal Component(s)	%	TLV Units
Aluminum Nitrate: (CAS No. 13473-90-0)	2.13%	None established.
Water: (CAS No. 7732-18-5)	97.87%	None established.

CAUTION! MAY BE HARMFUL IF SWALLOWED.

SECTION III PHYSICAL DATA

Melting Point (°F)	Freezes below 0°C (32°F)	Specific Gravity (H₂O = 1)	Approx. 1.0
Boiling Point (°F)	Approx. 100°C (212°F)	Percent Volatile by Volume (%)	97.87%
Vapor Pressure (mm Hg)	14 (water).	Evaporation Rate (Water = 1)	< 1
Vapor Density (Air=1)	0.7 (water).		
Solubility in Water	Complete.		
Appearance & Odor	Clear, water white liquid; no odor.		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used)	Non-flammable.	Flammable Limits in Air % by Volume	N/A	Lower	Upper
Extinguisher Media	Use any media suitable for extinguishing supporting fire.				

SPECIAL FIREFIGHTING PROCEDURES

If involved in fire situation, wear a NIOSH/MSHA-approved self-contained breathing apparatus. Use flooding amounts of water in early stages of fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS

In fire conditions, water may evaporate from this solution, which may cause hazardous decomposition products to be produced as dust or fume.

D.O.T. NON-REGULATED.

Approved by U.S. Department of Labor "essentially similar" to form OSHA-20