



ALDON CORPORATION

MATERIAL SAFETY DATA SHEET

1533 W. Henrietta Rd.
Avon, New York 14414
(716) 226-6177

MSDS No. SS 900
Effective Date April 6, 1999

SECTION V HEALTH HAZARD DATA

SS 900

Threshold Limited Value

None established for this mixture.

Effects of Overexposure

INHALATION: May irritate respiratory tract. **INGESTION:** May cause irritation of the gastrointestinal tract and purging. **SKIN:** May cause irritation from prolonged contact. **EYES:** May irritate or burn eyes.

Emergency and First Aid Procedures

EYES: Flush with water for at least 15 minutes, lifting upper and lower eyelids occasionally. If irritation persists, get medical attention. **SKIN:** Flush thoroughly with water, then wash with soap and water. **INHALATION AS MIST:** Remove to fresh air. If illness or discomfort develops, get medical attention. **INGESTION:** If swallowed, if conscious, promptly give two to four glasses of water and induce vomiting. Call physician. Never give anything by mouth to an unconscious person.

SECTION VI REACTIVITY DATA

Stability	Unstable		Conditions to Avoid	High temperatures (above 100°C): Yields sulfur dioxide gas and hazardous residue.
	Stable	X		

Incompatibility (Materials to Avoid)	Oxidizers, acids.
--------------------------------------	-------------------

Hazardous Decomposition Products	Sulfur dioxide gas: Toxic, corrosive and an oxidizer. Sodium sulfide residue: Flammable, dangerous, fire risk, strong irritant to skin and tissue, incompatible with acids.
----------------------------------	--

Hazardous Polymerization	Conditions to Avoid
May Occur	Will Not Occur
	X
Not applicable.	

SECTION VII SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled	Absorb with an inert dry material, sweep up and place in a suitable container for proper disposal. Wash spill area with soap and water.
---	---

Waste Disposal Method	Discharge, treatment, or disposal may be subject to Federal, State or Local laws. These disposal guidelines are intended for the disposal of catalog-size quantities only.
-----------------------	--

Dispose of in an approved incinerator equipped with an afterburner and scrubber.

SECTION VIII SPECIAL PROTECTION INFORMATION

Respiration Protection (Specify Type)	None should be needed in normal laboratory use. If misty conditions prevail, work in fume hood or wear a NIOSH/MSHA-approved respirator.
---------------------------------------	--

Ventilation	Local Exhaust	Recommended.	Special	No.
	Mechanical (General)	Recommended.	Other	No.

Protective Gloves	Rubber.	Eye Protection	Chemical safety glasses.
-------------------	---------	----------------	--------------------------

Other Protective Equipment	Goggles, smock, apron, proper gloves, eye wash station.
----------------------------	---

SECTION IX SPECIAL PRECAUTIONS

Precautions to be Taken in Handling & Storing	Store in a cool, dry place away from acids or oxidizers. Contact with acids releases irritating sulfur dioxide gas.
---	---

Other Precautions	Read label on container before using. Do not wear contact lenses when working with chemicals.
-------------------	---

Avoid contact with eyes, skin, and clothing. Avoid breathing mist. Use with adequate ventilation. Remove and wash contaminated clothing.

For laboratory use only. Not for drug, food or household use. Keep out of reach of children.

Revision	No. 4	Date	4/6/99	Approved	Michael Raszeja	Chemical Safety Coordinator	MR
----------	-------	------	--------	----------	-----------------	-----------------------------	----

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. * Hazardous Materials Industrial Standards. Printed on recycled paper.

SECTION I NAME 24 HOUR EMERGENCY ASSISTANCE

Product	SODIUM THIOSULFATE 0.1 M/ 0.1 N	 CHEMTREC 800-424-9300 Day 716-226-6177 NFPA HAZARD RATING LEAST SLIGHT MODERATE HIGH EXTREME 0 1 2 3 4 HMIS * 0 1 2 3 4
Chemical Synonyms	Sodium Thiosulfate Aqueous Solution	
Formula	Mixture.	
Unit Size	up to 3.785 Lt.	
C.A.S. No.	Mixture.	

SECTION II INGREDIENTS OF MIXTURES

Principal Component(s)	%	TLV Units
Sodium Thiosulfate: (CAS No. 7772-98-7)	1.58%	None established.
Water: (CAS No. 7732-18-5)	98.42%	

CAUTION! MAY BE HARMFUL IF SWALLOWED.

MAY CAUSE IRRITATION TO SKIN AND EYES.

SECTION III PHYSICAL DATA

Melting Point (°F)	Freezes approx. 0°C (32°F)	Specific Gravity (H ₂ O = 1)	1.0
Boiling Point (°F)	Approx. 100°C (212°F)	Percent Volatile by Volume (%)	98.42%
Vapor Pressure (mm Hg)	14 (water)	Evaporation Rate (Ether = 1)	Greater than 1.
Vapor Density (Air=1)	0.7 (water)		
Solubility in Water	Complete.		
Appearance & Odor	Clear, colorless liquid; no odor.		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used)	Non-flammable.	Flammable Limits in Air % by Volume	N/A	Lower	Upper
---------------------------	----------------	-------------------------------------	-----	-------	-------

Extinguisher Media	Use any media suitable for extinguishing supporting fire.
--------------------	---

SPECIAL FIREFIGHTING PROCEDURES

In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus. Use water spray to keep containers cool, and to knock down fumes.

UNUSUAL FIRE AND EXPLOSION HAZARDS

In fire conditions, water may evaporate from this solution, which may cause hazardous decomposition products to be produced as dust or fume.

D.O.T. NON-REGULATED.

Approved by U.S. Department of Labor "essentially similar" to form OSHA-20