



ALDON CORPORATION

MATERIAL SAFETY DATA SHEET

1533 W. Henrietta Rd.
Avon, New York 14414
(716) 226-6177

MSDS No. LL 223
Effective Date March 22, 1999

SECTION V HEALTH HAZARD DATA

LL 223

Threshold Limited Value

None established for this solution. ACGIH 1992-93.

Effects of Overexposure

TARGET ORGANS: Central nervous system, kidneys.
May be harmful by ingestion. May cause weakness, dizziness, stomach pain. May cause eye and skin irritation. To the best of our knowledge, the chemical, physical and toxicological properties have not been thoroughly investigated. Specific data is not available.

Emergency and First Aid Procedures

INGESTION: If swallowed, if conscious, give one or two glasses of water to drink, induce vomiting and call physician. **EYES:** Flush thoroughly with water for 15 minutes, lifting upper and lower eyelids occasionally. If irritation persists, get medical attention. **SKIN:** Flush with water, then wash with mild soap and water. **INHALATION AS MIST:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

SECTION VI REACTIVITY DATA

Stability	Unstable		Conditions to Avoid	Excessive temperature to cause evaporation.
	Stable	X		

Incompatibility (Materials to Avoid)	Keep away from strong acids.
--------------------------------------	------------------------------

Hazardous Decomposition Products	Thermal decomposition may produce chlorine gas.
----------------------------------	---

Hazardous Polymerization	Conditions to Avoid	Not applicable.
May Occur	Will Not Occur	
	X	

SECTION VII SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled	Flush to sewer with copious amounts of water.
---	---

Waste Disposal Method	Discharge, treatment, or disposal may be subject to Federal, State or Local laws. These disposal guidelines are intended for the disposal of catalog-size quantities only.
-----------------------	--

Flush to sewer with copious amounts of water.

SECTION VIII SPECIAL PROTECTION INFORMATION

Respiration Protection (Specify Type)	None needed in normal laboratory handling. If misty conditions prevail, work in ventilation hood or wear a NIOSH/MSHA-approved respirator.		
---------------------------------------	--	--	--

Ventilation	Local Exhaust	Not required.	Special	No.
	Mechanical (General)	Not required.	Other	No.

Protective Gloves	Rubber - may cause irritation on long exposure.	Eye Protection	Chemical safety glasses.
-------------------	---	----------------	--------------------------

Other Protective Equipment	Lab coat, apron, proper gloves, splash goggles, eye wash station.
----------------------------	---

SECTION IX SPECIAL PRECAUTIONS

Precautions to be Taken in Handling & Storing	Store away from strong acids. Wash thoroughly after handling.
---	--

Other Precautions	Read label on container before using. Do not wear contact lenses when working with chemicals. Avoid contact with eyes, skin and clothing. Remove and wash contaminated clothing.
-------------------	--

For laboratory use only. Not for drug, food or household use. Keep out of reach of children.

Revision No. 3	Date 3/22/99	Approved Michael Raszeja	Chemical Safety Coordinator MR
----------------	--------------	--------------------------	--------------------------------

The information contained herein is furnished without warranty of any kind. Employees should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. * Hazardous Materials Industrial Standards. Printed on recycled paper.

SECTION I NAME 24 HOUR EMERGENCY ASSISTANCE

Product	LITHIUM CHLORIDE 1 MOLAR AQUEOUS SOL ^N	 CHEMTREC 800-424-9300 Day 716-226-6177 NFPA HAZARD RATING LEAST SLIGHT MODERATE HIGH EXTREME 0 1 2 3 4 HMIS *	Health	2
Chemical Synonyms	Lithium Chloride, 1 Molar Aqueous Solution		Fire	0
Formula	Mixture.		Reactivity	0
Unit Size	up to 3.785 Lt.			
C.A.S. No.	Mixture.			

SECTION II INGREDIENTS OF MIXTURES

Principal Component(s)	%	TLV Units
Lithium Chloride: (CAS No. 7447-41-8)	4.2% (w/v)	None established.
Water: (CAS No. 7732-18-5)	95.8%	

CAUTION! CONTACT MAY CAUSE

IRRITATION TO SKIN AND EYES.

SECTION III PHYSICAL DATA

Melting Point (°F)	Freezes below 0°C (32°F).	Specific Gravity (H ₂ O = 1)	Approx. 1.0
Boiling Point (°F)	Approx. 100°C (water).	Percent Volatile by Volume (%)	95.8%
Vapor Pressure (mm Hg)	14 (water).	Evaporation Rate (Water = 1)	Slightly less than 1.
Vapor Density (Air=1)	0.7 (water).		
Solubility in Water	Complete.		
Appearance & Odor	Clear, water white, water like liquid; no odor.		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used)	Non-flammable.	Flammable Limits in Air % by Volume	NA	Lower	Upper
				-----	-----

Extinguisher Media	Use any media suitable for extinguishing supporting fire.
--------------------	---

SPECIAL FIREFIGHTING PROCEDURES

In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS

In fire conditions, water may evaporate from this solution, which may cause hazardous decomposition products to be produced as dust or fume.

D.O.T. NON-REGULATED.

Approved by U.S. Department of Labor "essentially similar" to form OSHA-20