



ALDON CORPORATION

MATERIAL SAFETY DATA SHEET

1533 W. Henrietta Rd.
Avon, New York 14414
(716) 226-6177

MSDS No. ZZ 92
Effective Date January 6, 1997

SECTION V HEALTH HAZARD DATA

ZZ 92

Threshold Limited Value None established (ACGIH 1992-93). As Zinc fume: OSHA - PEL 5 mg/m³; TLV 5 mg/m³; (as Zinc Oxide) STEL 10 mg/m³.

Effects of Overexposure Contact with skin or eyes may cause irritation. Ingestion may cause nausea, vomiting, headaches, dizziness, gastrointestinal irritation.

Emergency and First Aid Procedures
INGESTION: If swallowed, if conscious, give one or two glasses of water to drink, induce vomiting and call a physician. Never give anything by mouth to an unconscious person. **SKIN:** Flush with water, then wash with mild soap and water. **EYES:** Flush thoroughly with water, lifting upper and lower eyelids occasionally. If irritation develops or persists, get medical attention. **INHALATION AS MIST:** Remove to fresh air.

SECTION VI REACTIVITY DATA

Stability	Unstable		Conditions to Avoid	Excessive temperature to cause evaporation.
	Stable	X		

Incompatibility (Materials to Avoid) Combustible materials, reducing agents, strong acids.

Hazardous Decomposition Products Yield toxic gaseous oxides of nitrogen when involved in fire.

Hazardous Polymerization	Conditions to Avoid		Not applicable.
	May Occur	Will Not Occur	
		X	

SECTION VII SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled Absorb spill in vermiculite, sand, earth, paper towel and place in a suitable container. Wash spill area with soap and water.

Waste Disposal Method Discharge, treatment, or disposal may be subject to Federal, State or Local laws. These disposal guidelines are intended for the disposal of catalog-size quantities only. Dispose of in an approved chemical landfill or contract with a licensed waste disposal service.

SECTION VIII SPECIAL PROTECTION INFORMATION

Respiration Protection (Specify Type) None needed in normal laboratory handling. If misty conditions prevail, work in ventilation hood or wear a NIOSH/MSHA-approved respirator.

Ventilation	Local Exhaust	Not required.	Special	No.
	Mechanical (General)	Not required.	Other	No.

Protective Gloves Rubber. **Eye Protection** Chemical safety glasses.

Other Protective Equipment Lab coat, apron, eye wash station, proper gloves.

SECTION IX SPECIAL PRECAUTIONS

Precautions to be Taken in Handling & Storing Store in a cool place. Wash thoroughly after handling. Keep container tightly closed when not in use.

Other Precautions Read label on container before using. Do not wear contact lenses when working with chemicals. Avoid contact with skin and eyes. Remove and wash contaminated clothing.

For laboratory use only. Not for drug, food or household use. Keep out of reach of children.

Revision No. 1	Date 1/06/97	Approved Michael Raszeja	Chemical Safety Coordinator MR
-----------------------	---------------------	---------------------------------	---------------------------------------

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. * Hazardous Materials Industrial Standards. Printed on recycled paper.

SECTION I NAME 24 HOUR EMERGENCY ASSISTANCE

Product	ZINC NITRATE 1 MOLAR AQ. SOL'N	 CHEMTREC 800-424-9300 Day 716-226-6177 NFPA HAZARD RATING LEAST SLIGHT MODERATE HIGH EXTREME 0 1 2 3 4 HMIS * Health 1 Fire 0 Reactivity 1
Chemical Synonyms	Zinc Nitrate, Water Solution	
Formula	Mixture. See Section II.	
Unit Size	up to 4 Lt.	
C.A.S. No.	Mixture. See Section II.	

SECTION II INGREDIENTS OF MIXTURES

Principal Component(s)	%	TLV Units
Zinc Nitrate: (CAS No. 7779-88-6)	18.93%	None established.
Water: (CAS No. 7732-18-5)	81.07%	None established.
WARNING! HARMFUL IF SWALLOWED. CONTACT MAY CAUSE EYE OR SKIN IRRITATION.		

SECTION III PHYSICAL DATA

Melting Point (°F)	Freezes approx. 0°C (32°F)	Specific Gravity (H₂O = 1)	Approx. 1.0
Boiling Point (°F)	Approx. 100°C (212°F)	Percent Volatile by Volume (%)	81.07%
Vapor Pressure (mm Hg)	14 (water).	Evaporation Rate (Water = 1)	Slightly less than 1.
Vapor Density (Air=1)	0.7 (water).		
Solubility in Water	Complete.		
Appearance & Odor	Clear, water white liquid, water solution; no odor.		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used)	Non-flammable.	Flammable Limits in Air % by Volume	NA	Lower	Upper
Extinguisher Media	Use any media suitable for extinguishing supporting fire.				

SPECIAL FIREFIGHTING PROCEDURES

If involved in fire situation, wear a NIOSH/MSHA-approved self-contained breathing apparatus. Use flooding amounts of water in early stages of fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS

In fire conditions resulting in the evaporation of the water solution, Zinc Nitrate is an active oxidizing material. In contact with easily oxidizable substances it may react rapidly enough to cause ignition, violent combustion or explosion. Increases the flammability of any combustible substance. Yield toxic gaseous oxides of nitrogen when involved in fire.

D.O.T. NON-REGULATED.

Approved by U.S. Department of Labor "essentially similar" to form OSHA-20