



M24C32	SERIAL EXTENDED ADDRESSING COMPATIBLE WITH I ² C BUS 32K (4K X 8) EEPROM - BRIEF DATA
M24C64	SERIAL EXTENDED ADDRESSING COMPATIBLE WITH I ² C BUS 64K (8K X 8) EEPROM - BRIEF DATA
M27C1001	1 MEGABIT (128K X 8) UV EPROM AND OTP EPROM - BRIEF DATA
M27C1024	1 MEGABIT (64K X16) UV EPROM AND OTP EPROM - BRIEF DATA
M27C160	16 MEGABIT (2MEG X 8 OR 1MEG X 16) UV EPROM AND OTP EPROM - BRIEF DATA
M27C202	2 MEGABIT (128K X16) OTP EPROM - BRIEF DATA
M27C256B	256K (32K X 8) UV EPROM AND OTP EPROM - BRIEF DATA
M27C4001	4 MEGABIT (512K X 8) UV EPROM AND OTP EPROM - BRIEF DATA
M27C4002	4 MEGABIT (256K X 16) UV EPROM AND OTP EPROM - BRIEF DATA
M27C405	4 MEGABIT (512K X 8) OTP EPROM - BRIEF DATA
M27C512	512K (64K X 8) UV EPROM AND OTP EPROM - BRIEF DATA
M27C516	512K (32K X 16) OTP EPROM - BRIEF DATA
M27C64A	64K (8K X 8) UV EPROM AND OTP EPROM - BRIEF DATA
M27C800	8 MEGABIT (1MEG X 8 OR 512K X 16) UV EPROM AND OTP EPROM - BRIEF DATA
M27C801	8 MEGABIT (1MEG X 8) UV EPROM AND OTP EPROM - BRIEF DATA
M27V401	LOW VOLTAGE 4 MEGABIT (512K X 8) UV EPROM AND OTP EPROM - BRIEF DATA
M27V402	LOW VOLTAGE 4 MEGABIT (256K X 16) UV EPROM AND OTP EPROM - BRIEF DATA

* To obtain a copy of a document marked with an asterisk, please contact your local Sales Office



M27V405	LOW VOLTAGE 4 MEGABIT (512K X 8) OTP EPROM - BRIEF DATA
M27V800	LOW VOLTAGE 8 MEGABIT (1MEG X 8 OR 512K X 16) UV EPROM AND OTP EPROM - BRIEF DATA
M27W401	VERY LOW VOLTAGE 4 MEGABIT (512K X 8) UV EPROM AND OTP EPROM - BRIEF DATA
M27W402	VERY LOW VOLTAGE 4 MEGABIT (256K X 16) UV EPROM AND OTP EPROM - BRIEF DATA
M28C16	PARALLEL 16K (2K X 8) EEPROM WITH SOFTWARE DATA PROTECTION - BRIEF DATA
M28C17	PARALLEL 16K (2K X 8) EEPROM WITH SOFTWARE DATA PROTECTION - BRIEF DATA
M28C64	PARALLEL 64K (8K X 8) EEPROM WITH SOFTWARE DATA PROTECTION - BRIEF DATA
M28C64C	PARALLEL ACCESS 64K (8K X 8) EEPROM - BRIEF DATA
M28C64X	PARALLEL ACCESS 64K (8K X 8) EEPROM - BRIEF DATA
M28F101	1 MEGABIT (128K X 8, CHIP ERASE) FLASH MEMORY - BRIEF DATA
M28LV16	LOW VOLTAGE PARALLEL ACCESS 16K (2K X 8) EEPROM WITH SOFTWARE DATA PROTECTION - BRIEF DATA
M28LV17	LOW VOLTAGE PARALLEL ACCESS 16K (2K X 8) EEPROM WITH SOFTWARE DATA PROTECTION - BRIEF DATA
M28LV64	LOW VOLTAGE PARALLEL 64K (8K X 8) EEPROM WITH SOFTWARE DATA PROTECTION - BRIEF DATA
M29F040	SINGLE SUPPLY 4 MEGABIT (512K X 8, SECTOR ERASE) FLASH MEMORY - BRIEF DATA
M29V040	LOW VOLTAGE SINGLE SUPPLY 4 MEGABIT (512K X 8, SECTOR ERASE) FLASH MEMORY - BRIEF DATA

* To obtain a copy of a document marked with an asterisk, please contact your local Sales Office



M87C257

ADDRESS LATCHED 256K (32K X 8) UV EPROM AND OTP
EPROM - BRIEF DATA