

**Dedicated Products****Telecom & Data Communications**

<u>ST AN293</u>	TS5070/5071 COMBO II PROGRAM AND HYBRID BALANCE WITH MONOLITHIC SLICS
<u>ST AN349</u>	A VERY LOW COST AND POWERFUL SOLUTION FOR V.23 APPLICATION
<u>ST AN382</u>	PABX BIG COST REDUCTION AND PERFORMANCE IMPROVEMENT ARE OBTAINED WITH A NEW SLIC CHIP-SET
<u>ST AN384</u>	L3845 FOR PABX AND MODEM INTERFACE APPLICATION
<u>ST AN488</u>	PHONE REMOTE SYSTEM
<u>ST AN489</u>	MK5025 SINGLE CHANNEL LAPD
<u>ST AN490A</u>	MK5025 NET2 CONFORMANCE
<u>ST AN491</u>	MK5025 DAISY CHAIN DMA
<u>ST AN492</u>	MK5025 NRZ TO NRZI CONVERSION
<u>ST AN493</u>	MK5025 TRANSPARENT MODE
<u>ST AN494</u>	MK5025 SYNCHRONOUS TIMING
<u>ST AN496</u>	L3035-3036-L3037 MONOCHIP SLICS
<u>ST AN497</u>	SLICS L3092/L3000 MAX LOOP RESISTANCE ANALYSIS
<u>ST AN498</u>	SLIC L3092/L3000 PERFORMANCE ANALYSIS WITH -24V BATTERY
<u>ST AN501</u>	SGS-THOMSON SLIC KIT AC MODELS

**Dedicated Products****Telecom & Data Communications**

<u>ST AN502</u>	SGS-THOMSON SLIC KITS AND COMBO II
<u>ST AN504</u>	SLICS PROTECTION CIRCUITS
<u>ST AN505</u>	M3488 DIGITAL SWITCHING MATRIX
<u>ST AN534</u>	4.5W FLYBACK CONVERTER FOR POWER LINE MODEM APPLICATIONS
<u>ST AN535</u>	POWER LINE MODEM APPLICATION REMOTE CONTROL USING ST7537 AND ST6
<u>ST AN536</u>	RAM MAPPING ST75C50
<u>ST AN537</u>	ST75C502-DEFAULT TONE DETECTORS
<u>ST AN538</u>	ST75C502-BULK DELAY MANAGEMENT
<u>ST AN539</u>	ST75C502-RAM MAPPING
<u>ST AN653</u>	ST7536 TELECOM
<u>ST AN654</u>	ST7544-UNIVERSAL ANALOG FRONT-END
<u>ST AN655</u>	ST7537 POWER LINE MODEM APPLICATION
<u>ST AN681</u>	L3235 WITH EXTERNAL RINGING
<u>ST AN684</u>	APPLICATION NOTE HOW TO USE THE DUAL PORT RAM FOR PARALLEL DATA TRANSFER WITH THE ST75C502
<u>ST AN686</u>	ST7546-SIMPLIFIED ANALOG FRONT-END

** To obtain a copy of a document marked with an asterisk, please contact your local Sales Office*

**Dedicated Products****Telecom & Data Communications**

- [ST AN814](#) V.17 FAX EQUIPMENT REPLACING THE R144EFX WITH THE ST75C52/520
- [ST AN815](#) A STEREO AUDIO SOLUTION FOR MULTIMEDIA APPLICATIONS USING TWO ST7546 A/D AND D/A CONVERTERS
- [ST AN816](#) SET-UP, HANDSHAKE AND COMMUNICATION MONITORING IN MODEM AND FAX MODE WITH THE ST75C502
- [ST AN822](#) COMPUTATION OF TONE DETECTOR COEFFICIENTS USING TD SOFTWARE FOR ST75C502
- [ST AN823](#) ST75C52/ST75C520-SINGLE ENDED AND SINGLE POWER SUPPLY HYBRID CIRCUIT
- [ST AN838](#) STV0042/STV0056 APPLICATION NOTE
- [ST AN847](#) ST5080 ST5090 DEMOTOOL