

ISDN**ISDN**

Type	Description	Package
ST5410**	2B1Q-U-Interface Device	CDIP28
ST5421CP	SID-GCI: S/T Interface Device with GCI	DIP20
ST5421CFN	SID-GCI: S/T Interface Device with GCI	PLCC28
STLC5432	2M bit CEPT & Primary Rate Controller Device	TQFP44
ST5451	HDLC & GCI	DIP28
STLC5411FN	2B1Q-U-Interface Device	PLCC44
STLC5411P	2B1Q-U-Interface Device	DIP28
STLC5444	Quad Feeder Power Supply	DIP24, PLCC44
STLC5460	Line Card Interface Controller	DIP40, PLCC44
STU2071B1	4B3T-U-Interface Circuit	DIP28
STU2071FN	4B3T-U-Interface Circuit	PLCC28

ISDN DC-DC CONVERTER MODULES

NT DC-DC CONVERTER MODULE					
Dual Output Type	Output Power (W)	Input Voltage Range (V _{DC})	Output Volt/mA	Dimensions L . W . H (mm)	Package
GS1T70D540*	1	25 ÷ 115	5 / 90 ; 40 / 10.5	50.8 . 50.8 . 16.5	G
GS1T70D540F*	1	25 ÷ 115	5 / 90 ; 40 / 10.5	56 . 56 . 18	V

* According to CCITT I.430 recommendation.

** Replaced by STLC5411 for new design.