

ISDN**ISDN**

Type	Description	Package
ST5410** ST5421CP ST5421CFN STLC5432 ST5451 STLC5411FN STLC5411P STLC5444 STLC5460 STU2071B1 STU2071FN	2B1Q-U-Interface Device SID-GCI: S/T Interface Device with GCI SID-GCI: S/T Interface Device with GCI 2M bit CEPT & Primary Rate Controller Device HDLC & GCI 2B1Q-U-Interface Device 2B1Q-U-Interface Device Quad Feeder Power Supply Line Card Interface Controller 4B3T-U-Interface Circuit 4B3T-U-Interface Circuit	CDIP28 DIP20 PLCC28 TQFP44 DIP28 PLCC44 DIP28 DIP24, PLCC44 DIP40, PLCC44 DIP28 PLCC28

ISDN DC-DC CONVERTER MODULES

NT DC-DC CONVERTER MODULE					
Dual Output Type	Output Power (W)	Input Voltage Range (V _{DC})	Output Volt/mA	Dimensions L . W . H (mm)	Package
GS1T70D540*	1	25 ÷ 115	5 / 90 ; 40 / 10.5	50.8 . 50.8 . 16.5	G
GS1T70D540F*	1	25 ÷ 115	5 / 90 ; 40 / 10.5	56 . 56 . 18	V

* According to CCITT I.430 recommendation.

** Replaced by STLC5411 for new design.