

CheckBoxButton.dll

DLL LOAD "CheckBoxButton"

DLL GET "SHORT CheckBoxButton:ShowcButton"

DLL GET "VOID CheckBoxButton:ClosecButton"

DLL GET "VOID CheckBoxButton:SetFocus"

short ShowcButton()

ShowcButton is the main function for setting up and displaying the ShowcButton dialog box.

Parameter 1

Basic Type: INTEGER

C Type: short

Parameter 1 is a value between 1 and MAXOPTION. a 1 will call a modal dialog box suspending Program execution and returning the number of the button pushed or a zero if the dialog is closed with no button push.

Parameter 2

Basic Type: INTEGER

C Type: short

Parameter 2 is the number of Checkboxes from 0 to MAXBUTTON.

Parameter 3

Basic Type: LONG

C Type: long

Parameter 3 is the desired width of the dialog window and buttons.

Parameter 4

Basic Type: INTEGER

C Type: short *

Parameter 4 is the pressed button.

Parameter 5

Basic Type: STR\$

C Type: char *

This is the text for the window title.

Parameter 6

Basic Type: STR\$

C Type: char *

This is the text that will appear above the buttons

Parameter 7

Basic Type: STR\$
C Type: char *

This is the group text modifier that will appear over groupings of buttons.

Parameter 8

Basic Type: STR\$
C Type: char *

Text for button 1.

Parameter 9

Basic Type: STR\$
C Type: char *

Text for button 2.

Parameter 10

Basic Type: STR\$
C Type: char *

Text for button 3.

Parameter 11

Basic Type: STR\$
C Type: char *

Text for button 4.

Parameter 12

Basic Type: STR\$
C Type: char *

Text for button 5.

Parameter 13

Basic Type: STR\$
C Type: char *

Text for button 6.

Parameter 14

Basic Type: STR\$
C Type: char *

Text for button 7.

Parameter 15

Basic Type: STR\$
C Type: char *

Text for button 8.

Parameter 16

Basic Type: STR\$
C Type: char *

Text for button 9.

Parameter 17

Basic Type: STR\$
C Type: char *

Text for button 10.

ClosecButton ()

Closes the ShowcButton. There are no Parameters.

Setfocus()

Will bring the ShowcButton dialog box to the foreground and activate. No parameters.