

HTBmail.dll

DLL LOAD “HTBmail”

DLL GET “VOID HTBmail: Sendmailattach”

DLL GET “VOID HTBmail:Sendmail”

Sendmailattach()

This function will send an email attachment with your message. This can be sent to as many addresses as are in the address string delimited by a comma symbol.

Parameter 1

Basic Type: STRING
C Type: char *

This is the pointer to the address or string of addresses delimited by commas.

Parameter 2

Basic Type: STRING
C Type: char *

This is the pointer to the data used for subject in the message header.

Parameter 3

Basic Type: STRING
C Type: char *

This is the pointer to the data used for the attachments, this should contain a pathname and a filename.

Parameter 4

Basic Type: STRING
C Type: char *

This parameter is the text to be contained in the body of the message.

Parameter 5

Basic Type: LONG
C Type: short *

This parameter is return value for the failure or success of the mail send. 1=PASS and 0=FAIL.

Sendmail()

This function will send an email message. This can be sent to as many addresses as are in the address string delimited by a comma symbol.

Parameter 1

Basic Type: STRING
C Type: char *

This is the pointer to the address or string of addresses delimited by commas.

Parameter 2

Basic Type: STRING
C Type: char *

This is the pointer to the data used for subject in the message header.

Parameter 4

Basic Type: STRING
C Type: char *

This parameter is the text to be contained in the body of the message.