

# HTBmail.dll

## DLL LOAD “HTBmail”

## DLL GET “VOID HTBmail: Sendmailattach”

## DLL GET “VOID HTBmail:Sendmail”

### Sendmailattach()

This function will send an email attachment with your message. This can be sent to as many addresses as are in the address string delimited by a comma symbol.

#### *Parameter 1*

Basic Type:   STRING  
C Type:       char \*

This is the pointer to the address or string of addresses delimited by commas.

#### *Parameter 2*

Basic Type:   STRING  
C Type:       char \*

This is the pointer to the data used for subject in the message header.

#### *Parameter 3*

Basic Type:   STRING  
C Type:       char \*

This is the pointer to the data used for the attachments, this should contain a pathname and a filename.

#### *Parameter 4*

Basic Type:   STRING  
C Type:       char \*

This parameter is the text to be contained in the body of the message.

#### *Parameter 5*

Basic Type: LONG  
C Type: short \*

This parameter is return value for the failure or success of the mail send. 1=PASS and 0=FAIL.

### **Sendmail()**

This function will send an email message. This can be sent to as many addresses as are in the address string delimited by a comma symbol.

#### *Parameter 1*

Basic Type: STRING  
C Type: char \*

This is the pointer to the address or string of addresses delimited by commas.

#### *Parameter 2*

Basic Type: STRING  
C Type: char \*

This is the pointer to the data used for subject in the message header.

#### *Parameter 4*

Basic Type: STRING  
C Type: char \*

This parameter is the text to be contained in the body of the message.