

# Adobe Customer Services

## Cartridge Installation for Windows 3.0/3.1

---

### Adobe PostScript® Cartridge for HP II printers

After you have powered the printer down, inserted the PostScript cartridge into the printer's left cartridge slot, powered the printer back on and verified that the printer's display reads "POSTSCRIPT READY", follow the instructions below to complete the installation for Windows 3.0/3.1. NOTE: You may not need to use all the software packaged with your PostScript cartridge to get it successfully installed.

### Installing the Windows PostScript Printer Driver

1. Start Windows.
2. Locate the Control Panel icon in the Main program group and double-click on it.
3. Double-click on the Printers icon.
4. In the Printers windows, click on the Add Printer button in the lower right corner.
5. The Printers window expands, listing all known Windows printers. Click on "Apple LaserWriter IINT" and then click on the Install button.
6. Once "PostScript Printer on ..." displays in the Installed Printers window, highlight this entry and click on Configure (connect in windows 3.1). Here in the Configure window, click on the printer port to which your printer is attached, and change the Transmission Retry value to 999.
7. Now click on the Setup button. If not already selected, click on the down-arrow next to the printer's name and select Apple LaserWriter IINT from the list that appears (it's directly above Apple LaserWriter Plus). Then click on OK twice to return to the main Printers window.
8. You should see "PostScript Printer on" the port you selected in the list of available printers. Highlight this entry if it isn't already. If the printer is not active, click on the Active button to activate the printer driver. Once the entry in Installed Printers reads "PostScript Printer on xxxx, Active", double-click on the entry to make the PostScript Printer the default printer. (in windows 3.1, making a printer "Active" does not apply -once the printer is connected to a port, it is active)Then click on OK and exit the Control Panel.

You can now print with any of the base 35 fonts supplied on the PostScript Cartridge. Feel free to test this now in your favorite application. You may need to choose File...Printer Setup within the application to indicate your wish to use the PostScriptPrinter and update the available fonts within that application. For most people, the installation is now complete.



---

## Installing Screen Fonts / ATM Fonts (OPTIONAL)

If you do not have Adobe Type Manager for Windows (available separately) and you wish to install the optional pre-built bitmapped screen font software, follow the complete installation procedure described in your PostScript Cartridge manual starting on page 13.

If you DO have Adobe Type Manager for Windows (ATM), follow the instructions below to install your fonts from the PostScript Cartridge into ATM (and thus into Windows). You will only need the disks labeled "Font Disk" and "Supplemental Font Disk x" to complete the font installation. Be sure to completely install ATM and verify that it is working (as described in the ATM manual) before completing the following steps:

1. From a DOS prompt, make a temporary directory (MKDIR C:\ADOBE)
2. Copy all of the files from all of the Font and Supplemental Font disks into the temporary directory (Copy a:\*. \* C:\ADOBE for each disk).
3. Start Windows, and double-click on the ATM Control Panel icon in the Main program group.
4. In the ATM control panel, click the Add button. In the Add Fonts dialog box, find the subdirectory you created in the Directories list and double-click on it. All 35 cartridge fonts should then display in the Available Fonts box.
5. Highlight all the fonts in the Available Fonts box: Click on the top entry (Avant Garde), then use the Available Fonts scroll bar to scroll down to the last entry (Zapf Dingbats). Hold down the SHIFT key, click on the last entry (Zapf Dingbats), and release the SHIFT key. Now all the fonts in the Available Fonts list should be highlighted.
6. Click on the Add button. When the operation is completed, ATM will close the Add Fonts window and return to the main ATM Control Panel. You should find that all the Cartridge fonts are included in the Installed Fonts list. Click on Exit to close the Control Panel.
7. Exit Windows and restart to activate the changes to ATM. All your Cartridge fonts should display in all your Windows applications in any point size. Once you have confirmed this, it is OK to remove all the files in the temporary directory you created (DEL C:\ADOBE\\*.\*) and remove the temporary directory (RMDIR C:\ADOBE).

Adobe and the Adobe logo are trademarks and Adobe is a service mark of Adobe Systems Incorporated that may be registered in certain jurisdictions. All other products and brand names are trademarks of their respective holders.  
© 1993 Adobe Systems Incorporated. All rights reserved.



24-hour Automated Technical Support: 408-986-6560 • Fax Request Line: 408-986-6587