

# Adobe<sup>SM</sup> Customer Services

## ATM™ Network Installation

---

### VERSIONS 2.0, 2.02, AND 2.5

1 Copy the following files from the ATM Program disk to the <drive>:\<path>\WINDOWS\SYSTEM directory:

ATM16 . DLL  
ATM32 . DLL  
ATMSYS . DRV

2 Copy the following file to the <drive>:\<path>\WINDOWS directory:

ATMCNTRL . EXE

3 Modify the users SYSTEM.INI files by replacing

SYSTEM . DRV=SYSTEM . DRV

with

SYSTEM . DRV=ATMSYS . DRV  
ATM . SYSTEM . DRV=SYSTEM . DRV

4 Start Windows, and create an icon for the ATM Control Panel in the Main Program group.

5 Open the ATM Control Panel, and press the Add button.

6 At the bottom of the screen for the Target Directory for PostScript™ Outline fonts, enter the following:

<drive>:\PSFONTS

For the Target Directory for Font Metrics Files, enter the following:

<drive>:\PSFONTS\PFM

7 If you have a disk marked Fonts Disk, insert it in your floppy disk drive. If not, leave the ATM Program disk in the drive, and double-click on that drive letter in the box marked directories. A [PSFONTS] directory will appear in the box. Double-click on this as well.

8 When the font names come up in the Available Font box, highlight the fonts to install, and press the Add button.

9 When the font installation is complete, exit the control panel, and restart Windows so that the changes take effect.

---

## NETWORK INSTALLATION NOTES

- You must have read/write privileges.
- The PSFONTS directory should be at the root level of the drive on which it is installed. If the path becomes too long, ATM will not be able to find the fonts.
- Always make a backup copy of any file you modify by hand.
- If installing so that more than one user can access ATM, ensure that you purchased the appropriate site license.

If you install ATM on to a diskless workstation that accesses a single-user copy of Windows from the network, map a portion of the network drive to C:\, and install ATM with the installer.