

```

; Mod: 1/10/95 by Dave Nebinger
; This text describes the format for the Hosts file.
;
;
; Hosts
; This file is parsed by the MacTCP domain name resolver and the resource records
; are loaded into the resolver's cache.
;
;
; The Hosts file follows a SUBSET of the Master File Format (see rfc1035 pg 33).
; Each line in this file has the form: <domain-name> <rr> [<comment>]
; <domain-name> is an absolute domain name (see rfc1034 pg 11).
; <rr> = [<ttl>] [<class>] <type> <rdata> OR [<class>] [<ttl>] <type> <rdata>
; A comment starts with ";" or by a line beginning with a " ".
;
;
; NOTES:
;
; $INCLUDE is not implemented
;
; Class is always IN, ttl is in seconds, type can be A, CNAME or NS.
;
; Examples
; knowAll.apple.com.
A

```

```

128.8.1.1

```

```

; address of host knowAll.apple.com.
; apple.com.

```

```

NS

```

```

knowAll.apple.com.

```

```

; apple.com name server
; .

```

```

NS

```

```

knowAll.apple.com.

```

```

; root name server
;
; myHost.apple.com.
IN
604800
A
128.8.1.2

```

```
; ttl of 1 week
;JohnS.apple.com.
A
```

128.8.1.3

```
;Sculley.apple.com.
CNAME
```

JohnS.apple.com.

```
; canonical name for alias Sculley.apple.com
;
```