

Installing Hubi's Loopback Device - Topic 1 of 4

This Windows Help file guides you in installing Hubi's' Loopback Device, for use with Propellerhead Software ReBirth RB-338. As far as ReBirth is concerned, you only need to install this utility if you plan to synchronize ReBirth to another MIDI program, running on the same computer.

- We strongly recommend that you also copy the entire folder "Hld" to your hard disk. This is not required for installing the driver in your system, but will ensure that you have access to the documentation and the included utility programs. See the full ReBirth RB-338 manual for more details about how to use Hubi's Loopback Device in ReBirth RB-338.

► To begin the installation, click the [>>] (Forward) button at the top of this window.

Installing Hubi's Loopback Device - Topic 2 of 4

1. Click the Start button on the Taskbar.
 2. From the menu that appears, select Settings, and from the sub menu that pops up, select the Control Panel.
 3. In the Control Panel window, double click on the Add New Hardware icon.
 4. Click on the Next button.
 5. Select No in the next dialog, and again click Next.
- To continue with the installation, click the [>>] (Forward) button at the top of this window.

Installing Hubi's Loopback Device - Topic 3 of 4

1. From the list that you now have on-screen, select Sound, Video and game Controllers and click Next.
 2. Click on the Have Disk button.
 3. In the dialog that appears, click on the Browse button.
 4. In the file dialog that appears, locate the Rebirth CD-ROM, and open the HLD folder.
 5. Now, the text omesetup.inf will appear in the list to the left in the dialog.
 6. Click OK.
 7. Click OK again in the next two dialogs that appear.
 8. Click Finish.
- To continue with the installation, click the [>>] (Forward) button at the top of this window.

Installing Hubi's Loopback Device - Topic 4 of 4

You now have a small window on screen with settings for Hubi's Loopback Device.

1. Select the number of MIDI ports you desire, by clicking the Last Port radio buttons.
ReBirth requires only one of these to be activated but you might find it useful to activate more.
2. If you like, double click on the name of a port to change it.
This is not required and the ReBirth manual assumes you are using the standard names.
3. Click OK.
4. Again, click OK to confirm a restart of the computer.

The installation of Hubi's Loopback Device is now finished!

