

Some things to take care about scanning the target you need note/remember:

- Scan with the resolution you most often use with your scanner.
- Disable any color correction your scanning software offers. They only lower the quality ICS can achieve as ICS tries to undo your color changes. If your scanner software does support ICS directly, make sure the ICS or Calibration mode is enabled. This makes sure the scanner software does not disable all settings that might disturb color calibration by ICS.

ScanQuix V4: ScanQuix V4 (or newer) users should enable the ICS calibration mode using the ICS menu items in their ScanQuix software. The ICS menu items of ScanQuix are only available if ICS is installed on the system. Please see the ScanQuix manual for further information.

ScanTrax V2.2: ScanTrax users should now set the ICS mode to calibration in the ScanTrax preferences window.

ImageFX: The various ImageFX scanner drivers don't directly support ICS yet. But you can download an ImageFX hook module from the manufacturers ftp site (check for ftp://ftp.novadesign.com/imagefx/Hooks_N_Modules/icshook.lha). When using ImageFX follow the recommendations described below. Once you calibrated your scanner, you have to always use the same color and scanmode settings in the ImageFX scanner driver. After scanning, simply run the ICS hook module. It will call ICS for converting the scanned ImageFX image in memory.

So the ICS hook module basically saves you from saving and reloading images for color correcting using ICSConvert. It does not save you from setting up the scanner driver the wrong way as the scanner drivers mentioned above with direct ICS support. Also note that some scanner drivers supporting ICS do make use of a feature of ICS to generate the *perfect* download table for your scanner. This can improve quality especially on scanners with more than 8 Bit scan modes.

Don't forget to disable the calibration mode in your scanner software again after the calibration of your scanner.

- Most scanner software allows you to scan images gamma corrected or linear. Choose the linear setting. Often the unwanted gamma correction is hidden in a scan setting like NTSC/PAL or so. This setting should be done automatically if your scanner software does offer an ICS calibration mode.
 - Scanning the target with a bad skew or margin around the box outlining the target will cause ICS to fail. There are some checks done during calibration to make sure you correctly scanned the calibration target. But not all possible user faults while scanning the target are checked. So try to make sure to scan the boxed area positioned as good as possible.
- After scanning the target, run the ScanTarget program (see figure 5.1) shipped with ICS. ScanTarget can be found in the installed ICS drawer. Here you have to:
 - Select the type of calibration target you own/use.
 - Select the target image file you scanned in the steps above.
 - Select the target reference file you should have received with your target. Sometimes manufacturers do not ship the reference files with their calibration targets and you have to download the file for the batch of your target from their Internet site (Kodak seems to do this).

Note: some older IT targets have been shipped by manufacturers with faulty formatted reference files. As the reference files are text based you might be able to understand and fix the faults in the file based on the error messages ScanTarget produces on bad reference files. If not, contact the manufacturer for a correct reference file for your target batch. Don't worry. Many dealers do correct faulty target reference files of manufacturers before shipping the targets to end users.