NSBrowserCell

Inherits From: NSCell : NSObject

Declared In: appkit/NSBrowserCell.h

Accessing Graphic Attributes

+ (NSImage *)**branchImage**   Returns the default NSImage for branch NSBrowserCells.
+ (NSImage *)**highlightedBranchImage**   Returns the default NSImage for branch NSBrowserCells that are
                                                highlighted.
- (NSImage *)**alternateImage**   Returns this NSBrowserCell's image for the highlighted state.
- (void)**setAlternateImage:**(NSImage *)*anImage* Sets this NSBrowserCell's image for the highlighted state.

Placing in the Browser Hierarchy

- (BOOL)**isLeaf**   Returns whether the NSBrowserCell is a leaf or a branch.
- (void)**setLeaf:**(BOOL)*flag*   Sets whether the NSBrowserCell is a leaf or a branch.

Determining Loaded Status

- (BOOL)**isLoaded**   Returns YES if all the NSBrowserCell's state has been set and the cell is
                                                ready to display.
- (void)**setLoaded:**(BOOL)*flag*   Sets whether all the NSBrowserCell's state has been set and the cell is
                                                ready to display.

Setting State

- (void)**reset**   Unhighlights the NSBrowserCell and sets its state to 0.
- (void)**set**   Highlights the NSBrowserCell and sets its state to 1.